

Page 1 of 13

#### Antenna Gain Test Report

Project No.: 4791107448

Client Name: L&S Lighting Equipment (Shanghai) Co., Ltd.

Client Address: Building No.1, Lane 255 Longpan Road, Malu Town, Jiading

District, Shanghai, China

Product Name: Remote Controller

Product Model: RR-CONTROL-EASYLUX-1+4-CH

Manufacture Name: L&S Lighting Equipment (Shanghai) Co., Ltd.

Manufacture Address: Building No.1, Lane 255 Longpan Road, Malu Town, Jiading

District, Shanghai, China

Antenna Type: PCB

Antenna Size: 5.4mm\*14.4mm

Project Engineer: James Qin

Test Standards: ANSI/IEEE std 149-2021

Test Date: 2023.12.26

Issued Date: 2023.12.26



Page 2 of 13

## **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	2023.12.26	Initial Issue	\



Page 3 of 13

## **Table of Contents**

1	Test Equipment Information	4
2	Setup block diagram	5
3	Test Temperature and Humidity	6
4	Test Step Flow	7
5	Test Result	8
6	Photo	12



Page 4 of 13


# 1 Test Equipment Information

Equipment	Manufacturer	Mode No.	Serial No.	Cal date	Cal Due
Test	ETC Lindaron	9500	/	/	/
Chamber	ETS-Lindgren	8500			
Test	FTC Lindaran	EMQuest	4.400	,	,
Software	ETS-Lindgren	V1.12	1496	/	/
Network	Kovojaht	EE074C	MY46524531	2023.10.12	2024.10.11
Analyzer	Keysight	E5071C	W140524531	2023.10.12	2024.10.11
EXA Singal	V o voigibit	NOO40A	MVESTEDETA	2022 40 42	2024 40 44
Analyzer	Keysight	N9010A	MY55150514	2023.10.12	2024.10.11



Page 5 of 13

# 2 Setup block diagram





Page 6 of 13

# 3 Test Temperature and Humidity

Temperature: 21.5°C

Humidity: 53.6%



Page 7 of 13

# 4 Test Step Flow

- 1) Maintain the test ambient temperature of 23±2 C, the instrument is powered on and preheated for more than 30 minutes;
- 2) Turn on the darkroom power supply, connect the test cable, and set up the sample according to the standard;
- 3) Outline sets the test content objectives and conducts calibration tests;
- 4) Run the software, when the test is completed, export the corresponding test diagram and test data, and save to the corresponding directory.



Page 8 of 13

## 5 Test Result


Frequency (MHz)	Efficiency (%)	Gain (dBi)
2400	13.55	-2.86
2410	13.42	-2.91
2420	13.66	-2.78
2430	14.04	-2.66
2440	13.86	-2.65
2450	13.73	-2.73
2460	13.54	-2.87
2470	13.59	-2.89
2480	13.63	-3.01
2490	13.33	-3.21
2500	13.33	-3.18



Page 9 of 13


#### **Polarization Pattern Photos**

Theta Polarization(Theta Angle=90°)




Page 10 of 13





#### Total 3D Plot(Fre.2440MHz)





UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.



Page 11 of 13







# 6 Photo





UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.



Page 13 of 13

# **END OF REPORT**