

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test standard

 : CFR47 FCC Part 2: Section 2.1093
 CFR47 FCC Part 1: Section 1.1310
 FCC KDB Publication 447498 D01 v06
 RSS-102 Issue 5 2.5.1

FCC/IC requirements

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1093 this device has been defined as a portable device. SAR test exclusion considerations per KDB 447498 D01 v06 4.3.1 a)

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

SAR Test Exclusion Threshold (mW)

IC requirement: SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output level below.

 Table 1: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance^{4.5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Measurement Record

The minimum distance for the EUT is less than 5mm.

The maximum time averaged e.i.r.p. of 315MHz: 42.15dBuv/m @3m = -55.23dBm < 1mW

The maximum time averaged e.i.r.p. of 433.92MHz: 55.95dBuv/m @3m = -41.43dBm < 1mW

According to KDB 447498 D01 v06 4.3.1 a) and RSS-102 Issue 5 clause 2.5.1

EUT is compliance with the RF exposure.