

WSCT

TEST REPORT

WSCT**WSCT****WSCT****WSCT****WSCT****WSCT****WSCT**

FCC ID: 2BDBM-R6

Product: RF Remote Control

Main test model: R6

Serial models : R7.R8.R6-1.R7-1.R8-1.R8-5.R9.R15.R16.R17
R6(B).R7(B).R8(B).R6-1(B).
R7-1(B).R8-1(B).R8-5(B).R9(B).R15(B).R16(B).R17(B)Trade Mark: Skydance **WSCT**

Report No.: WSCT-ANAB-R&E241200072A-2.4G

Issued Date: 23 December 2024

Issued for:

Guangzhou Skydance Co.,Ltd.

1-3F, No.19, ChuangYuan Road, Zhongcun Street, Panyu District,
Guangzhou, China 511495

Issued By:

World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.
Building A-B,Baoli'an Industrial Park,No.58 and 60,Tangtou Avenue, Shiyan
Street, Bao'an District, Shenzhen City, Guangdong Province, China

TEL: +86-755-26996192

FAX: +86-755-86376605



Note: This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

1. Test Certification	3
2. Test Result Summary	4
3. EUT Description.....	5
4. Genera Information	6
4.1. TEST ENVIRONMENT AND MODE	6
4.2. DESCRIPTION OF SUPPORT UNITS	6
5. Facilities and Accreditations	7
5.1. FACILITIES	7
5.2. ACCREDITATIONS	7
5.3. MEASUREMENT UNCERTAINTY	8
5.4. MEASUREMENT INSTRUMENTS	9
6. Test Results and Measurement Data	10
6.1. ANTENNA REQUIREMENT	10
6.2. CONDUCTED EMISSION	11
6.3. CONDUCTED OUTPUT POWER	13
6.4. EMISSION BANDWIDTH.....	16
6.5. POWER SPECTRAL DENSITY	19
6.6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT	22
6.7. RADIATED SPURIOUS EMISSION MEASUREMENT	25
7. Test Setup Photographs	33



1. Test Certification

Product:	RF Remote Control
Model No.:	R6
Trade Mark:	Skydance
Applicant:	Guangzhou Skydance Co.,Ltd. 1-3F, No.19, ChuangYuan Road, Zhongcun Street, Panyu District, Guangzhou, China 511495
Manufacturer:	Guangzhou Skydance Co.,Ltd. 1-3F, No.19, ChuangYuan Road, Zhongcun Street, Panyu District, Guangzhou, China 511495
Date of Test:	29 November 2024 to 22 December 2024
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 KDB 558074 D01 DTS Meas Guidance v04

The above equipment has been tested by World Standardization Certification & Testing Group(Shenzhen)Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Wang Xiang
(Wang Xiang)

Checked By: Qin Shuiquan
(Qin Shuiquan)

Approved By: Li Huaibi
(Li Huaibi)

Date: 23 December 2024



2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	NA
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	1§5.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product Name:	RF Remote Control
Model :	R6
Trade Mark:	Skydance
Hardware version	C4
Operation Frequency:	2478MHz
Modulation Technology:	GFSK
Antenna Type:	Wire antenna
Antenna Gain:	2.5dBi.
Operating Voltage	Coin cell batteries:CR2032 Voltage: 3V
Remark:	N/A.

NOTE: R6.R7.R8.R6-1.R7-1.R8-1.R8-5.R9.R15.R16.R17 R6(B).R7(B).R8(B).R6-1(B).

R7-1(B).R8-1(B).R8-5(B).R9(B).R15(B).R16(B).R17(B) are series models with only differences in appearance and color, while all other specifications are identical.
R6 is the main test model.

Operation Frequency each of channel

Frequency
2478MHz

4. General Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) with Fully-charged battery.
<p>The sample was placed (0.1m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

All measurement facilities used to collect the measurement data are located at **World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.**

Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtou Avenue, Shiyan Street, Bao'an District, Shenzhen City, Guangdong Province, China

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2. ACCREDITATIONS

ANAB - Certificate Number: AT-3951

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (ANAB). Certification Number: AT-3951



5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Power Spectral Density	$\pm 3.2\text{dB}$
2	Duty Cycle and Tx-Sequence and Tx-Gap	$\pm 1\%$
3	Medium Utilisation Factor	$\pm 1.3\%$
4	Occupied Channel Bandwidth	$\pm 2.4\%$
5	Transmitter Unwanted Emission in the out-of Band	$\pm 1.3\%$
6	Transmitter Unwanted Emissions in the Spurious Domain	$\pm 2.5\%$
7	Receiver Spurious Emissions	$\pm 2.5\%$
8	Conducted Emission Test	$\pm 3.2\text{dB}$
9	RF power, conducted	$\pm 0.16\text{dB}$
10	Spurious emissions, conducted	$\pm 0.21\text{dB}$
11	All emissions, radiated(<1GHz)	$\pm 4.7\text{dB}$
12	All emissions, radiated(>1GHz)	$\pm 4.7\text{dB}$
13	Temperature	$\pm 0.5^\circ\text{C}$
14	Humidity	$\pm 2.0\%$

5.4. MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
Test software	--	EZ-EMC	CON-03A	-	-
Test software	--	MTS8310	-	-	-
EMI Test Receiver	R&S	ESCI	100005	11/05/2024	11/04/2025
LISN	AFJ	LS16	16010222119	11/05/2024	11/04/2025
LISN(EUT)	Mestec	AN3016	04/10040	11/05/2024	11/04/2025
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	11/05/2024	11/04/2025
Coaxial cable	Megalon	LMR400	N/A	11/05/2024	11/04/2025
GPIB cable	Megalon	GPIB	N/A	11/05/2024	11/04/2025
Spectrum Analyzer	R&S	FSU	100114	11/05/2024	11/04/2025
Pre Amplifier	H.P.	HP8447E	2945A02715	11/05/2024	11/04/2025
Pre-Amplifier	CDSI	PAP-1G18-38	--	11/05/2024	11/04/2025
Bi-log Antenna	SCHWARZBECK	VULB9168	01488	11/05/2024	11/04/2025
9*6*6 Anechoic	--	--	--	11/05/2024	11/04/2025
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	11/05/2024	11/04/2025
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	11/05/2024	11/04/2025
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	11/05/2024	11/04/2025
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	11/05/2024	11/04/2025
Loop Antenna	EMCO	6502	00042960	11/05/2024	11/04/2025
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	11/05/2024	11/04/2025
Power meter	Anritsu	ML2487A	6K00003613	11/05/2024	11/04/2025
Power sensor	Anritsu	MX248XD	--	11/05/2024	11/04/2025
Spectrum Analyzer	Keysight	N9010B	MY60241089	11/05/2024	11/04/2025

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The Bluetooth antenna is a Wire antenna. it meets the standards, and the best case gain of the antenna is 2.5dBi..	
Please refer to the attachment " R6 Internal Photo" for the antenna location	

6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2014														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p>Reference Plane</p> <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Charging + Transmitting Mode														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2014 on conducted measurement. 														
Test Result:	N/A														

6.2.2. EUT OPERATING CONDITIONS

The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Test data:

Note: NA (This product is powered by a DC source and does not require testing for this project.)




6.3. Conducted Output Power


6.3.1. Test Specification

6.3.2. Test Data

Test channel	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
2478MHz	-0.6	30.00	PASS

Test plots as follows:





6.4. Emission Bandwidth


6.4.1. Test Specification




6.4.2. Test data

Test channel	6dB Emission Bandwidth (kHz)		
	2478MHz	Limit	Result
Lowest	799.7	>500k	PASS


Test plots as follows:





6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 <p>Spectrum Analyzer EUT</p>
Test Mode:	Refer to item 4.1
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v04 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW) 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS




6.5.2. Test data

Test channel	Power Spectral Density (dBm/3kHz)		
	2478MHz	Limit	Result
Lowest	-15.91	8 dBm/3kHz	PASS

Test plots as follows:






6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification


Test Data

Test Graphs

Band Edge 2478MHz Ref




Band Edge 2478MHz Emission




Conducted RF Spurious Emission

Test Graphs

Tx. Spurious 2478MHz Ref




Tx. Spurious 2478MHz Emission



6.7. Radiated Spurious Emission Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209						
Test Method:	ANSI C63.10:2014						
Frequency Range:	9 kHz to 25 GHz						
Measurement Distance:	3 m						
Antenna Polarization:	Horizontal & Vertical						
Operation mode:	Refer to item 4.1						
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark		
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value		
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value		
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value		
	Above 1GHz	Peak	1MHz	3MHz	Peak Value		
		Peak	1MHz	10Hz	Average Value		
Limit:	Frequency	Field Strength (microvolts/meter)		Measurement Distance (meters)			
	0.009-0.490	2400/F(KHz)		300			
	0.490-1.705	24000/F(KHz)		30			
	1.705-30	30		30			
	30-88	100		3			
	88-216	150		3			
	216-960	200		3			
	Above 960	500		3			
Test setup:	Frequency	Field Strength (microvolts/meter)		Measurement Distance (meters)	Detector		
	Above 1GHz	500		3	Average		
		5000		3	Peak		
For radiated emissions below 30MHz							
30MHz to 1GHz							



1. For the radiated emission test below 1GHz:
 The EUT was placed on a turntable with 0.1 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.

For the radiated emission test above 1GHz:
 Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Test Procedure:

	<p>2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>4. Use the following spectrum analyzer settings:</p> <ol style="list-style-type: none"> (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, $VBW = 3$ MHz for $f \geq 1$ GHz for peak measurement. <p>For average measurement: $VBW = 10$ Hz, when duty cycle is no less than 98 percent. $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
Test mode:	Refer to section 4.1 for details
Test results:	PASS

Note: Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = Attenuation factor + Cable loss

Level (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Margin (dB) = Level (dB μ V) - Limits (dB μ V)



6.7.2. Test Data

Please refer to following diagram for individual
Below 1GHz

Horizontal:

87.0 dBuV/m

77

67

57

47

37

27

17

7

-3

-13

-23

-33

30.000

60.00

(MHz)

300.00

1000.000


FCC Part15 RE-Class B_30-1000MHz
Margin -6 dB

5

peak

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	48.0150	36.32	-19.02	17.30	40.00	-22.70	QP
2	68.9023	36.70	-22.11	14.59	40.00	-25.41	QP
3	130.3218	34.69	-20.55	14.14	43.50	-29.36	QP
4	249.2065	36.03	-21.84	14.19	46.00	-31.81	QP
5	613.9450	35.94	-13.27	22.67	46.00	-23.33	QP
6	961.3192	36.96	-9.29	27.67	54.00	-26.33	QP

Vertical:



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	47.3463	35.61	-19.08	16.53	40.00	-23.47	QP
2	75.9441	35.54	-23.61	11.93	40.00	-28.07	QP
3	147.2099	35.27	-19.59	15.68	43.50	-27.82	QP
4	255.6231	35.38	-21.59	13.79	46.00	-32.21	QP
5	595.9160	36.32	-13.82	22.50	46.00	-23.50	QP
6 *	918.0785	37.34	-9.71	27.63	46.00	-18.37	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.


Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)Limit (dB μ V) = Limit stated in standardMargin (dB) = Measurement (dB μ V) – Limits (dB μ V)

Above 1GHz

Note 1: The spurious above 18G is noise only, do not show on the report.

Test channel: 2478MHz


Horizontal:



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2463.7500	48.37	27.48	20.89	74	-25.63	253.2	Horizontal	PK	Pass
1	2463.7500	35.66	27.48	8.18	54	-18.34	253.2	Horizontal	AV	Pass
2	3496.8750	48.63	28.5	20.13	74	-25.37	201.8	Horizontal	PK	Pass
2	3496.8750	36.89	28.5	8.39	54	-17.11	201.8	Horizontal	AV	Pass
3	5803.7500	61.11	32.49	28.62	74	-12.89	358.4	Horizontal	PK	Pass
3	5803.7500	46.38	32.49	13.89	54	-7.62	358.4	Horizontal	AV	Pass
4	8932.5000	42.45	9.8	32.65	74	-31.55	28.1	Horizontal	PK	Pass
4	8932.5000	35.24	9.8	25.44	54	-18.76	28.1	Horizontal	AV	Pass
5	11991.0000	47.42	16.81	30.61	74	-26.58	267	Horizontal	PK	Pass
5	11991.0000	41.62	16.81	24.81	54	-12.38	267	Horizontal	AV	Pass
6	17911.5000	53.71	23.34	30.37	74	-20.29	141.5	Horizontal	PK	Pass
6	17911.5000	46.65	23.34	23.31	54	-7.35	141.5	Horizontal	AV	Pass

Vertical :



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2453.7500	45.64	27.44	18.2	74	-28.36	208.9	Vertical	PK	Pass
1	2453.7500	36.02	27.44	8.58	54	-17.98	208.9	Vertical	AV	Pass
2	3435.6250	45.35	28.46	16.89	74	-28.65	334.4	Vertical	PK	Pass
2	3435.6250	36.47	28.46	8.01	54	-17.53	334.4	Vertical	AV	Pass
3	5751.8750	55.88	32.4	23.48	74	-18.12	-0.1	Vertical	PK	Pass
3	5751.8750	46.7	32.4	14.3	54	-7.3	-0.1	Vertical	AV	Pass
4	9792.0000	40.83	11.87	28.96	74	-33.17	318.5	Vertical	PK	Pass
4	9792.0000	33.24	11.87	21.37	54	-20.76	318.5	Vertical	AV	Pass
5	11830.5000	45.01	16.31	28.7	74	-28.99	146.3	Vertical	PK	Pass
5	11830.5000	37.71	16.31	21.4	54	-16.29	146.3	Vertical	AV	Pass
6	17857.5000	53.63	22.99	30.64	74	-20.37	134.4	Vertical	PK	Pass
6	17857.5000	45.64	22.99	22.65	54	-8.36	134.4	Vertical	AV	Pass

Note:

1. All emissions not reported were more than 20dB below the specified limit or in the noise floor.
2. Emission Level= Reading Level+Probe Factor +Cable Loss.
3. Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



6.7.3. Restricted Bands Requirements

Frequency	Reading	Correct Factor	Emission Level	Limit	Margin	Polar	Detector
(MHz)	(dB μ V/m)	dB/m	(dB μ V/m)	(dB μ V/m)	(dB)	H/V	
2483.5	64.86	-8.17	56.69	74	17.31	H	PK
2483.5	53.01	-8.17	44.84	54	9.16	H	AV
2483.5	61.56	-8.17	53.39	74	20.61	V	PK
2483.5	53.39	-8.17	45.22	54	8.78	V	AV

Note: Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = Attenuation factor + Cable loss

Level (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)Limit (dB μ V) = Limit stated in standardMargin (dB) = Level (dB μ V) – Limits (dB μ V)

7. Test Setup Photographs

Please refer to the attachment "Set Up Photos-15B" for relevant test setup photos

*****END OF REPORT*****