

## Label



### HYX-M1000-SW-NA

Grid Support Utility Interactive Inverter

<b>Input (DC)</b>	
Max. Input Voltage	65V
Range of MPPT Voltage	16-60V
Start-up Voltage	20V
Max. Input Current	2*16A
Max. Input Short Circuit Current	2*20A
<b>Output (AC)</b>	
Nominal Output Voltage	208V
Nominal Output Frequency/Range	60Hz/57Hz-63Hz
Max. Continuous Output Power	960VA
Max. Continuous Output Current	4.62A
Power Factor (Default/Adjustable)	>0.99/ 0.8leading...0.8lagging
<b>General Data</b>	
Operating Ambient Temperature	-40 to +65°C
Type of Enclosure	Type 6
Type of Isolation	Isolated

Made in China  
Zhejiang Hyxi Technology Co., Ltd. [www.hyxipower.com](http://www.hyxipower.com)

P/N: X X XXXX XXXXXX  
  
S/N: XXXXXXXXXXXXXXXX X

303599

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

**CAUTION:**

Risk of electric shock - Do not remove cover. No user serviceable parts inside. Refer servicing to qualified service personnel. Both AC and DC voltage sources are terminated inside this equipment. All circuits must be individually disconnected before servicing. When the photovoltaic array is exposed to light, it supplies a DC voltage to this equipment. Hot surfaces - To reduce the risk of burns - Do not touch.

**MISE EN GARDE:**

Risque de choc électrique, ne pas retirer le couvercle. L'appareil ne contient aucune pièce réparable par l'utilisateur. Confier l'entretien à un personnel qualifié. Les sources de tension CA et CC sont terminées à l'intérieur de cet appareil. Tous les circuits doivent être débranchés individuellement avant de procéder à l'entretien. Lorsque le réseau photovoltaïque est exposé à la lumière, il fournit une tension continue à cet appareil. Surfaces chaudes - Pour réduire le risque de brûlures, ne pas toucher.

FCC ID: 2BDBN-2MSWG1    UL 1741  
IC:31516-2MSWG1    CSA C22.2 NO.107.1

Size: 40\*30mm

The label is printed on the shell