

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a Drone Halo LED operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 x 3.7V rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -16.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -16.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 78.4dB $\mu$ V/m at 3m in the frequency 2440MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -16.83dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 77.8dB $\mu$ V/m at 3m in the frequency 2420MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -17.43dBm  
which is within the production variation.

The maximum conducted output power specified is -13dBm= 0.050mW  
The source- based time-averaging conducted output power  
=0.050mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)  
= 3.0 \* 5 / sqrt (2.460) mW  
= 9.56 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: 2BDBQSF2024KR2