



## RF EXPOSURE EVALUATION METHOD

**FCC ID: 2BDC6-BLUGTW-GEN3**

### Applicable standard:

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEEC95.1-1992. and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

### SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and $\leq 50$ mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

| MHz  | 5  | 10 | 15  | 20  | 25  | mm                                      |
|------|----|----|-----|-----|-----|-----------------------------------------|
| 150  | 39 | 77 | 116 | 155 | 194 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 27 | 55 | 82  | 110 | 137 |                                         |
| 450  | 22 | 45 | 67  | 89  | 112 |                                         |
| 835  | 16 | 33 | 49  | 66  | 82  |                                         |
| 900  | 16 | 32 | 47  | 63  | 79  |                                         |
| 1500 | 12 | 24 | 37  | 49  | 61  |                                         |
| 1900 | 11 | 22 | 33  | 44  | 54  |                                         |
| 2450 | 10 | 19 | 29  | 38  | 48  |                                         |
| 3600 | 8  | 16 | 24  | 32  | 40  |                                         |
| 5200 | 7  | 13 | 20  | 26  | 33  |                                         |
| 5400 | 6  | 13 | 19  | 26  | 32  |                                         |
| 5800 | 6  | 12 | 19  | 25  | 31  |                                         |

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.



## 2.4G WiFi

| Modulation | Frequency | Maximum Conducted Output Power(PK) | Conducted Output Power Limit |
|------------|-----------|------------------------------------|------------------------------|
|            | (MHz)     | (dBm)                              | dBm                          |
| 802.11b    | 2412      | 4.74                               | 30                           |
|            | 2437      | 5.5                                | 30                           |
|            | 2462      | 5.6                                | 30                           |
| 802.11g    | 2412      | 3.48                               | 30                           |
|            | 2437      | 4.37                               | 30                           |
|            | 2462      | 4.56                               | 30                           |
| 802.11n20  | 2412      | 2.72                               | 30                           |
|            | 2437      | 3.69                               | 30                           |
|            | 2462      | 3.75                               | 30                           |
| 802.11n40  | 2422      | 1.07                               | 30                           |
|            | 2437      | 1.48                               | 30                           |
|            | 2452      | 1.99                               | 30                           |

max possible output power (PK, conducted): 6±1dBm

7dBm=5.01mW

2412MHz

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,mm})] \cdot [\sqrt{f(\text{GHz})}] = 5.01/5 \cdot \sqrt{2.412} = 1.56 \leq 3.0$

2422MHz

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,mm})] \cdot [\sqrt{f(\text{GHz})}] = 5.01/5 \cdot \sqrt{2.422} = 1.56 \leq 3.0$

2437MHz

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,mm})] \cdot [\sqrt{f(\text{GHz})}] = 5.01/5 \cdot \sqrt{2.437} = 1.56 \leq 3.0$

2452MHz

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,mm})] \cdot [\sqrt{f(\text{GHz})}] = 5.01/5 \cdot \sqrt{2.452} = 1.57 \leq 3.0$

2462MHz

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,mm})] \cdot [\sqrt{f(\text{GHz})}] = 5.01/5 \cdot \sqrt{2.462} = 1.57 \leq 3.0$



BLE

| Modulation  | Frequency | Maximum Conducted Output Power(PK) | Conducted Output Power Limit |
|-------------|-----------|------------------------------------|------------------------------|
|             | (MHz)     | (dBm)                              | dBm                          |
| GFSK(1Mbps) | 2402      | 0.16                               | 30                           |
|             | 2440      | 1.00                               | 30                           |
|             | 2480      | 0.83                               | 30                           |
| GFSK(2Mbps) | 2402      | -0.04                              | 30                           |
|             | 2440      | 0.71                               | 30                           |
|             | 2480      | 0.59                               | 30                           |

max possible output power (PK, conducted): 1±1dBm

2dBm=1.58mW

2402MHz

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]}{1.58/5 \cdot \sqrt{2.402}} = 0.49 \leq 3.0$$

2440MHz

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]}{1.58/5 \cdot \sqrt{2.440}} = 0.49 \leq 3.0$$

2480MHz

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]}{1.58/5 \cdot \sqrt{2.48}} = 0.50 \leq 3.0$$

The Bluetooth and WIFI can transmit at the same time.

So the worst simultaneous transmitting consideration:

The ratio=1.57/3+0.50/3=0.39< 3.0

Conclusion:

1. 
$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]}{1.58/5 \cdot \sqrt{2.402}} < 3.0.$$
2. SAR Test Exclusion Thresholds is 3.0 for separation distance 5mm. Therefore, SAR test is not required.