

## RF Exposure Evaluation

### LIMIT

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

### EVALUATION METHOD

Transmission formula:  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

$Pd$  = power density in mW/cm<sup>2</sup>,  $Pout$  = output power to antenna in mW,  $G$  = gain of antenna in linear scale;

$\pi$  = 3.1416,  $R$  = distance between observation point and center of the radiator in cm

### TEST RESULT

Passed

Not Applicable

Radio Type	Frequency range (MHz)	Conducted Average Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Bluetooth-EDR	2402-2480	8.84	9.00	0.003	1.0000	Pass
Bluetooth-BLE	2402-2480	7.56	8.00	0.0024	1.0000	Pass
WIFI (RF CHIP: AP6398S)	2412-2472	13.54	14.00	0.0095	1.0000	Pass
WIFI (RF CHIP: MT7628AN)	2412-2472	13.77	14.00	0.01	1.0000	Pass
WIFI	5150~5850	10.79	11.00	0.009	1.0000	Pass

Radio Type	Frequency range (MHz)	field strength (dBuV/m)	field strength (dBm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
NFC	13.56MHz	72.42	-22.78	0.0000021	4.89	Pass

Consider the BT and wifi can transmitting simultaneously, the total transmitting MPE rate as below formula:  
MPE rate=Power density of BT/limit + Power density of wifi/limit + Power density of NFC/limit <1

The worst case is BT-EDR,13.56MHz and 2.4G WIFI transmitting simultaneously, the result as below:

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
BT-EDR	0.003	0.0040004	1
2.4G WIFI	0.001		
13.56MHz	0.0000004		

Note:

- 1) The maximum antenna gain is 2.79dBi (BT and 2.4G WiFi ) and 5.55dBi (5G WiFi )
- 2) The maximum antenna gain is 3.00dBi (2.4G WiFi )
- 3) The maximum antenna gain is 3.00dBi (13.56MHz)
- 4) The exposure evaluation safety distance is 20cm