



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

RF Exposure evaluation

FCC ID: 2BDHJINSRA01

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

Z2000 PRO can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
BT/BLE	/	Internal antenna	4.5dBi for 2400-2500MHz;	
2.4GWIFI	/	Internal antenna	4.5dBi for 2400-2500MHz for ANT 1&2	
5.2GWIFI	/	Internal antenna	4.5dBi for 5180-5825MHz for ANT 1&2	
16QAM 14.0525GHz	/	Internal antenna	75dBi for 14000-145000MHz for ANT	

5. Manufacturing Tolerance

WIFI(Peak) ANT1

Frequency (MHz)	11b		
	2412	2437	2462
Target (dBm)	16.0	16.0	16.0
Tolerance ± (dB)	1.0	1.0	1.0

WIFI(Peak) ANT2

Frequency (MHz)	11b		
	2412	2437	2462
Target (dBm)	16.0	16.0	16.0
Tolerance ± (dB)	1.0	1.0	1.0
Frequency (MHz)	11g		
	2412	2437	2462
Tolerance ± (dB)	1.0	1.0	1.0



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

[5.2GHz WLAN] ANT 1

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	14.0	/	14.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5210	/
Target (dBm)	/	14.0	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.2GHz WLAN] ANT 2

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	14.5	14.5	14.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	14.5	/	14.5
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5210	/
Target (dBm)	/	14.5	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.3GHz WLAN] ANT 1

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5260	5300	5320
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5270	/	5310
Target (dBm)	14.0	/	14.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5290	/



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Target (dBm)	/	14.0	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.3GHz WLAN] ANT 2

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5260	5300	5320
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5270	/	5310
Target (dBm)	14.0	/	14.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5290	/
Target (dBm)	/	14.0	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.6GHz WLAN] ANT 1

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5500	5580	5700
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5510	5550	5670
Target (dBm)	14.0	/	14.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5530	/
Target (dBm)	/	14.0	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.6GHz WLAN] ANT 2

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5500	5580	5700
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5510	5550	5670
Target (dBm)	14.0	/	14.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Frequency (MHz)	/	5530	/
Target (dBm)	/	14.0	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.8GHz WLAN] ANT1

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	13.5	13.5	13.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5755	/	5795
Target (dBm)	13.5	/	13.5
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5775	/
Target (dBm)	/	13.5	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.8GHz WLAN] ANT2

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5755	/	5795
Target (dBm)	14.0	/	14.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5775	/
Target (dBm)	/	14.0	/
Tolerance $\pm$ (dB)	/	1.0	/

MIMIO:

[5.2GHz WLAN] ANT

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	17.5	17.5	17.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	17.5	/	17.5



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5210	/
Target (dBm)	/	17.5	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.3GHz WLAN] ANT

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5260	5300	5320
Target (dBm)	17.0	17.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5270	/	5310
Target (dBm)	17.0	/	17.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5290	/
Target (dBm)	/	17.0	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.6GHz WLAN] ANT

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5500	5580	5700
Target (dBm)	17.0	17.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5510	5550	5670
Target (dBm)	17.0	/	17.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5530	/
Target (dBm)	/	17.0	/
Tolerance $\pm$ (dB)	/	1.0	/

[5.8GHz WLAN] ANT

IEEE 802.11ac20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	17.0	17.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac40 (Average)			



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Frequency (MHz)	5755	/	5795
Target (dBm)	17.0	/	17.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5775	/
Target (dBm)	/	17.0	/
Tolerance $\pm$ (dB)	/	1.0	/

QPSK			
Frequency (MHz)	/	14.0525GHz	/
Target (dBm)	/	5.0	/
Tolerance $\pm$ (dB)	/	1.0	/
8PSK			
Frequency (MHz)	/	14.0525GHz	/
Target (dBm)	/	5.0	/
Tolerance $\pm$ (dB)	/	1.0	/
16QAM			
Frequency (MHz)	/	14.0525GHz	/
Target (dBm)	/	5.0	/
Tolerance $\pm$ (dB)	/	1.0	/

6. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 3500 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=3500\text{cm}$, as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI ANT1	17.0	50.118723	4.5	2.818383	0.0000009	1.0000
2.4GWIFI ANT2	17.0	50.118723	4.5	2.818383	0.0000009	1.0000
5.2GWIFI ANT1	15.0	31.622777	4.5	2.818383	0.0000006	1.0000
5.2GWIFI ANT2	15.5	35.481339	4.5	2.818383	0.0000006	1.0000
5.3GWIFI ANT1	15.0	31.622777	4.5	2.818383	0.0000006	1.0000
5.3GWIFI ANT2	15.0	31.622777	4.5	2.818383	0.0000006	1.0000
5.6GWIFI ANT1	15.0	31.622777	4.5	2.818383	0.0000006	1.0000
5.6GWIFI ANT2	15.0	31.622777	4.5	2.818383	0.0000006	1.0000
5.8GWIFI ANT1	14.5	28.183829	4.5	2.818383	0.0000005	1.0000
5.8GWIFI ANT2	15.0	31.622777	4.5	2.818383	0.0000006	1.0000



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

5.2GWIFI MIMO	18.5	70.794578	4.5	2.818383	0.0000013	1.0000
5.3GWIFI MIMO	18.5	70.794578	4.5	2.818383	0.0000013	1.0000
5.6GWIFI MIMO	18.5	70.794578	4.5	2.818383	0.0000013	1.0000
5.8GWIFI MIMO	18.5	70.794578	4.5	2.818383	0.0000013	1.0000
QPSK 14.0525GHz	6.0	3.981072	75	31622776.601684	0.8182279	1.0000
8PSK 14.0525GHz	6.0	3.981072	75	31622776.601684	0.8182279	1.0000
16QAM 14.0525GHz	6.0	3.981072	75	31622776.601684	0.8182279	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 3500cm from user manual provide by manufacturer.

7. simultaneous MPE Result

14.0525GHz ANT1 MPE (Ratio)	WIFI ANT2 MPE (Ratio)	simultaneous MPE (Ratio)	MPE Limits (Ratio)
0.8182279	0.0000013	0.81822932	1.0000

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----