



FCC Test Report

**Test report
On Behalf of
Shenzhen Haimeilan Technology Co., LTD.
For
Smart Phone**

Model No.: I16 Pro max, AE01, AE02, AE03, AE04, AE05, AE06, AE07, AE08, AE09, AE10, AE11, AE12, AE13, AE14, AE15, AE16, AE17, AE18, AE19, AE20, FA01, FA02, FA03, FA04, FA05, FA06, FA07, FA08, FA09, FA10, FA11, FA12, FA13, FA14, FA15, FA16, FA17, FA18, FA19, FA20, Viral11, Alpha10 Pro, Zero 5 neo, Echo8 Se, S26 Ultra, Pixel 9, SP30 Pro, MT Ultimate, M15 pro

FCC ID: 2BDI3-V

Prepared For : Shenzhen Haimeilan Technology Co., LTD.
9V777, East 9th Floor, Building 2, SEG Science Park, Huaqiang North Street, Futian District, Shenzhen, 518000 China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Date of Test: Feb. 20, 2025 ~ Apr. 18, 2025

Date of Report: Apr. 18, 2025

Report Number: HK2502080444-3E

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



HUAK TESTING

HUAK TESTING

Applicant's name

Page 2 of 130

Report No.: HK2502080444-3E

Test Result Certification

Address

Shenzhen Haimeilan Technology Co., LTD.

Address

9V777, East 9th Floor, Building 2, SEG Science Park, Huaqiang North Street, Futian District, Shenzhen, 518000 China

Manufacturer's Name

Shenzhen Haimeilan Technology Co., LTD.

Address

9V777, East 9th Floor, Building 2, SEG Science Park, Huaqiang North Street, Futian District, Shenzhen, 518000 China

Product description

Trade Mark:

N/A

Product name

Smart Phone

Model and/or type reference ..

I16 Pro max, AE01, AE02, AE03, AE04, AE05, AE06, AE07, AE08, AE09, AE10, AE11, AE12, AE13, AE14, AE15, AE16, AE17, AE18, AE19, AE20, FA01, FA02, FA03, FA04, FA05, FA06, FA07, FA08, FA09, FA10, FA11, FA12, FA13, FA14, FA15, FA16, FA17, FA18, FA19, FA20, Viral11, Alpha10 Pro, Zero 5 neo, Echo8 Se, S26 Ultra, Pixel 9, SP30 Pro, MT Ultimate, M15 pro FCC Rules and Regulations Part 15 Subpart E Section 15.407 ANSI C63.10: 2013

Standards

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test

Feb. 20, 2025 ~ Apr. 18, 2025

Date of Issue

Apr. 18, 2025

Test Result

Pass

Testing Engineer



Len Liao

Technical Manager



Sliver Wan

Authorized Signatory



Jason Zhou

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Table of Contents

1. Test Result Summary	5
1.1. Test Procedures and Results.....	5
1.2. Information of the Test Laboratory	5
1.3. Measurement Uncertainty	6
2. EUT Description	7
2.1. General Description of EUT	7
2.2. Operation Frequency Each of Channel.....	8
2.3. Operation of EUT During Testing	8
2.4. Description of Test Setup.....	9
2.5. Description of Support Units	10
3. Genera Information.....	11
3.1. Test Environment and Mode	11
4. Test Results and Measurement Data	14
4.1. AC Power Line Conducted Emission.....	14
4.2. Maximum Conducted Output Power	28
4.3. 6db Emission Bandwidth	31
4.4. 26db Bandwidth and 99% Occupied Bandwidth.....	38
4.5. Power Spectral Density	39
4.6. Band Edge.....	46
4.7. Spurious Emission.....	71
4.8. Frequency Stability Measurement.....	115
4.9. Antenna Requirement	117
5. Test Setup Photos of the EUT	118
6. Photos of the EUT.....	130



HUAK TESTING

HUAK TESTING



HUAK TESTING

HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING




HUAK TESTING




HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING



HUAK TESTING

** Modified History **

Revision	Description	Issued Data	Remark
Revision 1.0	Initial Test Report Release	Apr. 18, 2025	Jason Zhou

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



1.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	±0.37dB
2	RF power, conducted	±3.35dB
3	Spurious emissions, conducted	±2.20dB
4	All emissions, radiated(<1G)	±3.90dB
5	All emissions, radiated(>1G)	±4.28dB
6	Temperature	±0.1°C
7	Humidity	±1.0%



2. EUT Description

2.1. General Description of EUT

Equipment:	Smart Phone
Model Name:	I16 Pro max
Serial Models:	AE01, AE02, AE03, AE04, AE05, AE06, AE07, AE08, AE09, AE10, AE11, AE12, AE13, AE14, AE15, AE16, AE17, AE18, AE19, AE20, FA01, FA02, FA03, FA04, FA05, FA06, FA07, FA08, FA09, FA10, FA11, FA12, FA13, FA14, FA15, FA16, FA17, FA18, FA19, FA20, Viral11, Alpha10 Pro, Zero 5 neo, Echo8 Se, S26 Ultra, Pixel 9, SP30 Pro, MT Ultimate, M15 pro
Model Difference:	All model's the function, software and electric circuit are the same, only with a product appearance, color and model named different. Test sample mode: I16 Pro max.
Trade Mark:	N/A
FCC ID:	2BDI3-V
Operation Frequency:	IEEE 802.11a/n/ac (HT20)5.745GHz-5.825GHz IEEE 802.11n/ac (HT40)5.755GHz-5.795GHz IEEE 802.11ac (HT80) 5.775GHz
Modulation Technology:	IEEE 802.11a/n/ac
Modulation Type:	256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM
Antenna Type:	FPC Antenna
Antenna Gain:	0.98dBi
Power Source:	DC 5V From Type-C or DC 3.85V From Battery
Power Supply:	DC 5V From Type-C or DC 3.85V From Battery
Hardware Version:	V1.0
Software Version:	V1.0

Note: 1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Antenna gain Refer to the antenna specifications.

2. Antenna gain Refer to the antenna specifications.
3. The cable loss data is obtained from the supplier.

3. The cable loss data is obtained from the supplier.
4. The test results in the report only apply to the tested sample.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2.2. Operation Frequency Each of Channel

802.11a/802.11n(HT20) 802.11ac(HT20)		802.11n(HT40) 802.11ac(HT40)		802.11ac(HT80)	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

2.3. Operation of EUT During Testing

Band IV (5725 - 5850 MHz)

For 802.11a/n (HT20)/ac(HT20)

Channel Number	Channel	Frequency (MHz)
149	Low	5745
157	Mid	5785
165	High	5825

For 802.11n (HT40)/ ac(HT40)

Channel Number	Channel	Frequency (MHz)
151	Low	5755
159	High	5795

For 802.11ac(HT80)

Channel Number	Channel	Frequency (MHz)
155	/	5775


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

2.4. Description of Test Setup


Operation of EUT during AC conducted testing and below 1GHz radiation testing:



Operation of EUT during above 1GHz radiation testing:



Operation of EUT during RF conducted testing:



The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position.



HUAK TESTING

HUAK TESTING

2.5. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Trade Mark	Model/Type No.	Specification	Remark
1	Smart Phone	N/A	I16 Pro max	N/A	EUT
2	USB Cable	N/A	N/A	Length:0.82m	Accessory
3	Adapter	N/A	APD5-2	Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 5V, 2A	Accessory

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6db Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



HUAK TESTING

HUAK TESTING

3. General Information

3.1. Test Environment and Mode


Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
802.11ac(HT20)/ac(HT40)/ac(HT80)	MCS0
Final Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.


Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

4. Test Results and Measurement Data

4.1. AC Power Line Conducted Emission

4.1.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	 <p>Reference Plane</p> <p>40cm</p> <p>E.U.T</p> <p>AC power</p> <p>LISN</p> <p>Filter</p> <p>EMI Receiver</p> <p>Test table/Insulation plane</p> <p>Remark E.U.T Equipment Under Test LISN Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Tx Mode														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Result:	Pass														

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

4.1.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)

Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Receiver	R&S	ESR	HKE-005	Feb. 19, 2025	Feb. 18, 2026
LISN	R&S	ENV216	HKE-002	Feb. 19, 2025	Feb. 18, 2026
LISN	R&S	ENV216	HKE-059	Feb. 19, 2025	Feb. 18, 2026
Coax cable (9KHz-30MHz)	Times	381806-002	N/A	Feb. 19, 2025	Feb. 18, 2026
EMI Test Software	Tonscend	JS32-CE 2.5.0.6	HKE-081	N/A	N/A
10dB Attenuator	Schwarzbeck	VTSD9561F	HKE-153	Feb. 19, 2025	Feb. 18, 2026


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



HUAK TESTING

4.1.3. Test data

Test Model No.: I16 Pro max
Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1725	42.22	19.84	64.84	22.62	22.38	PK	L
2	0.2985	37.43	19.84	60.28	22.85	17.59	PK	L
3	1.0140	39.45	19.87	56.00	16.55	19.58	PK	L
4	1.6890	40.28	19.95	56.00	15.72	20.33	PK	L
5	3.7680	42.22	20.09	56.00	13.78	22.13	PK	L
6	6.4140	38.79	20.08	60.00	21.21	18.71	PK	L

Remark: Margin = Limit – Level

Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor




HUAK TESTING
HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1635	39.81	19.68	65.28	25.47	20.13	PK	N
2	0.2625	38.69	19.73	61.35	22.66	18.96	PK	N
3	0.5730	44.71	19.74	56.00	11.29	24.97	PK	N
4	0.9915	39.08	19.74	56.00	16.92	19.34	PK	N
5	1.6980	39.96	19.82	56.00	16.04	20.14	PK	N
6	3.8040	41.32	19.97	56.00	14.68	21.35	PK	N

Remark: Margin = Limit – Level


Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor



HUAK TESTING

Series Model No.: S26 Ultra
Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1500	46.82	19.83	66.00	19.18	26.99	PK	L
2	0.4875	41.99	19.84	56.21	14.22	22.15	PK	L
3	1.0995	38.35	19.88	56.00	17.65	18.47	PK	L
4	2.3280	40.13	20.00	56.00	15.87	20.13	PK	L
5	4.2765	44.14	20.09	56.00	11.86	24.05	PK	L
6	6.8955	40.22	20.07	60.00	19.78	20.15	PK	L

Remark: Margin = Limit – Level
 Correction factor = Cable loss + LISN insertion loss
 Level=Test receiver reading + correction factor




HUAK TESTING
HUAK TESTING

HUAK TESTING
HUAKE TEST

HUAK TESTING

HUAK TESTING

Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1545	47.75	19.73	65.75	18.00	28.02	PK	N
2	0.6090	37.77	19.74	56.00	18.23	18.03	PK	N
3	1.0995	38.07	19.75	56.00	17.93	18.32	PK	N
4	2.2965	40.95	19.88	56.00	15.05	21.07	PK	N
5	4.2090	42.77	19.98	56.00	13.23	22.79	PK	N
6	7.0440	39.20	19.96	60.00	20.80	19.24	PK	N

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



HUAK TESTING
HUAK TESTING


HUAK TESTING

HUAK TESTING

HUAK TESTING

Series Model No.: Pixel 9
Test Specification: Line

FCC PART 15 C CLASS B(L)



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1545	46.61	19.83	65.75	19.14	24.12	PK	L
2	0.2220	42.07	19.84	62.74	20.67	22.93	PK	L
3	0.3750	37.08	19.85	58.39	21.31	17.93	PK	L
4	0.5640	35.68	19.86	56.00	20.32	15.31	PK	L
5	1.9095	37.32	19.96	56.00	18.68	19.39	PK	L
6	4.0560	43.29	20.09	56.00	12.71	22.52	PK	L

Remark: Margin = Limit - Level

Correction factor = Cable loss + LISN insertion loss

Level = Test receiver reading + correction factor




HUAK TESTING

HUAK TESTING



Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1905	42.94	19.74	64.01	21.07	23.20	PK	N
2	0.2850	40.84	19.73	60.67	19.83	21.11	PK	N
3	0.4695	38.28	19.73	56.52	18.24	18.55	PK	N
4	1.2165	38.12	19.77	56.00	17.88	18.35	PK	N
5	2.2965	40.85	19.88	56.00	15.15	20.97	PK	N
6	4.3080	42.04	19.98	56.00	13.96	22.06	PK	N

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor




HUAK TESTING

HUAK TESTING



Series Model No.: SP30 Pro
Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1500	47.62	19.83	66.00	18.38	27.79	PK	L
2	0.3165	39.35	19.85	59.80	20.45	19.50	PK	L
3	0.5685	38.85	19.86	56.00	17.15	18.99	PK	L
4	1.0995	39.15	19.88	56.00	16.85	19.27	PK	L
5	1.9500	41.18	19.96	56.00	14.82	21.22	PK	L
6	4.2810	45.69	20.09	56.00	10.31	25.60	PK	L

Remark: Margin = Limit – Level

Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




HUAK TESTING

HUAK TESTING



Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1500	45.92	19.73	66.00	20.08	26.19	PK	N
2	0.2850	40.14	19.73	60.67	20.53	20.41	PK	N
3	0.4695	37.58	19.73	56.52	18.94	17.85	PK	N
4	1.6935	38.94	19.82	56.00	17.06	19.12	PK	N
5	4.2990	43.29	19.98	56.00	12.71	23.31	PK	N
6	7.0440	38.40	19.96	60.00	21.60	18.44	PK	N

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss


Level=Test receiver reading + correction factor



HUAK TESTING



Series Model No.: MT Ultimate
Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1500	45.92	19.83	66.00	20.08	26.09	PK	L
2	0.2220	41.17	19.84	62.74	21.57	21.33	PK	L
3	0.3480	36.20	19.83	59.01	22.81	16.37	PK	L
4	0.8160	36.03	19.87	56.00	19.97	16.16	PK	L
5	1.9140	38.73	19.96	56.00	17.27	18.77	PK	L
6	4.2810	43.99	20.09	56.00	12.01	23.90	PK	L

Remark: Margin = Limit - Level

Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor




HUAK TESTING
HUAK TESTING

HUAK TESTING

HUAK TESTING

HUAK TESTING

Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1590	45.78	19.70	65.52	19.74	26.08	PK	N
2	0.4695	37.58	19.73	56.52	18.94	17.85	PK	N
3	1.0995	37.27	19.75	56.00	18.73	17.52	PK	N
4	2.2965	40.15	19.88	56.00	15.85	20.27	PK	N
5	4.2990	43.29	19.98	56.00	12.71	23.31	PK	N
6	7.0440	38.40	19.96	60.00	21.60	18.44	PK	N

Remark: Margin = Limit – Level

Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor




HUAK TESTING

HUAK TESTING



Series Model No.: M15 pro
Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1500	46.32	19.83	66.00	19.68	26.49	PK	L
2	0.2220	41.57	19.84	62.74	21.17	21.73	PK	L
3	0.3750	36.58	19.85	58.39	21.81	16.73	PK	L
4	0.9555	39.93	19.87	56.00	16.07	20.06	PK	L
5	1.9500	39.88	19.96	56.00	16.12	19.92	PK	L
6	4.2810	44.39	20.09	56.00	11.61	24.30	PK	L

Remark: Margin = Limit – Level

Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor




HUAK TESTING
HUAK TESTING

HUAK TESTING
HUAKE TEST

HUAK TESTING

HUAK TESTING

Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1500	46.90	19.73	66.00	19.10	27.17	PK	N
2	0.4155	37.23	19.73	57.54	20.31	17.50	PK	N
3	1.0995	35.97	19.75	56.00	20.03	16.22	PK	N
4	1.9815	38.12	19.84	56.00	17.88	18.28	PK	N
5	4.2990	41.99	19.98	56.00	14.01	22.01	PK	N
6	7.0440	37.10	19.96	60.00	22.90	17.14	PK	N


Remark: Margin = Limit – Level

Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor

4.2. Maximum Conducted Output Power

4.2.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407(a)				
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02.r01 Section E				
Limit:	<table border="1"> <thead> <tr> <th>Frequency Band (MHz)</th> <th>Limit</th> </tr> </thead> <tbody> <tr> <td>5725-5850</td> <td>1 W</td> </tr> </tbody> </table>	Frequency Band (MHz)	Limit	5725-5850	1 W
Frequency Band (MHz)	Limit				
5725-5850	1 W				
Test Setup:					
Test Mode:	Transmitting mode with modulation				
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a. 2. The RF output of EUT was connected to the RF automatic control unit by RF cable. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power and record the results in the test report. 				
Test Result:	PASS				
Remark:	<p>Conducted output power= measurement power +$10\log(1/x)$ X is duty cycle=1, so $10\log(1/1)=0$</p> <p>Conducted output power= measurement power</p>				

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

4.2.2. Test Instruments

RF Test Room

Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 19, 2025	Feb. 18, 2026
Power meter	Agilent	E4419B	HKE-085	Feb. 19, 2025	Feb. 18, 2026
Power Sensor	Agilent	E9300A	HKE-086	Feb. 19, 2025	Feb. 18, 2026
RF cable	Times	1-40G	HKE-034	Feb. 19, 2025	Feb. 18, 2026
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Feb. 19, 2025	Feb. 18, 2026
RF Test Software	Tonscend	JS1120-3 Version 3.5.39	HKE-083	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



HUAK TESTING

HUAK TESTING

Test Data

Configuration Band IV (5725 - 5850 MHz)				
Mode	Test channel	Maximum Conducted Output Power (dBm)	FCC Limit (dBm)	Result
802.11a	CH149	7.58	30	PASS
802.11a	CH157	8.19	30	PASS
802.11a	CH165	8.45	30	PASS
802.11n(HT20)	CH149	7.23	30	PASS
802.11n(HT20)	CH157	7.58	30	PASS
802.11n(HT20)	CH165	8.19	30	PASS
802.11n(HT40)	CH151	6.70	30	PASS
802.11n(HT40)	CH159	7.54	30	PASS
802.11ac(HT20)	CH149	7.26	30	PASS
802.11ac(HT20)	CH157	8.15	30	PASS
802.11ac(HT20)	CH165	7.16	30	PASS
802.11ac(HT40)	CH151	6.75	30	PASS
802.11ac(HT40)	CH159	7.49	30	PASS
802.11ac(HT80)	CH155	7.26	30	PASS

Note: 1. The test results including the cable loss.

4.3. 6db Emission Bandwidth

4.3.1. Test Specification

4.3.2. Test Instruments

RF Test Room					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 19, 2025	Feb. 18, 2026
RF cable	Times	1-40G	HKE-034	Feb. 19, 2025	Feb. 18, 2026
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Feb. 19, 2025	Feb. 18, 2026
RF Test Software	Tonscend	JS1120-3 Version 3.5.39	HKE-083	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



HUAK TESTING

4.3.3. Test data

Band IV (5725 - 5850 MHz)					
Mode	Test Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
802.11a	CH149	5745	15.32	0.5	PASS
802.11a	CH157	5785	15.12	0.5	PASS
802.11a	CH165	5825	15.12	0.5	PASS
802.11n(HT20)	CH149	5745	15.12	0.5	PASS
802.11n(HT20)	CH157	5785	15.12	0.5	PASS
802.11n(HT20)	CH165	5825	15.04	0.5	PASS
802.11n(HT40)	CH151	5755	35.04	0.5	PASS
802.11n(HT40)	CH159	5795	35.12	0.5	PASS
802.11ac(HT20)	CH149	5745	15.08	0.5	PASS
802.11ac(HT20)	CH157	5785	15.20	0.5	PASS
802.11ac(HT20)	CH165	5825	15.08	0.5	PASS
802.11ac(HT40)	CH151	5755	35.12	0.5	PASS
802.11ac(HT40)	CH159	5795	35.12	0.5	PASS
802.11ac(HT80)	CH155	5775	75.20	0.5	PASS

Test plots as follows:



Band IV (5725 – 5850 MHz)


802.11a



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com


Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



802.11ac(HT20)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

802.11ac(HT40)



LOW



High

802.11ac(HT80)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

4.4. 26db Bandwidth and 99% Occupied Bandwidth

4.4.1. Test Specification

Test Requirement:	47 CFR Part 15C Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	No restriction limits
Test Setup:	 <p>Spectrum Analyzer ————— EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth $RBW = 1\% EBW$, $VBW \geq 3RBW$, In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	N/A

4.4.2. Test Instruments

RF Test Room					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 19, 2025	Feb. 18, 2026
RF cable	Times	1-40G	HKE-034	Feb. 19, 2025	Feb. 18, 2026
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Feb. 19, 2025	Feb. 18, 2026
RF Test Software	Tonscend	JS1120-3 Version 3.5.39	HKE-083	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

4.4.3. Test Result

N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

4.5. Power Spectral Density

4.5.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	$\leq 30.00 \text{dBm}/500\text{kHz}$ for Band IV 5725MHz-5850MHz
Test Setup:	 <p>Spectrum Analyzer ————— EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 2. Set RBW = 510 kHz/1 MHz, VBW $\geq 3 \times \text{RBW}$, Sweep time = Auto, Detector = RMS. 3. Allow the sweeps to continue until the trace stabilizes. 4. Use the peak marker function to determine the maximum amplitude level. 5. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS

4.5.2. Test Instruments

RF Test Room					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 19, 2025	Feb. 18, 2026
RF cable	Times	1-40G	HKE-034	Feb. 19, 2025	Feb. 18, 2026
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Feb. 19, 2025	Feb. 18, 2026
RF Test Software	Tonscend	JS1120-3 Version 3.5.39	HKE-083	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



HUAK TESTING

4.5.3. Test data

Configuration Band IV (5725 - 5850 MHz)						
Mode	Test Channel	Level [dBm/510kHz]	10log(500/510)	Power Spectral Density	Limit (dBm/500kHz)	Result
802.11a	CH149	-2.54	-0.086	-2.626	30	PASS
802.11a	CH157	-3.35	-0.086	-3.436	30	PASS
802.11a	CH165	-3.45	-0.086	-3.536	30	PASS
802.11n(HT20)	CH149	-3.11	-0.086	-3.196	30	PASS
802.11n(HT20)	CH157	-3.48	-0.086	-3.566	30	PASS
802.11n(HT20)	CH165	-4.05	-0.086	-4.136	30	PASS
802.11n(HT40)	CH151	-5.82	-0.086	-5.906	30	PASS
802.11n(HT40)	CH159	-6.25	-0.086	-6.336	30	PASS
802.11ac(HT20)	CH149	-3.24	-0.086	-3.326	30	PASS
802.11ac(HT20)	CH157	-3.34	-0.086	-3.426	30	PASS
802.11ac(HT20)	CH165	-3.96	-0.086	-4.046	30	PASS
802.11ac(HT40)	CH151	-5.11	-0.086	-5.196	30	PASS
802.11ac(HT40)	CH159	-6.19	-0.086	-6.276	30	PASS
802.11ac(HT80)	CH155	-8.43	-0.086	-8.516	30	PASS

Note: Power Spectral Density= Level [dBm/510kHz]+ (10log(Limit RBW/Test RBW))

Test plots as follows:

Band IV (5725-5850 MHz)

802.11a




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com


Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

802.11n(HT20)




Frequency
Auto Tune
Center Freq 5.745000000 GHz
Start Freq 5.725000000 GHz
Stop Freq 5.765000000 GHz
CF Step 4.000000 MHz Auto
Freq Offset 0 Hz

Low



Frequency
Auto Tune
Center Freq 5.785000000 GHz
Start Freq 5.765000000 GHz
Stop Freq 5.805000000 GHz
CF Step 4.000000 MHz Auto
Freq Offset 0 Hz

Mid



Frequency
Auto Tune
Center Freq 5.825000000 GHz
Start Freq 5.805000000 GHz
Stop Freq 5.845000000 GHz
CF Step 4.000000 MHz Auto
Freq Offset 0 Hz

High


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



802.11n(HT40)



Frequency

Auto Tune

Center Freq


Start Freq

Stop Freq

CF Step

Freq Offset

LOW



Frequency

Auto Tune

Center Freq

Start Freq

Stop Freq

CF Step

Freq Offset

High

802.11ac(HT20)



Frequency

Auto Tune

Center Freq

Start Freq

Stop Freq

CF Step

Freq Offset

LOW

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAK Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China