



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: QINGDAO HAINERGY TECHNOLOGY CORP., LIMITED

Address: Room 309 (A), Baotai Office Building, No. 45 Beijing Road, Bonded Port Area, Qingdao, SHANDONG, China

FCC ID: 2BDQO-HNBMD14H

Product Name: Personal Computer

Standard(s): 47 CFR Part 15, Subpart E(15.407)

ANSI C63.10-2013

KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: 2403T78885E-RF-00D

Date Of Issue: 2024/6/18

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.1.1 General:.....	6
1.1.2 Operation Frequency Detail:	7
1.1.3 Antenna Information Detail▲:	8
1.1.4 Accessory Information:.....	8
1.2 DESCRIPTION OF TEST CONFIGURATION.....	9
1.2.1 EUT Operation Condition:.....	9
1.2.2 Support Equipment List and Details	11
1.2.3 Support Cable List and Details	11
1.2.4 Block Diagram of Test Setup.....	12
1.3 MEASUREMENT UNCERTAINTY	13
2. SUMMARY OF TEST RESULTS	14
3. REQUIREMENTS AND TEST PROCEDURES	15
3.1 AC LINE CONDUCTED EMISSIONS.....	15
3.1.1 Applicable Standard.....	15
3.1.2 EUT Setup.....	16
3.1.3 EMI Test Receiver Setup	16
3.1.4 Test Procedure	17
3.1.5 Corrected Amplitude & Margin Calculation.....	17
3.2 RADIATION SPURIOUS EMISSIONS.....	18
3.2.1 Applicable Standard.....	18
3.2.2 EUT Setup.....	19
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	20
3.2.4 Test Procedure	21
3.2.5 Corrected Amplitude & Margin Calculation.....	21
3.3 EMISSION BANDWIDTH.....	22
3.3.1 Applicable Standard.....	22
3.3.2 EUT Setup.....	22
3.3.3 Test Procedure	22
3.4 MAXIMUM CONDUCTED OUTPUT POWER.....	25
3.4.1 Applicable Standard.....	25
3.4.2 EUT Setup.....	25
3.4.3 Test Procedure	25
3.5 MAXIMUM POWER SPECTRAL DENSITY.....	26
3.5.1 Applicable Standard.....	26
3.5.2 EUT Setup.....	26
3.5.3 Test Procedure	26
3.6 DUTY CYCLE	28
3.6.1 EUT Setup.....	28
3.6.2 Test Procedure	28
3.7 ANTENNA REQUIREMENT.....	29
3.7.1 Applicable Standard.....	29
3.7.2 Judgment.....	29
4. Test DATA AND RESULTS	30

4.1 AC LINE CONDUCTED EMISSIONS30

4.2 RADIATION SPURIOUS EMISSIONS33

 4.2.1 9 kHz – 1 GHz:33

 4.2.2 1GHz – 40 GHz:36

4.3 MAXIMUM CONDUCTED OUTPUT POWER.....66

4.4 EMISSION BANDWIDTH.....69

4.5 99% OCCUPIED BANDWIDTH.....79

4.6 POWER SPECTRAL DENSITY89

4.7 DUTY CYCLE109

5. EUT PHOTOGRAPHS112

6. TEST SETUP PHOTOGRAPHS113

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2403T78885E-RF-00D	Original Report	2024/6/18

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

1.1.1 General:

EUT Name:	Personal Computer
Trade Name:	
EUT Model:	HNBMD14HAWREG
Operation Frequency:	Band1: 5180-5240 MHz(802.11a/n ht20/ac vht20) 5190-5230 MHz(802.11n ht40/ac vht40) 5210 MHz(802.11ac vht80) Band2: 5260-5320 MHz (802.11a/n ht20/ac vht20) 5270-5310 MHz(802.11n ht40/ac vht40) 5290 MHz(802.11ac vht80) Band3: 5500-5720 MHz (802.11a/n ht20/ac vht20) 5510-5710 MHz(802.11n ht40/vht40) 5530-5690MHz(802.11ac vht80) Band4: 5745-5825 MHz (802.11a/n ht20/ac vht20) 5755-5795 MHz(802.11n ht40/ac vht40) 5775 MHz(802.11ac vht80)
Maximum Average Conducted Output Power:	13.46 dBm (5150-5250MHz Band) 13.30 dBm (5250-5350MHz Band) 15.61 dBm (5470-5725MHz Band) 11.59 dBm (5725-5825MHz Band)
Modulation Type:	802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM,256QAM
Rated Input Voltage:	DC 19V from adapter or DC 11.4V from battery
Serial Number:	RF:2MBO-2 CE&RE: 2MBO-1
EUT Received Date:	2024/5/30
EUT Received Status:	Good

1.1.2 Operation Frequency Detail:**For 802.11a/n ht20/ac vht20:**

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	56	5280	104	5520	153	5765
44	5220	60	5300	108	5540	157	5785
48	5240	64	5320	112	5560	161	5805
/	/	/	/	116	5580	165	5825
/	/	/	/	120	5600	/	/
/	/	/	/	124	5620	/	/
/	/	/	/	128	5640	/	/
/	/	/	/	132	5660	/	/
/	/	/	/	136	5680	/	/
/	/	/	/	140	5700	/	/
/	/	/	/	144	5720	/	/

Per section 15.31(m), the below channels were performed the test as below:

Test Channel	Test Frequency (MHz)			
	5150-5250 MHz	5250-5350 MHz	5470-5725 MHz	5725-5850 MHz
Lowest	5180	5260	5500	5745
Middle	5200	5280	5580	5785
Highest	5240	5320	5700	5825
Additional	/	/	5720	/

For 802.11n ht40/ac vht40:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
/	/	/	/	118	5590	/	/
/	/	/	/	126	5630	/	/
/	/	/	/	134	5670	/	/
/	/	/	/	142	5710	/	/

Per section 15.31(m), the below channels were performed the test as below:

Test Channel	Test Frequency (MHz)			
	5150-5250 MHz	5250-5350 MHz	5470-5725 MHz	5725-5850 MHz
Lowest	5190	5270	5510	5755
Middle	/	/	5550	/
Highest	5230	5310	5670	5795
Additional	/	/	5710	/

For 802.11ac vht80:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
/	/	/	/	122	5610	/	/
/	/	/	/	138	5690	/	/

Per section 15.31(m), the below channels were performed the test as below:

Test Channel	Test Frequency (MHz)			
	5150-5250 MHz	5250-5350 MHz	5470-5725 MHz	5725-5850 MHz
Lowest	/	/	5530	/
Middle	5210	5290	/	5775
Highest	/	/	5610	/
Additional	/	/	5690	/

Note: Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

1.1.3 Antenna Information Detail▲ :

Antenna	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
MAIN(Chain 0)	FPC	50	5.15~5.85GHz	2.37
			5.25~5.35 GHz	2.37
			5.47~5.725 GHz	4.6
			5.725~5.85 GHz	4.6
AUX(Chain 1)	FPC	50	5.15~5.85GHz	1.84
			5.25~5.35 GHz	2.01
			5.47~5.725 GHz	3.57
			5.725~5.85 GHz	3.79

The Method of §15.203 Compliance:

- ☒ Antenna was permanently attached to the unit.
☐ Antenna uses a unique type of connector to attach to the EUT.
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

1.1.4 Accessory Information:

Accessory Description	Manufacturer	Model
Adapter	SHENZHEN BSY TECHNOLOGY CO.,LTD	BSY065T1903423 D

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.			
Equipment Modifications:		No			
EUT Exercise Software:		DRTU.exe			
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:					
5150-5250 MHz Band:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5180	MCS0	Default	Default
	Middle	5200	6Mbps	Default	Default
	Highest	5240	6Mbps	Default	Default
802.11n ht20	Lowest	5180	MCS0	Default	Default
	Middle	5200	MCS0	Default	Default
	Highest	5240	MCS0	Default	Default
802.11n ht40	Lowest	5190	MCS0	Default	Default
	Highest	5230	MCS0	Default	Default
802.11ac vht80	Middle	5210	MCS0	Default	Default
5250-5350 MHz Band:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5260	6Mbps	Default	Default
	Middle	5280	6Mbps	Default	Default
	Highest	5320	6Mbps	Default	Default
802.11n ht20	Lowest	5260	MCS0	Default	Default
	Middle	5280	MCS0	Default	Default
	Highest	5320	MCS0	Default	Default
802.11n ht40	Lowest	5270	MCS0	Default	Default
	Highest	5310	MCS0	Default	Default
802.11ac vht80	Middle	5290	MCS0	Default	Default

5470-5725 MHz Band:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5500	6Mbps	Default	Default
	Middle	5580	6Mbps	Default	Default
	Highest	5700	6Mbps	Default	Default
	Cross	5720	6Mbps	Default	Default
802.11n ht20	Lowest	5500	MCS0	Default	Default
	Middle	5580	MCS0	Default	Default
	Highest	5700	MCS0	Default	Default
	Cross	5720	MCS0	Default	Default
802.11n ht40	Lowest	5510	MCS0	Default	Default
	Middle	5550	MCS0	Default	Default
	Highest	5670	MCS0	Default	Default
	Cross	5710	MCS0	Default	Default
802.11ac vht80	Lowest	5530	MCS0	Default	Default
	Middle	5610	MCS0	Default	Default
	Highest	5690	MCS0	Default	Default
5725-5850 MHz Band:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5745	6Mbps	Default	Default
	Middle	5785	6Mbps	Default	Default
	Highest	5825	6Mbps	Default	Default
802.11n ht20	Lowest	5745	MCS0	Default	Default
	Middle	5785	MCS0	Default	Default
	Highest	5825	MCS0	Default	Default
802.11n ht40	Lowest	5755	MCS0	Default	Default
	Highest	5795	MCS0	Default	Default
802.11ac vht80	Middle	5775	MCS0	Default	Default
Note: 1. The system support 802.11a/n ht20/n ht40/ac vht20/vht40/vht80, the vht20/vht40 were reduced since the identical parameters with 802.11n ht20 and ht40. 2. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. 3. The device supports SISO in all modes and MIMO in 802.11n/ac modes, per pretest, MIMO mode was the worst mode and reported for 802.11n/ac modes.					

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
PHILIPS	Keyboard	SPT6234	K234210510746
PHILIPS	Mouse	SPT6234	C234210506222
CLC	Earphone	Whiteview5.0	EP21106054
DongFeng	Phone	P3	UP3_BSGF187E000165
ViewSonic	Monitor	VX1630-4K-HD	W9F203900071
ViewSonic	Adapter	HKA01212010-XQ	H12G94218P010302
SanDisk	TF Card	16 GB	1183DRECV11N

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Power Cable	NO	NO	1.2	Adapter	EUT
Keyboard Cable	NO	NO	1.5	EUT	Keyboard
Mouse Cable	NO	NO	1.5	EUT	Mouse
HDMI Cable	NO	NO	1.2	EUT	Monitor
Earphone Cable	NO	NO	1.2	EUT	Earphone
Power Cable	NO	Yes	1.5	Monitor	Adapter
USB Cable	NO	NO	1	EUT	Phone

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9k~30MHz: 4.12dB, 30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC Line Conducted Emissions	Pass
FCC §15.207(a)	Undesirable Emission& Restricted Bands	Pass
FCC§15.407(a) (e)	Emission Bandwidth	Pass
FCC§15.407(a) (e)	99% Occupied Bandwidth	Pass
FCC§15.407 (a)	Maximum Conducted Output Power	Pass
FCC§15.407 (a)	Power Spectral Density	Pass
C63.10 §11.6	Duty Cycle	Pass

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions

3.2.1 Applicable Standard


FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.
- (10) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.
- (c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

3.2.2 EUT Setup


9kHz - 30MHz:




30MHz - 1GHz:



1GHz - 26.5GHz:



26.5GHz - 40 GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was FCC 15.209, FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	300 Hz	1 kHz	/	PK
	/	/	200 Hz	QP/AV
150 kHz – 30 MHz	10 kHz	30 kHz	/	PK
	/	/	9 kHz	QP/AV
30 MHz – 1000 MHz	100 kHz	300 kHz	/	PK
	/	/	120 kHz	QP

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	≥1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9–90 kHz, 110–490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$ dB = 6.02 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

For 9kHz-26.5GHz:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For 26.5GHz-40GHz

Factor = Antenna Factor + Cable Loss- Amplifier Gain -Distance extrapolation Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.3 Emission Bandwidth

3.3.1 Applicable Standard


FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2013 Section 12.4.1

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) ≥ 3 RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.4 Maximum Conducted Output Power

3.4.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 12.3.3.1

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.5.3 Maximum Power Spectral Density

3.5.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle <98%, duty cycle variations exceed $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

3.6 Duty Cycle

3.6.1 EUT Setup



3.6.2 Test Procedure

According to ANSI C63.10-2013 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.7 Antenna Requirement

3.7.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Judgment

Result: Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	2MBO-1	Test Date:	2024/6/6
Test Site:	CE	Test Mode:	Transmitting(maximum output power mode, 802.11n ht40 5550MHz)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	27.4	Relative Humidity: (%)	66	ATM Pressure: (kPa)	100.1
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101132	2024/4/1	2025/3/31
R&S	EMI Test Receiver	ESR3	103104	2024/5/10	2025/5/9
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2024/1/15	2025/1/14
Audix	Test Software	E3	191218 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Project No.: 2403T78885E-RF
 Tester: David Huang
 Port: Line
 Note: Transmitting(5G WIFI)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.151	41.32	10.31	51.63	65.96	14.33	QP
2	0.151	14.94	10.31	25.25	55.96	30.71	Average
3	0.198	40.31	10.02	50.33	63.67	13.34	QP
4	0.198	23.97	10.02	33.99	53.67	19.68	Average
5	0.253	32.90	10.10	43.00	61.66	18.66	QP
6	0.253	16.67	10.10	26.77	51.66	24.89	Average
7	3.589	32.97	10.29	43.26	56.00	12.74	QP
8	3.589	17.10	10.29	27.39	46.00	18.61	Average
9	5.306	31.90	10.39	42.29	60.00	17.71	QP
10	5.306	22.23	10.39	32.62	50.00	17.38	Average
11	17.006	25.60	10.17	35.77	60.00	24.23	QP
12	17.006	18.01	10.17	28.18	50.00	21.82	Average

Project No.: 2403T78885E-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(5G WIFI)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.151	41.04	10.51	51.55	65.95	14.40	QP
2	0.151	14.83	10.51	25.34	55.95	30.61	Average
3	0.187	37.89	10.51	48.40	64.17	15.77	QP
4	0.187	15.66	10.51	26.17	54.17	28.00	Average
5	0.257	33.49	10.53	44.02	61.53	17.51	QP
6	0.257	18.52	10.53	29.05	51.53	22.48	Average
7	3.643	34.30	10.37	44.67	56.00	11.33	QP
8	3.643	17.48	10.37	27.85	46.00	18.15	Average
9	5.152	32.06	10.32	42.38	60.00	17.62	QP
10	5.152	22.37	10.32	32.69	50.00	17.31	Average
11	17.598	25.81	10.06	35.87	60.00	24.13	QP
12	17.598	18.71	10.06	28.77	50.00	21.23	Average

4.2 Radiation Spurious Emissions

4.2.1 9 kHz – 1 GHz:

Serial Number:	2MBO-1	Test Date:	2024/6/7
Test Site:	966-2	Test Mode:	Transmitting(maximum output power mode, 802.11n ht40 5550MHz)
Tester:	Carl Xue	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.8	Relative Humidity: (%)	59	ATM Pressure: (kPa)	100.2
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2023/12/1	2026/11/30
BACL	Loop Antenna	1313-1A	3110611	2023/12/4	2026/12/3
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0300-01	2024/1/11	2025/1/10
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0500-01	2024/1/11	2025/1/10
R&S	EMI Test Receiver	ESR3	102724	2024/2/29	2025/2/28
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0100-03	2023/12/4	2024/12/3
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0370-01	2023/12/4	2024/12/3
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/12/4	2024/12/3
Sonoma	Amplifier	310N	186165	2023/12/4	2024/12/3
Audix	Test Software	E3	191218 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.
For 9kHz-30MHz, The amplitude of spurious emissions attenuated more than 20 dB below the limit was not be reported.

Project No.: 2403T78885E-RF
Tester: Carl Xue
Polarization: horizontal
Note: Transmitting 5G WIFI



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	84.110	50.33	-17.24	33.09	40.00	6.91	Peak
2	133.151	48.04	-11.47	36.57	43.50	6.93	Peak
3	266.609	50.48	-11.05	39.43	46.00	6.57	Peak
4	297.224	48.78	-10.50	38.28	46.00	7.72	Peak
5	494.199	45.42	-5.89	39.53	46.00	6.47	Peak
6	668.142	42.66	-3.48	39.18	46.00	6.82	Peak

Project No.: 2403T78885E-RF
Tester: Carl Xue
Polarization: vertical
Note: Transmitting 5G WIFI



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.319	34.03	-4.06	29.97	40.00	10.03	QP
2	444.851	44.35	-6.90	37.45	46.00	8.55	Peak
3	481.218	36.74	-6.15	30.59	46.00	15.41	QP
4	504.254	37.39	-5.77	31.62	46.00	14.38	QP
5	517.041	36.11	-5.63	30.48	46.00	15.52	QP
6	663.473	40.67	-3.44	37.23	46.00	8.77	Peak

4.2.2 1GHz – 40 GHz:

Serial Number:	2MBO-1	Test Date:	2024/6/13-2024/6/14
Test Site:	966-1	Test Mode:	Transmitting
Tester:	Tao Zhu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.6-26.8	Relative Humidity: (%)	65	ATM Pressure: (kPa)	99.7-99.9
----------------------	-----------	---------------------------	----	---------------------------	-----------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2023/12/6	2026/12/5
R&S	Spectrum Analyzer	FSV40	101591	2024/4/1	2025/3/31
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2024/1/15	2025/1/14
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2024/1/15	2025/1/14
BACL	Preamplifier	1313-A20M18G	4032311	2024/4/1	2025/3/31
Audix	Test Software	E3	191218 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2024/2/4	2027/2/3
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2024/1/15	2025/1/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2024/1/15	2025/1/14
E-Microwave	Band Rejection Filter	5150-5850MHz	OE01902423	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2024/2/4	2027/2/3

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

5150-5250MHz:**802.11a Mode Chain 0:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5180	MHz		
5150.000	44.69	PK	H	9.48	54.17	74.00	19.83
5150.000	31.52	AV	H	9.48	41.00	54.00	13.00
5150.000	44.39	PK	V	9.48	53.87	74.00	20.13
5150.000	31.58	AV	V	9.48	41.06	54.00	12.94
10360.000	36.47	PK	H	13.24	49.71	68.20	18.49
10360.000	36.23	PK	V	13.24	49.47	68.20	18.73
15540.000	36.08	PK	H	17.28	53.36	74.00	20.64
15540.000	23.21	AV	H	17.28	40.49	54.00	13.51
15540.000	35.84	PK	V	17.28	53.12	74.00	20.88
15540.000	22.69	AV	V	17.28	39.97	54.00	14.03
Middle Channel:				5200	MHz		
10400.000	36.24	PK	H	13.61	49.85	68.20	18.35
10400.000	35.63	PK	V	13.61	49.24	68.20	18.96
15600.000	37.76	PK	H	16.58	54.34	74.00	19.66
15600.000	24.28	AV	H	16.58	40.86	54.00	13.14
15600.000	37.21	PK	V	16.58	53.79	74.00	20.21
15600.000	24.31	AV	V	16.58	40.89	54.00	13.11
High Channel:				5240	MHz		
5350.000	44.21	PK	H	9.34	53.55	74.00	20.45
5350.000	31.19	AV	H	9.34	40.53	54.00	13.47
5350.000	44.28	PK	V	9.34	53.62	74.00	20.38
5350.000	31.27	AV	V	9.34	40.61	54.00	13.39
10480.000	34.54	PK	H	14.13	48.67	68.20	19.53
10480.000	35.11	PK	V	14.13	49.24	68.20	18.96
15720.000	39.16	PK	H	16.07	55.23	74.00	18.77
15720.000	26.34	AV	H	16.07	42.41	54.00	11.59
15720.000	39.24	PK	V	16.07	55.31	74.00	18.69
15720.000	26.20	AV	V	16.07	42.27	54.00	11.73

802.11a Mode Chain 1:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5180	MHz		
5150.000	43.69	PK	H	9.48	53.17	74.00	20.83
5150.000	30.20	AV	H	9.48	39.68	54.00	14.32
5150.000	43.58	PK	V	9.48	53.06	74.00	20.94
5150.000	30.69	AV	V	9.48	40.17	54.00	13.83
10360.000	36.20	PK	H	13.24	49.44	68.20	18.76
10360.000	36.18	PK	V	13.24	49.42	68.20	18.78
15540.000	36.26	PK	H	17.28	53.54	74.00	20.46
15540.000	23.05	AV	H	17.28	40.33	54.00	13.67
15540.000	36.47	PK	V	17.28	53.75	74.00	20.25
15540.000	23.24	AV	V	17.28	40.52	54.00	13.48
Middle Channel:				5200	MHz		
10400.000	36.14	PK	H	13.61	49.75	68.20	18.45
10400.000	35.88	PK	V	13.61	49.49	68.20	18.71
15600.000	40.46	PK	H	16.58	57.04	74.00	16.96
15600.000	27.65	AV	H	16.58	44.23	54.00	9.77
15600.000	40.21	PK	V	16.58	56.79	74.00	17.21
15600.000	27.53	AV	V	16.58	44.11	54.00	9.89
High Channel:				5240	MHz		
5350.000	42.92	PK	H	9.34	52.26	74.00	21.74
5350.000	29.88	AV	H	9.34	39.22	54.00	14.78
5350.000	43.35	PK	V	9.34	52.69	74.00	21.31
5350.000	30.32	AV	V	9.34	39.66	54.00	14.34
10480.000	35.21	PK	H	14.13	49.34	68.20	18.86
10480.000	35.32	PK	V	14.13	49.45	68.20	18.75
15720.000	38.47	PK	H	16.07	54.54	74.00	19.46
15720.000	25.69	AV	H	16.07	41.76	54.00	12.24
15720.000	38.66	PK	V	16.07	54.73	74.00	19.27
15720.000	25.46	AV	V	16.07	41.53	54.00	12.47

802.11n20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5180	MHz		
5150.000	43.87	PK	H	9.48	53.35	74.00	20.65
5150.000	30.63	AV	H	9.48	40.11	54.00	13.89
5150.000	44.23	PK	V	9.48	53.71	74.00	20.29
5150.000	31.54	AV	V	9.48	41.02	54.00	12.98
10360.000	36.35	PK	H	13.24	49.59	68.20	18.61
10360.000	34.72	PK	V	13.24	47.96	68.20	20.24
15540.000	35.31	PK	H	17.28	52.59	74.00	21.41
15540.000	22.28	AV	H	17.28	39.56	54.00	14.44
15540.000	35.53	PK	V	17.28	52.81	74.00	21.19
15540.000	22.17	AV	V	17.28	39.45	54.00	14.55
Middle Channel:				5200	MHz		
10400.000	36.46	PK	H	13.61	50.07	68.20	18.13
10400.000	35.55	PK	V	13.61	49.16	68.20	19.04
15600.000	37.59	PK	H	16.58	54.17	74.00	19.83
15600.000	24.63	AV	H	16.58	41.21	54.00	12.79
15600.000	37.12	PK	V	16.58	53.70	74.00	20.30
15600.000	24.36	AV	V	16.58	40.94	54.00	13.06
High Channel:				5240	MHz		
5350.000	43.39	PK	H	9.34	52.73	74.00	21.27
5350.000	30.54	AV	H	9.34	39.88	54.00	14.12
5350.000	43.87	PK	V	9.34	53.21	74.00	20.79
5350.000	30.69	AV	V	9.34	40.03	54.00	13.97
10480.000	35.72	PK	H	14.13	49.85	68.20	18.35
10480.000	35.20	PK	V	14.13	49.33	68.20	18.87
15720.000	39.69	PK	H	16.07	55.76	74.00	18.24
15720.000	26.38	AV	H	16.07	42.45	54.00	11.55
15720.000	38.47	PK	V	16.07	54.54	74.00	19.46
15720.000	25.67	AV	V	16.07	41.74	54.00	12.26

802.11n40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5190	MHz		
5150.000	44.62	PK	H	9.48	54.10	74.00	19.90
5150.000	31.66	AV	H	9.48	41.14	54.00	12.86
5150.000	44.57	PK	V	9.48	54.05	74.00	19.95
5150.000	31.38	AV	V	9.48	40.86	54.00	13.14
10380.000	35.50	PK	H	13.43	48.93	68.20	19.27
10380.000	35.26	PK	V	13.43	48.69	68.20	19.51
15570.000	35.22	PK	H	16.93	52.15	74.00	21.85
15570.000	22.17	AV	H	16.93	39.10	54.00	14.90
15570.000	36.59	PK	V	16.93	53.52	74.00	20.48
15570.000	23.57	AV	V	16.93	40.50	54.00	13.50
High Channel:				5230	MHz		
5350.000	44.56	PK	H	9.34	53.90	74.00	20.10
5350.000	31.34	AV	H	9.34	40.68	54.00	13.32
5350.000	44.37	PK	V	9.34	53.71	74.00	20.29
5350.000	31.50	AV	V	9.34	40.84	54.00	13.16
10460.000	35.62	PK	H	14.00	49.62	68.20	18.58
10460.000	35.20	PK	V	14.00	49.20	68.20	19.00
15690.000	38.50	PK	H	15.98	54.48	74.00	19.52
15690.000	25.19	AV	H	15.98	41.17	54.00	12.83
15690.000	38.34	PK	V	15.98	54.32	74.00	19.68
15690.000	25.29	AV	V	15.98	41.27	54.00	12.73

802.11ac80 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Middle Channel:				5210	MHz		
5150.000	44.68	PK	H	9.48	54.16	74.00	19.84
5150.000	31.56	AV	H	9.48	41.04	54.00	12.96
5150.000	44.97	PK	V	9.48	54.45	74.00	19.55
5150.000	32.03	AV	V	9.48	41.51	54.00	12.49
5350.000	44.54	PK	H	9.34	53.88	74.00	20.12
5350.000	31.44	AV	H	9.34	40.78	54.00	13.22
5350.000	45.63	PK	V	9.34	54.97	74.00	19.03
5350.000	32.22	AV	V	9.34	41.56	54.00	12.44
10420.000	37.41	PK	H	13.74	51.15	68.20	17.05
10420.000	37.78	PK	V	13.74	51.52	68.20	16.68
15630.000	37.49	PK	H	16.38	53.87	74.00	20.13
15630.000	24.69	AV	H	16.38	41.07	54.00	12.93
15630.000	37.19	PK	V	16.38	53.57	74.00	20.43
15630.000	24.63	AV	V	16.38	41.01	54.00	12.99

5250-5350MHz:**802.11a Mode Chain 0:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5260	MHz		
5150.000	43.87	PK	H	9.48	53.35	74.00	20.65
5150.000	30.58	AV	H	9.48	40.06	54.00	13.94
5150.000	43.68	PK	V	9.48	53.16	74.00	20.84
5150.000	31.02	AV	V	9.48	40.50	54.00	13.50
10520.000	34.12	PK	H	14.35	48.47	68.20	19.73
10520.000	34.56	PK	V	14.35	48.91	68.20	19.29
15780.000	37.60	PK	H	16.56	54.16	74.00	19.84
15780.000	24.65	AV	H	16.56	41.21	54.00	12.79
15780.000	37.54	PK	V	16.56	54.10	74.00	19.90
15780.000	24.63	AV	V	16.56	41.19	54.00	12.81
Middle Channel:				5280	MHz		
10560.000	35.10	PK	H	14.54	49.64	68.20	18.56
10560.000	35.33	PK	V	14.54	49.87	68.20	18.33
15840.000	36.28	PK	H	17.07	53.35	74.00	20.65
15840.000	23.27	AV	H	17.07	40.34	54.00	13.66
15840.000	36.31	PK	V	17.07	53.38	74.00	20.62
15840.000	23.66	AV	V	17.07	40.73	54.00	13.27
High Channel:				5320	MHz		
5350.000	43.66	PK	H	9.34	53.00	74.00	21.00
5350.000	30.41	AV	H	9.34	39.75	54.00	14.25
5350.000	43.68	PK	V	9.34	53.02	74.00	20.98
5350.000	30.55	AV	V	9.34	39.89	54.00	14.11
10640.000	34.72	PK	H	13.87	48.59	74.00	25.41
10640.000	21.02	AV	H	13.87	34.89	54.00	19.11
10640.000	34.36	PK	V	13.87	48.23	74.00	25.77
10640.000	21.11	AV	V	13.87	34.98	54.00	19.02
15960.000	38.04	PK	H	17.44	55.48	74.00	18.52
15960.000	25.41	AV	H	17.44	42.85	54.00	11.15
15960.000	38.27	PK	V	17.44	55.71	74.00	18.29
15960.000	25.33	AV	V	17.44	42.77	54.00	11.23

802.11a Mode Chain 1:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5260	MHz		
5150.000	42.98	PK	H	9.48	52.46	74.00	21.54
5150.000	29.87	AV	H	9.48	39.35	54.00	14.65
5150.000	43.34	PK	V	9.48	52.82	74.00	21.18
5150.000	30.66	AV	V	9.48	40.14	54.00	13.86
10520.000	35.24	PK	H	14.35	49.59	68.20	18.61
10520.000	34.29	PK	V	14.35	48.64	68.20	19.56
15780.000	37.42	PK	H	16.56	53.98	74.00	20.02
15780.000	24.56	AV	H	16.56	41.12	54.00	12.88
15780.000	37.63	PK	V	16.56	54.19	74.00	19.81
15780.000	23.88	AV	V	16.56	40.44	54.00	13.56
Middle Channel:				5280	MHz		
10560.000	34.66	PK	H	14.54	49.20	68.20	19.00
10560.000	34.58	PK	V	14.54	49.12	68.20	19.08
15840.000	35.99	PK	H	17.07	53.06	74.00	20.94
15840.000	22.58	AV	H	17.07	39.65	54.00	14.35
15840.000	35.47	PK	V	17.07	52.54	74.00	21.46
15840.000	22.31	AV	V	17.07	39.38	54.00	14.62
High Channel:				5320	MHz		
5350.000	45.32	PK	H	9.34	54.66	74.00	19.34
5350.000	32.29	AV	H	9.34	41.63	54.00	12.37
5350.000	45.70	PK	V	9.34	55.04	74.00	18.96
5350.000	32.85	AV	V	9.34	42.19	54.00	11.81
10640.000	35.09	PK	H	13.87	48.96	74.00	25.04
10640.000	21.88	AV	H	13.87	35.75	54.00	18.25
10640.000	35.23	PK	V	13.87	49.10	74.00	24.90
10640.000	21.74	AV	V	13.87	35.61	54.00	18.39
15960.000	37.44	PK	H	17.44	54.88	74.00	19.12
15960.000	24.74	AV	H	17.44	42.18	54.00	11.82
15960.000	37.69	PK	V	17.44	55.13	74.00	18.87
15960.000	23.87	AV	V	17.44	41.31	54.00	12.69

802.11n20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 5260 MHz							
5150.000	43.12	PK	H	9.48	52.60	74.00	21.40
5150.000	30.08	AV	H	9.48	39.56	54.00	14.44
5150.000	43.22	PK	V	9.48	52.70	74.00	21.30
5150.000	30.34	AV	V	9.48	39.82	54.00	14.18
10520.000	34.51	PK	H	14.35	48.86	68.20	19.34
10520.000	34.20	PK	V	14.35	48.55	68.20	19.65
15780.000	37.65	PK	H	16.56	54.21	74.00	19.79
15780.000	24.56	AV	H	16.56	41.12	54.00	12.88
15780.000	37.11	PK	V	16.56	53.67	74.00	20.33
15780.000	24.39	AV	V	16.56	40.95	54.00	13.05
Middle Channel: 5280 MHz							
10560.000	35.10	PK	H	14.54	49.64	68.20	18.56
10560.000	35.22	PK	V	14.54	49.76	68.20	18.44
15840.000	35.65	PK	H	17.07	52.72	74.00	21.28
15840.000	22.70	AV	H	17.07	39.77	54.00	14.23
15840.000	35.58	PK	V	17.07	52.65	74.00	21.35
15840.000	22.65	AV	V	17.07	39.72	54.00	14.28
High Channel: 5320 MHz							
5350.000	45.28	PK	H	9.34	54.62	74.00	19.38
5350.000	32.10	AV	H	9.34	41.44	54.00	12.56
5350.000	45.56	PK	V	9.34	54.90	74.00	19.10
5350.000	32.69	AV	V	9.34	42.03	54.00	11.97
10640.000	36.20	PK	H	13.87	50.07	74.00	23.93
10640.000	22.90	AV	H	13.87	36.77	54.00	17.23
10640.000	35.84	PK	V	13.87	49.71	74.00	24.29
10640.000	22.21	AV	V	13.87	36.08	54.00	17.92
15960.000	37.92	PK	H	17.44	55.36	74.00	18.64
15960.000	23.68	AV	H	17.44	41.12	54.00	12.88
15960.000	37.84	PK	V	17.44	55.28	74.00	18.72
15960.000	23.55	AV	V	17.44	40.99	54.00	13.01

802.11n40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 5270 MHz							
5150.000	43.20	PK	H	9.48	52.68	74.00	21.32
5150.000	30.26	AV	H	9.48	39.74	54.00	14.26
5150.000	44.02	PK	V	9.48	53.50	74.00	20.50
5150.000	30.18	AV	V	9.48	39.66	54.00	14.34
10540.000	33.89	PK	H	14.44	48.33	68.20	19.87
10540.000	34.10	PK	V	14.44	48.54	68.20	19.66
15810.000	38.32	PK	H	16.80	55.12	74.00	18.88
15810.000	25.28	AV	H	16.80	42.08	54.00	11.92
15810.000	38.37	PK	V	16.80	55.17	74.00	18.83
15810.000	25.43	AV	V	16.80	42.23	54.00	11.77
High Channel: 5310 MHz							
5350.000	45.38	PK	H	9.34	54.72	74.00	19.28
5350.000	32.41	AV	H	9.34	41.75	54.00	12.25
5350.000	45.62	PK	V	9.34	54.96	74.00	19.04
5350.000	32.56	AV	V	9.34	41.90	54.00	12.10
10620.000	36.30	PK	H	14.29	50.59	74.00	23.41
10620.000	23.35	AV	H	14.29	37.64	54.00	16.36
10620.000	36.38	PK	V	14.29	50.67	74.00	23.33
10620.000	22.97	AV	V	14.29	37.26	54.00	16.74
15930.000	34.12	PK	H	17.53	51.65	74.00	22.35
15930.000	21.28	AV	H	17.53	38.81	54.00	15.19
15930.000	33.96	PK	V	17.53	51.49	74.00	22.51
15930.000	20.11	AV	V	17.53	37.64	54.00	16.36

802.11ac80 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Middle Channel:				5290	MHz		
5150.000	42.98	PK	H	9.48	52.46	74.00	21.54
5150.000	29.66	AV	H	9.48	39.14	54.00	14.86
5150.000	43.25	PK	V	9.48	52.73	74.00	21.27
5150.000	30.14	AV	V	9.48	39.62	54.00	14.38
5350.000	42.51	PK	H	9.34	51.85	74.00	22.15
5350.000	30.05	AV	H	9.34	39.39	54.00	14.61
5350.000	43.56	PK	V	9.34	52.90	74.00	21.10
5350.000	30.11	AV	V	9.34	39.45	54.00	14.55
10580.000	34.98	PK	H	14.63	49.61	68.20	18.59
10580.000	34.61	PK	V	14.63	49.24	68.20	18.96
15870.000	35.92	PK	H	17.34	53.26	74.00	20.74
15870.000	22.20	AV	H	17.34	39.54	54.00	14.46
15870.000	36.30	PK	V	17.34	53.64	74.00	20.36
15870.000	23.06	AV	V	17.34	40.40	54.00	13.60

5470-5725MHz**802.11a Mode Chain 0:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5500	MHz		
5470.000	43.25	PK	H	10.09	53.34	68.20	14.86
5470.000	43.09	PK	V	10.09	53.18	68.20	15.02
11000.000	35.04	PK	H	14.62	49.66	74.00	24.34
11000.000	22.39	AV	H	14.62	37.01	54.00	16.99
11000.000	35.20	PK	V	14.62	49.82	74.00	24.18
11000.000	22.41	AV	V	14.62	37.03	54.00	16.97
16500.000	35.86	PK	H	18.36	54.22	68.20	13.98
16500.000	35.40	PK	V	18.36	53.76	68.20	14.44
Middle Channel:				5580	MHz		
11160.000	35.90	PK	H	14.64	50.54	74.00	23.46
11160.000	22.14	AV	H	14.64	36.78	54.00	17.22
11160.000	35.67	PK	V	14.64	50.31	74.00	23.69
11160.000	22.26	AV	V	14.64	36.90	54.00	17.10
16740.000	36.55	PK	H	18.30	54.85	68.20	13.35
16740.000	36.78	PK	V	18.30	55.08	68.20	13.12
High Channel:				5700	MHz		
5725.000	42.82	PK	H	9.41	52.23	68.20	15.97
5725.000	43.12	PK	V	9.41	52.53	68.20	15.67
11400.000	35.63	PK	H	13.59	49.22	74.00	24.78
11400.000	22.52	AV	H	13.59	36.11	54.00	17.89
11400.000	35.30	PK	V	13.59	48.89	74.00	25.11
11400.000	22.21	AV	V	13.59	35.80	54.00	18.20
17100.000	36.00	PK	H	21.60	57.60	68.20	10.60
17100.000	36.32	PK	H	21.60	57.92	68.20	10.28

802.11a Mode Chain 1:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5500	MHz		
5470.000	42.78	PK	H	10.09	52.87	68.20	15.33
5470.000	43.18	PK	V	10.09	53.27	68.20	14.93
11000.000	35.00	PK	H	14.62	49.62	74.00	24.38
11000.000	22.20	AV	H	14.62	36.82	54.00	17.18
11000.000	35.31	PK	V	14.62	49.93	74.00	24.07
11000.000	22.17	AV	V	14.62	36.79	54.00	17.21
16500.000	36.97	PK	H	18.36	55.33	68.20	12.87
16500.000	36.68	PK	V	18.36	55.04	68.20	13.16
Middle Channel:				5580	MHz		
11160.000	36.31	PK	H	14.64	50.95	74.00	23.05
11160.000	23.34	AV	H	14.64	37.98	54.00	16.02
11160.000	36.25	PK	V	14.64	50.89	74.00	23.11
11160.000	23.12	AV	V	14.64	37.76	54.00	16.24
16740.000	37.68	PK	H	18.30	55.98	68.20	12.22
16740.000	37.59	PK	V	18.30	55.89	68.20	12.31
High Channel:				5700	MHz		
5725.000	43.36	PK	H	9.41	52.77	68.20	15.43
5725.000	43.20	PK	V	9.41	52.61	68.20	15.59
11400.000	36.23	PK	H	13.59	49.82	74.00	24.18
11400.000	23.22	AV	H	13.59	36.81	54.00	17.19
11400.000	36.38	PK	V	13.59	49.97	74.00	24.03
11400.000	23.34	AV	V	13.59	36.93	54.00	17.07
17100.000	35.78	PK	H	21.60	57.38	68.20	10.82
17100.000	35.63	PK	H	21.60	57.23	68.20	10.97

802.11n20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 5500 MHz							
5470.000	48.78	PK	H	10.09	58.87	68.20	9.33
5470.000	49.56	PK	V	10.09	59.65	68.20	8.55
11000.000	35.48	PK	H	14.62	50.10	74.00	23.90
11000.000	22.63	AV	H	14.62	37.25	54.00	16.75
11000.000	35.41	PK	V	14.62	50.03	74.00	23.97
11000.000	22.31	AV	V	14.62	36.93	54.00	17.07
16500.000	36.97	PK	H	18.36	55.33	68.20	12.87
16500.000	36.69	PK	V	18.36	55.05	68.20	13.15
Middle Channel: 5580 MHz							
11160.000	36.54	PK	H	14.64	51.18	74.00	22.82
11160.000	23.41	AV	H	14.64	38.05	54.00	15.95
11160.000	36.37	PK	V	14.64	51.01	74.00	22.99
11160.000	23.33	AV	V	14.64	37.97	54.00	16.03
16740.000	37.45	PK	H	18.30	55.75	68.20	12.45
16740.000	37.65	PK	V	18.30	55.95	68.20	12.25
High Channel: 5700 MHz							
5725.000	49.62	PK	H	9.41	59.03	68.20	9.17
5725.000	50.35	PK	V	9.41	59.76	68.20	8.44
11400.000	36.75	PK	H	13.59	50.34	74.00	23.66
11400.000	23.64	AV	H	13.59	37.23	54.00	16.77
11400.000	36.82	PK	V	13.59	50.41	74.00	23.59
11400.000	23.45	AV	V	13.59	37.04	54.00	16.96
17100.000	36.11	PK	H	21.60	57.71	68.20	10.49
17100.000	35.98	PK	H	21.60	57.58	68.20	10.62

802.11n40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 5510 MHz							
5470.000	49.69	PK	H	10.09	59.78	68.20	8.42
5470.000	51.43	PK	V	10.09	61.52	68.20	6.68
11020.000	35.03	PK	H	14.54	49.57	74.00	24.43
11020.000	21.88	AV	H	14.54	36.42	54.00	17.58
11020.000	35.47	PK	V	14.54	50.01	74.00	23.99
11020.000	22.20	AV	V	14.54	36.74	54.00	17.26
16530.000	35.50	PK	H	18.64	54.14	68.20	14.06
16530.000	35.41	PK	V	18.64	54.05	68.20	14.15
Middle Channel: 5550 MHz							
11100.000	36.39	PK	H	14.18	50.57	74.00	23.43
11100.000	23.55	AV	H	14.18	37.73	54.00	16.27
11100.000	36.41	PK	V	14.18	50.59	74.00	23.41
11100.000	23.42	AV	V	14.18	37.60	54.00	16.40
16650.000	37.12	PK	H	18.76	55.88	68.20	12.32
16650.000	37.65	PK	V	18.76	56.41	68.20	11.79
High Channel: 5670 MHz							
5725.000	44.54	PK	H	9.41	53.95	68.20	14.25
5725.000	45.74	PK	V	9.41	55.15	68.20	13.05
11340.000	36.54	PK	H	14.40	50.94	74.00	23.06
11340.000	22.97	AV	H	14.40	37.37	54.00	16.63
11340.000	36.20	PK	V	14.40	50.60	74.00	23.40
11340.000	22.62	AV	V	14.40	37.02	54.00	16.98
17010.000	37.26	PK	H	20.10	57.36	68.20	10.84
17010.000	37.66	PK	H	20.10	57.76	68.20	10.44

802.11ac80 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5530	MHz		
5470.000	43.67	PK	H	10.09	53.76	68.20	14.44
5470.000	44.05	PK	V	10.09	54.14	68.20	14.06
11060.000	35.78	PK	H	14.36	50.14	74.00	23.86
11060.000	22.28	AV	H	14.36	36.64	54.00	17.36
11060.000	35.34	PK	V	14.36	49.70	74.00	24.30
11060.000	22.31	AV	V	14.36	36.67	54.00	17.33
16590.000	36.32	PK	H	19.19	55.51	68.20	12.69
16590.000	36.44	PK	V	19.19	55.63	68.20	12.57
High Channel:				5610	MHz		
5725.000	43.20	PK	H	9.41	52.61	68.20	15.59
5725.000	43.11	PK	V	9.41	52.52	68.20	15.68
11220.000	35.37	PK	H	14.95	50.32	74.00	23.68
11220.000	22.41	AV	H	14.95	37.36	54.00	16.64
11220.000	35.29	PK	V	14.95	50.24	74.00	23.76
11220.000	22.20	AV	V	14.95	37.15	54.00	16.85
16830.000	35.94	PK	H	18.92	54.86	68.20	13.34
16830.000	35.58	PK	H	18.92	54.50	68.20	13.70

5725-5850MHz**802.11a Mode Chain 0:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5745	MHz		
5725.000	43.32	PK	H	9.41	52.73	122.20	69.47
5720.000	43.28	PK	H	9.41	52.69	110.80	58.11
5700.000	42.88	PK	H	9.42	52.30	105.20	52.90
5650.000	42.63	PK	H	9.61	52.24	68.20	15.96
5725.000	43.68	PK	V	9.41	53.09	122.20	69.11
5720.000	43.36	PK	V	9.41	52.77	110.80	58.03
5700.000	42.85	PK	V	9.42	52.27	105.20	52.93
5650.000	42.65	PK	V	9.61	52.26	68.20	15.94
11490.000	34.83	PK	H	14.06	48.89	74.00	25.11
11490.000	21.25	AV	H	14.06	35.31	54.00	18.69
11490.000	35.60	PK	V	14.06	49.66	74.00	24.34
11490.000	22.58	AV	V	14.06	36.64	54.00	17.36
17235.000	35.24	PK	H	21.38	56.62	68.20	11.58
17235.000	35.36	PK	V	21.38	56.74	68.20	11.46
Middle Channel:				5785	MHz		
11570.000	34.92	PK	H	15.47	50.39	74.00	23.61
11570.000	22.02	AV	H	15.47	37.49	54.00	16.51
11570.000	34.86	PK	V	15.47	50.33	74.00	23.67
11570.000	21.55	AV	V	15.47	37.02	54.00	16.98
17355.000	35.34	PK	H	21.48	56.82	68.20	11.38
17355.000	35.47	PK	V	21.48	56.95	68.20	11.25
High Channel:				5825	MHz		
5850.000	43.63	PK	H	9.27	52.90	122.20	69.30
5855.000	43.28	PK	H	9.31	52.59	110.80	58.21
5875.000	42.51	PK	H	9.44	51.95	105.20	53.25
5925.000	42.36	PK	H	9.83	52.19	68.20	16.01
5850.000	43.55	PK	V	9.27	52.82	122.20	69.38
5855.000	43.66	PK	V	9.31	52.97	110.80	57.83
5875.000	43.57	PK	V	9.44	53.01	105.20	52.19
5925.000	42.10	PK	V	9.83	51.93	68.20	16.27
11650.000	36.08	PK	H	15.54	51.62	74.00	22.38
11650.000	23.12	AV	H	15.54	38.66	54.00	15.34
11650.000	35.91	PK	V	15.54	51.45	74.00	22.55
11650.000	23.23	AV	V	15.54	38.77	54.00	15.23
17475.000	36.16	PK	H	22.53	58.69	68.20	9.51
17475.000	36.22	PK	V	22.53	58.75	68.20	9.45

802.11a Mode Chain 1:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5745	MHz		
5725.000	44.55	PK	H	9.41	53.96	122.20	68.24
5720.000	43.54	PK	H	9.41	52.95	110.80	57.85
5700.000	44.21	PK	H	9.42	53.63	105.20	51.57
5650.000	43.69	PK	H	9.61	53.30	68.20	14.90
5725.000	46.76	PK	V	9.41	56.17	122.20	66.03
5720.000	45.97	PK	V	9.41	55.38	110.80	55.42
5700.000	44.68	PK	V	9.42	54.10	105.20	51.10
5650.000	43.69	PK	V	9.61	53.30	68.20	14.90
11490.000	34.74	PK	H	14.06	48.80	74.00	25.20
11490.000	21.58	AV	H	14.06	35.64	54.00	18.36
11490.000	34.66	PK	V	14.06	48.72	74.00	25.28
11490.000	21.47	AV	V	14.06	35.53	54.00	18.47
17235.000	34.93	PK	H	21.38	56.31	68.20	11.89
17235.000	35.02	PK	V	21.38	56.40	68.20	11.80
Middle Channel:				5785	MHz		
11570.000	35.05	PK	H	15.47	50.52	74.00	23.48
11570.000	22.25	AV	H	15.47	37.72	54.00	16.28
11570.000	35.24	PK	V	15.47	50.71	74.00	23.29
11570.000	22.38	AV	V	15.47	37.85	54.00	16.15
17355.000	34.33	PK	H	21.48	55.81	68.20	12.39
17355.000	34.58	PK	V	21.48	56.06	68.20	12.14
High Channel:				5825	MHz		
5850.000	45.62	PK	H	9.27	54.89	122.20	67.31
5855.000	44.58	PK	H	9.31	53.89	110.80	56.91
5875.000	43.28	PK	H	9.44	52.72	105.20	52.48
5925.000	43.18	PK	H	9.83	53.01	68.20	15.19
5850.000	45.68	PK	V	9.27	54.95	122.20	67.25
5855.000	44.65	PK	V	9.31	53.96	110.80	56.84
5875.000	43.50	PK	V	9.44	52.94	105.20	52.26
5925.000	43.39	PK	V	9.83	53.22	68.20	14.98
11650.000	34.88	PK	H	15.55	50.43	74.00	23.57
11650.000	21.41	AV	H	15.55	36.96	54.00	17.04
11650.000	34.69	PK	V	15.55	50.24	74.00	23.76
11650.000	21.32	AV	V	15.55	36.87	54.00	17.13
17475.000	35.35	PK	H	22.53	57.88	68.20	10.32
17475.000	35.49	PK	V	22.53	58.02	68.20	10.18

802.11n20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5745	MHz		
5725.000	44.64	PK	H	9.41	54.05	122.20	68.15
5720.000	43.85	PK	H	9.41	53.26	110.80	57.54
5700.000	42.87	PK	H	9.42	52.29	105.20	52.91
5650.000	42.21	PK	H	9.61	51.82	68.20	16.38
5725.000	44.59	PK	V	9.41	54.00	122.20	68.20
5720.000	43.51	PK	V	9.41	52.92	110.80	57.88
5700.000	42.63	PK	V	9.42	52.05	105.20	53.15
5650.000	42.27	PK	V	9.61	51.88	68.20	16.32
11490.000	34.67	PK	H	14.06	48.73	74.00	25.27
11490.000	21.50	AV	H	14.06	35.56	54.00	18.44
11490.000	34.32	PK	V	14.06	48.38	74.00	25.62
11490.000	21.59	AV	V	14.06	35.65	54.00	18.35
17235.000	34.57	PK	H	21.38	55.95	68.20	12.25
17235.000	34.93	PK	V	21.38	56.31	68.20	11.89
Middle Channel:				5785	MHz		
11570.000	35.17	PK	H	15.47	50.64	74.00	23.36
11570.000	22.63	AV	H	15.47	38.10	54.00	15.90
11570.000	35.20	PK	V	15.47	50.67	74.00	23.33
11570.000	22.34	AV	V	15.47	37.81	54.00	16.19
17355.000	34.95	PK	H	21.48	56.43	68.20	11.77
17355.000	35.03	PK	V	21.48	56.51	68.20	11.69
High Channel:				5825	MHz		
5850.000	43.66	PK	H	9.27	52.93	122.20	69.27
5855.000	42.87	PK	H	9.31	52.18	110.80	58.62
5875.000	42.63	PK	H	9.44	52.07	105.20	53.13
5925.000	42.22	PK	H	9.83	52.05	68.20	16.15
5850.000	43.58	PK	V	9.27	52.85	122.20	69.35
5855.000	42.59	PK	V	9.31	51.90	110.80	58.90
5875.000	42.34	PK	V	9.44	51.78	105.20	53.42
5925.000	42.66	PK	V	9.83	52.49	68.20	15.71
11650.000	35.85	PK	H	15.55	51.40	74.00	22.60
11650.000	22.41	AV	H	15.55	37.96	54.00	16.04
11650.000	35.63	PK	V	15.55	51.18	74.00	22.82
11650.000	22.66	AV	V	15.55	38.21	54.00	15.79
17475.000	34.79	PK	H	22.53	57.32	68.20	10.88
17475.000	34.50	PK	V	22.53	57.03	68.20	11.17

802.11n40 Mode:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5755	MHz		
5725.000	44.28	PK	H	9.41	53.69	122.20	68.51
5720.000	43.69	PK	H	9.41	53.10	110.80	57.70
5700.000	42.87	PK	H	9.42	52.29	105.20	52.91
5650.000	42.29	PK	H	9.61	51.90	68.20	16.30
5725.000	44.69	PK	V	9.41	54.10	122.20	68.10
5720.000	43.46	PK	V	9.41	52.87	110.80	57.93
5700.000	42.50	PK	V	9.42	51.92	105.20	53.28
5650.000	42.32	PK	V	9.61	51.93	68.20	16.27
11510.000	35.32	PK	H	14.31	49.63	74.00	24.37
11510.000	22.18	AV	H	14.31	36.49	54.00	17.51
11510.000	35.23	PK	V	14.31	49.54	74.00	24.46
11510.000	22.23	AV	V	14.31	36.54	54.00	17.46
17265.000	33.77	PK	H	21.25	55.02	68.20	13.18
17265.000	34.34	PK	V	21.25	55.59	68.20	12.61
High Channel:				5795	MHz		
5850.000	43.55	PK	H	9.27	52.82	122.20	69.38
5855.000	43.20	PK	H	9.31	52.51	110.80	58.29
5875.000	42.58	PK	H	9.44	52.02	105.20	53.18
5925.000	42.69	PK	H	9.83	52.52	68.20	15.68
5850.000	43.54	PK	V	9.27	52.81	122.20	69.39
5855.000	42.56	PK	V	9.31	51.87	110.80	58.93
5875.000	42.27	PK	V	9.44	51.71	105.20	53.49
5925.000	42.19	PK	V	9.83	52.02	68.20	16.18
11590.000	34.92	PK	H	15.85	50.77	74.00	23.23
11590.000	22.08	AV	H	15.85	37.93	54.00	16.07
11590.000	35.17	PK	V	15.85	51.02	74.00	22.98
11590.000	22.19	AV	V	15.85	38.04	54.00	15.96
17385.000	35.14	PK	H	21.68	56.82	68.20	11.38
17385.000	35.28	PK	V	21.68	56.96	68.20	11.24

802.11ac80 Mode:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Middle Channel:				5775	MHz		
5725.000	44.63	PK	H	9.41	54.04	122.20	68.16
5720.000	43.88	PK	H	9.41	53.29	110.80	57.51
5700.000	43.33	PK	H	9.42	52.75	105.20	52.45
5650.000	42.87	PK	H	9.61	52.48	68.20	15.72
5725.000	44.65	PK	V	9.41	54.06	122.20	68.14
5720.000	43.20	PK	V	9.41	52.61	110.80	58.19
5700.000	43.02	PK	V	9.42	52.44	105.20	52.76
5650.000	43.11	PK	V	9.61	52.72	68.20	15.48
5850.000	44.25	PK	H	9.27	53.52	122.20	68.68
5855.000	43.71	PK	H	9.31	53.02	110.80	57.78
5875.000	43.20	PK	H	9.44	52.64	105.20	52.56
5925.000	42.82	PK	H	9.83	52.65	68.20	15.55
5850.000	44.52	PK	V	9.27	53.79	122.20	68.41
5855.000	43.66	PK	V	9.31	52.97	110.80	57.83
5875.000	42.28	PK	V	9.44	51.72	105.20	53.48
5925.000	42.18	PK	V	9.83	52.01	68.20	16.19
11550.000	36.00	PK	H	15.08	51.08	74.00	22.92
11550.000	23.09	AV	H	15.08	38.17	54.00	15.83
11550.000	35.88	PK	V	15.08	50.96	74.00	23.04
11550.000	22.68	AV	V	15.08	37.76	54.00	16.24
17325.000	34.31	PK	H	21.27	55.58	68.20	12.62
17325.000	34.44	PK	V	21.27	55.71	68.20	12.49

Worst band edge test plots

Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: Horizontal
Note: n40 Low 5510MHz Band3




Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: Vertical
Note: n40 Low 5510MHz Band3




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5455.668	48.33	10.08	58.41	74.00	15.59	Peak
2	5455.668	35.60	10.08	45.68	54.00	8.32	Average
3	5470.000	51.43	10.09	61.52	68.20	6.68	Peak

Worst radiation spurious emissions margin test plots


Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: horizontal
Note: a High 5825MHz Band4 Chain 0




Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: vertical
Note: a High 5825MHz Band4 Chain 0




Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: horizontal
Note: a High 5825MHz Band4 Chain 0



Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: vertical
Note: a High 5825MHz Band4 Chain 0




Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: Horizontal
Note: a High 5825MHz Band4 Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	19824.100	50.48	7.95	58.43	74.00	15.57	Peak
2	19824.100	37.72	7.95	45.67	54.00	8.33	Average


Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: vertical
Note: a High 5825MHz Band4 Chain 0



Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: Horizontal
Note: a High 5825MHz Band4 Chain 0



Project No.: 2403T78885E-RF
Tester: Tao Zhu
Polarization: vertical
Note: a High 5825MHz Band4 Chain 0



4.3 Maximum Conducted Output Power

Serial Number:	2MBO-2	Test Date:	2024/6/6
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.1	Relative Humidity: (%)	47	ATM Pressure: (kPa)	100.4
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Anritsu	Power Meter	ML2495A	1106009	2023/8/4	2024/8/3
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/8/4	2024/8/3

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

5150-5250 MHz:

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)			
		Chain 0	Chain 1	Total	Limit
802.11a	5180	13.35	13.24	/	24
	5200	12.98	12.83	/	24
	5240	12.87	12.73	/	24
802.11n ht20	5180	10.22	10.11	13.18	24
	5200	9.91	9.73	12.83	24
	5240	9.72	9.55	12.65	24
802.11n ht40	5190	10.5	10.39	13.46	24
	5230	10.33	10.13	13.24	24
802.11ac vht80	5210	5.94	5.88	8.92	24

Note:
The device is a client unit.
The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:
Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$, so directional gain is 2.37 dBi.

5250-5350 MHz:

Test Modes	Test Frequency(MHz)	Max. Conducted Average Output Power(dBm)			
		Chain 0	Chain 1	Total	Limit
802.11a	5260	12.55	12.35	/	24
	5280	12.62	12.42	/	24
	5320	12.51	12.34	/	24
802.11n ht20	5260	9.44	9.24	12.35	24
	5280	9.38	9.19	12.30	24
	5320	9.21	9.07	12.15	24
802.11n ht40	5270	10.44	10.14	13.30	24
	5310	9.24	9.03	12.15	24
802.11ac vht80	5290	7.99	7.65	10.83	24

Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:
 Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$, so directional gain is 2.37 dBi.

5470-5725 MHz:

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)			
		Chain 0	Chain 1	Total	Limit
802.11a	5500	13.35	13.38	/	24
	5580	13.59	13.73	/	24
	5700	13.18	13.33	/	24
	5720	13.22	13.48	/	24
802.11n ht20	5500	10.96	11.05	14.02	24
	5580	11.32	11.43	14.39	24
	5700	10.71	10.85	13.79	24
	5720	10.78	10.99	13.90	24
802.11n ht40	5510	10.33	10.14	13.25	24
	5550	12.68	12.51	15.61	24
	5670	11.87	12.06	14.98	24
	5710	11.67	11.91	14.80	24
802.11ac vht80	5530	7.93	7.94	10.95	24
	5610	7.34	7.61	10.49	24
	5690	6.94	7.14	10.05	24

Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:
 Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$, so directional gain is 4.6 dBi.

5725-5850 MHz:

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)			
		Chain 0	Chain 1	Total	Limit
802.11a	5745	11.52	11.53	/	30
	5785	11.59	11.54	/	30
	5825	11.57	11.56	/	30
802.11n ht20	5745	8.25	8.2	11.24	30
	5785	8.16	8.19	11.19	30
	5825	8.08	8.12	11.11	30
802.11n ht40	5755	8.31	8.15	11.24	30
	5795	7.66	7.81	10.75	30
802.11ac vht80	5775	6.75	6.92	9.85	30

Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:
 Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$, so directional gain is 4.6 dBi.

4.4 Emission Bandwidth

Test Information:

Serial No.:	2MBO-2	Test Date:	2024/6/17
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.4	Relative Humidity: (%)	55	ATM Pressure: (kPa)	100.1
-----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/04/01	2025/03/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

5.2G 26 dB EBW

Mode	Value (MHz)
a_5180MHz_Chain 0	23.723
a_5200MHz_Chain 0	23.646
a_5240MHz_Chain 0	23.918
n20_5180MHz_Chain 0	24.049
n20_5200MHz_Chain 0	24.125
n20_5240MHz_Chain 0	23.693
n40_5190MHz_Chain 0	45.554
n40_5230MHz_Chain 0	45.554
ac80_5210MHz_Chain 0	82.517

5.3G 26 dB EBW

Mode	Value (MHz)
a_5260MHz_Chain 0	23.981
a_5280MHz_Chain 0	23.521
a_5320MHz_Chain 0	23.180
n20_5260MHz_Chain 0	23.971
n20_5280MHz_Chain 0	24.068
n20_5320MHz_Chain 0	23.973
n40_5270MHz_Chain 0	44.356
n40_5310MHz_Chain 0	43.157
ac80_5290MHz_Chain 0	82.917

5.6G 26 dB EBW

Mode	Value (MHz)
a_5500MHz_Chain 0	23.763
a_5580MHz_Chain 0	23.726
a_5700MHz_Chain 0	23.862
a_5720MHz_Chain 0	23.855
n20_5500MHz_Chain 0	24.171
n20_5580MHz_Chain 0	23.973
n20_5700MHz_Chain 0	23.712
n20_5720MHz_Chain 0	23.747
n40_5510MHz_Chain 0	44.156


Mode	Value (MHz)
n40_5550MHz_Chain 0	43.656
n40_5670MHz_Chain 0	43.856
n40_5710MHz_Chain 0	44.855
ac80_5530MHz_Chain 0	82.318
ac80_5610MHz_Chain 0	82.517
ac80_5690MHz_Chain 0	82.517

5.8G 6 dB EBW

Mode	Value (MHz)	Limit (MHz)	Result
a_5745MHz_Chain 0	15.285	0.5	Pass
a_5785MHz_Chain 0	15.285	0.5	Pass
a_5825MHz_Chain 0	15.235	0.5	Pass
n20_5745MHz_Chain 0	15.584	0.5	Pass
n20_5785MHz_Chain 0	15.285	0.5	Pass
n20_5825MHz_Chain 0	15.285	0.5	Pass
n40_5755MHz_Chain 0	35.365	0.5	Pass
n40_5795MHz_Chain 0	35.365	0.5	Pass
ac80_5775MHz_Chain 0	75.724	0.5	Pass


5.2G

a_5180MHz_Chain 0 23.723MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:36:44

a_5200MHz_Chain 0 23.646MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:39:21

a_5240MHz_Chain 0 23.918MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:41:55

n20_5180MHz_Chain 0 24.049MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:27:55

n20_5200MHz_Chain 0 24.125MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:30:40

n20_5240MHz_Chain 0 23.693MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:35:12

n40_5190MHz_Chain 0 45.554MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN.2024 16:04:59


n40_5230MHz_Chain 0 45.554MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN.2024 16:07:17


5.3G

ac80_5210MHz_Chain 0 82.517MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN.2024 16:34:41

a_5260MHz_Chain 0 23.981MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN.2024 14:44:53

a_5280MHz_Chain 0 23.521MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN.2024 14:47:22

a_5320MHz_Chain 0 23.180MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN.2024 14:50:31

n20_5260MHz_Chain 0 23.971MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:37:44

n20_5280MHz_Chain 0 24.068MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:48:19

n20_5320MHz_Chain 0 23.973MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:42:51

n40_5270MHz_Chain 0 44.356MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:18:19

n40_5310MHz_Chain 0 43.157MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:12:35


ac80_5290MHz_Chain 0 82.917MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:37:01


5.6G

a_5500MHz_Chain 0 23.763MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:53:05

a_5580MHz_Chain 0 23.726MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:55:48

a_5700MHz_Chain 0 23.862MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:59:10

a_5720MHz_Chain 0 23.855MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:02:00

n20_5500MHz_Chain 0 24.171MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:45:37

n20_5580MHz_Chain 0 23.973MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:48:34

n20_5700MHz_Chain 0 23.712MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:51:09

n20_5720MHz_Chain 0 23.747MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:53:37

n40_5510MHz_Chain 0 44.156MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:15:36

n40_5550MHz_Chain 0 43.656MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:17:58

n40_5670MHz_Chain 0 43.856MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:21:41

n40_5710MHz_Chain 0 44.855MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:24:08

ac80_5530MHz_Chain 0 82.318MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 16:39:34


ac80_5610MHz_Chain 0 82.517MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 16:42:28


5.8G

ac80_5690MHz_Chain 0 82.517MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 16:45:04

a_5745MHz_Chain 0 15.285MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:04:28

a_5785MHz_Chain 0 15.285MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:06:23

a_5825MHz_Chain 0 15.235MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:08:19

n20_5745MHz_Chain 0 15.584MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:55:35

n20_5785MHz_Chain 0 15.285MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:57:27

n20_5825MHz_Chain 0 15.285MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:59:23

n40_5755MHz_Chain 0 35.365MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:26:22

n40_5795MHz_Chain 0 35.365MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:28:41

ac80_5775MHz_Chain 0 75.724MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:47:51

4.5 99% Occupied Bandwidth

Test Information:

Serial No.:	2MBO-2	Test Date:	2024/6/17
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	N/A

Environmental Conditions:

Temperature: (°C):	26.4	Relative Humidity: (%)	55	ATM Pressure: (kPa)	100.1
-----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/04/01	2025/03/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

5.2G

Mode	99% OBW (MHz)
a_5180MHz_Chain 0	16.700
a_5200MHz_Chain 0	16.700
a_5240MHz_Chain 0	16.750
n20_5180MHz_Chain 0	17.750
n20_5200MHz_Chain 0	17.800
n20_5240MHz_Chain 0	17.750
n40_5190MHz_Chain 0	36.400
n40_5230MHz_Chain 0	36.300
ac80_5210MHz_Chain 0	75.600

Note:

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

5.3G

Mode	99% OBW (MHz)
a_5260MHz_Chain 0	16.700
a_5280MHz_Chain 0	16.650
a_5320MHz_Chain 0	16.650
n20_5260MHz_Chain 0	17.750
n20_5280MHz_Chain 0	17.750
n20_5320MHz_Chain 0	17.750
n40_5270MHz_Chain 0	36.200
n40_5310MHz_Chain 0	36.300
ac80_5290MHz_Chain 0	75.200

5.6G

Mode	99% OBW (MHz)
a_5500MHz_Chain 0	16.700
a_5580MHz_Chain 0	16.650
a_5700MHz_Chain 0	16.700
a_5720MHz_Chain 0	16.700
n20_5500MHz_Chain 0	17.750
n20_5580MHz_Chain 0	17.750
n20_5700MHz_Chain 0	17.750

Mode	99% OBW (MHz)
n20_5720MHz_Chain 0	17.750
n40_5510MHz_Chain 0	36.200
n40_5550MHz_Chain 0	36.200
n40_5670MHz_Chain 0	36.300
n40_5710MHz_Chain 0	36.300
ac80_5530MHz_Chain 0	75.200
ac80_5610MHz_Chain 0	75.400
ac80_5690MHz_Chain 0	75.400

5.8G

Mode	99% OBW (MHz)
a_5745MHz_Chain 0	16.650
a_5785MHz_Chain 0	16.700
a_5825MHz_Chain 0	16.700
n20_5745MHz_Chain 0	17.750
n20_5785MHz_Chain 0	17.700
n20_5825MHz_Chain 0	17.750
n40_5755MHz_Chain 0	36.300
n40_5795MHz_Chain 0	36.300
ac80_5775MHz_Chain 0	75.400

Note:

The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.

a_5180MHz_Chain 0 16.700MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 14:38:07


ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 14:40:42

ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:26:44

ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:29:27

ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:33:59


n40_5230MHz_Chain 0 36.300MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:06:31


a_5260MHz_Chain 0 16.700MHz

a_5260MHz_Chain 0 16.700MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 14:43:41

a_5320MHz_Chain 0 16.650MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 14:49:20

n20_5260MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:36:33

n20_5280MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:39:08

n20_5320MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:41:40

n40_5270MHz_Chain 0 36.200MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:09:31

n40_5310MHz_Chain 0 36.300MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:11:48


ac80_5290MHz_Chain 0 75.200MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:36:14


5.6G

a_5500MHz_Chain 0 16.700MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:53:51

a_5580MHz_Chain 0 16.650MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:54:35

a_5700MHz_Chain 0 16.700MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:57:58

a_5720MHz_Chain 0 16.700MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:00:47

n20_5500MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:44:26

n20_5580MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 15:47:23

n20_5700MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN. 2024 15:49:58

n20_5720MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN. 2024 15:52:25

n40_5510MHz_Chain 0 36.200MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN. 2024 16:14:49

n40_5550MHz_Chain 0 36.200MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN. 2024 16:17:11

n40_5670MHz_Chain 0 36.300MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN. 2024 16:20:53

n40_5710MHz_Chain 0 36.300MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN. 2024 16:23:13

ac80_5530MHz_Chain 0 75.200MHz




ac80_5610MHz_Chain 0 75.400MHz




5.8G


ac80_5690MHz_Chain 0 75.400MHz




a_5745MHz_Chain 0 16.650MHz




a_5785MHz_Chain 0 16.700MHz



a_5825MHz_Chain 0 16.700MHz




n20_5745MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:55:02

n20_5785MHz_Chain 0 17.700MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:56:55

n20_5825MHz_Chain 0 17.750MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 15:58:50

n40_5755MHz_Chain 0 36.300MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:25:38

n40_5795MHz_Chain 0 36.300MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:27:57

ac80_5775MHz_Chain 0 75.400MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17.JUN.2024 16:47:07

4.6 Power Spectral Density

Test Information:

Serial No.:	2MBO-2	Test Date:	2024/6/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.8	Relative Humidity: (%)	52	ATM Pressure: (kPa)	99.9
-----------------------	------	------------------------------	----	------------------------	------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/04/01	2025/03/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

5.2G

Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5180MHz_Chain 0	1.28	0.11	1.39	11.00	Pass
a_5180MHz_Chain 1	1.11	0.11	1.22	11.00	Pass
a_5200MHz_Chain 0	1.24	0.11	1.35	11.00	Pass
a_5200MHz_Chain 1	1.05	0.11	1.16	11.00	Pass
a_5240MHz_Chain 0	0.95	0.11	1.06	11.00	Pass
a_5240MHz_Chain 1	0.82	0.11	0.93	11.00	Pass
n20_5180MHz_Chain 0	-1.99	0.23	-1.76	11.00	Pass
n20_5180MHz_Chain 1	-2.03	0.23	-1.80	11.00	Pass
n20_5180MHz_Chain 0+Chain 1	1.00	0.23	1.23	11.00	Pass
n20_5200MHz_Chain 0	-1.98	0.23	-1.75	11.00	Pass
n20_5200MHz_Chain 1	-2.07	0.23	-1.84	11.00	Pass
n20_5200MHz_Chain 0+Chain 1	0.99	0.23	1.22	11.00	Pass
n20_5240MHz_Chain 0	-2.25	0.23	-2.02	11.00	Pass
n20_5240MHz_Chain 1	-2.22	0.23	-1.99	11.00	Pass
n20_5240MHz_Chain 0+Chain 1	0.78	0.23	1.01	11.00	Pass
n40_5190MHz_Chain 0	-4.88	0.41	-4.47	11.00	Pass
n40_5190MHz_Chain 1	-4.92	0.41	-4.51	11.00	Pass
n40_5190MHz_Chain 0+Chain 1	-1.89	0.41	-1.48	11.00	Pass
n40_5230MHz_Chain 0	-5.11	0.41	-4.70	11.00	Pass
n40_5230MHz_Chain 1	-5.05	0.41	-4.64	11.00	Pass
n40_5230MHz_Chain 0+Chain 1	-2.07	0.41	-1.66	11.00	Pass
ac80_5210MHz_Chain 0	-12.38	2.38	-10.00	11.00	Pass
ac80_5210MHz_Chain 1	-12.28	2.38	-9.90	11.00	Pass
ac80_5210MHz_Chain 0+Chain 1	-9.32	2.38	-6.94	11.00	Pass

Note:

The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB, so directional gain is $2.37+10*\log(2/1) = 5.37$ dBi.

5.3G

Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5260MHz_Chain 0	0.91	0.11	1.02	11.00	Pass
a_5260MHz_Chain 1	0.73	0.11	0.84	11.00	Pass
a_5280MHz_Chain 0	1.11	0.11	1.22	11.00	Pass
a_5280MHz_Chain 1	1.00	0.11	1.11	11.00	Pass
a_5320MHz_Chain 0	1.34	0.11	1.45	11.00	Pass
a_5320MHz_Chain 1	1.24	0.11	1.35	11.00	Pass
n20_5260MHz_Chain 0	-2.38	0.23	-2.15	11.00	Pass
n20_5260MHz_Chain 1	-2.36	0.23	-2.13	11.00	Pass
n20_5260MHz_Chain 0+Chain 1	0.64	0.23	0.87	11.00	Pass
n20_5280MHz_Chain 0	-2.12	0.23	-1.89	11.00	Pass
n20_5280MHz_Chain 1	-2.14	0.23	-1.91	11.00	Pass
n20_5280MHz_Chain 0+Chain 1	0.88	0.23	1.11	11.00	Pass
n20_5320MHz_Chain 0	-2.02	0.23	-1.79	11.00	Pass
n20_5320MHz_Chain 1	-2.03	0.23	-1.80	11.00	Pass
n20_5320MHz_Chain 0+Chain 1	0.99	0.23	1.22	11.00	Pass
n40_5270MHz_Chain 0	-4.60	0.41	-4.19	11.00	Pass
n40_5270MHz_Chain 1	-4.66	0.41	-4.25	11.00	Pass
n40_5270MHz_Chain 0+Chain 1	-1.62	0.41	-1.21	11.00	Pass
n40_5310MHz_Chain 0	-5.45	0.41	-5.04	11.00	Pass
n40_5310MHz_Chain 1	-5.44	0.41	-5.03	11.00	Pass
n40_5310MHz_Chain 0+Chain 1	-2.43	0.41	-2.02	11.00	Pass
ac80_5290MHz_Chain 0	-10.11	2.38	-7.73	11.00	Pass
ac80_5290MHz_Chain 1	-10.29	2.38	-7.91	11.00	Pass
ac80_5290MHz_Chain 0+Chain 1	-7.19	2.38	-4.81	11.00	Pass

Note:

The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB, so directional gain is $2.37+10*\log(2/1) = 5.37$ dBi.

5.6G

Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5500MHz_Chain 0	1.74	0.11	1.85	11.00	Pass
a_5500MHz_Chain 1	1.61	0.11	1.72	11.00	Pass
a_5580MHz_Chain 0	1.64	0.11	1.75	11.00	Pass
a_5580MHz_Chain 1	1.54	0.11	1.65	11.00	Pass
a_5700MHz_Chain 0	1.62	0.11	1.73	11.00	Pass
a_5700MHz_Chain 1	1.45	0.11	1.56	11.00	Pass
a_5720MHz_Chain 0	1.76	0.11	1.87	11.00	Pass
a_5720MHz_Chain 1	1.63	0.11	1.74	11.00	Pass
n20_5500MHz_Chain 0	-0.76	0.23	-0.53	11.00	Pass
n20_5500MHz_Chain 1	-0.82	0.23	-0.59	11.00	Pass
n20_5500MHz_Chain 0+Chain 1	2.22	0.23	2.45	9.40	Pass
n20_5580MHz_Chain 0	-0.93	0.23	-0.70	11.00	Pass
n20_5580MHz_Chain 1	-0.90	0.23	-0.67	11.00	Pass
n20_5580MHz_Chain 0+Chain 1	2.10	0.23	2.33	9.40	Pass
n20_5700MHz_Chain 0	-1.13	0.23	-0.90	11.00	Pass
n20_5700MHz_Chain 1	-1.10	0.23	-0.87	11.00	Pass
n20_5700MHz_Chain 0+Chain 1	1.90	0.23	2.13	9.40	Pass
n20_5720MHz_Chain 0	-0.91	0.23	-0.68	11.00	Pass
n20_5720MHz_Chain 1	-0.89	0.23	-0.66	11.00	Pass
n20_5720MHz_Chain 0+Chain 1	2.11	0.23	2.34	9.40	Pass
n40_5510MHz_Chain 0	-5.15	0.41	-4.74	11.00	Pass
n40_5510MHz_Chain 1	-5.04	0.41	-4.63	11.00	Pass
n40_5510MHz_Chain 0+Chain 1	-2.08	0.41	-1.67	9.40	Pass
n40_5550MHz_Chain 0	-3.04	0.41	-2.63	11.00	Pass
n40_5550MHz_Chain 1	-3.06	0.41	-2.65	11.00	Pass
n40_5550MHz_Chain 0+Chain 1	-0.04	0.41	0.37	9.40	Pass
n40_5670MHz_Chain 0	-3.53	0.41	-3.12	11.00	Pass
n40_5670MHz_Chain 1	-3.45	0.41	-3.04	11.00	Pass
n40_5670MHz_Chain 0+Chain 1	-0.48	0.41	-0.07	9.40	Pass
n40_5710MHz_Chain 0	-3.34	0.41	-2.93	11.00	Pass

Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
n40_5710MHz_Chain 1	-3.35	0.41	-2.94	11.00	Pass
n40_5710MHz_Chain 0+Chain 1	-0.33	0.41	0.08	9.40	Pass
ac80_5530MHz_Chain 0	-10.77	2.38	-8.39	11.00	Pass
ac80_5530MHz_Chain 1	-10.80	2.38	-8.42	11.00	Pass
ac80_5530MHz_Chain 0+Chain 1	-7.77	2.38	-5.39	9.40	Pass
ac80_5610MHz_Chain 0	-11.53	2.38	-9.15	11.00	Pass
ac80_5610MHz_Chain 1	-11.53	2.38	-9.15	11.00	Pass
ac80_5610MHz_Chain 0+Chain 1	-8.52	2.38	-6.14	9.40	Pass
ac80_5690MHz_Chain 0	-11.31	2.38	-8.93	11.00	Pass
ac80_5690MHz_Chain 1	-11.29	2.38	-8.91	11.00	Pass
ac80_5690MHz_Chain 0+Chain 1	-8.29	2.38	-5.91	9.40	Pass

Note:

The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB, so directional gain is $4.6+10*\log(2/1) = 7.6$ dBi.

5.8G

Mode	Value (dBm/500kHz)	Duty Cycle Factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
a_5745MHz_Chain 0	-2.88	0.11	-2.77	30	Pass
a_5745MHz_Chain 1	-3.06	0.11	-2.95	30	Pass
a_5785MHz_Chain 0	-3.05	0.11	-2.94	30	Pass
a_5785MHz_Chain 1	-3.25	0.11	-3.14	30	Pass
a_5825MHz_Chain 0	-3.14	0.11	-3.03	30	Pass
a_5825MHz_Chain 1	-3.28	0.11	-3.17	30	Pass
n20_5745MHz_Chain 0	-6.38	0.23	-6.15	30	Pass
n20_5745MHz_Chain 1	-6.25	0.23	-6.02	30	Pass
n20_5745MHz_Chain 0+Chain 1	-3.3	0.23	-3.07	28.4	Pass
n20_5785MHz_Chain 0	-6.46	0.23	-6.23	30	Pass
n20_5785MHz_Chain 1	-6.47	0.23	-6.24	30	Pass
n20_5785MHz_Chain 0+Chain 1	-3.45	0.23	-3.22	28.4	Pass
n20_5825MHz_Chain 0	-6.51	0.23	-6.28	30	Pass
n20_5825MHz_Chain 1	-6.36	0.23	-6.13	30	Pass
n20_5825MHz_Chain 0+Chain 1	-3.42	0.23	-3.19	28.4	Pass
n40_5755MHz_Chain 0	-9.59	0.41	-9.18	30	Pass
n40_5755MHz_Chain 1	-9.57	0.41	-9.16	30	Pass
n40_5755MHz_Chain 0+Chain 1	-6.57	0.41	-6.16	28.4	Pass
n40_5795MHz_Chain 0	-10.11	0.41	-9.70	30	Pass
n40_5795MHz_Chain 1	-10.02	0.41	-9.61	30	Pass
n40_5795MHz_Chain 0+Chain 1	-7.05	0.41	-6.64	28.4	Pass
ac80_5775MHz_Chain 0	-13.21	2.38	-10.83	30	Pass
ac80_5775MHz_Chain 1	-13.50	2.38	-11.12	30	Pass
ac80_5775MHz_Chain 0+Chain 1	-10.34	2.38	-7.96	28.4	Pass


Note:

The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB, so directional gain is $4.6+10*\log(2/1) = 7.6$ dBi.


5.2G

a_5180MHz_Chain 0 1.28dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 13:39:12

a_5180MHz_Chain 1 1.11dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 14:28:32

a_5200MHz_Chain 0 1.24dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 13:39:52

a_5200MHz_Chain 1 1.05dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 14:28:59

a_5240MHz_Chain 0 0.95dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 13:40:27

a_5240MHz_Chain 1 0.82dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 14:21:42

n20_5180MHz_Chain 0 -1.99dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:51:15

n20_5180MHz_Chain 1 -2.03dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:29:21

n20_5200MHz_Chain 0 -1.98dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:51:50

n20_5200MHz_Chain 1 -2.07dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:29:57

n20_5240MHz_Chain 0 -2.25dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:52:30

n20_5240MHz_Chain 1 -2.22dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:30:40

n40_5190MHz_Chain 0 -4.88dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:06:40

n40_5190MHz_Chain 1 -4.92dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:40:13

n40_5230MHz_Chain 0 -5.11dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:07:20

n40_5230MHz_Chain 1 -5.05dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:40:54

ac80_5210MHz_Chain 0 -12.38dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:13:32


ac80_5210MHz_Chain 1 -12.28dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:51:54


5.3G

a_5260MHz_Chain 0 0.91dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 13:43:39

a_5260MHz_Chain 1 0.73dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 14:22:21

a_5280MHz_Chain 0 1.11dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 13:42:13

a_5280MHz_Chain 1 1.00dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 14:22:53

a_5320MHz_Chain 0 1.34dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 13:42:47

a_5320MHz_Chain 1 1.24dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 14:23:22

n20_5260MHz_Chain 0 -2.38dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:53:20

n20_5260MHz_Chain 1 -2.36dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:31:18

n20_5280MHz_Chain 0 -2.12dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:54:10

n20_5280MHz_Chain 1 -2.14dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:31:55

n20_5320MHz_Chain 0 -2.02dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:54:44

n20_5320MHz_Chain 1 -2.03dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:32:36

n40_5270MHz_Chain 0 -4.60dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:07:56

n40_5270MHz_Chain 1 -4.66dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:42:03

n40_5310MHz_Chain 0 -5.45dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:08:29

n40_5310MHz_Chain 1 -5.44dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:42:53

ac80_5290MHz_Chain 0 -10.11dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:14:10


ac80_5290MHz_Chain 1 -10.29dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:52:35


5.6G

a_5500MHz_Chain 0 1.74dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 13:43:26

a_5500MHz_Chain 1 1.61dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 14:24:48

a_5580MHz_Chain 0 1.64dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 13:44:03

a_5580MHz_Chain 1 1.54dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 14:25:17

a_5700MHz_Chain 0 1.62dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 13:44:41

a_5700MHz_Chain 1 1.45dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN.2024 14:25:45

a_5720MHz_Chain 0 1.76dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:45:18

a_5720MHz_Chain 1 1.63dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:26:13

n20_5500MHz_Chain 0 -0.76dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:55:32

n20_5500MHz_Chain 1 -0.82dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:33:12

n20_5580MHz_Chain 0 -0.93dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:56:22

n20_5580MHz_Chain 1 -0.90dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:33:51

n20_5700MHz_Chain 0 -1.13dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:57:01

n20_5700MHz_Chain 1 -1.10dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:36:06

n20_5720MHz_Chain 0 -0.91dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 13:57:35

n20_5720MHz_Chain 1 -0.89dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:36:44

n40_5510MHz_Chain 0 -5.15dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:09:03

n40_5510MHz_Chain 1 -5.04dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:43:28

n40_5550MHz_Chain 0 -3.04dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:09:41

n40_5550MHz_Chain 1 -3.06dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:44:04

n40_5670MHz_Chain 0 -3.53dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:10:21

n40_5670MHz_Chain 1 -3.45dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:44:42

n40_5710MHz_Chain 0 -3.34dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:10:58

n40_5710MHz_Chain 1 -3.35dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:45:24

ac80_5530MHz_Chain 0 -10.77dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:14:50

ac80_5530MHz_Chain 1 -10.80dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:53:18

ac80_5610MHz_Chain 0 -11.53dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:16:27

ac80_5610MHz_Chain 1 -11.53dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:55:06

ac80_5690MHz_Chain 0 -11.31dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:17:08


ac80_5690MHz_Chain 1 -11.29dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:56:17


5.8G

a_5745MHz_Chain 0 -2.88dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 13:48:34

a_5745MHz_Chain 1 -3.06dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 14:27:00

a_5785MHz_Chain 0 -3.05dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 13:49:22

a_5785MHz_Chain 1 -3.25dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 14:27:28

a_5825MHz_Chain 0 -3.14dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 13:49:57

a_5825MHz_Chain 1 -3.28dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18 JUN. 2024 14:27:55

n20_5745MHz_Chain 0 -6.38dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:03:20

n20_5745MHz_Chain 1 -6.25dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:37:21

n20_5785MHz_Chain 0 -6.46dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:00:13

n20_5785MHz_Chain 1 -6.47dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:38:02

n20_5825MHz_Chain 0 -6.51dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:00:52

n20_5825MHz_Chain 1 -6.36dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:38:38

n40_5755MHz_Chain 0 -9.59dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:11:30

n40_5755MHz_Chain 1 -9.57dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:46:56

n40_5795MHz_Chain 0 -10.11dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:12:11

n40_5795MHz_Chain 1 -10.02dBm/MHz




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:47:41

ac80_5775MHz_Chain 0 -13.21dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:17:57

ac80_5775MHz_Chain 1 -13.50dBm/MHz



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 18.JUN.2024 14:57:02

4.7 Duty Cycle

Test Information:

Serial No.:	2MBO-2	Test Date:	2024/6/17
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	N/A

Environmental Conditions:

Temperature: (°C):	26.4	Relative Humidity: (%)	55	ATM Pressure: (kPa)	100.1
-----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/04/01	2025/03/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK- 18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


5.2G

Mode	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T (Hz)	VBW Setting (kHz)
a_5200MHz_Chain 0	2.035	2.086	97.56	0.11	491.0	0.500
n20_5200MHz_Chain 0	0.965	1.017	94.89	0.23	1036.0	2.000
n40_5190MHz_Chain 0	0.490	0.538	91.08	0.41	2041.0	3.000
ac80_5210MHz_Chain 0	0.063	0.109	57.80	2.38	15873.0	20.000

Duty Cycle = Ton/(Ton+Toff)*100%


5.2G

a_5200MHz_Chain 0
2.035ms,2.086ms




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:13:12

n20_5200MHz_Chain 0
0.965ms,1.017ms




ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:15:28

n40_5190MHz_Chain 0
0.490ms,0.538ms



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:20:44

ac80_5210MHz_Chain 0
0.063ms,0.109ms



ProjectNo.:2403T78885E-RF Tester:Arthur Su
Date: 17 JUN 2024 14:24:19

5. EUT PHOTOGRAPHS

Please refer to the attachment 2403T78885E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2403T78885E-RF-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2403T78885E-RF-00D-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====