



Report No.: PTC23091909601E-FC02

FCC TEST REPORT

FCC ID: 2BDRB-EM3-DXB

Product	:	BMS
Model Name	:	DXB30A,DXB46A
Brand	:	N/A
Report No.	:	PTC23091909601E-FC02

Prepared for

Changzhou Emissions Free Technology Co., Ltd.
#A401, A HIT Mingseal Technology Building, NO.18 Middle ChangWu Road, WuJin,
ChangZhou, Jiangsu, China

Prepared by

Precise Testing & Certification Co., Ltd.
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.



TEST RESULT CERTIFICATION

Applicant's name : Changzhou Emissions Free Technology Co., Ltd.
Address : #A401, A HIT Mingseal Technology Building, NO.18 Middle ChangWu Road, WuJin, ChangZhou, Jiangsu, China
Manufacturer's name : Tianjin D-powercore Co.,LTD
Address : Building C, No 8,Haitai East Road,Xiqing District,Tianjin,China
Product name : BMS
Model name : DXB30A,DXB46A
Test procedure : FCC CFR47 Part 1.1307(b)(1)
Test Date : Nov. 07, 2023 to Nov. 25, 2023
Date of Issue : Dec. 05, 2023
Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	BMS
Model Name	:	DXB30A
Additional model	:	DXB46A
Specification	:	802.11b/g/n HT20/HT40
Operation Frequency	:	BLE
Number of Channel	:	40 channels For DTS
Type of Modulation	:	GFSK, For DTS
Antenna installation	:	PCB antenna
Antenna Gain	:	-4.00 dBi
Power supply	:	DC58V
Hardware Version	:	DXB30-TV1.5;DXB30-BV1.5;EM3-46A;TV0.2;EM3-46A;BV0.2
Software Version	:	DXB30A-1440BU-1003V0212.hex;DXB46A-1480BUC-1201V3.22



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta \varphi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2402	0.40	0.43	0.43±1	0.001390	0.001101	1	Pass

*****THE END REPORT*****