

Appendix B

RF Test Data for BT LE (Conducted Measurement)

Product Name: LED PROJECTOR


Test Model: Gimbal N6 Pro


Environmental Conditions

Temperature:	23.8°C
Relative Humidity:	52.9%
ATM Pressure:	100.0 kPa
Test Engineer:	Suichao Lai
Supervised by:	Yan Chen

B.1 -6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.664	≥ 0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.65	≥ 0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.645	≥ 0.5	Pass






B.2 Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	0.98	30	Pass
NVNT	BLE 1M	2440	Ant1	0.54	30	Pass
NVNT	BLE 1M	2480	Ant1	-0.52	30	Pass






B.3 Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-15.59	8	Pass
NVNT	BLE 1M	2440	Ant1	-15.92	8	Pass
NVNT	BLE 1M	2480	Ant1	-17.07	8	Pass


Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1




PSD NVNT BLE 1M 2440MHz Ant1






B.4 Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-57.28	-20	Pass
NVNT	BLE 1M	2480	Ant1	-56.7	-20	Pass







B.5 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-56	-20	Pass
NVNT	BLE 1M	2440	Ant1	-54.57	-20	Pass
NVNT	BLE 1M	2480	Ant1	-54.79	-20	Pass









B.6 Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	87.39	0.59	0.61
NVNT	BLE 1M	2440	Ant1	87.39	0.59	0.61
NVNT	BLE 1M	2480	Ant1	87.39	0.59	0.61






B.7 Restrict Band


Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor (dB)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1M	2402	Ant1	2310	-49.62	2.67	-	48.31	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2310	-58.79	2.67	0.59	39.73	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2369.04	-47.27	2.67	-	50.66	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2384.112	-58.38	2.67	0.59	40.14	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2390	-49.51	2.67	-	48.42	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2390	-58.49	2.67	0.59	40.03	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-50.46	2.67	-	47.47	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-57.73	2.67	0.59	40.79	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2487.136	-46.65	2.67	-	51.28	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2483.656	-57.57	2.67	0.59	40.95	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2500	-49.88	2.67	-	48.05	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2500	-58.3	2.67	0.59	40.22	Average	54	Pass

Test Graphs


Restrict Band NVNT BLE 1M 2402MHz Ant1 Peak



Restrict Band NVNT BLE 1M 2402MHz Ant1 Average



Restrict Band NVNT BLE 1M 2480MHz Ant1 Peak



Restrict Band NVNT BLE 1M 2480MHz Ant1 Average

