


## TEST REPORT

**Application No.:** BTEK240727005AE  
**Applicant:** Shenzhen Litime Technology Co., Ltd  
**Address of Applicant:** 301 Room 301, Building B, Tongzhou Electronics Longgang Factory, No. 1, Baolong 5th Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China  
**Manufacturer:** Shenzhen Litime Technology Co., Ltd  
**Address of Manufacturer:** 301 Room 301, Building B, Tongzhou Electronics Longgang Factory, No. 1, Baolong 5th Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China  
**Equipment Under Test (EUT):**  
**EUT Name:** Litime 12.8V 230Ah Plus LTCP LiFePO4 Battery  
**Test Model.:** 12.8V 230Ah Plus LTCP  
**Adding Model(s):** 12.8V 230Ah, 12.8V 230Ah Self-Heating, 12.8V 230Ah BT, 12.8V 230Ah HBT, 12.8V 230Ah Mini, 12.8V 230Ah Smart, 12.8V 230Ah LTCP, 12.8V 230Ah TM, 12.8V 230Ah H190, 12.8V 230Ah GC  
**Trade Mark:** LiTime  
**FCC ID:** 2BDSV12230  
**Standard(s) :** 47 CFR Part 2 Subpart J Section 2.1091  
447498 D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2024-07-27  
**Date of Test:** 2024-07-29 to 2024-08-05  
**Date of Issue:** 2024-08-06

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|



\* In the configuration tested, the EUT complied with the standards specified above.



Lion Cai/ Approved & Authorized  
EMC Laboratory Manager



| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| V0              |         | 2024-08-06 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                          |  |                                                                                   |  |  |
|--------------------------|--|-----------------------------------------------------------------------------------|--|--|
| Authorized for issue by: |  |                                                                                   |  |  |
|                          |  |  |  |  |
|                          |  | David Zhuang/Project Engineer                                                     |  |  |
|                          |  |  |  |  |
|                          |  | Elma Yang/Reviewer                                                                |  |  |

## Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.



## 2 Contents

|                                                  | Page     |
|--------------------------------------------------|----------|
| <b>1 Cover Page</b> .....                        | <b>1</b> |
| <b>2 Contents</b> .....                          | <b>3</b> |
| <b>3 General Information</b> .....               | <b>4</b> |
| 3.1 Details of E.U.T. ....                       | 4        |
| 3.2 Description of Support Units .....           | 4        |
| 3.3 Test Location .....                          | 4        |
| 3.4 Deviation from Standards .....               | 4        |
| 3.5 Abnormalities from Standard Conditions ..... | 4        |
| <b>4 Test Requirement</b> .....                  | <b>5</b> |
| 4.1 Assessment Result .....                      | 5        |



### 3 General Information

#### 3.1 Details of E.U.T.

|                                                                                                                                                                                           |                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Power supply:                                                                                                                                                                             | Battery:12.8V 230Ah Max2944W<br>Input:14.4±0.2V 200A<br>Output:200A 2560W |
| Frequency Range:                                                                                                                                                                          | 2402MHz to 2480MHz                                                        |
| Bluetooth Version:                                                                                                                                                                        | V5.0 BLE                                                                  |
| Modulation Type:                                                                                                                                                                          | GFSK                                                                      |
| Number of Channels:                                                                                                                                                                       | 40                                                                        |
| Antenna Type:                                                                                                                                                                             | PCB Antenna                                                               |
| Antenna Gain:                                                                                                                                                                             | 1.2dBi                                                                    |
| Sample No.:                                                                                                                                                                               | BTEK240727005AE-01                                                        |
| Remark: The information in this section is provided by the applicant or manufacturer, BANTEK is not liable to the accuracy, suitability, reliability or/and integrity of the information. |                                                                           |

Model No.: 12.8V 230Ah Plus LTCP;12.8V 230Ah,12.8V 230Ah Self-Heating,12.8V 230Ah BT,12.8V 230Ah HBT,12.8V 230Ah Mini,12.8V 230Ah Smart,12.8V 230Ah LTCP,12.8V 230Ah TM,12.8V 230Ah H190,12.8V 230Ah GC

Only the model 12.8V 230Ah Plus LTCP was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions of other models are identical for the above models, with only difference on Model No.

#### 3.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|-------------|--------------|-----------|------------|
| /           | /            | /         | /          |

#### 3.3 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.,

A5&A6, Building B1&B2, No.45 Gangtou Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518103

Tel:0755-2334 4200 Fax: 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

#### 3.4 Deviation from Standards

None

#### 3.5 Abnormalities from Standard Conditions

None



## 4 Test Requirement

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

### Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                               |                               |                                     |                          |
| 0.3–3.0                                                 | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0–30                                                  | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30–300                                                  | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500                                                |                               |                               | f/300                               | 6                        |
| 1500–100,000                                            |                               |                               | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3–1.34                                                | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30                                                 | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30–300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500                                                |                               |                               | f/1500                              | 30                       |
| 1500–100,000                                            |                               |                               | 1.0                                 | 30                       |

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 4.1 Assessment Result

☒ Passed ☐ Not Applicable

| Frequency (MHz) | Type | Conducted Power (dBm) | Maximum Tune-up (dBm) | Power Density (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|-----------------|------|-----------------------|-----------------------|-------------------------------------|-----------------------------|--------|
| 2440            | BLE  | 2.38                  | 2.5                   | 0.0006                              | 1.0000                      | Pass   |

Note: 1. The exposure evaluation safety distance is 20cm.

2. Only show the worst case in the test report.

- End of the Report -

