


Test report No: 4909377.52

## TEST REPORT

### Radio Spectrum Matters (RF)

Identification of item tested	Remote controller
Trademark	
Model and /or type reference	ME-FL01
FCC ID	2BDTY-MEFL01231129
Features	3Vdc
Applicant's name / address	Foshan Yunlu Lighting Factory No. 1, Jiebei Road, Nanhai National Eco-industrial Zone, Danzao Town, Nanhai District, Foshan City, Guangdong Province, P. R. China
Test method requested, standard	KDB 447498 D01V06 FCC Part 1.1310
Verdict Summary	COMPLIANCE
Tested by (name & signature)	Johnny Bo 
Approved by (name & signature)	Tim Yan 
Date of issue	2025-03-25
Report template No	TRF_EMС 2017-06- FCC_Exposure

## INDEX

	page
General conditions .....	3
Uncertainty .....	3
Environmental conditions .....	3
Possible test case verdicts .....	3
Definition of symbols used in this test report .....	4
Abbreviations .....	4
Document History .....	4
Remarks and Comments .....	4
1 General Information .....	5
1.1 General Description of the Item(s) .....	5
1.2 Test data .....	6
1.3 The environment(s) in which the EUT is intended to be used .....	6
2 Description of Test Setup .....	7
2.1 Operating mode(s) used for tests .....	7
2.2 Support / Auxiliary equipment / unit / software for the EUT .....	7
2.3 Test Configuration / Block diagram used for tests .....	7
3 RF Exposure Evaluation .....	8
3.1 Limits .....	8
3.2 Test Procedure .....	9
3.3 Test Result .....	9

## GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

## UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

## ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

## POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

## DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

<input checked="" type="checkbox"/> Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
<input type="checkbox"/> Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	<input checked="" type="checkbox"/>	Comma (,)	<input type="checkbox"/> Point (.)

## ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	:	Equipment Under Test
QP	:	Quasi-Peak
CAV	:	CISPR Average
AV	:	Average
CDN	:	Coupling Decoupling Network
SAC	:	Semi-Anechoic Chamber
OATS	:	Open Area Test Site
BW	:	Bandwidth
AM	:	Amplitude Modulation
PM	:	Pulse Modulation
HCP	:	Horizontal Coupling Plane
VCP	:	Vertical Coupling Plane
$U_N$	:	Nominal voltage
$T_x$	:	Transmitter
$R_x$	:	Receiver
N/A	:	Not Applicable
N/M	:	Not Measured

## DOCUMENT HISTORY

Report nr.	Date	Description
4909377.52	2025-03-25	First release.

## REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

## 1 GENERAL INFORMATION

### 1.1 General Description of the Item(s)

Description of the item .....	Remote controller
Trademark.....	<b>MEDIACOUS</b>
Model / Type number.....	ME-FL01
FCC ID .....	2BDTY-MEFL01231129
Ratings.....	3Vdc
Manufacturer.....	Same as applicant
Factory .....	Same as applicant

The product contains wireless RF module and the characteristics of wireless module:

Operating frequency range(s).....	433.92 MHz
Type of Modulation .....	ASK
Antenna type.....	Integral Antenna
Operating Temperature Range.....	-40 – 85 °C
Antenna gain.....	3 dBi

Rated power supply .....	Voltage and Frequency	Reference poles				
		L1	L2	L3	N	PE
	<input type="checkbox"/> AC: 100 – 240 V	<input type="checkbox"/>				
	<input type="checkbox"/> DC: 3,3 V					
	<input checked="" type="checkbox"/> Battery: 3 V					
Mounting position.....	<input type="checkbox"/> Table top equipment					
	<input type="checkbox"/> Wall/Ceiling mounted equipment					
	<input type="checkbox"/> Floor standing equipment					
	<input checked="" type="checkbox"/> Hand-held equipment					
	<input type="checkbox"/> Other: Built-in					

#### Intended use of the Equipment Under Test (EUT)

The apparatus as supplied for the test is Remote controller which intended for residential use, the product contains electronic control circuitry.

Copy of marking plate:

No provide.

## 1.2 Test data

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324; ISED CAB identifier: CN0130
Date of receipt of test item	2023-10-09
Date (s) of performance of tests	2023-10-09 to 2023-11-17
Test sample	Normal sample: ME-FL01 (lab on.4909377-1)

## 1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

<input checked="" type="checkbox"/>	Residential (domestic) environment.
<input checked="" type="checkbox"/>	Commercial and light-industrial environment.
<input type="checkbox"/>	Industrial environment.

## 2 DESCRIPTION OF TEST SETUP

### 2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methos	
		Conducted	Radiated
1	Transmitting	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2		<input type="checkbox"/>	<input type="checkbox"/>
3		<input type="checkbox"/>	<input type="checkbox"/>
<u>Supplemental information:</u> ---			

### 2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
---	---	---	---
<u>Supplemental information:</u> ---			

### 2.3 Test Configuration / Block diagram used for tests

Refer to Annex 3.

### 3 RF EXPOSURE EVALUATION

#### 3.1 Limits

According to KDB 447498 D01 General RF Exposure Guidance v06: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Table B.2.

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

### 3.2 Test Procedure

The product provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 23°C and 50% RH.

### 3.3 Test Result

Test Mode	Frequency Band (MHz)	Radiated RF Power Output (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	Maximum Power (mW)	Limit of Power (mW)
TX	433.92	-33.04	3.04	-30.04	0.00099	22

Remark:

$mW = 10^{(EIRP/10)}$

The test separation distances at 5 mm.

--- END ---