

## RF Exposure Evaluation Report

**Report Reference No.**..... : **MTEB25020142-H**

**FCC ID**..... : **2BDUR-2607173**

Compiled by

( position+printed name+signature)..: File administrators Alisa Luo




Supervised by

( position+printed name+signature)..: Test Engineer Sunny Deng



Approved by

( position+printed name+signature)..: Manager Yvette Zhou



Date of issue..... : **Feb.24,2025**

**Representative Laboratory Name. :** **Shenzhen Most Technology Service Co., Ltd.**

Address..... : No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,  
Nanshan, Shenzhen, Guangdong, China.

**Applicant's name**..... : **RADIOSHACK WORLDWIDE CORP.**

Address..... : Millennium Tower, 18th floor Paseo General Escalon Number 3675  
Col. Escalon, San Salvador, El Salvador

**Test specification/ Standard**..... : **47 CFR Part 1.1307**

**47 CFR Part 2.1093**

TRF Originator..... : Shenzhen Most Technology Service Co., Ltd.

**Shenzhen Most Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**..... : **TRIPLE FOLDING TOUCH KEYBOARD**

Trade Mark..... : Radioshack

Model/Type reference..... : 2607173

Listed Models ..... : 2607173 Black , 2607173 Grey

Modulation Type..... : GFSK,  $\pi/4$ DQPSK, 8DPSK

Operation Frequency..... : From 2402MHz to 2480MHz

Hardware Version..... : VER01-00

Software Version..... : CRC\_6569-FUS08

Rating..... : DC 3.7V by Battery  
DC 5V by USB Port

Result..... : **PASS**

**TEST REPORT**

Equipment under Test : TRIPLE FOLDING TOUCH KEYBOARD

Model /Type : 2607173

Listed Models : 2607173 Black , 2607173 Grey

Remark : Different color

Applicant : **RADIOSHACK WORLDWIDE CORP.**

Address : Millennium Tower, 18th floor Paseo General Escalon Number 3675 Col. Escalon, San Salvador, El Salvador

Manufacturer : **SHENZHEN MARVO TECHNOLOGY CO. LTD**

Address : 6th Floor, Building A, DongFangYaYuan, Chen Tian communities, Xixiang Bao'an District, Shenzhen

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

| Revision | Issue Date | Revisions     | Revised By |
|----------|------------|---------------|------------|
| 00       | 2025.02.24 | Initial Issue | Alisa Luo  |
|          |            |               |            |
|          |            |               |            |

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 2.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \left[ \sqrt{f(\text{GHz})} \right]$$
  
 $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

## 2.1.3 EUT RF Exposure

## Measurement Data

## EDR

| GFSK             |                         |                         |                       |
|------------------|-------------------------|-------------------------|-----------------------|
| Test channel     | Peak Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |
|                  |                         |                         | (dBm)                 |
| Lowest(2402MHz)  | -1.147                  | $-1.147 \pm 1$          | -0.147                |
| Middle(2441MHz)  | -1.709                  | $-1.709 \pm 1$          | -0.709                |
| Highest(2480MHz) | -2.434                  | $-2.434 \pm 1$          | -1.434                |

| $\pi/4$ DQPSK    |                         |                         |                       |
|------------------|-------------------------|-------------------------|-----------------------|
| Test channel     | Peak Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |
|                  |                         |                         | (dBm)                 |
| Lowest(2402MHz)  | -0.218                  | $-0.218 \pm 1$          | 0.782                 |
| Middle(2441MHz)  | -0.893                  | $-0.893 \pm 1$          | 0.107                 |
| Highest(2480MHz) | -1.561                  | $-1.561 \pm 1$          | -0.561                |

| 8DPSK            |                         |                         |                       |
|------------------|-------------------------|-------------------------|-----------------------|
| Test channel     | Peak Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |
|                  |                         |                         | (dBm)                 |
| Lowest(2402MHz)  | 0.182                   | $0.182 \pm 1$           | 1.182                 |
| Middle(2441MHz)  | -0.466                  | $-0.466 \pm 1$          | 0.534                 |
| Highest(2480MHz) | -1.244                  | $-1.244 \pm 1$          | -0.244                |

| Worst case: 8DPSK |                                                    |                          |      |                     |                        |                       |
|-------------------|----------------------------------------------------|--------------------------|------|---------------------|------------------------|-----------------------|
| Channel           | Maximum Peak<br>Conducted Output<br>Power<br>(dBm) | Maximum tune-up<br>Power |      | Calculated<br>value | Exclusion<br>threshold | SAR Test<br>Exclusion |
|                   |                                                    | (dBm)                    | (mW) |                     |                        |                       |
| Lowest(2402MHz)   | 0.182                                              | 1.182                    | 1.31 | 0.40                | 3.0                    | Yes                   |

.....THE END OF REPORT.....