

FCC RF Exposure Evaluation

1. Product Information

FCC ID	2BDZD-M6GE
Product Name	MINI PC
Test Model	N/A
Power Supply	Input: 100-240V~ 50/60Hz 1.0A Output: 12.0V-3.0A
Modulation Type	Bluetooth BR/EDR: GFSK, π /4DQPSK, 8DPSK Bluetooth LE: GFSK 2.4G WIFI: IEEE 802.11b: DSSS IEEE 802.11g/n: OFDM 5G WIFI : IEEE 802.11a/ac/n: OFDM
Antenna Type	BT/WIFI ANT 1: FPC Antenna WIFI ANT 2: FPC Antenna
Antenna Gain	Bluetooth: 1.96dBi 2.4G WIFI ANT 1: 1.96dBi 2.4G WIFI ANT 2: 2.12dBi 5G WIFI ANT 1: 2.78dBi 5G WIFI ANT 2: 3.22dBi
Frequency Range	Bluetooth: 2402 – 2480MHz 2.4G WIFI: 2412MHz~2462MHz 5G WIFI: 5745 - 5825MHz
Exposure Category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	fixed device

2. Evaluation Method and Limit

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

CPW-1 can only use antennas certificated as follows provided by manufacturer;

Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Note
FPC Antenna	2402 MHz-2480 MHz 2412MHz-2462MHz 5745MHz-5825MHz	Bluetooth: 1.96dBi 2.4G WIFI ANT 1: 1.96dBi 2.4G WIFI ANT 2: 2.12dBi 5G WIFI ANT 1: 2.78dBi 5G WIFI ANT 2: 3.22dBi	Bluetooth & WLAN Antenna

6. Conducted Power Results

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	4.66
	39	2441	3.69
	78	2480	3.42
$\pi/4$ DQPSK	0	2402	7.81
	39	2441	7.47
	78	2480	7.14
8DPSK	0	2402	8.70
	39	2441	8.35
	78	2480	7.63

[BLE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
1M	0	2402	6.35
	19	2440	5.97
	39	2480	5.61
2M	0	2402	6.00
	19	2440	5.63
	39	2480	5.26

[2.4GWIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)		
			ANT1	ANT2	MIMO
IEEE 802.11b	1	2412	13.35	13.65	/
	6	2437	12.57	13.42	/
	11	2462	12.60	13.00	/
IEEE 802.11g	1	2412	13.77	13.39	/
	6	2437	12.86	12.89	/
	11	2462	12.90	12.65	/
IEEE 802.11n HT20 SISO	1	2412	13.66	13.63	/
	6	2437	12.94	12.98	/
	11	2462	12.78	12.46	/
IEEE 802.11n HT40 SISO	3	2422	14.16	14.04	/
	6	2437	13.30	13.24	/
	9	2452	13.20	12.99	/
IEEE 802.11n HT20 MIMO	1	2412	13.13	12.95	16.05
	6	2437	12.34	12.21	15.29
	11	2462	12.02	11.60	14.83
IEEE 802.11n HT40 MIMO	3	2422	13.18	13.59	16.40
	6	2437	12.58	13.00	15.81
	9	2452	12.46	12.39	15.44

[5.8WIFI Max Conducted Power]

Mode	TX Type	Frequency (MHz)	Conducted Output Power (dBm)		
			ANT1	ANT2	MIMO
802.11a	SISO	5745	11.45	12.21	/
		5785	12.66	13.12	/
		5825	13.14	13.23	/
802.11n (HT20)	SISO	5745	11.76	11.88	/
		5785	12.88	12.58	/
		5825	13.47	12.89	/
802.11n (HT40)	SISO	5755	12.20	12.41	/
		5795	12.97	12.73	/
802.11n (HT20)	MIMO	5745	10.64	11.12	13.90
		5785	11.50	11.51	14.52
		5825	11.98	11.79	14.90
802.11n (HT40)	MIMO	5755	11.05	11.58	14.33
		5795	12.00	11.81	14.92
802.11ac (VHT20)	SISO	5745	11.83	12.61	/
		5785	12.85	13.25	/
		5825	13.36	13.49	/
802.11ac (VHT40)	SISO	5755	12.36	12.99	/
		5795	13.20	13.39	/
802.11ac (VHT80)	SISO	5775	12.83	12.96	/
802.11ac (VHT20)	MIMO	5745	11.18	11.89	14.56
		5785	12.12	12.61	15.38
		5825	12.71	12.93	15.83
802.11ac (VHT40)	MIMO	5755	11.88	12.64	15.29
		5795	12.76	13.16	15.97
802.11ac (VHT80)	MIMO	5775	12.50	13.07	15.80

7.Manufacturing Tolerance

<BT>

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	5.0	4.0	4.0
Tolerance ±(dB)	1.0	1.0	1.0
$\pi/4$ DQPSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8.0	8.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0
8DPSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	9.0	9.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0

<BLE-1M>

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	7.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

<BLE-2M>

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

<2.4G WIFI >

11B (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	17.0	16.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	17.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

<5.8GWIFI >

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	14.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	15.0	15.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165

Target (dBm)	15.0	16.0	16.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	16.0	16.0	
Tolerance ±(dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	16.0		
Tolerance ±(dB)	1.0		

8. Evaluation Results

8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

BT

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
GFSK	9.0	7.9433	1.96	1.5704	100%	0.0025	1.0000
$\pi/4$ DQPSK	9.0	7.9433	1.96	1.5704	100%	0.0025	1.0000
8-DPSK	8.0	6.3096	1.96	1.5704	100%	0.0020	1.0000

BLE

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
GFSK	7.0	5.0119	1.96	1.5704	100%	0.0016	1.0000
GFSK	6.0	3.9811	1.96	1.5704	100%	0.0012	1.0000

2.4G WIFI

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11b	14.0	25.1189	2.12	1.6293	100%	0.0081	1.0000
IEEE 802.11g	14.0	25.1189	1.96	1.5704	100%	0.0078	1.0000
IEEE 802.11n HT20	17.0	50.1187	5.13	3.2584	100%	0.0325	1.0000
IEEE 802.11n HT40	17.0	50.1187	5.13	3.2584	100%	0.0325	1.0000

5.8G WIFI

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	14.0	25.1189	3.22	2.0989	100%	0.0105	1.0000
IEEE 802.11 n HT20	15.0	31.6228	6.23	4.1976	100%	0.0264	1.0000
IEEE 802.11 n HT40	15.0	31.6228	6.23	4.1976	100%	0.0264	1.0000
IEEE 802.11 ac20	16.0	39.8107	6.23	4.1976	100%	0.0332	1.0000
IEEE 802.11 ac40	16.0	39.8107	6.23	4.1976	100%	0.0332	1.0000
IEEE 802.11 Ac80	16.0	39.8107	6.23	4.1976	100%	0.0332	1.0000

Remark:

1. Output power including tune-up tolerance;

2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

8.2 Simultaneous Transmission MPE

Simultaneous transmission MPE

2.4G WIFI MPE (mW/cm ²)	5G WIFI MPE (mW/cm ²)	BT MPE (mW/cm ²)	BLE MPE (mW/cm ²)	Max.sum of the MPE ratios	Limit	Test Results
0.0325	0.0332	0.0025	0.0016	0.0698	1	PASS

9.Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....THE END OF REPORT.....