

Passive Test For BT												
Freq (MHz)	Effi (%)	Effi (dBi)	Gain (dBi)	Gain (dB)	UHS (%)	DRIS (%)	Max (dB)	Min (dB)	irectivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	15.25	-9.49	-4.14	-6.29	5.169	6.081	-4.14	-17.04	5.35	30	46.52	46.42
2410	15.1	-9.83	-3.43	-5.58	6.064	7.022	-3.43	-17.41	5.4	0	46.11	46.03
2420	16.77	-9.29	-3.9	-6.05	5.559	6.209	-3.9	-18.82	5.39	0	46.45	46.36
2430	17.54	-9.38	-4	-6.15	5.545	5.994	-4	-19.73	5.38	0	46.15	46.03
2440	18.4	-8.83	-4.56	-6.71	4.995	5.402	-4.56	-20.83	5.27	0	46.75	46.57
2450	16.17	-8.93	-4.81	-6.96	4.925	5.249	-4.81	-24.59	5.12	0	46.74	46.58
2460	15.53	-8.23	-6.28	-8.43	3.693	3.837	-6.28	-29.88	4.95	0	46.92	46.75
2470	14.17	-8.44	-6.7	-8.85	3.576	3.594	-6.7	-29.77	4.75	0	46.63	46.48
2480	13.41	-9.93	-7.37	-9.52	3.198	3.207	-7.37	-28.72	4.57	0	46.92	46.8

Application Information	
O4Version	4.95.303
TotalTime	3m 57s 937ms
AdditionalInfor	NULL

