

## FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density

### Calculated Formulary:

Predication of MPE limit at a given distance

S = PG/4  $\pi$  R<sup>2</sup> = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

**Calculated Data:**

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Output Power★		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
2.4G Wi-Fi	2412~2462	6	3.98	28.00	630.96	30	0.2220	1.0
5G Wi-Fi	5150~5250	6	3.98	29.50	891.25	30	0.3136	1.0
	5725-5850	6	3.98	30.00	1000.00	30	0.3520	1.0

**Note:**

1. For the above tune up power were declared by the manufacturer.
2. 2.4G Wi-Fi and 5G Wi-Fi can transmit simultaneously.

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.2220/1.00 + 0.3520/1 = 0.2220 + 0.3520 = 0.5740 < 1.0$$

**Result:** The device meet FCC MPE at 30 cm distance.