

Label Location On EUT



NODSOLEX

PRODUCT ----- Portable Power Station
MODEL ----- SN-300X
CAPACITY ----- 249.6Wh
NOMINAL VOLTAGE ----- 12.8V
AC INPUT ----- 100-130V AC / 60Hz (200W Max)
XT60 INPUT ----- 12-28V DC, 8A (100W Max)
Type-C INPUT / OUTPUT ----- 5V---3A, 9V---3A
12V---3A, 15V---3A
20V---5A (100W Max)
USB-A1 / A2 OUTPUT ----- 5V---3A, 9V---2A
12V---1.5A (18W Max)
Wireless Charge ----- 15W Max
AC OUTPUT ----- 120V AC / 60Hz, 300W Total
DC OUTPUT ----- 12V DC 10A, 120W Total
CHARGING TEMPERATURE ----- 0~40°C (32~104°F)
DISCHARGING TEMPERATURE ----- -10~40°C (14~104°F)
FCC ID: 2BE3Z-SN300X

CAUTION:
This device is not intended for use in a commercial repair facility. Risk of Electric Shock. Refer replacement to qualified service personnel. Do not remove cover. Risk of Injury To Persons. Do not use this product if the power cord or the internal batteries are damaged in any way. Risk of Electric Shock. Connect only to properly grounded outlets.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
This device must accept any interference received, including interference that may cause undesired operation.

WARNING:

Risk of Electric Shock and Risk of Fire. This device is not to be stored in a vehicle. Do not overcharge the internal battery. See Instruction Manual. Do not smoke, strike a match, or cause a spark in the vicinity of the power pack. Only charge the internal battery in a well ventilated area.

FCC | **UN38.3**

www.nodsolex.com

