

FCC&ISED EMC TEST REPORT

Report No.: DDT-B24042312-4E01

Applicant	:	Rhino Sp. z o o
Address	:	Strzegomska 140A, 54-429 Wrocław, Poland
Equipment under Test	:	Smart Metering Gateway
Model No.	:	Rhino AP GSM
Manufacturer	:	Rhino Sp. z o o
Address	:	Strzegomska 140A, 54-429 Wrocław, Poland
Trade Mark	:	N/A

Issued By: Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park, Development Area, Tianjin, China.

Tel: +86-022-58038033, E-mail: ddt@dga.com <http://www.ddttest.com>



REPORT

CONTENTS

1 Summary of Test Results	5
2 General Test Information	6
2.1 Description of EUT	6
2.2 Port of EUT	6
2.3 Accessories of EUT	6
2.4 Test peripherals	6
2.5 Block diagram EUT configuration for test	6
2.6 EUT operating mode(s)	7
2.7 Deviations of test standard	7
2.8 Test laboratory	7
2.9 Measurement uncertainty	7
2.10 Abbreviations	7
3 Conducted Emissions	8
3.1 General Information	8
3.2 Test Equipment	8
3.3 Reference Standard	8
3.4 Test Arrangement	8
3.5 Test Specification and Limit	9
3.6 Test Result	9
4 Radiated Emissions (30MHz to 1GHz)	11
4.1 General Information	11
4.2 Test Equipment	11
4.3 Reference Standard	11
4.4 Test Arrangement	12
4.5 Test Specification and Limit	13
4.6 Test Result	13
Annex A. Test Setup Photos	15
Annex B. Photos of EUT	17

Test Report Declare

Applicant	:	Rhino Sp. z o o
Address	:	Strzegomska 140A, 54-429 Wrocław, Poland
Equipment under Test	:	Smart Metering Gateway
Model No.	:	Rhino AP GSM
Manufacturer	:	Rhino Sp. z o o
Address	:	Strzegomska 140A, 54-429 Wrocław, Poland
Trade Mark	:	N/A

Test Standard Used:

47 CFR Part 15 Subpart B, ICES-003 Issue 7: October 2020, IEEE/ANSI C63.4-2014, IEEE/ANSI C63.4a-2017

We Declare:

The equipment described above is tested and assessed by Tianjin Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The tested and assessed results are contained in this test report and Tianjin Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assessments.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above standards.

Report No.:	DDT-B24042312-4E01	
Date of Receipt:	Jul. 04, 2024	Date of Test: Jul. 04, 2024~Jul. 05, 2024

Prepared By:

Novak Wei/Engineer

Approved By:

Aaron Zhang/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Tianjin Dongdian Testing Service Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Aug. 15, 2024	

1 Summary of Test Results

Description of Test Item	Standard	Result
Conducted Emissions	IEEE/ANSI C63.4-2014, IEEE/ANSI C63.4a-2017, 47 CFR Part 15 Subpart B, ICES-003 Issue 7: October 2020	Pass
Radiated Emissions (30MHz to 1GHz)	IEEE/ANSI C63.4-2014, IEEE/ANSI C63.4a-2017, 47 CFR Part 15 Subpart B, ICES-003 Issue 7: October 2020,	Pass

2 General Test Information

2.1 Description of EUT

EUT Name	:	Smart Metering Gateway
Model Number	:	Rhino AP GSM
Sample No.	:	Y24042312-04
Power supply	:	DC 5V-24V
Test Power supply	:	DC 12V
EUT Class	:	Class B

2.2 Port of EUT

Port	Description
DC Port	Supply Power to EUT
RS485 Port	Connect other RS485 devices to collect information
RS232 Port	Connect other RS232 devices to collect information
Ethernet Port	Connect to Rhino Cloud

2.3 Accessories of EUT


Accessories	Manufacturer	Model No.	Description	Remark
N/A	N/A	N/A	N/A	N/A

2.4 Test peripherals

Device	Manufacturer	Model No.	Description	Remark
Notebook	Lenovo Beijing Co. Ltd.	ThinkPad E450c	CE/FCC	TP00067A
AE	N/A	N/A	N/A	N/A
AC/DC Adapter	N/A	N/A	N/A	N/A

2.5 Block diagram EUT configuration for test

Mode 1



2.6 EUT operating mode(s)

Mode 1	The EUT is powered by an AC to DC adapter, RS485 and RS232 and AE connection. The EUT communicates with the Notebook through the network cable, and the Notebook outputs instructions to keep the sample in the firing state for testing.
--------	---

2.7 Deviations of test standard

No Deviation.

2.8 Test laboratory

Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China.

Tel: +86-22-58038033, <http://www.ddttest.com>, Email: ddt@dgddt.com

NVLAP (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

CNAS (China National Accreditation Service for Conformity Assessment) CODE: L13402

FCC Designation Number: CN5004; FCC Test Firm Registration Number: 368676

ISED (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

VCCI Facility Registration Number: C-20089, T-20093, R-20125, G-20122

2.9 Measurement uncertainty

Test Item	Uncertainty
Conducted Emissions at Mains Power Port	3.4 dB (150KHz-30MHz)
Radiated Emissions (30MHz to 1GHz)	5.2 dB (Antenna Polarize: Hor.)
	5.2 dB (Antenna Polarize: Ver.)
Radiated Emissions (Above 1GHz)	5.0 dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.10 Abbreviations

For the purposes of the present document, the following abbreviations apply:

EUT: Equipment Under Test

QP: Quasi-Peak

PK: Peak,

AV: Average

CAV: CISPR Average

CDN: Coupling Decoupling Network

AM: Amplitude Modulation

N/A: Not Applicable

3 Conducted Emissions

3.1 General Information

Test date	Jul. 05, 2024	Test engineer	Freya Wei	
Climate condition	Ambient temperature	27.0°C	Relative humidity	48.7%
	Atmospheric pressure	100.1kPa		
Test place	Shield Room 2#			


3.2 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Two-Line V-Network	Rohde & Schwarz	ENV216	101122	Feb. 18, 2024	1 Year
EMI Test Receiver	Rohde & Schwarz	ESCI	100375	Feb. 18, 2024	1 Year
Impedance Stabilization Network	TESEQ	ISN T800	30844	Sep. 28, 2023	1 Year
Test Software	TOYO	EP5/CE	Ver 5.4.40	N/A	N/A

3.3 Reference Standard

IEEE/ANSI C63.4-2014,
 IEEE/ANSI C63.4a-2017,
 47 CFR Part 15 Subpart B,
 ICES-003 Issue 7: October 2020

3.4 Test Arrangement



The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT's power adapter was connected to the power mains through a line impedance stabilization network (AMN), which provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted disturbance.

The bandwidth of test receiver is set at 9 kHz.

The frequency range from 150 kHz to 30MHz is checked.

Pre-scan measurements were performed in all operating mode or resolution. But final measurements were performed in worst cases based on pre-scan measurements.

3.5 Test Specification and Limit

Class B

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

Note for test result

Note1): According pre-test, the worst test modes decided as below and reported. Only data of worst mode was reported in test result.

Note2) Line = Polarity of input power (Live or Neutral), N: Abbreviation of Neutral Polarity, L1: Abbreviation of Live Polarity,


Note3) Level (Quasi-Peak and/or C/Average) = Meter Reading + Factor,

Note4) Factor = AMN (or AAN) Insertion Loss + Cable Loss,

Note5) Margin = Limit – Level (Quasi-Peak and/or C/Average)

3.6 Test Result

Sample No.	Operation Mode	Remarks	Result
Y24042312-04	Mode 1	Final measurement, minimum margin 12.2dB	Pass



Final Result

--- N Phase ---

No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]		[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.16535	43.2	28.6	9.8	53.0	38.4	65.2	55.2	12.2	16.8
2	0.15525	42.8	27.7	9.8	52.6	37.5	65.7	55.7	13.1	18.2
3	0.19201	40.4	26.3	9.8	50.2	36.1	63.9	53.9	13.7	17.8
4	0.15021	41.9	26.9	9.8	51.7	36.7	66.0	56.0	14.3	19.3
5	0.4903	24.2	17.4	9.8	34.0	27.2	56.2	46.2	22.2	19.0
6	6.49367	22.5	18.1	10.0	32.5	28.1	60.0	50.0	27.5	21.9
7	2.86789	12.5	7.8	10.0	22.5	17.8	56.0	46.0	33.5	28.2

--- L1 Phase ---

No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]		[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.15974	42.9	28.6	9.8	52.7	38.4	65.5	55.5	12.8	17.1
2	0.19299	40.6	26.5	9.8	50.4	36.3	63.9	53.9	13.5	17.6
3	0.15145	41.0	26.1	9.8	50.8	35.9	65.9	55.9	15.1	20.0
4	0.49218	24.1	17.1	9.8	33.9	26.9	56.1	46.1	22.2	19.2
5	6.51821	20.7	15.9	10.0	30.7	25.9	60.0	50.0	29.3	24.1
6	2.82296	12.4	7.9	10.0	22.4	17.9	56.0	46.0	33.6	28.1

4 Radiated Emissions (30MHz to 1GHz)

4.1 General Information

Test date	Jul. 04, 2024	Test engineer	Dominic Du	
Climate condition	Ambient temperature	26.4°C	Relative humidity	47.5%
	Atmospheric pressure	100.4kPa		
Test place	10m Chamber			


4.2 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101024	Feb. 18, 2024	1 Year
BiLog Antenna	TESEQ	CBL 6112D	29068	Oct. 10, 2022	2 Year
Low Noise Amplifier	SONOMA	310N	300913	Feb. 18, 2024	1 Year
RF Selector 4CH	TOYO	NS4904N	Selector1	N/A	N/A
RF Selector 4CH	TOYO	NS4904N	Selector2	N/A	N/A
Mast Control	INNCO	CONTROLLE R CO2000	ZOAA97AZ10 0013D	N/A	N/A
BiLog Antenna	TESEQ	CBL 6112D	29069	Oct. 10, 2022	2 Year
EMI Test Receiver	Rohde & Schwarz	ESCI	101030	Feb. 18, 2024	1 Year
Low Noise Amplifier	SONOMA	310N	334532	Feb. 18, 2024	1 Year
Test Software	TOYO	EP5/RE	Ver 5.7.10	N/A	N/A

4.3 Reference Standard

IEEE/ANSI C63.4-2014,
 IEEE/ANSI C63.4a-2017,
 47 CFR Part 15 Subpart B,
 ICES-003 Issue 7: October 2020,

4.4 Test Arrangement



Procedure of Preliminary Test

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in operation modes.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

Mains cables, telephone lines or other connections to auxiliary equipment located outside the test are shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No extension cords shall be used to mains receptacle.

The antenna was placed at 3 meters away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.

The Analyzer / Receiver quickly scanned from 30MHz to 1GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

The test mode(s) described were scanned during the preliminary test:

After the preliminary scan, we found the test mode producing the highest emission level. The EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

Procedure of Final Test

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.

Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

The test data of the worst-case condition(s) was recorded.

4.5 Test Specification and Limit

Class B

Frequencies (MHz)	Radiated Emissions Limits at 3 meters (dB μ V/m)
30-88	40
88-216	43.5
216-230	46
230-960	
960-1000	54

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
3. If results comply with FCC part 15 limits, then they also comply with ICES-003 Issue 7: October 202.

Note for test result

Note1): According pre-test, the worst test modes decided as below and reported. Only data of worst mode was reported in test result.

Note2) (P): Abbreviation of Antenna Polarity

Note3) Receiving antenna polarization: Horizontal and/or Vertical. Antenna Height: 1 m to 4 m

Note4) Level QP (Quasi-Peak) = Reading QP + Factor


Note5) Factor = Antenna Factor + Cable Loss - Amp. Gain

Note6) Margin = Limit – Level QP

Note7) The spike (902MHz~928MHz) over the limit is coming from the SRD, radiated emissions shall be ignored.

4.6 Test Result

Sample No.	Operation Mode	Remarks	Result
Y24042312-04	Mode 1	Final measurement, minimum margin 8.8 dB	Pass



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μ V)]	c. f [dB(1/m)]	Result QP [dB(μ V/m)]	Limit QP [dB(μ V/m)]	Margin QP [dB]	Height [cm]	Angle [°]
1	81.412	H	46.2	-15.9	30.3	40.0	9.7	227.0	359.7
2	138.389	H	27.6	-11.1	16.5	43.5	27.0	316.0	231.9
3	500.009	H	39.0	-1.8	37.2	46.0	8.8	179.0	134.5
4	91.374	V	47.2	-13.7	33.5	43.5	10.0	138.0	224.3
5	126.312	V	43.8	-10.6	33.2	43.5	10.3	102.0	88.0
6	499.994	V	35.6	-1.8	33.8	46.0	12.2	103.0	279.4

Annex A. Test Setup Photos


A.1 Conducted Emissions




A.2 Radiated Emissions (30MHz to 1GHz)




Annex B.Photos of EUT















Regulatory Statement and Label Marking Advice for the FCC SDoC

1. Marking Suggested for the label:

Trade Name and model number

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2. Statement suggested for the User Manual:

Warning: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Note: If shielded cables or special accessories are required for compliance, a statement must be included which instructs the user to employ them, for example, shielded cables must be used with this unit to ensure compliance with the Class B FCC limits.

Suggested text for the notice indicating compliance with this Standard:

CAN ICES (B) / NMB (B)

Statement

1. The report is invalid without the inspection and testing special seal of the company.
2. This report is invalid if altered.
3. This report is responsible for the conformance testing of sample(s) received.
4. This report shall not be reproduced, without the written approval of test laboratory. The copy of the report not stamped again with the inspection and testing special seal is invalid.
5. Item with “☆” was subcontracted to other laboratories.
6. The report without CMA mark has no effect on social proof.
7. Any objections must be raised to our company within 15 days on receiving the report, overdue will not be accepted.
8. The sample(s) must be collected within three months, overdue will be dealt with by our company.
9. The report is invalid without the signature of editor, reviewer, approver.

Test Laboratory: Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China.

Postcode: 300385

Tel: 022-58038033

Fax: 022-58038033

Website: <http://www.ddttest.com>

END OF REPORT