




# TEST REPORT

<b>FCC ID</b> ..... :	2BE6N-W520	
<b>Test Report No</b> ..... :	TCT250619E057	
<b>Date of issue</b> ..... :	Jul. 17, 2025	
<b>Testing laboratory</b> .....	SHENZHEN TONGCE TESTING LAB	
<b>Testing location/ address:</b>	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
<b>Applicant's name</b> ..... :	GIRAFIT INC	
<b>Address</b> ..... :	21642 GOLDEN POPPY COURT, WALNUT, California 91749, United States	
<b>Manufacturer's name</b> ... :	GIRAFIT INC	
<b>Address</b> ..... :	21642 GOLDEN POPPY COURT, WALNUT, California 91749, United States	
<b>Standard(s)</b> .....	FCC CFR Title 47 Part 15 Subpart C Section 15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2020	
<b>Product Name</b> ..... :	W520 Window Camera	
<b>Trade Mark</b> .....	N/A	
<b>Model/Type reference</b> ..... :	GRF-W520, GRF-W520G, GRF-W520GW, GRF-W520S, GRF-W520SW, W520, W520G, W520S	
<b>Rating(s)</b> ..... :	Refer to EUT description of page 3	
<b>Date of receipt of test item</b> .....	Jun. 19, 2025	
<b>Date (s) of performance of test</b> ..... :	Jun. 19, 2025 ~ Jul. 17, 2025	
<b>Tested by (+signature)</b> ... :	Yannie ZHONG	
<b>Check by (+signature)</b> ..... :	Beryl ZHAO	
<b>Approved by (+signature)</b> :	Tomsin	



**General disclaimer:**

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## Table of Contents

<b>1. General Product Information .....</b>	<b>3</b>
1.1. EUT description .....	3
1.2. Model(s) list.....	3
1.3. Operation Frequency .....	4
<b>2. Test Result Summary .....</b>	<b>5</b>
<b>3. General Information.....</b>	<b>6</b>
3.1. Test environment and mode.....	6
3.2. Description of Support Units.....	7
<b>4. Facilities and Accreditations .....</b>	<b>8</b>
4.1. Facilities .....	8
4.2. Location .....	8
<b>5. Measurement Uncertainty .....</b>	<b>8</b>
<b>6. Test Results and Measurement Data .....</b>	<b>9</b>
6.1. Antenna requirement .....	9
6.2. Conducted Emission.....	10
6.3. Maximum Conducted (Peak) Output Power .....	14
6.4. Emission Bandwidth .....	15
6.5. Power Spectral Density.....	16
6.6. Conducted Band Edge and Spurious Emission Measurement .....	17
6.7. Radiated Spurious Emission Measurement.....	19
<b>Appendix A: Test Result of Conducted Test</b>	
<b>Appendix B: Photographs of Test Setup</b>	
<b>Appendix C: Photographs of EUT</b>	

## 1. General Product Information

### 1.1. EUT description

Product Name.....:	W520 Window Camera
Model/Type reference.....:	GRF-W520
Sample Number.....:	TCT250619E056-0101
Operation Frequency .....	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)/802.11ax(HE20)) 2422MHz~2452MHz (802.11n(HT40)/802.11ax(HE40))
Channel Separation .....	5MHz
Number of Channel .....	11 for 802.11b/802.11g/802.11n(HT20)/802.11ax(HE20) 7 for 802.11n(HT40)/802.11ax(HE40)
Modulation Technology .....	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n/802.11ax: Orthogonal Frequency Division Multiplexing (OFDM)
Data speed.....:	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n/802.11ax: Up to 150Mbps
Antenna Type.....:	Chip Antenna
Antenna Gain.....:	1.75dBi
Rating(s).....:	Adapter Information 1/2: MODEL: BS05A-0501000US INPUT: AC 100-240V, 50/60Hz, 0.25A Max OUTPUT: DC 5V, 1000mA Adapter Information 3: Model: CS-0501000 Input: AC 100-240V, 50/60Hz, 0.5A Max. Output: DC 5V, 1.0A

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

### 1.2. Model(s) list

No.	Model No.	Tested with
1	GRF-W520	<input checked="" type="checkbox"/>
Other models	GRF-W520G, GRF-W520GW, GRF-W520S, GRF-W520SW, W520, W520G, W520S	<input type="checkbox"/>

Note: GRF-W520 is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names, image pixel, flash memory capacity and product appearance color. So the test data of GRF-W520 can represent the remaining models.

### 1.3. Operation Frequency

#### For 802.11b/g/n(HT20)/ax(HE20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	--	--

#### For 802.11n(HT40)/ax(HE40)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

**Note:**

*In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:*

#### 802.11b/802.11g/802.11n(HT20)/802.11ax(HE20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

#### 802.11n(HT40)/802.11ax(HE40)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

## 2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3)	PASS
6dB Emission Bandwidth	§15.247 (a)(2)	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d)	PASS
Spurious Emission	§15.205/§15.209	PASS

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. General Information

#### 3.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	24.3 °C	25.7 °C
Humidity:	48 % RH	51 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar
Test Software:		
Software Information:	SSCOM V5.13.1	
Power Level:	13	
Test Mode:		
Engineer mode:	Keep the EUT in continuous transmitting by select channel and modulations with max duty cycle.	
<p>The sample was placed 0.8m &amp; 1.5m for the measurement below &amp; above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case (Z axis) are shown in Test Results of the following pages.</p>		

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

**Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.**

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	6.5Mbps
802.11n(HT40)	13.5Mbps
802.11ax(HE20)	6.5Mbps
802.11ax(HE40)	13.5Mbps

### 3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 4. Facilities and Accreditations

### 4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098  
SHENZHEN TONGCE TESTING LAB  
Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

### 4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

## 5. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 3.10$ dB
2	RF power, conducted	$\pm 0.12$ dB
3	Spurious emissions, conducted	$\pm 0.11$ dB
4	All emissions, radiated(<1 GHz)	$\pm 4.56$ dB
5	All emissions, radiated(1 GHz - 18 GHz)	$\pm 4.22$ dB
6	All emissions, radiated(18 GHz- 40 GHz)	$\pm 4.36$ dB



## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

**Standard requirement:**

FCC Part15 C Section 15.203 /247(c)

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

**E.U.T Antenna:**

The WIFI antenna is chip antenna which permanently attached, and the best case gain of the antenna is 1.75dBi.



## 6.2. Conducted Emission

### 6.2.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.207														
<b>Test Method:</b>	ANSI C63.10:2020														
<b>Frequency Range:</b>	150 kHz to 30 MHz														
<b>Receiver setup:</b>	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
<b>Limits:</b>	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
<b>Test Setup:</b>	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
<b>Test Mode:</b>	Transmitting Mode														
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.</li> </ol>														
<b>Test Result:</b>	PASS														


**6.2.2. Test Instruments**

Conducted Emission Shielding Room Test Site (843)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI3	100898	Jun. 26, 2025	Jun. 25, 2026
LISN	Schwarzbeck	NSLK 8126	8126453	Jan. 21, 2025	Jan. 20, 2026
Attenuator	N/A	10dB	164080	Jun. 26, 2025	Jun. 25, 2026
Line-5	TCT	CE-05	/	Jun. 26, 2025	Jun. 25, 2026
EMI Test Software	EZ_EMG	EMEC-3A1	1.1.4.2	/	/

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: L1

Temperature: 24.3 (°C)

Humidity: 48 %

Limit: FCC Part 15C Conduction(QP)

Power: AC 120V/60Hz (Adapter Model No.:CS-0501000)

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	42.76	9.96	52.72	66.00	-13.28	QP	
2		0.1500	21.41	9.96	31.37	56.00	-24.63	AVG	
3		0.2340	37.40	9.93	47.33	62.31	-14.98	QP	
4		0.2340	17.03	9.93	26.96	52.31	-25.35	AVG	
5		0.4900	31.83	9.90	41.73	56.17	-14.44	QP	
6		0.4900	22.37	9.90	32.27	46.17	-13.90	AVG	
7		1.5420	24.38	9.98	34.36	56.00	-21.64	QP	
8		1.5420	13.79	9.98	23.77	46.00	-22.23	AVG	
9		3.5139	22.82	10.09	32.91	56.00	-23.09	QP	
10		3.5139	7.42	10.09	17.51	46.00	-28.49	AVG	
11		29.2100	18.60	10.87	29.47	60.00	-30.53	QP	
12		29.2100	-0.91	10.87	9.96	50.00	-40.04	AVG	

**Note:**

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

**Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)**



Site 844 Shielding Room Phase: **N** Temperature: 24.3 (°C) Humidity: 48 %  
 Limit: FCC Part 15C Conduction(QP) Power: AC 120V/60Hz (Adapter Model No.:CS-0501000)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1620	42.30	9.94	52.24	65.36	-13.12	QP	
2		0.1620	22.72	9.94	32.66	55.36	-22.70	AVG	
3		0.2459	36.29	9.93	46.22	61.89	-15.67	QP	
4		0.2459	14.34	9.93	24.27	51.89	-27.62	AVG	
5		0.4900	30.62	9.93	40.55	56.17	-15.62	QP	
6		0.4900	22.12	9.93	32.05	46.17	-14.12	AVG	
7		1.2660	21.83	9.98	31.81	56.00	-24.19	QP	
8		1.2660	5.58	9.98	15.56	46.00	-30.44	AVG	
9		4.2538	22.15	10.12	32.27	56.00	-23.73	QP	
10		4.2538	4.22	10.12	14.34	46.00	-31.66	AVG	
11		8.8300	17.06	10.30	27.36	60.00	-32.64	QP	
12		8.8300	-0.35	10.30	9.95	50.00	-40.05	AVG	

**Note 1:** Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak


AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

**Note 2:** Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11ax(HE20), 802.11n(HT40), 802.11ax(HE40)), and the worst case Mode (Middle channel and 802.11ax(HE20)) was submitted only. And the test data in this project is powered by adapter 3 which is in the worse case.

### 6.3. Maximum Conducted (Peak) Output Power

#### 6.3.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (b)(3)
<b>Test Method:</b>	KDB 558074 D01 v05r02
<b>Limit:</b>	30dBm
<b>Test Setup:</b>	 <p>The diagram illustrates the test setup. On the left is a green power meter with a screen and two red indicator lights. A black RF cable connects the power meter to a yellow rectangular EUT (Equipment Under Test) on the right. The power meter is labeled 'Power meter' and the EUT is labeled 'EUT'.</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Measure the Peak output power and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS


#### 6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
Power Sensor	Agilent	8184A	MY41096530	Jun. 26, 2025	Jun. 25, 2026
Power Meter	Agilent	E4418B	MY45100357	Jun. 26, 2025	Jun. 25, 2026



## 6.4. Emission Bandwidth

### 6.4.1. Test Specification


<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (a)(2)
<b>Test Method:</b>	KDB 558074 D01 v05r02
<b>Limit:</b>	>500kHz
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<p>Set to the maximum power setting and enable the EUT transmit continuously.</p> <p>2. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% ~5% of OBW. Set the Video bandwidth (VBW) ≥ 3 x RBW. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.</p> <p>3. Measure and record the results in the test report.</p>
<b>Test Result:</b>	PASS

### 6.4.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026

## 6.5. Power Spectral Density

### 6.5.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (e)
<b>Test Method:</b>	KDB 558074 D01 v05r02
<b>Limit:</b>	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>. Video bandwidth <math>\text{VBW} \geq 3 \times \text{RBW}</math>. Set the span to at least 1.5 times the OBW.</li> <li>4. Detector = Peak, Sweep time = auto couple.</li> <li>5. Trace mode =max hold. Use the peak marker function to determine the maximum power level.</li> <li>6. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS


### 6.5.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026



## 6.6. Conducted Band Edge and Spurious Emission Measurement

### 6.6.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (d)
<b>Test Method:</b>	KDB558074 D01 v05r02
<b>Limit:</b>	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).</li> <li>4. Measure and record the results in the test report.</li> <li>5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</li> </ol>
<b>Test Result:</b>	PASS

**6.6.2. Test Instruments**


Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026




## 6.7. Radiated Spurious Emission Measurement

### 6.7.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.209																													
<b>Test Method:</b>	ANSI C63.10:2020																													
<b>Frequency Range:</b>	9 kHz to 25 GHz																													
<b>Measurement Distance:</b>	3 m																													
<b>Antenna Polarization:</b>	Horizontal & Vertical																													
<b>Operation mode:</b>	Transmitting mode with modulation																													
<b>Receiver Setup:</b>	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>9kHz- 150kHz</td> <td>Quasi-peak</td> <td>200Hz</td> <td>1kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>150kHz- 30MHz</td> <td>Quasi-peak</td> <td>9kHz</td> <td>30kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>120KHz</td> <td>300KHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td> <td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>	Frequency	Detector	RBW	VBW	Remark	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value
	Frequency	Detector	RBW	VBW	Remark																									
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value																									
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value																									
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value																									
Above 1GHz	Peak	1MHz	3MHz	Peak Value																										
	Peak	1MHz	10Hz	Average Value																										
<b>Limit:</b>	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> </tr> </thead> <tbody> <tr> <td>0.009-0.490</td> <td>2400/F(KHz)</td> <td>300</td> </tr> <tr> <td>0.490-1.705</td> <td>24000/F(KHz)</td> <td>30</td> </tr> <tr> <td>1.705-30</td> <td>30</td> <td>30</td> </tr> <tr> <td>30-88</td> <td>100</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>3</td> </tr> </tbody> </table>	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	0.009-0.490	2400/F(KHz)	300	0.490-1.705	24000/F(KHz)	30	1.705-30	30	30	30-88	100	3	88-216	150	3	216-960	200	3	Above 960	500	3					
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)																											
	0.009-0.490	2400/F(KHz)	300																											
	0.490-1.705	24000/F(KHz)	30																											
	1.705-30	30	30																											
	30-88	100	3																											
	88-216	150	3																											
	216-960	200	3																											
	Above 960	500	3																											
	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Above 1GHz</td> <td>500</td> <td>3</td> <td>Average</td> </tr> <tr> <td>5000</td> <td>3</td> <td>Peak</td> </tr> </tbody> </table>	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	Above 1GHz	500	3	Average	5000	3	Peak																		
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector																											
Above 1GHz	500	3	Average																											
	5000	3	Peak																											
<b>Test setup:</b>	For radiated emissions below 30MHz																													
	<p>30MHz to 1GHz</p>																													



Above 1GHz



**Test Procedure:**

1. For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which

	<p>maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <p>(1) Span shall wide enough to fully capture the emission being measured;</p> <p>(2) Set RBW=120 kHz for <math>f &lt; 1</math> GHz; VBW <math>\geq</math> RBW; Sweep = auto; Detector function = peak; Trace = max hold;</p> <p>(3) Set RBW = 1 MHz, VBW= 3MHz for <math>f &gt; 1</math> GHz for peak measurement.</p> <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW <math>\geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
<b>Test results:</b>	PASS


### 6.7.2. Test Instruments

Radiated Emission Test Site (966)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI7	100529	Jan. 21, 2025	Jan. 20, 2026
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025	Jun. 25, 2026
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 21, 2025	Jan. 20, 2026
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jan. 21, 2025	Jan. 20, 2026
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025	Jun. 25, 2026
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 26, 2025	Jun. 25, 2026
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 26, 2025	Jun. 25, 2026
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 26, 2025	Jun. 25, 2026
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Jan. 23, 2025	Jan. 22, 2026
Coaxial cable	SKET	RE-03-D	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-03-M	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-03-L	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-04-D	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-04-M	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-04-L	/	Jun. 26, 2025	Jun. 25, 2026
Antenna Mast	Keleto	RE-AM	/	/	/
EMI Test Software	EZ EMC	FA-03A2 RE+	1.1.4.2	/	/

**6.7.3. Test Data**

Please refer to following diagram for individual  
Below 1GHz

Horizontal:




Site: 3m Anechoic Chamber1      Polarization: **Horizontal**      Temperature: 25.7(C)      Humidity: 51 %

Limit: FCC Part 15C RE\_3m      Power: AC 120V/60Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	49.7066	26.47	-12.27	14.20	40.00	-25.80	QP	P	
2	115.3204	31.76	-14.03	17.73	43.50	-25.77	QP	P	
3	153.7384	29.43	-11.03	18.40	43.50	-25.10	QP	P	
4	351.7078	35.28	-10.12	25.16	46.00	-20.84	QP	P	
5	550.9479	33.51	-6.65	26.86	46.00	-19.14	QP	P	
6 *	952.0937	28.95	0.28	29.23	46.00	-16.77	QP	P	

Vertical:



Site: 3m Anechoic Chamber1      Polarization: **Vertical**      Temperature: 25.7(C)      Humidity: 51 %

Limit: FCC Part 15C RE\_3m      Power: AC 120V/60Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	33.5623	34.11	-12.58	21.53	40.00	-18.47	QP	P	
2 *	50.0566	40.62	-12.28	28.34	40.00	-11.66	QP	P	
3	123.6984	32.04	-13.11	18.93	43.50	-24.57	QP	P	
4	351.7078	31.45	-10.12	21.33	46.00	-24.67	QP	P	
5	449.5557	32.44	-8.30	24.14	46.00	-21.86	QP	P	
6	709.1821	32.71	-4.10	28.61	46.00	-17.39	QP	P	


- Note:**
- The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported
  - Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11ax(HE20), 802.11n(HT40), 802.11ax(HE40)), and the worst case Mode (Middle channel and 802.11ax(HE20)) was submitted only. And the test data in this project is powered by adapter 1 which is in the worse case.
  - Freq. = Emission frequency in MHz  
 Measurement (dBuV/m) = Reading level (dBuV) + Corr. Factor (dB)  
 Correction Factor = Antenna Factor + Cable loss - Pre-amplifier  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Measurement (dBuV/m) - Limits (dBuV/m)  
 \* is meaning the worst frequency has been tested in the test frequency range.



## Test Result of Radiated Spurious at Band edges

Lowest channel 2422:

Horizontal:



Site: 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 24.1(°C)


Humidity: 53 %

Limit: FCC part 15.247 bandedge(peak)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	2390.000	79.70	-16.26	63.44	74.00	-10.56	peak	P	
2 *	2390.000	66.48	-16.26	50.22	54.00	-3.78	AVG	P	

Vertical:



Site: 3m Anechoic Chamber      Polarization: **Vertical**      Temperature: 24.1(°C)      Humidity: 53 %


Limit: FCC part 15.247 bandedge(peak)      Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	2390.000	69.82	-16.26	53.56	74.00	-20.44	peak	P	
2	2390.000	45.14	-16.26	28.88	54.00	-25.12	AVG	P	



Highest channel 2452:

Horizontal:



Site: 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 24.1(°C)

Humidity: 53 %


Limit: FCC part 15.247 bandedge(peak)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	2483.500	78.02	-15.91	62.11	74.00	-11.89	peak	P	
2 *	2483.500	67.63	-15.91	51.72	54.00	-2.28	AVG	P	



Vertical:



Site: 3m Anechoic Chamber      Polarization: **Vertical**      Temperature: 24.1(°C)      Humidity: 53 %

Limit: FCC part 15.247 bandedge(peak)      Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	2483.500	70.95	-15.91	55.04	74.00	-18.96	peak	P	
2	2483.500	45.44	-15.91	29.53	54.00	-24.47	AVG	P	

**Note:**

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
3. Measurements were conducted in all modulation (802.11b, 802.11g, 802.11n(HT20), 802.11ax(HE20), 802.11n(HT40), 802.11ax(HE40)), and the worst case Mode 802.11ax(HE40)) was submitted only.

## Above 1GHz

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	56.42	---	-9.48	46.94	---	74	54	-7.06
7236	H	47.33	---	-1.34	45.99	---	74	54	-8.01
---	H	---	---	---	---	---	---	---	---
4824	V	54.96	---	-9.48	45.48	---	74	54	-8.52
7236	V	45.81	---	-1.34	44.47	---	74	54	-9.53
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	56.55	---	-9.37	47.18	---	74	54	-6.82
7311	H	47.24	---	-1.17	46.07	---	74	54	-7.93
---	H	---	---	---	---	---	---	---	---
4874	V	55.97	---	-9.37	46.60	---	74	54	-7.40
7311	V	46.34	---	-1.17	45.17	---	74	54	-8.83
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	55.68	---	-9.26	46.42	---	74	54	-7.58
7386	H	46.17	---	-1.01	45.16	---	74	54	-8.84
---	H	---	---	---	---	---	---	---	---
4924	V	55.99	---	-9.26	46.73	---	74	54	-7.27
7386	V	45.70	---	-1.01	44.69	---	74	54	-9.31
---	V	---	---	---	---	---	---	---	---

### Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "----" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	57.06	---	-9.48	47.58	---	74	54	-6.42
7236	H	47.39	---	-1.34	46.05	---	74	54	-7.95
---	H	---	---	---	---	---	---	---	---
4824	V	55.87	---	-9.48	46.39	---	74	54	-7.61
7236	V	45.92	---	-1.34	44.58	---	74	54	-9.42
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	57.13	---	-9.37	47.76	---	74	54	-6.24
7311	H	46.36	---	-1.17	45.19	---	74	54	-8.81
---	H	---	---	---	---	---	---	---	---
4874	V	54.97	---	-9.37	45.60	---	74	54	-8.40
7311	V	45.48	---	-1.17	44.31	---	74	54	-9.69
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	55.56	---	-9.26	46.30	---	74	54	-7.70
7386	H	45.89	---	-1.01	44.88	---	74	54	-9.12
---	H	---	---	---	---	---	---	---	---
4924	V	56.15	---	-9.26	46.89	---	74	54	-7.11
7386	V	46.74	---	-1.01	45.73	---	74	54	-8.27
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	57.11	---	-9.48	47.63	---	74	54	-6.37
7236	H	46.86	---	-1.34	45.52	---	74	54	-8.48
---	H	---	---	---	---	---	---	---	---
4824	V	56.28	---	-9.48	46.80	---	74	54	-7.20
7236	V	45.76	---	-1.34	44.42	---	74	54	-9.58
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	55.49	---	-9.37	46.12	---	74	54	-7.88
7311	H	46.13	---	-1.17	44.96	---	74	54	-9.04
---	H	---	---	---	---	---	---	---	---
4874	V	55.72	---	-9.37	46.35	---	74	54	-7.65
7311	V	46.26	---	-1.17	45.09	---	74	54	-8.91
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	55.72	---	-9.26	46.46	---	74	54	-7.54
7386	H	46.97	---	-1.01	45.96	---	74	54	-8.04
---	H	---	---	---	---	---	---	---	---
4924	V	54.76	---	-9.26	45.50	---	74	54	-8.50
7386	V	45.25	---	-1.01	44.24	---	74	54	-9.76
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11ax (HE20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	55.79	---	-9.48	46.31	---	74	54	-7.69
7236	H	46.38	---	-1.34	45.04	---	74	54	-8.96
---	H	---	---	---	---	---	---	---	---
4824	V	54.93	---	-9.48	45.45	---	74	54	-8.55
7236	V	45.54	---	-1.34	44.20	---	74	54	-9.80
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	55.83	---	-9.37	46.46	---	74	54	-7.54
7311	H	46.26	---	-1.17	45.09	---	74	54	-8.91
---	H	---	---	---	---	---	---	---	---
4874	V	55.69	---	-9.37	46.32	---	74	54	-7.68
7311	V	47.21	---	-1.17	46.04	---	74	54	-7.96
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	55.45	---	-9.26	46.19	---	74	54	-7.81
7386	H	45.89	---	-1.01	44.88	---	74	54	-9.12
---	H	---	---	---	---	---	---	---	---
4924	V	55.77	---	-9.26	46.51	---	74	54	-7.49
7386	V	45.52	---	-1.01	44.51	---	74	54	-9.49
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.



Modulation Type: 802.11n (HT40)

Low channel: 2422 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4844	H	55.67	---	-9.43	46.24	---	74	54	-7.76
7266	H	45.43	---	-1.28	44.15	---	74	54	-9.85
---	H	---	---	---	---	---	---	---	---
4824	V	55.78	---	-9.43	46.35	---	74	54	-7.65
7236	V	47.06	---	-1.28	45.78	---	74	54	-8.22
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	55.27	---	-9.37	45.90	---	74	54	-8.10
7311	H	45.92	---	-1.17	44.75	---	74	54	-9.25
---	H	---	---	---	---	---	---	---	---
4874	V	56.05	---	-9.37	46.68	---	74	54	-7.32
7311	V	46.29	---	-1.17	45.12	---	74	54	-8.88
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4904	H	55.64	---	-9.30	46.34	---	74	54	-7.66
7356	H	45.42	---	-1.08	44.34	---	74	54	-9.66
---	H	---	---	---	---	---	---	---	---
4904	V	54.78	---	-9.30	45.48	---	74	54	-8.52
7356	V	46.16	---	-1.08	45.08	---	74	54	-8.92
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11ax (HE40)

Low channel: 2422 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4844	H	55.53	---	-9.43	46.10	---	74	54	-7.90
7266	H	45.79	---	-1.28	44.51	---	74	54	-9.49
---	H	---	---	---	---	---	---	---	---
4824	V	55.68	---	-9.43	46.25	---	74	54	-7.75
7236	V	45.46	---	-1.28	44.18	---	74	54	-9.82
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	55.96	---	-9.37	46.59	---	74	54	-7.41
7311	H	46.37	---	-1.17	45.20	---	74	54	-8.80
---	H	---	---	---	---	---	---	---	---
4874	V	55.42	---	-9.37	46.05	---	74	54	-7.95
7311	V	45.86	---	-1.17	44.69	---	74	54	-9.31
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4904	H	55.74	---	-9.30	46.44	---	74	54	-7.56
7356	H	45.36	---	-1.08	44.28	---	74	54	-9.72
---	H	---	---	---	---	---	---	---	---
4904	V	56.48	---	-9.30	47.18	---	74	54	-6.82
7356	V	45.29	---	-1.08	44.21	---	74	54	-9.79
---	V	---	---	---	---	---	---	---	---

**Note:**


1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

## Appendix A: Test Result of Conducted Test


### Duty Cycle



Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
NVNT	b	2412	99.9	0
NVNT	b	2437	99.5	0
NVNT	b	2462	99.6	0
NVNT	g	2412	98.5	0
NVNT	g	2437	98.3	0
NVNT	g	2462	96.8	0
NVNT	n20	2412	98.3	0
NVNT	n20	2437	99.3	0
NVNT	n20	2462	98.4	0
NVNT	n40	2422	98.5	0
NVNT	n40	2437	98.6	0
NVNT	n40	2452	99.4	0
NVNT	ax20	2412	97.5	0.11
NVNT	ax20	2437	98.2	0
NVNT	ax20	2462	96.1	0.17
NVNT	ax40	2422	98.5	0
NVNT	ax40	2437	97.7	0.10
NVNT	ax40	2452	98.7	0



### Test Graphs Duty Cycle NVNT b 2412MHz




### Duty Cycle NVNT b 2437MHz









### Duty Cycle NVNT n20 2412MHz




### Duty Cycle NVNT n20 2437MHz



### Duty Cycle NVNT n20 2462MHz




### Duty Cycle NVNT n40 2422MHz







Duty Cycle NVNT n40 2437MHz




Duty Cycle NVNT n40 2452MHz




### Test Graphs Duty Cycle NVNT ax20 2412MHz




### Duty Cycle NVNT ax20 2437MHz




### Duty Cycle NVNT ax20 2462MHz




### Duty Cycle NVNT ax40 2422MHz



### Duty Cycle NVNT ax40 2437MHz



### Duty Cycle NVNT ax40 2452MHz



**Maximum Conducted Output Power**


Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	12.98	30	Pass
NVNT	b	2437	13.08	30	Pass
NVNT	b	2462	12.02	30	Pass
NVNT	g	2412	13.65	30	Pass
NVNT	g	2437	14.78	30	Pass
NVNT	g	2462	14.12	30	Pass
NVNT	n20	2412	13.58	30	Pass
NVNT	n20	2437	14.70	30	Pass
NVNT	n20	2462	14.02	30	Pass
NVNT	n40	2422	13.48	30	Pass
NVNT	n40	2437	14.58	30	Pass
NVNT	n40	2452	14.30	30	Pass
NVNT	ax20	2412	13.17	30	Pass
NVNT	ax20	2437	14.86	30	Pass
NVNT	ax20	2462	14.09	30	Pass
NVNT	ax40	2422	13.69	30	Pass
NVNT	ax40	2437	14.67	30	Pass
NVNT	ax40	2452	14.47	30	Pass

**-6dB Bandwidth**


Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	9.144	0.5	Pass
NVNT	b	2437	9.154	0.5	Pass
NVNT	b	2462	9.144	0.5	Pass
NVNT	g	2412	16.40	0.5	Pass
NVNT	g	2437	16.36	0.5	Pass
NVNT	g	2462	16.35	0.5	Pass
NVNT	n20	2412	17.60	0.5	Pass
NVNT	n20	2437	17.57	0.5	Pass
NVNT	n20	2462	17.60	0.5	Pass
NVNT	n40	2422	36.36	0.5	Pass
NVNT	n40	2437	36.39	0.5	Pass
NVNT	n40	2452	36.32	0.5	Pass
NVNT	ax20	2412	18.92	0.5	Pass
NVNT	ax20	2437	18.91	0.5	Pass
NVNT	ax20	2462	18.81	0.5	Pass
NVNT	ax40	2422	37.87	0.5	Pass
NVNT	ax40	2437	37.72	0.5	Pass
NVNT	ax40	2452	37.89	0.5	Pass

## Test Graphs


### -6dB Bandwidth NVNT b 2412MHz




### -6dB Bandwidth NVNT b 2437MHz



## -6dB Bandwidth NVNT b 2462MHz




## -6dB Bandwidth NVNT g 2412MHz










## -6dB Bandwidth NVNT g 2437MHz





## -6dB Bandwidth NVNT g 2462MHz











## Test Graphs


### -6dB Bandwidth NVNT ax20 2412MHz




### -6dB Bandwidth NVNT ax20 2437MHz




## -6dB Bandwidth NVNT ax20 2462MHz




## -6dB Bandwidth NVNT ax40 2422MHz



## -6dB Bandwidth NVNT ax40 2437MHz



## -6dB Bandwidth NVNT ax40 2452MHz




**Maximum Power Spectral Density Level**


Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	-9.94	8	Pass
NVNT	b	2437	-9.13	8	Pass
NVNT	b	2462	-10.31	8	Pass
NVNT	g	2412	-10.57	8	Pass
NVNT	g	2437	-8.61	8	Pass
NVNT	g	2462	-9.78	8	Pass
NVNT	n20	2412	-10.60	8	Pass
NVNT	n20	2437	-9.85	8	Pass
NVNT	n20	2462	-9.93	8	Pass
NVNT	n40	2422	-13.01	8	Pass
NVNT	n40	2437	-12.73	8	Pass
NVNT	n40	2452	-13.04	8	Pass
NVNT	ax20	2412	-12.67	8	Pass
NVNT	ax20	2437	-9.76	8	Pass
NVNT	ax20	2462	-10.58	8	Pass
NVNT	ax40	2422	-14.52	8	Pass
NVNT	ax40	2437	-13.21	8	Pass
NVNT	ax40	2452	-12.89	8	Pass




## Test Graphs PSD NVNT b 2412MHz




## PSD NVNT b 2437MHz




## PSD NVNT b 2462MHz




## PSD NVNT g 2412MHz





## PSD NVNT g 2437MHz




## PSD NVNT g 2462MHz







## PSD NVNT n20 2462MHz




## PSD NVNT n40 2422MHz



## PSD NVNT n40 2437MHz




## PSD NVNT n40 2452MHz




## Test Graphs


### PSD NVNT ax20 2412MHz




### PSD NVNT ax20 2437MHz



## PSD NVNT ax20 2462MHz




## PSD NVNT ax40 2422MHz






PSD NVNT ax40 2437MHz



PSD NVNT ax40 2452MHz




**Band Edge**


Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-57.80	-20	Pass
NVNT	b	2462	-58.63	-20	Pass
NVNT	g	2412	-48.50	-20	Pass
NVNT	g	2462	-49.32	-20	Pass
NVNT	n20	2412	-48.71	-20	Pass
NVNT	n20	2462	-45.00	-20	Pass
NVNT	n40	2422	-44.17	-20	Pass
NVNT	n40	2452	-40.22	-20	Pass
NVNT	ax20	2412	-42.84	-20	Pass
NVNT	ax20	2462	-43.80	-20	Pass
NVNT	ax40	2422	-36.24	-20	Pass
NVNT	ax40	2452	-33.58	-20	Pass



## Test Graphs



### Band Edge NVNT b 2412MHz Ref







### Band Edge NVNT b 2412MHz Emission





























## Test Graphs



### Band Edge NVNT ax20 2412MHz Ref





### Band Edge NVNT ax20 2412MHz Emission











**Conducted RF Spurious Emission**

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-43.35	-20	Pass
NVNT	b	2437	-44.87	-20	Pass
NVNT	b	2462	-44.07	-20	Pass
NVNT	g	2412	-41.75	-20	Pass
NVNT	g	2437	-43.34	-20	Pass
NVNT	g	2462	-43.79	-20	Pass
NVNT	n20	2412	-43.31	-20	Pass
NVNT	n20	2437	-44.40	-20	Pass
NVNT	n20	2462	-43.28	-20	Pass
NVNT	n40	2422	-41.07	-20	Pass
NVNT	n40	2437	-41.56	-20	Pass
NVNT	n40	2452	-41.46	-20	Pass
NVNT	ax20	2412	-42.71	-20	Pass
NVNT	ax20	2437	-45.28	-20	Pass
NVNT	ax20	2462	-44.28	-20	Pass
NVNT	ax40	2422	-40.51	-20	Pass
NVNT	ax40	2437	-41.77	-20	Pass
NVNT	ax40	2452	-41.70	-20	Pass

Test Graphs  
Tx. Spurious NVNT b 2412MHz Ref




Tx. Spurious NVNT b 2412MHz Emission







## Tx. Spurious NVNT b 2437MHz Ref




## Tx. Spurious NVNT b 2437MHz Emission




## Tx. Spurious NVNT b 2462MHz Ref




## Tx. Spurious NVNT b 2462MHz Emission




## Tx. Spurious NVNT g 2412MHz Ref




## Tx. Spurious NVNT g 2412MHz Emission




## Tx. Spurious NVNT g 2437MHz Ref




## Tx. Spurious NVNT g 2437MHz Emission







## Tx. Spurious NVNT g 2462MHz Ref





## Tx. Spurious NVNT g 2462MHz Emission


























Test Graphs  
Tx. Spurious NVNT ax20 2412MHz Ref




Tx. Spurious NVNT ax20 2412MHz Emission




## Tx. Spurious NVNT ax20 2437MHz Ref




## Tx. Spurious NVNT ax20 2437MHz Emission




Tx. Spurious NVNT ax20 2462MHz Ref




Tx. Spurious NVNT ax20 2462MHz Emission




## Tx. Spurious NVNT ax40 2422MHz Ref




## Tx. Spurious NVNT ax40 2422MHz Emission



## Tx. Spurious NVNT ax40 2437MHz Ref




## Tx. Spurious NVNT ax40 2437MHz Emission






## Tx. Spurious NVNT ax40 2452MHz Ref



## Tx. Spurious NVNT ax40 2452MHz Emission



## Appendix B: Photographs of Test Setup

Please refer to document Appendix No.: TCT250619E056-A

## Appendix C: Photographs of EUT

Please refer to document Appendix No.: TCT250619E056-B & TCT250619E056-C

**\*\*\*\*\*END OF REPORT\*\*\*\*\***