

RF EXPOSURE REPORT

Equipment Under Test	Bluetooth Speaker
Model Name	R50TE
Variant Model Name	-
FCC ID	2BE6R-R50TE
Applicant	SR Lab Co., Ltd.
Manufacturer	SR Lab Co., Ltd.
Date of Test(s)	2024. 02. 16 ~ 2024. 02. 19
Date of Issue	2024. 04. 02

In the configuration tested, the EUT complied with the standards specified above.

Issue to	Issue by
SR Lab Co., Ltd. 46, Jiyang-ro, Yangcheon-gu, Seoul, Korea Tel.: +82-10-6430-2253 Fax: -	DEKRA Korea Co., Ltd. 498-2, Geumeo-ro, Pogok-eup, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17030 Tel.: +82-31-338-8837 Fax: +82-31-338-8847

RF EXPOSURE

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, * = plane-wave equivalent power density

MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

MPE Calculations : Bluetooth BDR

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : 7.70 dBm
- Target Power & Tolerance 7.00 dBm & \pm 1.00 dB
(Maximum : 8.00 dBm & Minimum : 6.00 dBm)
- Maximum Peak Antenna Gain : -0.58 dBi
- Maximum Output Power for the Calculation : 8.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the The MPE calculation for this exposure is shown below.

$ \begin{aligned} - \text{EIRP} &= P + G \\ &= \underline{8.00} \text{ dBm} + \underline{-0.58} \text{ dBi} \\ &= \underline{7.42} \text{ dBm} \\ &= \underline{5.52} \text{ mW} \end{aligned} $	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	---

Power Density at the specific separation

$ \begin{aligned} - S &= \text{EIRP} / (4 \times R^2 \pi) \\ &= 5.52 / (4 \times 20^2 \times \pi) \\ &= \underline{0.001\ 098} \text{ mW/cm}^2 \end{aligned} $	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
--	---

MPE Calculations : Bluetooth EDR

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : 7.92 dBm
- Target Power & Tolerance 7.00 dBm & \pm 1.00 dB
(Maximum : 8.00 dBm & Minimum : 6.00 dBm)
- Maximum Peak Antenna Gain : -0.58 dBi
- Maximum Output Power for the Calculation : 8.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the The MPE calculation for this exposure is shown below.

$ \begin{aligned} - \text{EIRP} &= P + G \\ &= \underline{8.00} \text{ dBm} + \underline{-0.58} \text{ dBi} \\ &= \underline{7.42} \text{ dBm} \\ &= \underline{5.52} \text{ mW} \end{aligned} $	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	---

Power Density at the specific separation

$ \begin{aligned} - S &= \text{EIRP} / (4 \times R^2 \pi) \\ &= 5.52 / (4 \times 20^2 \times \pi) \\ &= \underline{0.001\ 098} \text{ mW/cm}^2 \end{aligned} $	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
--	---

MPE Calculations : Bluetooth LE 1 Mbps

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : 7.71 dBm
- Target Power & Tolerance 7.00 dBm & \pm 1.00 dB
 - (Maximum : 8.00 dBm & Minimum : 6.00 dBm)
- Maximum Peak Antenna Gain : -0.58 dBi
- Maximum Output Power for the Calculation : 8.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the The MPE calculation for this exposure is shown below.

$ \begin{aligned} - \text{EIRP} &= P + G \\ &= \underline{8.00} \text{ dBm} + \underline{-0.58} \text{ dBi} \\ &= \underline{7.42} \text{ dBm} \\ &= \underline{5.52} \text{ mW} \end{aligned} $	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

Power Density at the specific separation

$ \begin{aligned} - S &= \text{EIRP} / (4 \times R^2 \pi) \\ &= 5.52 / (4 \times 20^2 \times \pi) \\ &= \underline{0.001\ 098} \text{ mW/cm}^2 \end{aligned} $	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
--	--

RF Exposure Compliance Issue

Therefore, EUT is not required the SAR Evaluation.

MPE Calculations : Bluetooth EDR + Bluetooth LE 1 Mbps

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the device. The MPE calculation for this exposure is shown below.

Simultaneous MPE for BLE and Bluetooth

Bluetooth EDR + Bluetooth LE 1 Mbps

<p>- Total (%) =</p> $[\text{Bluetooth EDR Result(mW/cm}^2\text{) / Limit(mW/cm}^2\text{) } + [\text{Bluetooth LE 1 Mbps Result(mW/cm}^2\text{) / Limit(mW/cm}^2\text{) } * 100]]$ $= [\underline{0.001\ 098} / 1] + [\underline{0.001\ 773} / 1] * 100$ $= \underline{0.287} \%$	<p>- NOTE</p> <p>Bluetooth EDR + Bluetooth LE 1 Mbps</p> <p>Bluetooth EDR = <u>0.001 098</u> mW/cm²</p> <p>Bluetooth LE 1 Mbps = <u>0.001 773</u> mW/cm²</p> <p>Distance to the center of the radiation of the antenna (<u>20</u> cm)</p> <p>Limit : $\leq 100 \%$</p>
---	---

RF Exposure Compliance Issue

Therefore, EUT is not required the SAR Evaluation.