

Model: LIBRA-RCS25(Y)-N4-3

Moisture Removal Capacity: 22.5Pints/Day (18.33°C/RH60%)
52Pints/Day (26.7°C/RH80%)

boglvr

Power Supply: 120V~60Hz

Stand Power: 280W

261W at 18.33°C/RH60%

Rated Power: 380W

Total Input Rated Current: 3.93A

Operating Temperature: 5-35°C

Fan Motor FLA: 0.32A

Motor Compressor: RLA:1.96A, LRA:11A

Refrigerant: R32/115g

Maximum Allowable Pressure: 5.5MPa

Max Discharge Pressure: 3.8MPa

Max Suction Pressure: 1.2MPa

Net Weight: 32.19 lb

Product Size: 14.41 X 8.66 X 24.13 inch

SN: WZSLIBRARCS25(Y)N432528000001

FCC ID: 2BE82-LIBRA

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) This device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.



Intertek
5028527



A2L



CONFORMS TO UL STD. 60335-1&60335-2-40
CERTIFIED TO CSA STD. C22.2 NO. 60335-1&60335-2-40

