

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Band-edge measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW $\geq 1\%$ of the span=100kHz Set VBW $\geq 3 \times$ RBW

Set Sweep = autoSet Detector function = peakSet Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW =300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements . Report the three highest emissions relative to the limit.

8.5.5 Test Results

All the antenna(Antenna 1) and modes(802.11b/g/n) have been tested and the worst(Antenna 1,802.11b) result(Antenna 1,802.11b) was reported as below:

Temperature:	24.9°C
Relative Humidity:	51%
ATM Pressure:	1011 mbar

Note: N/A

Band-edge measurement


TestMode	Antenna	ChName	Frequency [MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	5.20	-42.34	≤ -24.81	PASS
11B	Ant1	High	2462	4.84	-46.19	≤ -25.16	PASS
11G	Ant1	Low	2412	1.70	-30.71	≤ -28.3	PASS
11G	Ant1	High	2462	2.02	-40.99	≤ -27.99	PASS
11N20SISO	Ant1	Low	2412	0.91	-31.25	≤ -29.09	PASS
11N20SISO	Ant1	High	2462	1.70	-38.64	≤ -28.3	PASS

Emission level measurement


TestMode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	0~Reference	3.87	3.87	---	PASS
11B	Ant1	2412	30~1000	3.87	-56.26	≤ -26.13	PASS
11B	Ant1	2412	1000~26500	3.87	-39.06	≤ -26.13	PASS

11B	Ant1	2437	0~Reference	3.93	3.93	---	PASS
11B	Ant1	2437	30~1000	3.93	-56.01	≤-26.07	PASS
11B	Ant1	2437	1000~26500	3.93	-39.44	≤-26.07	PASS
11B	Ant1	2462	0~Reference	4.11	4.11	---	PASS
11B	Ant1	2462	30~1000	4.11	-56.22	≤-25.89	PASS
11B	Ant1	2462	1000~26500	4.11	-38.82	≤-25.89	PASS
11G	Ant1	2412	0~Reference	-1.69	-1.69	---	PASS
11G	Ant1	2412	30~1000	-1.69	-55.76	≤-31.69	PASS
11G	Ant1	2412	1000~26500	-1.69	-39.16	≤-31.69	PASS
11G	Ant1	2437	0~Reference	-1.08	-1.08	---	PASS
11G	Ant1	2437	30~1000	-1.08	-56.23	≤-31.08	PASS
11G	Ant1	2437	1000~26500	-1.08	-39.02	≤-31.08	PASS
11G	Ant1	2462	0~Reference	-0.58	-0.58	---	PASS
11G	Ant1	2462	30~1000	-0.58	-54.74	≤-30.58	PASS
11G	Ant1	2462	1000~26500	-0.58	-39.22	≤-30.58	PASS
11N20SISO	Ant1	2412	0~Reference	-0.95	-0.95	---	PASS
11N20SISO	Ant1	2412	30~1000	-0.95	-56.44	≤-30.95	PASS
11N20SISO	Ant1	2412	1000~26500	-0.95	-38.05	≤-30.95	PASS
11N20SISO	Ant1	2437	0~Reference	1.54	1.54	---	PASS
11N20SISO	Ant1	2437	30~1000	1.54	-55.32	≤-28.46	PASS
11N20SISO	Ant1	2437	1000~26500	1.54	-39.31	≤-28.46	PASS
11N20SISO	Ant1	2462	0~Reference	-0.58	-0.58	---	PASS
11N20SISO	Ant1	2462	30~1000	-0.58	-56.24	≤-30.58	PASS
11N20SISO	Ant1	2462	1000~26500	-0.58	-39.25	≤-30.58	PASS


Band-edge measurement




11B-Ant1-2412-PASS




11B-Ant1-2462-PASS




11G-Ant1-2412-PASS



11G-Ant1-2462-PASS





11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2462-PASS

Emission level measurement







11B-Ant1-2412-1000~26500-PASS




11B-Ant1-2437-0~Reference-PASS



11B-Ant1-2437-30~1000-PASS




11B-Ant1-2437-1000~26500-PASS







11B-Ant1-2462-1000~26500-PASS



11G-Ant1-2412-0~Reference-PASS




11G-Ant1-2412-30-1000-PASS




11G-Ant1-2412-1000-26500-PASS




11G-Ant1-2437-0~Reference-PASS




11G-Ant1-2437-30~1000-PASS




11G-Ant1-2437-1000~26500-PASS




11G-Ant1-2462-0~Reference-PASS



11G-Ant1-2462-30-1000-PASS




11G-Ant1-2462-1000-26500-PASS






11N20SISO-Ant1-2412-1000-26500-PASS




11N20SISO-Ant1-2437-0-Reference-PASS





11N20SISO-Ant1-2462-0~Reference-PASS



11N20SISO-Ant1-2462-30~1000-PASS



8.6 RADIATED SPURIOUS EMISSION

8.6.1 Applicable Standard

According to FCC Part 15.247(d), 15.205, 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02
According to IC RSS-Gen and RSS-247

8.6.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205 the level of any transmitter spurious emission in Restricted bands shall not

exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V/m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V/m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.6.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

8.6.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this

test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit. Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.6.5 Test Results

Temperature:	25° C
Relative Humidity:	60%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All the antenna(Antenna 1) and modes(802.11b/g/n) have been tested and the worst(Antenna 1,802.11b) result(Antenna 1,802.11b) was reported as below:

Test mode: 802.11b Frequency: Channel 1: 2412MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
	H/V	PK	AV	PK	AV	PK	AV
8336.25	V	53.88	39.37	74.00	54.00	20.12	14.63
13151.2	V	63.55	48.29	74.00	54.00	10.45	5.71
17938.1	V	65.51	45.86	74.00	54.00	8.49	8.14
7745.62	H	53.71	39.25	74.00	54.00	20.29	14.75
13228.1	H	63.53	47.45	74.00	54.00	10.47	6.55
17930.6	H	65.43	45.75	74.00	54.00	8.57	8.25

Test mode: 802.11b Frequency: Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
	H/V	PK	AV	PK	AV	PK	AV
10081.8	V	56.90	45.86	74.00	54.00	17.10	8.14
11553.7	V	59.46	43.74	74.00	54.00	14.54	10.26
17596.8	V	65.30	46.82	74.00	54.00	8.70	7.18
10119.3	H	57.17	45.49	74.00	54.00	16.83	8.51
13224.3	H	63.55	48.27	74.00	54.00	10.45	5.73
17506.8	H	64.83	45.94	74.00	54.00	9.17	8.06

Test mode: 802.11b Frequency: Channel 11: 2462MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
	H/V	PK	AV	PK	AV	PK	AV
7755	V	53.17	39.16	74.00	54.00	20.83	14.84
13181.2	V	64.08	48.89	74.00	54.00	9.92	5.11
17514.3	V	64.90	46.05	74.00	54.00	9.10	7.95
8266.87	H	54.25	38.76	74.00	54.00	19.75	15.24
13145.6	H	63.51	48.23	74.00	54.00	10.49	5.77
17525.6	H	66.02	46.16	74.00	54.00	7.98	7.84

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) Margin = Limit - Corrected Reading
 - (5)The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All the antenna(Antenna 1) and modes(802.11b/g/n) have been tested and the worst(Antenna 1,802.11n(HT20)) result(Antenna 1,802.11n(HT20)) was reported as below:

Test mode: 802.11n(HT20) Frequency: Channel 1: 2412MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2387.78	H	43.02	74.00	39.02	54.00
2386.13	V	43.15	74.00	38.78	54.00

Test mode: 802.11n(HT20) Frequency: Channel 11: 2462MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.66	H	43.32	74.00	39.77	54.00
2483.69	V	43.83	74.00	39.78	54.00

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model 802.11b Spurious Emission in Restricted Band 2310-2390MHz
Channel 1: 2412MHz VBW=3MHz Polarity: H




Test Model 802.11b Spurious Emission in Restricted Band 2310-2390MHz
Channel 1: 2412MHz VBW=3MHz Polarity: V



Test Model 802.11b Spurious Emission in Restricted Band 2483.5-2500MHz
Channel 11: 2462MHz VBW=3MHz Polarity: H




Test Model 802.11b Spurious Emission in Restricted Band 2483.5-2500MHz
Channel 11: 2462MHz VBW=3MHz Polarity: V



■ Spurious Emission below 1GHz (30MHz to 1GHz)

All the antenna(Antenna 1) and modes(802.11b/g/n) have been tested and the worst(Antenna 1,802.11b) result(Antenna 1,802.11b) was reported as below:

2412




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	95.0551	44.69	-17.97	26.72	PK	43.50	16.78	Vertical
2	143.603	43.91	-19.71	24.20	PK	43.50	19.30	Vertical
3	167.877	42.75	-19.13	23.62	PK	43.50	19.88	Vertical
4	192.152	42.68	-17.98	24.70	PK	43.50	18.80	Vertical
5	289.249	40.81	-14.39	26.42	PK	46.00	19.58	Vertical
6	832.022	31.27	-4.54	26.73	PK	46.00	19.27	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	95.0551	-17.97	26.20	43.50	17.30
2	143.6036	-19.71	24.04	43.50	19.46
3	167.8779	-19.13	22.82	43.50	20.68
4	192.1522	-17.98	23.90	43.50	19.60
5	289.2492	-14.39	25.46	46.00	20.54
6	832.022	-4.54	25.96	46.00	20.04




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	64.955	39.13	-18.07	21.06	PK	40.00	18.94	Horizontal
2	79.5195	41.44	-20.20	21.24	PK	40.00	18.76	Horizontal
3	95.0551	56.52	-17.97	38.55	PK	43.50	4.95	Horizontal
4	119.329	47.35	-18.54	28.81	PK	43.50	14.69	Horizontal
5	639.769	35.36	-7.14	28.22	PK	46.00	17.78	Horizontal
6	818.428	30.83	-4.74	26.09	PK	46.00	19.91	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	64.955	-18.07	20.87	40.00	19.13
2	79.5195	-20.20	20.41	40.00	19.59
3	95.0551	-17.97	37.56	43.50	5.94
4	119.3293	-18.54	28.18	43.50	15.32
5	639.7698	-7.14	27.42	46.00	18.58
6	818.4284	-4.74	25.29	46.00	20.71

2437




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	96.026	44.92	-17.83	27.09	PK	43.50	16.41	Vertical
2	143.603	44.94	-19.71	25.23	PK	43.50	18.27	Vertical
3	191.181	42.01	-18.03	23.98	PK	43.50	19.52	Vertical
4	709.679	31.74	-5.79	25.95	PK	46.00	20.05	Vertical
5	843.673	31.44	-4.17	27.27	PK	46.00	18.73	Vertical
6	958.248	31.88	-2.07	29.81	PK	46.00	16.19	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	96.026	-17.83	26.60	43.50	16.90
2	143.6036	-19.71	24.58	43.50	18.92
3	191.1812	-18.03	23.05	43.50	20.45
4	709.6797	-5.79	25.21	46.00	20.79
5	843.6737	-4.17	26.37	46.00	19.63
6	958.2482	-2.07	28.91	46.00	17.09




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	51.3614	37.18	-16.21	20.97	PK	40.00	19.03	Horizontal
2	63.984	39.20	-17.94	21.26	PK	40.00	18.74	Horizontal
3	96.026	56.11	-17.83	38.28	PK	43.50	5.22	Horizontal
4	119.329	46.90	-18.54	28.36	PK	43.50	15.14	Horizontal
5	639.769	35.71	-7.14	28.57	PK	46.00	17.43	Horizontal
6	950.480	31.51	-2.55	28.96	PK	46.00	17.04	Horizontal

Final Data List


NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	51.3614	-16.21	20.18	40.00	19.82
2	63.984	-17.94	20.67	40.00	19.33
3	96.026	-17.83	37.69	43.50	5.81
4	119.3293	-18.54	27.48	43.50	16.02
5	639.7698	-7.14	27.69	46.00	18.31
6	950.4805	-2.55	28.64	46.00	17.36

2462



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	95.0551	45.26	-17.97	27.29	PK	43.50	16.21	Vertical
2	159.139	45.76	-19.43	26.33	PK	43.50	17.17	Vertical
3	167.877	43.03	-19.13	23.90	PK	43.50	19.60	Vertical
4	191.181	41.97	-18.03	23.94	PK	43.50	19.56	Vertical
5	287.307	40.34	-14.48	25.86	PK	46.00	20.14	Vertical
6	838.818	31.77	-4.39	27.38	PK	46.00	18.62	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	95.0551	-17.97	26.37	43.50	17.13
2	159.1391	-19.43	26.24	43.50	17.26
3	167.8779	-19.13	23.53	43.50	19.97
4	191.1812	-18.03	23.57	43.50	19.93
5	287.3073	-14.48	25.33	46.00	20.67
6	838.8188	-4.39	27.21	46.00	18.79



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	51.3614	37.22	-16.21	21.01	PK	40.00	18.99	Horizontal
2	64.955	39.04	-18.07	20.97	PK	40.00	19.03	Horizontal
3	96.026	57.40	-17.83	39.57	PK	43.50	3.93	Horizontal
4	119.329	48.31	-18.54	29.77	PK	43.50	13.73	Horizontal
5	639.769	35.53	-7.14	28.39	PK	46.00	17.61	Horizontal
6	956.306	31.73	-2.18	29.55	PK	46.00	16.45	Horizontal

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	51.3614	-16.21	20.33	40.00	19.67
2	64.955	-18.07	20.65	40.00	19.35
3	96.026	-17.83	38.61	43.50	4.89
4	119.3293	-18.54	29.65	43.50	13.85
5	639.7698	-7.14	27.46	46.00	18.54
6	956.3063	-2.18	29.34	46.00	16.66

8.7 CONDUCTED EMISSION TEST

8.7.1 Applicable Standard

According to FCC Part 15.207(a)

According to IC RSS-Gen 8.8

8.7.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.7.3 Test Configuration


Test according to clause 6.3conducted emission test setup

8.7.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.7.5 Test Results

Pass



Site Conduction #1

Phase: **L1**

Temperature: 24.9

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 53 %

Mode: WiFi 2

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	32.61	9.70	42.31	66.00	-23.69	QP	
2		0.1500	14.91	9.70	24.61	56.00	-31.39	AVG	
3		0.2940	23.65	9.70	33.35	60.41	-27.06	QP	
4		0.2940	3.69	9.70	13.39	50.41	-37.02	AVG	
5		0.4460	22.05	9.70	31.75	56.95	-25.20	QP	
6		0.4460	5.95	9.70	15.65	46.95	-31.30	AVG	
7		1.5020	12.67	9.72	22.39	56.00	-33.61	QP	
8		1.5020	1.13	9.72	10.85	46.00	-35.15	AVG	
9		11.3060	26.45	9.94	36.39	60.00	-23.61	QP	
10		11.3060	12.89	9.94	22.83	50.00	-27.17	AVG	
11	*	17.5900	36.45	9.99	46.44	60.00	-13.56	QP	
12		17.5900	22.77	9.99	32.76	50.00	-17.24	AVG	



Site Conduction #1

Phase: **N**

Temperature: 24.9

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 53 %

Mode: WiFi 2

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	29.19	9.71	38.90	66.00	-27.10	QP	
2		0.1500	15.43	9.71	25.14	56.00	-30.86	AVG	
3		0.2980	18.06	9.73	27.79	60.30	-32.51	QP	
4		0.2980	4.95	9.73	14.68	50.30	-35.62	AVG	
5		0.4460	17.42	9.71	27.13	56.95	-29.82	QP	
6		0.4460	5.11	9.71	14.82	46.95	-32.13	AVG	
7		0.5940	12.51	9.72	22.23	56.00	-33.77	QP	
8		0.5940	1.83	9.72	11.55	46.00	-34.45	AVG	
9		12.0460	27.86	9.94	37.80	60.00	-22.20	QP	
10		12.0460	15.23	9.94	25.17	50.00	-24.83	AVG	
11	*	17.3660	35.59	9.97	45.56	60.00	-14.44	QP	
12		17.3660	22.63	9.97	32.60	50.00	-17.40	AVG	

8.8 ANTENNA APPLICATION

8.8.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
FCC 47 CFR Part 15.247 (b)	If transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
RSS-Gen Section 6.8	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.
RSS-247 Section 5.4	If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

8.8.2 Result

PASS.

- Note:
- ☒ Antenna use a permanently attached antenna which is not replaceable.
 - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
 - ☐ The antenna has to be professionally installed (please provide method of installation)

Please refer to the attached documentInternal Photos to show the antenna connector.

Detail of factor for radiated emission

Frequency(MHz)	Ant F(dB)	Cab L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

----- END OF REPORT -----