



# RF TEST REPORT

Product Name: ATK Dragonfly A9 Ultra Lightweight Wireless Mouse

Model Name: ATK Dragonfly A9 Ultra

FCC ID: 2BE9P-MSHVVDBPX

Issued For : Shenzhen Yizhita Technology Co., Ltd  
Room 1901, Qianhai HOP Int'l, No. 19 Xinghua 1st Rd  
(Extension), Bao'an District, Shenzhen, Guangdong,  
China.

Issued By : Shenzhen LGT Test Service Co., Ltd.  
Room 205, Building 13, Zone B, Zhenxiong Industrial Park,  
No.177, Renmin West Road, Jinsha, Kengzi Street,  
Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT25G232HA02

Sample Received Date: Jul. 25, 2025

Date of Test: Jul. 25, 2025 ~ Aug. 05, 2025

Date of Issue: Aug. 05, 2025

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



## TEST REPORT CERTIFICATION

**Applicant:** Shenzhen Yizhita Technology Co., Ltd

**Address:** Room 1901, Qianhai HOP Int'l, No. 19 Xinghua 1st Rd (Extension),  
Bao'an District, Shenzhen, Guangdong, China.

**Manufacturer:** Shenzhen Yizhita Technology Co., Ltd

**Address:** Room 1901, Qianhai HOP Int'l, No. 19 Xinghua 1st Rd (Extension),  
Bao'an District, Shenzhen, Guangdong, China.

**Factory:** Dongguan Dianxuntong Electronics Technology Co., Ltd.

**Address:** Room 302, Building 1, No. 6 Wende Street, Xiabian, Chang'an Town,  
Dongguan City, Guangdong Province

**Product Name:** ATK Dragonfly A9 Ultra Lightweight Wireless Mouse

**Trademark:** 艾泰克 ATK

**Model Name:** ATK Dragonfly A9 Ultra

**Sample Status:** Normal

| APPLICABLE STANDARDS                                                     |              |
|--------------------------------------------------------------------------|--------------|
| STANDARD                                                                 | TEST RESULTS |
| FCC 47 CFR §2.1093<br>KDB 447498 D01 General RF Exposure<br>Guidance v06 | PASS         |

Prepared by:

Zane Shan

Zane Shan  
Engineer

Approved by:

Vita Li

Vita Li  
Technical Director





## TABLE OF CONTENTS

|                                           |          |
|-------------------------------------------|----------|
| <b>1 . GENERAL INFORMATION</b>            | <b>5</b> |
| 1.1 GENERAL DESCRIPTION OF THE EUT        | 5        |
| 1.2 TEST LABORATORY                       | 5        |
| <b>2 . FCC 47CFR § 2.1093 REQUIREMENT</b> | <b>6</b> |
| 2.1 TEST STANDARDS                        | 6        |
| 2.2 LIMIT                                 | 6        |
| 2.3 TEST RESULT                           | 8        |



### Revision History

| Rev. | Issue Date    | Revisions     |
|------|---------------|---------------|
| 00   | Aug. 05, 2025 | Initial Issue |
|      |               |               |



## 1. GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF THE EUT

|                   |                                                   |               |
|-------------------|---------------------------------------------------|---------------|
| Product Name:     | ATK Dragonfly A9 Ultra Lightweight Wireless Mouse |               |
| Trademark:        | 艾泰克 ATK                                           |               |
| Test Model Name:  | ATK Dragonfly A9 Ultra                            |               |
| Series Model:     | N/A                                               |               |
| Model Difference: | N/A                                               |               |
| Frequency Bands:  | Bluetooth                                         | 2402-2480MHz  |
|                   | 2.4G                                              | 2403~2480 MHz |
| Rating:           | Input: DC 5V 500mA                                |               |
| Battery:          | Capacity: 500mAh<br>Rated Voltage: 3.7V           |               |
| Hardware Version: | N/A                                               |               |
| Software Version: | N/A                                               |               |

### 1.2 TEST LABORATORY

|                            |                                                                                                                                                          |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Company Name:              | Shenzhen LGT Test Service Co., Ltd.                                                                                                                      |
| Address:                   | Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China |
| Accreditation Certificate: | A2LA Certificate No.: 6727.01                                                                                                                            |
|                            | FCC Registration No.: 746540                                                                                                                             |
|                            | CAB ID: CN0136                                                                                                                                           |



## 2. FCC 47CFR §2.1093 REQUIREMENT

### 2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in KDB 447498 D01 General RF Exposure Guidance v06 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

### 2.2 LIMIT

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

| MHz  | 5   | 10  | 15  | 20  | 25  | mm                                      |
|------|-----|-----|-----|-----|-----|-----------------------------------------|
| 150  | 39  | 77  | 116 | 155 | 194 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 27  | 55  | 82  | 110 | 137 |                                         |
| 450  | 22  | 45  | 67  | 89  | 112 |                                         |
| 835  | 16  | 33  | 49  | 66  | 82  |                                         |
| 900  | 16  | 32  | 47  | 63  | 79  |                                         |
| 1500 | 12  | 24  | 37  | 49  | 61  |                                         |
| 1900 | 11  | 22  | 33  | 44  | 54  |                                         |
| 2450 | 10  | 19  | 29  | 38  | 48  |                                         |
| 3600 | 8   | 16  | 24  | 32  | 40  |                                         |
| 5200 | 7   | 13  | 20  | 26  | 33  |                                         |
| 5400 | 6   | 13  | 19  | 26  | 32  |                                         |
| 5800 | 6   | 12  | 19  | 25  | 31  |                                         |
| MHz  | 30  | 35  | 40  | 45  | 50  | mm                                      |
| 150  | 232 | 271 | 310 | 349 | 387 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 164 | 192 | 219 | 246 | 274 |                                         |
| 450  | 134 | 157 | 179 | 201 | 224 |                                         |
| 835  | 98  | 115 | 131 | 148 | 164 |                                         |
| 900  | 95  | 111 | 126 | 142 | 158 |                                         |
| 1500 | 73  | 86  | 98  | 110 | 122 |                                         |
| 1900 | 65  | 76  | 87  | 98  | 109 |                                         |
| 2450 | 57  | 67  | 77  | 86  | 96  |                                         |
| 3600 | 47  | 55  | 63  | 71  | 79  |                                         |
| 5200 | 39  | 46  | 53  | 59  | 66  |                                         |
| 5400 | 39  | 45  | 52  | 58  | 65  |                                         |
| 5800 | 37  | 44  | 50  | 56  | 62  |                                         |



The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz.}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.



## 2.3 TEST RESULT

### Turn up Result

| Mode        | Turn up Power |
|-------------|---------------|
| BLE 1M-GFSK | 4.5±1dBm      |
| 2.4G-GFSK   | -1±1dBm       |

### The MPE result of worst mode:

| RF Function | Frequency (MHz) | Max Turn up Power (dBm) | Max Turn up Power (mW) | Estimated SAR | Limit | Ratio | Result |
|-------------|-----------------|-------------------------|------------------------|---------------|-------|-------|--------|
| BLE         | 2440            | 5.50                    | 3.55                   | 1.108         | 3     | 0.369 | Pass   |
| 2.4G        | 2403            | 0.00                    | 1.00                   | 0.310         | 3     | 0.103 | Pass   |

### Note:

1. The Maximum Power Density is less than the limit, complies with the exemption requirements.

※※※※※END OF THE REPORT※※※※※