

FCC ID : 2BEA6HMI04

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

TABLE 1 TO § 1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. * = Plane-wave equivalent power density.*

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm², If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.

11.2 Measurement Result

Mode	Max Conducted Power (dBm)	Antenna gain (dBi)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
BLE	2.15	1.48	1.41	0.0046	1
BT	1.87	1.48	1.41	0.0043	1
2.4G WIFI	18.44	1.48	1.41	0.1953	1
5G WIFI	13.73	2.45	1.76	0.0825	1

Mode	Channel Number	Channel Frequency (MHz)	Emission Level(dBuV/m)	EIRP (dBm)	Max power (mW)
RFID	1	13.56	51.73	-43.5	0
Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)		
0	1	0.00020	1		
* EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77					

Max RF Exposure evaluation.

RFID (mW/cm ²)	2.4G WIFI (mW/cm ²)	Summation of Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
0.00020	0.1953	0.1955	1

Note: All the modes are tested, only the worst data are described in the table.

----- The End -----