





Test Report No.:
FCCSZ2024-0069-H

RF Test Report

FCC ID : 2BEA6VOSM350
EUT : Module
MODEL : VOSM350
BRAND NAME : N/A
APPLICANT : Vantron Technology, Inc.
Classification of Test : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Client	Name: Vantron Technology, Inc. Address: 48434 Milmont Drive Fremont, CA 94538-7324, USA		
Manufacturer	Name: Vantron Technology, Inc. Address: 48434 Milmont Drive Fremont, CA 94538-7324, USA		
Equipment Under Test	Product Name: Module Model/Type: VOSM350 Brand Name: N/A Serial NO.: N/A Sample NO.: 3-1		
Date of Receipt.	2024.09.04	Date of Testing	2024.09.04~2024.10.11
Test Specification		Test Result	
FCC Part 2 (Section 2.1091) KDB 447498 D04 v01, IEEE C95.3		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: 2024.11.10		
Compiled by:  <u>Cai Jianyu</u> Name Signature	Reviewed by:  <u>Mo Xianbiao</u> Name Signature	Approved by:  <u>Dong Sanbi</u> Name Signature	
Other Aspects: NONE.			
Abbreviations: OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

RELEASE CONTROL RECORD4

1. GENERAL PRODUCT INFORMATION5

2. RF EXPOSURE LIMIT6

3. CLASSIFICATION7

4. CALCULATION RESULT OF MAXIMUM CONDUCTED PK POWER7



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2024-0069-H	Original release	2024.11.10



1. GENERAL PRODUCT INFORMATION

PRODUCT	Module
BRAND	N/A
MODEL	VOSM350
ADDITIONAL MODEL	N/A
POWER SUPPLY	DC 5V
STANDARDS	FCC Part 2 (Section 2.1091) KDB 447498 D04 v01, IEEE C95.3
Remark: 1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report. 3. EUT photo refer to the report (Report NO.: FCCSZ2024-0069-EUT).	



2. RF EXPOSURE LIMIT

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda / 2 \pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda / 4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF SOURCE FREQUENCY (MHZ)	THRESHOLD ERP(W)
0.3 -1.34	$1,920 R^2$
1.34 - 30	$3,450 R^2 F^2$
30 -300	$3.83 R^2$
300-1500	$0.0128 R^2 F$
1500-100,000	$19.2 R^2$



3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

4. CALCULATION RESULT OF MAXIMUM CONDUCTED PK POWER

The measured conducted Peak Power

Mode	Antenna	Power (dBm)
BT-EDR	ANT3	11.96
2.4G WIFI	ANT1	13.86
	ANT2	14.87
5.1G WIFI	ANT1	11.46
	ANT2	9.94
5.8G WIFI	ANT1	12.21
	ANT2	10.90

MAXIMUM PERMISSIBLE EXPOSURE (FCC)

Mode	Frequency (MHz)	Antenna	Max Power (dBm)	Antenna Gain (dBi)	R (cm)	EIRP (dBm)	ERP (dBm)	ERP (W)	Threshold ERP(W)	Ratio
BT-EDR	2402-2480	ANT1	11.96	1.82	20	13.78	11.63	0.015	0.77	0.019
2.4G WIFI	2412-2472	ANT1	13.86	1.82	20	15.68	13.53	0.023	0.77	0.030
		ANT2	14.87	1.82	20	16.69	14.54	0.028	0.77	0.036
5.1G WIFI	5180-5240	ANT1	11.46	3.49	20	14.95	12.80	0.019	0.77	0.025
		ANT2	9.94	3.49	20	13.43	11.28	0.013	0.77	0.017
5.8G WIFI	5745-5825	ANT1	12.21	3.49	20	15.70	13.55	0.023	0.77	0.030
		ANT2	10.90	3.49	20	14.39	12.24	0.017	0.77	0.022
Sum of ratio = BT + WIFI ANT1+ WIFI ANT2										0.085

Note1: This device operate simultaneously in BT and WIFI.

Note2: ERP=EIRP-2.15dB

Conclusion:

Therefore, the worst-case situation is 0.085(Sum of Ratios), which is less than “1”. This confirmed that the device compliance with FCC RF exposure requirements..

----- End of the Report -----



Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Lab Address: No. 1301-14&16, Guanguang Road, Xinlan Community,
Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong, China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>