

SPECIFICATION APPROVAL

产品型号： D E S T:	Ø13.8*0.08*105P*12TS- 6.5UH-5mm/42*1.0双槽	版本： VERSION:	V0	客 户：	
				客 户 料 号：	

一、尺寸 DIMENSION: (mm)

The technical drawing shows four views of a circular component. The top-left view is a top-down view of a black circular disc with a central white circle and a notch. Dimensions A and B are indicated. The top-right view is a side view of a coil with two leads. Dimensions C and D are indicated. The bottom-left view is a front view of the coil with dimensions E and F. The bottom-right view is a side view of the coil with dimensions G and H. Dimensions I, J, K, and L are also indicated on the leads.

A	5.3±0.5
B	42-0.5
C	13.8±0.5
D	39.5±1
E	100/+2.5
F	3±1.5
G	1.0±0.1
H	2.4 Max
I	
J	
K	
L	

制定/日期 PREPARED BY/DATE	审核/日期 CHECKED BY/DATE
2023. 12. 21	2023. 12. 21

SPECIFICATION APPROVAL

产品型号： D E S T:	Ø13.8*0.08*105P*12TS- 6.5UH-5mm/42*1.0双槽	版本 : VERSION:	V0	客 户:	
				客 户 料 号:	

二、原理图 SCHEMATIC DIAGRAM:					
S F					
三、绕线参数 WINDING SPECIFICATION:					

序号 NO	端子 TERMINAL		线径 WIRE	圈数 TURNS	绕线方向 WINDING DIRECTION
1	S	F	0.08*105P丝包线	12TS	逆时针

四、电气特性 ELECTRICAL CHARACTERISTICS:					
温度 TEMPERATURE:25℃±10℃,湿度 RELATIVE HUMIDITY:65±20%					

序号 NO	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND	S-F	3.6UH±10%单线圈	100KHZ/1V	LCZ METER1062B
2	IND	S-F	6.5UH-6.8UH带磁片	100KHZ/1V	LCZ METER1062B
3	DCR	S-F	50mΩ MAX	1KHZ/1V	TH2810
4	Q值	S-F	52MIN	100KHZ/1V	LCZ METER1062B

制定/日期 PREPARED BY/DATE			审核/日期 CHECKED BY/DATE		
2023.12.21			2023.12.21		