


TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N40MIMO 5710MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5GWIFI134
Memo: Sample Number:S23111537-05 Power Setting:65

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5451.76	10.75	33.00	5.74	0.00	49.49	74.00	24.51	PK	Vertical
2	5470.00	10.24	33.00	5.75	0.00	48.99	68.20	19.21	PK	Vertical
3	5850.00	6.74	34.00	5.94	0.00	46.68	68.20	21.52	PK	Vertical
4	5879.75	10.80	34.06	5.95	0.00	50.81	68.20	17.39	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC40MIMO 5710MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5GWIFI135
Memo: Sample Number:S23111537-05 Power Setting:65

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5468.09	11.45	33.00	5.74	0.00	50.19	68.20	18.01	PK	Horizontal
2	5470.00	9.60	33.00	5.75	0.00	48.35	68.20	19.85	PK	Horizontal
3	5850.00	8.13	34.00	5.94	0.00	48.07	68.20	20.13	PK	Horizontal
4	5875.43	11.08	34.05	5.95	0.00	51.08	68.20	17.12	PK	Horizontal


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC40MIMO 5710MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5GWIFI136
Memo: Sample Number:S23111537-05 Power Setting:65

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5461.16	11.39	33.00	5.74	0.00	50.13	68.20	18.07	PK	Vertical
2	5470.00	9.34	33.00	5.75	0.00	48.09	68.20	20.11	PK	Vertical
3	5850.00	7.33	34.00	5.94	0.00	47.27	68.20	20.93	PK	Vertical
4	5872.28	10.70	34.04	5.95	0.00	50.69	68.20	17.51	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC80MIMO 5690MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5GWIFI137
Memo: Sample Number:S23111537-05 Power Setting:65

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5468.05	10.81	33.00	5.74	0.00	49.55	68.20	18.65	PK	Horizontal
2	5470.00	9.31	33.00	5.75	0.00	48.06	68.20	20.14	PK	Horizontal
3	5850.00	9.31	34.00	5.94	0.00	49.25	68.20	18.95	PK	Horizontal
4	5857.07	10.83	34.01	5.94	0.00	50.78	68.20	17.42	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC80MIMO 5690MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5GWIFI138
Memo: Sample Number:S23111537-05 Power Setting:65

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5466.34	10.94	33.00	5.74	0.00	49.68	68.20	18.52	PK	Vertical
2	5470.00	8.64	33.00	5.75	0.00	47.39	68.20	20.81	PK	Vertical
3	5850.00	7.99	34.00	5.94	0.00	47.93	68.20	20.27	PK	Vertical
4	5853.92	10.66	34.01	5.94	0.00	50.61	68.20	17.59	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT1 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI41
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5723.93	35.20	33.74	5.87	0.00	74.81	122.21	47.40	PK	Horizontal
2	5725.00	32.69	33.75	5.87	0.00	72.31	125.30	52.99	PK	Horizontal
3	5748.91	67.69	33.89	5.88	0.00	107.46	125.30	17.84	PK	Horizontal
4	5850.00	16.94	34.00	5.94	0.00	56.88	125.27	68.39	PK	Horizontal
5	5870.19	20.68	34.04	5.95	0.00	60.67	106.65	45.98	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT1 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI42
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5724.25	29.59	33.75	5.87	0.00	69.21	123.15	53.94	PK	Vertical
2	5725.00	27.36	33.75	5.87	0.00	66.98	125.30	58.32	PK	Vertical
3	5747.32	62.23	33.88	5.88	0.00	101.99	125.30	23.31	PK	Vertical
4	5850.00	16.90	34.00	5.94	0.00	56.84	125.27	68.43	PK	Vertical
5	5891.58	20.80	34.08	5.96	0.00	60.84	93.00	32.16	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT2 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI43
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5724.49	34.29	33.75	5.87	0.00	73.91	123.83	49.92	PK	Horizontal
2	5725.00	33.77	33.75	5.87	0.00	73.39	125.30	51.91	PK	Horizontal
3	5750.98	68.47	33.91	5.89	0.00	108.27	125.30	17.03	PK	Horizontal
4	5850.00	18.53	34.00	5.94	0.00	58.47	125.27	66.80	PK	Horizontal
5	5903.11	20.00	34.11	5.96	0.00	60.07	84.44	24.37	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT2 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI44
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5720.54	26.24	33.72	5.87	0.00	65.83	112.44	46.61	PK	Vertical
2	5725.00	27.05	33.75	5.87	0.00	66.67	125.30	58.63	PK	Vertical
3	5744.11	61.79	33.86	5.88	0.00	101.53	125.30	23.77	PK	Vertical
4	5850.00	17.52	34.00	5.94	0.00	57.46	125.27	67.81	PK	Vertical
5	5901.05	20.75	34.10	5.96	0.00	60.81	85.97	25.16	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N20MIMO 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI45
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5723.93	35.33	33.74	5.87	0.00	74.94	122.21	47.27	PK	Horizontal
2	5725.00	34.02	33.75	5.87	0.00	73.64	125.30	51.66	PK	Horizontal
3	5748.18	70.08	33.89	5.88	0.00	109.85	125.30	15.45	PK	Horizontal
4	5850.00	16.73	34.00	5.94	0.00	56.67	125.27	68.60	PK	Horizontal
5	5883.97	20.11	34.07	5.95	0.00	60.13	98.65	38.52	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N20MIMO 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI46
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5723.46	29.09	33.74	5.87	0.00	68.70	120.85	52.15	PK	Vertical
2	5725.00	29.23	33.75	5.87	0.00	68.85	125.30	56.45	PK	Vertical
3	5749.80	65.69	33.90	5.88	0.00	105.47	125.30	19.83	PK	Vertical
4	5850.00	17.59	34.00	5.94	0.00	57.53	125.27	67.74	PK	Vertical
5	5887.00	20.91	34.07	5.95	0.00	60.93	96.39	35.46	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC20MIMO 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI47
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5723.57	32.32	33.74	5.87	0.00	71.93	121.19	49.26	PK	Horizontal
2	5725.00	33.95	33.75	5.87	0.00	73.57	125.30	51.73	PK	Horizontal
3	5750.21	69.17	33.90	5.89	0.00	108.96	125.30	16.34	PK	Horizontal
4	5850.00	18.33	34.00	5.94	0.00	58.27	125.27	67.00	PK	Horizontal
5	5869.95	20.12	34.04	5.94	0.00	60.10	106.71	46.61	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC20MIMO 5745MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI48
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5723.07	31.10	33.74	5.87	0.00	70.71	119.75	49.04	PK	Vertical
2	5725.00	30.07	33.75	5.87	0.00	69.69	125.30	55.61	PK	Vertical
3	5747.94	65.47	33.89	5.88	0.00	105.24	125.30	20.06	PK	Vertical
4	5850.00	17.57	34.00	5.94	0.00	57.51	125.27	67.76	PK	Vertical
5	5882.14	19.91	34.06	5.95	0.00	59.92	100.01	40.09	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT1 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI49
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5724.31	21.71	33.75	5.87	0.00	61.33	123.32	61.99	PK	Horizontal
2	5725.00	17.58	33.75	5.87	0.00	57.20	125.30	68.10	PK	Horizontal
3	5781.28	66.95	34.09	5.90	0.00	106.94	125.30	18.36	PK	Horizontal
4	5850.00	17.96	34.00	5.94	0.00	57.90	125.27	67.37	PK	Horizontal
5	5923.64	20.77	34.15	5.97	0.00	60.89	69.21	8.32	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT1 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\50
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5710.48	20.15	33.66	5.87	0.00	59.68	108.23	48.55	PK	Vertical
2	5725.00	16.84	33.75	5.87	0.00	56.46	125.30	68.84	PK	Vertical
3	5780.72	64.72	34.08	5.90	0.00	104.70	125.30	20.60	PK	Vertical
4	5850.00	17.11	34.00	5.94	0.00	57.05	125.27	68.22	PK	Vertical
5	5857.12	19.86	34.01	5.94	0.00	59.81	110.31	50.50	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT2 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\51
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5716.14	21.04	33.70	5.87	0.00	60.61	109.82	49.21	PK	Horizontal
2	5725.00	18.68	33.75	5.87	0.00	58.30	125.30	67.00	PK	Horizontal
3	5779.86	67.30	34.08	5.90	0.00	107.28	125.30	18.02	PK	Horizontal
4	5850.00	16.49	34.00	5.94	0.00	56.43	125.27	68.84	PK	Horizontal
5	5864.58	21.03	34.03	5.94	0.00	61.00	108.22	47.22	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT2 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\52
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5691.39	20.83	33.57	5.86	0.00	60.26	98.91	38.65	PK	Vertical
2	5725.00	17.74	33.75	5.87	0.00	57.36	125.30	67.94	PK	Vertical
3	5788.00	64.73	34.13	5.90	0.00	104.76	125.30	20.54	PK	Vertical
4	5850.00	17.77	34.00	5.94	0.00	57.71	125.27	67.56	PK	Vertical
5	5875.85	19.80	34.05	5.95	0.00	59.80	104.67	44.87	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N20MIMO 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\53
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5683.54	20.90	33.53	5.85	0.00	60.28	93.09	32.81	PK	Horizontal
2	5725.00	17.70	33.75	5.87	0.00	57.32	125.30	67.98	PK	Horizontal
3	5785.88	69.60	34.12	5.90	0.00	109.62	125.30	15.68	PK	Horizontal
4	5850.00	18.64	34.00	5.94	0.00	58.58	125.27	66.69	PK	Horizontal
5	5902.28	20.32	34.10	5.96	0.00	60.38	85.05	24.67	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N20MIMO 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\54
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5720.45	20.74	33.72	5.87	0.00	60.33	112.19	51.86	PK	Vertical
2	5725.00	17.87	33.75	5.87	0.00	57.49	125.30	67.81	PK	Vertical
3	5789.36	66.10	34.14	5.90	0.00	106.14	125.30	19.16	PK	Vertical
4	5850.00	19.51	34.00	5.94	0.00	59.45	125.27	65.82	PK	Vertical
5	5861.96	20.73	34.02	5.94	0.00	60.69	108.95	48.26	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC20MIMO 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\55
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5692.81	20.46	33.57	5.86	0.00	59.89	99.96	40.07	PK	Horizontal
2	5725.00	17.55	33.75	5.87	0.00	57.17	125.30	68.13	PK	Horizontal
3	5779.95	69.51	34.08	5.90	0.00	109.49	125.30	15.81	PK	Horizontal
4	5850.00	17.60	34.00	5.94	0.00	57.54	125.27	67.73	PK	Horizontal
5	5887.30	20.26	34.07	5.95	0.00	60.28	96.17	35.89	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC20MIMO 5785MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\56
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5650.53	21.51	33.40	5.84	0.00	60.75	68.59	7.84	PK	Vertical
2	5725.00	17.19	33.75	5.87	0.00	56.81	125.30	68.49	PK	Vertical
3	5787.35	65.24	34.12	5.90	0.00	105.26	125.30	20.04	PK	Vertical
4	5850.00	18.74	34.00	5.94	0.00	58.68	125.27	66.59	PK	Vertical
5	5920.10	20.29	34.14	5.97	0.00	60.40	71.83	11.43	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT1 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\57
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5692.66	21.43	33.57	5.86	0.00	60.86	99.85	38.99	PK	Horizontal
2	5725.00	18.55	33.75	5.87	0.00	58.17	125.30	67.13	PK	Horizontal
3	5830.75	69.07	34.08	5.93	0.00	109.08	125.30	16.22	PK	Horizontal
4	5850.00	19.92	34.00	5.94	0.00	59.86	125.27	65.41	PK	Horizontal
5	5851.66	22.73	34.00	5.94	0.00	62.67	120.51	57.84	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT1 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\58
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5700.45	20.91	33.60	5.86	0.00	60.37	105.42	45.05	PK	Vertical
2	5725.00	17.73	33.75	5.87	0.00	57.35	125.30	67.95	PK	Vertical
3	5819.66	65.68	34.12	5.92	0.00	105.72	125.30	19.58	PK	Vertical
4	5850.00	19.53	34.00	5.94	0.00	59.47	125.27	65.80	PK	Vertical
5	5851.81	21.67	34.00	5.94	0.00	61.61	120.09	58.48	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT2 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\59
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5722.19	21.01	33.73	5.87	0.00	60.61	117.20	56.59	PK	Horizontal
2	5725.00	18.35	33.75	5.87	0.00	57.97	125.30	67.33	PK	Horizontal
3	5827.97	69.83	34.09	5.92	0.00	109.84	125.30	15.46	PK	Horizontal
4	5850.00	23.17	34.00	5.94	0.00	63.11	125.27	62.16	PK	Horizontal
5	5852.02	23.55	34.00	5.94	0.00	63.49	119.49	56.00	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11A ANT2 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\60
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5672.39	21.82	33.49	5.85	0.00	61.16	84.81	23.65	PK	Vertical
2	5725.00	17.28	33.75	5.87	0.00	56.90	125.30	68.40	PK	Vertical
3	5818.74	65.23	34.13	5.92	0.00	105.28	125.30	20.02	PK	Vertical
4	5850.00	20.64	34.00	5.94	0.00	60.58	125.27	64.69	PK	Vertical
5	5851.01	24.15	34.00	5.94	0.00	64.09	122.38	58.29	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N20MIMO 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\61
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5646.20	20.93	33.39	5.83	0.00	60.15	68.20	8.05	PK	Horizontal
2	5725.00	17.51	33.75	5.87	0.00	57.13	125.30	68.17	PK	Horizontal
3	5827.89	68.07	34.09	5.92	0.00	108.08	125.30	17.22	PK	Horizontal
4	5850.00	23.02	34.00	5.94	0.00	62.96	125.27	62.31	PK	Horizontal
5	5851.46	24.11	34.00	5.94	0.00	64.05	121.11	57.06	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N20MIMO 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\62
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5663.28	20.80	33.45	5.84	0.00	60.09	78.05	17.96	PK	Vertical
2	5725.00	17.14	33.75	5.87	0.00	56.76	125.30	68.54	PK	Vertical
3	5819.89	64.92	34.12	5.92	0.00	104.96	125.30	20.34	PK	Vertical
4	5850.00	21.68	34.00	5.94	0.00	61.62	125.27	63.65	PK	Vertical
5	5852.99	24.23	34.01	5.94	0.00	64.18	116.69	52.51	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC20MIMO 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\63
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5711.39	21.98	33.67	5.87	0.00	61.52	108.49	46.97	PK	Horizontal
2	5725.00	18.02	33.75	5.87	0.00	57.64	125.30	67.66	PK	Horizontal
3	5819.60	67.97	34.12	5.92	0.00	108.01	125.30	17.29	PK	Horizontal
4	5850.00	23.28	34.00	5.94	0.00	63.22	125.27	62.05	PK	Horizontal
5	5851.37	23.28	34.00	5.94	0.00	63.22	121.36	58.14	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC20MIMO 5825MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\64
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5659.35	21.84	33.44	5.84	0.00	61.12	75.14	14.02	PK	Vertical
2	5725.00	18.77	33.75	5.87	0.00	58.39	125.30	66.91	PK	Vertical
3	5820.45	65.32	34.12	5.92	0.00	105.36	125.30	19.94	PK	Vertical
4	5850.00	20.89	34.00	5.94	0.00	60.83	125.27	64.44	PK	Vertical
5	5853.14	22.69	34.01	5.94	0.00	62.64	116.26	53.62	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N40MIMO 5755MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\65
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5719.21	40.21	33.72	5.87	0.00	79.80	110.68	30.88	PK	Horizontal
2	5725.00	36.45	33.75	5.87	0.00	76.07	125.30	49.23	PK	Horizontal
3	5753.46	67.22	33.92	5.89	0.00	107.03	125.30	18.27	PK	Horizontal
4	5850.00	17.72	34.00	5.94	0.00	57.66	125.27	67.61	PK	Horizontal
5	5877.39	20.11	34.05	5.95	0.00	60.11	103.53	43.42	PK	Horizontal


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N40MIMO 5755MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\66
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5722.07	33.59	33.73	5.87	0.00	73.19	116.86	43.67	PK	Vertical
2	5725.00	28.69	33.75	5.87	0.00	68.31	125.30	56.99	PK	Vertical
3	5743.69	62.29	33.86	5.88	0.00	102.03	125.30	23.27	PK	Vertical
4	5850.00	17.56	34.00	5.94	0.00	57.50	125.27	67.77	PK	Vertical
5	5857.92	20.16	34.02	5.94	0.00	60.12	110.08	49.96	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC40MIMO 5755MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\67
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List

N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5719.68	40.24	33.72	5.87	0.00	79.83	110.81	30.98	PK	Horizontal
2	5725.00	35.25	33.75	5.87	0.00	74.87	125.30	50.43	PK	Horizontal
3	5760.98	67.13	33.97	5.89	0.00	106.99	125.30	18.31	PK	Horizontal
4	5850.00	17.88	34.00	5.94	0.00	57.82	125.27	67.45	PK	Horizontal
5	5863.40	20.83	34.03	5.94	0.00	60.80	108.55	47.75	PK	Horizontal


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC40MIMO 5755MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\68
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5719.68	34.65	33.72	5.87	0.00	74.24	110.81	36.57	PK	Vertical
2	5725.00	30.84	33.75	5.87	0.00	70.46	125.30	54.84	PK	Vertical
3	5751.42	63.05	33.91	5.89	0.00	102.85	125.30	22.45	PK	Vertical
4	5850.00	17.42	34.00	5.94	0.00	57.36	125.27	67.91	PK	Vertical
5	5884.14	20.19	34.07	5.95	0.00	60.21	98.52	38.31	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N40MIMO 5795MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\69
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5658.47	21.04	33.43	5.84	0.00	60.31	74.48	14.17	PK	Horizontal
2	5725.00	18.54	33.75	5.87	0.00	58.16	125.30	67.14	PK	Horizontal
3	5791.90	68.04	34.15	5.91	0.00	108.10	125.30	17.20	PK	Horizontal
4	5850.00	20.13	34.00	5.94	0.00	60.07	125.27	65.20	PK	Horizontal
5	5851.75	22.83	34.00	5.94	0.00	62.77	120.26	57.49	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11N40MIMO 5795MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\70
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5675.08	20.74	33.50	5.85	0.00	60.09	86.81	26.72	PK	Vertical
2	5725.00	17.12	33.75	5.87	0.00	56.74	125.30	68.56	PK	Vertical
3	5787.56	63.13	34.13	5.90	0.00	103.16	125.30	22.14	PK	Vertical
4	5850.00	19.17	34.00	5.94	0.00	59.11	125.27	66.16	PK	Vertical
5	5852.70	21.52	34.01	5.94	0.00	61.47	117.54	56.07	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC40MIMO 5795MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\71
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5714.02	22.02	33.68	5.87	0.00	61.57	109.22	47.65	PK	Horizontal
2	5725.00	18.08	33.75	5.87	0.00	57.70	125.30	67.60	PK	Horizontal
3	5792.57	66.66	34.16	5.91	0.00	106.73	125.30	18.57	PK	Horizontal
4	5850.00	19.00	34.00	5.94	0.00	58.94	125.27	66.33	PK	Horizontal
5	5850.51	23.55	34.00	5.94	0.00	63.49	123.83	60.34	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC40MIMO 5795MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\72
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5663.51	20.75	33.45	5.84	0.00	60.04	78.23	18.19	PK	Vertical
2	5725.00	18.65	33.75	5.87	0.00	58.27	125.30	67.03	PK	Vertical
3	5787.32	63.46	34.12	5.90	0.00	103.48	125.30	21.82	PK	Vertical
4	5850.00	19.54	34.00	5.94	0.00	59.48	125.27	65.79	PK	Vertical
5	5850.60	22.23	34.00	5.94	0.00	62.17	123.57	61.40	PK	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC80MIMO 5775MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\73
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5718.97	38.14	33.71	5.87	0.00	77.72	110.61	32.89	PK	Horizontal
2	5725.00	33.05	33.75	5.87	0.00	72.67	125.30	52.63	PK	Horizontal
3	5787.53	64.47	34.13	5.90	0.00	104.50	125.30	20.80	PK	Horizontal
4	5850.00	32.60	34.00	5.94	0.00	72.54	125.27	52.73	PK	Horizontal
5	5858.92	31.36	34.02	5.94	0.00	71.32	109.80	38.48	PK	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-01-17 **Tested By:** Bairong
EUT: AloT Edge Controller **Model Number:** MB41
Test Mode: 11AC80MIMO 5775MHz TX **Power Supply:** DC 5V
Condition: Temp:21.4°C;Humi:54.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23111537-2E MB41\FCC ABOVE 1G 5.8GWIFI\74
Memo: Sample Number:S23111537-05 Power Setting:NA

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	5721.95	33.74	33.73	5.87	0.00	73.34	116.52	43.18	PK	Vertical
2	5725.00	28.86	33.75	5.87	0.00	68.48	125.30	56.82	PK	Vertical
3	5787.65	61.02	34.13	5.90	0.00	101.05	125.30	24.25	PK	Vertical
4	5850.00	27.54	34.00	5.94	0.00	67.48	125.27	57.79	PK	Vertical
5	5850.10	29.71	34.00	5.94	0.00	69.65	125.01	55.36	PK	Vertical

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Power Line Conducted Emission

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑Power Line Conducted Emissions Test 2#				
Test Receiver	R&S	ESCI	101032	2024/04/22
LISN 1	R&S	ENV216	101170	2024/07/11
LISN 2	R&S	ENV216	101209	2024/07/11
Pulse Limiter	R&S	KH43101	431011801568-12#	2024/05/04
CE Cable 2	HUBSER	RG214-5	N/A	2024/04/26
Test software	Audix	E3	V 6.11111b	N/A

14.2. Block diagram of test setup



14.3. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.4. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver

connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.5. Test Result

Pass. (See below detailed test result)


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means peak detection; “-----” means average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room D:\2024 report data\Q23111537-2E\FCC CE.EM6
Test Date : 2024-01-31 **Tested By** : Junchang Du
EUT : AIoT Edge Controller **Model Number** : MB41
Power Supply : AC 120V/60Hz **Test Mode** : 5G WIFI mode
Condition : Temp:24.5°C,Humi:55.5% **LISN** : 2023 ENV216 2#/NEUTRAL
Memo :




Item (Mark)	Freq. (MHz)	Read Level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Detector	Phase
1	0.18	16.01	9.95	0.19	10.15	36.30	64.42	-28.12	QP	NEUTRAL
2	0.18	9.91	9.95	0.19	10.15	30.20	54.42	-24.22	Average	NEUTRAL
3	0.32	13.89	10.03	0.24	10.10	34.26	59.80	-25.54	QP	NEUTRAL
4	0.32	8.90	10.03	0.24	10.10	29.27	49.80	-20.53	Average	NEUTRAL
5	0.46	14.18	9.98	0.25	10.06	34.47	56.63	-22.16	QP	NEUTRAL
6	0.46	8.73	9.98	0.25	10.06	29.02	46.63	-17.61	Average	NEUTRAL
7	0.91	20.91	9.97	0.32	9.90	41.10	56.00	-14.90	QP	NEUTRAL
8	0.91	12.86	9.97	0.32	9.90	33.05	46.00	-12.95	Average	NEUTRAL
9	1.60	10.41	9.97	0.35	9.78	30.51	56.00	-25.49	QP	NEUTRAL
10	1.60	5.07	9.97	0.35	9.78	25.17	46.00	-20.83	Average	NEUTRAL
11	3.86	3.38	10.06	0.36	9.92	23.72	56.00	-32.28	QP	NEUTRAL
12	3.86	-2.82	10.06	0.36	9.92	17.52	46.00	-28.48	Average	NEUTRAL

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 5# Shield Room	D:	: 2024 report data\Q23111537-2E\FCC CE.EM6
Test Date	: 2024-01-31	Tested By	: Junchang Du
EUT	: AIoT Edge Controller	Model Number	: MB41
Power Supply	: AC 120V/60Hz	Test Mode	: 5G WIFI mode
Condition	: Temp:24.5°C,Humi:55.5%	LISN	: 2023 ENV216 2#/LINE
Memo	:		



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Detector	Phase
1	0.18	16.34	9.95	0.19	10.15	36.63	64.50	-27.87	QP	LINE
2	0.18	9.96	9.95	0.19	10.15	30.25	54.50	-24.25	Average	LINE
3	0.29	15.01	9.90	0.24	10.11	35.26	60.50	-25.24	QP	LINE
4	0.29	9.06	9.90	0.24	10.11	29.31	50.50	-21.19	Average	LINE
5	0.54	12.95	9.97	0.25	10.03	33.20	56.00	-22.80	QP	LINE
6	0.54	7.49	9.97	0.25	10.03	27.74	46.00	-18.26	Average	LINE
7	0.78	15.20	9.97	0.28	9.94	35.39	56.00	-20.61	QP	LINE
8	0.78	10.87	9.97	0.28	9.94	31.06	46.00	-14.94	Average	LINE
9	2.10	6.42	10.03	0.35	9.74	26.54	56.00	-29.46	QP	LINE
10	2.10	0.69	10.03	0.35	9.74	20.81	46.00	-25.19	Average	LINE
11	25.46	2.57	9.97	0.41	10.03	22.98	60.00	-37.02	QP	LINE
12	25.46	-2.87	9.97	0.41	10.03	17.54	50.00	-32.46	Average	LINE

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

15. Antenna Requirements

15.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

15.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

17. Photos of the EUT

Please refer to DDT-Q23111537-1E appendix I.

END OF REPORT