



# FCC Radio Test Report


## FCC ID: 2BEECYK500A-2

**This report concerns: Original Grant**

**Project No.** : 2311G192  
**Equipment** : Remote Controller  
**Brand Name** : Y DIANS S  
**Test Model** : YK500A-2  
**Series Model** : N/A  
**Applicant** : Hangzhou Yasong Electronic Co.,Ltd.  
**Address** : Moganshan Road No.1418-36, Building 2, Room 501 Hangzhou Zhejiang  
**Date of Receipt** : Dec. 01, 2023  
**Date of Test** : Dec. 05, 2023 ~ Jan. 02, 2024  
**Issued Date** : Jan. 12, 2024  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: SSL202312011 for conducted, SSL202312012 for radiated emissions below 30MHz, SSL202312182 for radiated emissions above 30MHz.  
**Standard(s)** : FCC CFR Title 47, Part 15, Subpart C  
ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

**Prepared by**

  
Evan Yang

**Approved by**

  
Welly Zhou

Room 108, Building 2, No. 1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong 523000 China

Tel: +86-769-8318-3000 Web: [www.newbtl.com](http://www.newbtl.com) Service mail: [btl\\_qa@newbtl.com](mailto:btl_qa@newbtl.com)

### Declaration

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL**'s reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL**'s laboratory quality assurance procedures are in compliance with the ISO/IEC 17025: 2017 requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

### Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents	Page
<b>REPORT ISSUED HISTORY</b>	<b>5</b>
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>6</b>
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
<b>2 . GENERAL INFORMATION</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	9
2.3 DUTY CYCLE	10
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 SUPPORT UNITS	11
<b>3 . AC POWER LINE CONDUCTED EMISSIONS</b>	<b>12</b>
3.1 LIMIT	12
3.2 TEST PROCEDURE	12
3.3 DEVIATION FROM TEST STANDARD	12
3.4 TEST SETUP	13
3.5 EUT OPERATING CONDITIONS	13
3.6 TEST RESULTS	13
<b>4 . RADIATED EMISSION</b>	<b>14</b>
4.1 LIMIT	14
4.2 TEST PROCEDURE	15
4.3 DEVIATION FROM TEST STANDARD	16
4.4 TEST SETUP	17
4.5 EUT OPERATING CONDITIONS	18
4.6 TEST RESULTS - 9 KHZ TO 30 MHZ	18
4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ	18
4.8 TEST RESULTS - ABOVE 1000 MHZ	18
<b>5 . 20 DB SPECTRUM BANDWIDTH MEASUREMENT</b>	<b>19</b>
5.1 LIMIT	19
5.2 TEST PROCEDURE	19
5.3 DEVIATION FROM STANDARD	19
5.4 TEST SETUP	19
5.5 EUT OPERATION CONDITIONS	19

Table of Contents	Page
<b>5.6 TEST RESULTS</b>	<b>19</b>
<b>6 . TIMING TESTING</b>	<b>20</b>
<b>6.1 LIMIT</b>	<b>20</b>
<b>6.2 TEST PROCEDURE</b>	<b>20</b>
<b>6.3 DEVIATION FROM STANDARD</b>	<b>20</b>
<b>6.4 TEST SETUP</b>	<b>20</b>
<b>6.5 EUT OPERATION CONDITIONS</b>	<b>20</b>
<b>6.6 TEST RESULTS</b>	<b>20</b>
<b>7 . MEASUREMENT INSTRUMENTS LIST</b>	<b>21</b>
<b>8 . EUT TEST PHOTO</b>	<b>23</b>
<b>APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS</b>	<b>27</b>
<b>APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ</b>	<b>28</b>
<b>APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ</b>	<b>33</b>
<b>APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ</b>	<b>38</b>
<b>APPENDIX E - 20 DB SPECTRUM BANDWIDTH</b>	<b>41</b>
<b>APPENDIX F - TIMING TESTING</b>	<b>43</b>

**REPORT ISSUED HISTORY**

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-1-2311G192	R00	Original Report.	Jan. 12, 2024	Valid

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	Test Item	Test Result	Judgment	Remark
15.207	AC Power Line Conducted Emissions	APPENDIX A	N/A	-----
15.205 15.209 15.231(b)	Radiated Emission	APPENDIX B APPENDIX C APPENDIX D	PASS	-----
15.231(c)	20 dB Spectrum Bandwidth	APPENDIX E	PASS	-----
15.231(a)	Timing Testing	APPENDIX F	PASS	-----
15.203	Antenna Requirement	-----	PASS	Note(2)

Note:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

## 1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong 523792.

BTL's Registration Number for FCC: 162128  
BTL's Designation Number for FCC: CN5042

## 1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))  
The BTL measurement uncertainty as below table:

A. Radiated emissions test:

Test Site	Method	Measurement Frequency Range	$U$ ,(dB)
DG-CB01	CISPR	9kHz ~ 30MHz	2.36

Test Site	Method	Measurement Frequency Range	Ant. H / V	$U$ ,(dB)
DG-CB03 (3m)	CISPR	30MHz ~ 200MHz	V	4.40
		30MHz ~ 200MHz	H	3.62
		200MHz ~ 1,000MHz	V	4.58
		200MHz ~ 1,000MHz	H	3.98

Test Site	Method	Measurement Frequency Range	$U$ ,(dB)
DG-CB03 (3m)	CISPR	1GHz ~ 6GHz	4.08

B. Other Measurement test:

Test Item	Uncertainty
Bandwidth	0.90 %
Temperature	0.8 °C
Humidity	2.2 %

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

## 1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
Radiated Emissions-9kHz to 30 MHz	22°C	48%	DC 9V	Hayden Chen
Radiated Emissions-30MHz to 1000MHz	22°C	41%	DC 9V	Allen Tong
Radiated Emissions-Above 1000MHz	22°C	41%	DC 9V	Allen Tong
20 dB Spectrum Bandwidth	25°C	52%	DC 9V	Steve Zhou
Timing Testing	25°C	52%	DC 9V	Parper Yang

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Remote Controller
Brand Name	Y DIANS S
Test Model	YK500A-2
Series Model	N/A
Model Difference(s)	N/A
Power Source	Battery Supplied. Model: 6F22
Power Rating	DC 9V
Operation Frequency	315MHz
Modulation Type	OOK
Antenna Type	Telescope
Field Strength	74.78 dB $\mu$ V/m

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

EUT Test Channel	Test Frequency (MHz)
CH01	315

## 2.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode_315MHz

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

<b>Radiated Emissions test - Below 1GHz</b>	
Final Test Mode	Description
Mode 1	TX Mode_315MHz

<b>Radiated Emissions test - Above 1GHz</b>	
Final Test Mode	Description
Mode 1	TX Mode_315MHz

<b>Conducted test</b>	
Final Test Mode	Description
Mode 1	TX Mode_315MHz

### 2.3 DUTY CYCLE


Test Frequency (MHz)	On Time (ms)	Total Time (ms)	Duty Cycle (%)
315	15.8	100	15.80

Duty Cycle =  $(N1 \cdot L1 + N2 \cdot L2 + \dots + Nn-1 \cdot Ln-1 + Nn \cdot Ln) / 100$  or T


Duty Cycle =  $15.8 / 100 = 0.158$

Average Reading = Peak Reading (dBuV/m) +  $20 \log_{10}$  (Duty cycle)

Average Reading = Peak +  $20 \log_{10}$  (Duty Cycle) = Peak - 16.03



Date: 30.DEC.2023 09:51:40



Date: 30.DEC.2023 09:52:32

**2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED****2.5 SUPPORT UNITS**

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
-	-	-	-	-

Item	Cable Type	Shielded Type	Ferrite Core	Length
-	-	-	-	-

### 3. AC POWER LINE CONDUCTED EMISSIONS

#### 3.1 LIMIT

Frequency of Emission (MHz)	Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

#### 3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.


The following table is the setting of the receiver:

Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 3.3 DEVIATION FROM TEST STANDARD

No deviation.

### 3.4 TEST SETUP



### 3.5 EUT OPERATING CONDITIONS

EUT was programmed to be in continuously transmitting mode.

### 3.6 TEST RESULTS

Please refer to the APPENDIX A.

## 4. RADIATED EMISSION

### 4.1 LIMIT

Frequency Band (MHz)	Fundamental Emissions Limit( $\mu$ V/m) at 3m
40.66-40.70	1000
70-130	500
130-174	500-1500(Note1)
174-260	1500
260-470	1500-5000(Note1)
Above 470	5000

Frequency Band (MHz)	Spurious Emissions Limit( $\mu$ V/m) at 3m (Note2)
40.66-40.70	100
70-130	50
130-174	50-150(Note1)
174-260	150
260-470	150-500(Note1)
Above 470	500

Note:

- 1) Linear interpolations, the formulas for calculating the maximum permitted fundamental field strengths are as follows:
  - a) For the band 130 - 174 MHz,  $\mu$ V/m at 3 meters =  $22.73 \times (\text{operating frequency, MHz}) - 2454.55$ ;
  - b) For the band 260 - 470 MHz,  $\mu$ V/m at 3 meters =  $16.67 \times (\text{operating frequency, MHz}) - 2833.33$ .So the field strength of emission limits has been calculated in below table.

Carrier Frequency (MHz)	Fundamental Emissions Limit(dB $\mu$ V/m) at 3m
315 MHz	75.62 (Average)
315 MHz	95.62 (Peak)

- 2) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in 15.209, whichever limit permits a higher field strength.

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

#### LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

#### NOTE:

- (1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### 4.2 TEST PROCEDURE

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i. For the actual test configuration, please refer to the related Item -EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Receiver Parameter	Setting
Attenuation	Auto
Center Frequency	Fundamental Frequency
RBW	120 kHz
Detector	Peak / Average

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 1MHz for Peak, AV Mode with Dwell time


Receiver Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~6 GHz for PK/AVG detector
Start ~ Stop Frequency	431.920 MHz~435.92 MHz for PK/AVG detector

#### 4.3 DEVIATION FROM TEST STANDARD


No deviation.


#### 4.4 TEST SETUP

##### 9 kHz to 30 MHz



##### 30 MHz to 1 GHz



**Above 1 GHz****4.5 EUT OPERATING CONDITIONS**

The EUT was programmed to be in continuously transmitting mode.

**4.6 TEST RESULTS - 9 KHZ TO 30 MHZ**

Please refer to the APPENDIX B.

Remark:

- (1) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (2) Limit line = specific limits (dBuV) + distance extrapolation factor.

**4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ**

Please refer to the APPENDIX C.

**4.8 TEST RESULTS - ABOVE 1000 MHZ**

Please refer to the APPENDIX D.

## 5. 20 DB SPECTRUM BANDWIDTH MEASUREMENT

### 5.1 LIMIT

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

### 5.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	> 20dB Bandwidth
RBW	10 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 5.3 DEVIATION FROM STANDARD

No deviation.

### 5.4 TEST SETUP



### 5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 5.6 TEST RESULTS

Please refer to the APPENDIX E.

## 6. TIMING TESTING

### 6.1 LIMIT

Devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

### 6.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	Zero Span
RBW	1 MHz
VBW	1 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	50s

### 6.3 DEVIATION FROM STANDARD

No deviation.

### 6.4 TEST SETUP



### 6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 6.6 TEST RESULTS

Please refer to the APPENDIX F.

**7. MEASUREMENT INSTRUMENTS LIST**

<b>Radiated Emissions - 9 kHz to 30 MHz</b>					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Active Loop Antenna	Schwarzbeck	FMZB 1513-60B	1513-60 B-034	Apr. 01, 2024
2	MXE EMI Receiver	Keysight	N9038A	MY56400091	Jan. 07, 2024
3	Cable	N/A	RW2350-3.8A-NMB M-1.5M	N/A	Jun. 10, 2024
4	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
5	966 Chamber room	ETS	9*6*6	N/A	Jul. 11, 2024



<b>Radiated Emissions - 30 MHz to 1 GHz</b>					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	1462	Dec. 13, 2024
2	Attenuator	EMC INSTRUMENT	EMCI-N-6-06	AT-06009	Dec. 13, 2024
3	Preamplifier	EMC INSTRUMENT	EMC001330	980863	Nov. 17, 2024
4	Cable	RegalWay	LMR400-NMNM-12 .5m	N/A	Jul. 04, 2024
5	Cable	RegalWay	LMR400-NMNM-3 m	N/A	Jul. 04, 2024
6	Cable	RegalWay	LMR400-NMNM-0. 5m	N/A	Jul. 04, 2024
7	Receiver	Agilent	N9038A	MY52130039	Jan. 07, 2024
8	Positioning Controller	MF	MF-7802	N/A	N/A
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
10	966 Chamber room	CM	9*6*6	N/A	May 17, 2024



<b>Radiated Emissions - Above 1 GHz</b>					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Receiver	Agilent	N9038A	MY52130039	Jan. 07, 2024
2	Preamplifier	EMC INSTRUMENT	EMC118A45SE	980888	Nov. 17, 2024
3	Double Ridged Guide Antenna	ETS	3115	75789	May 31, 2024
4	Cable	RegalWay	A81-SMAMSMAM- 12.5M	N/A	Aug. 08, 2024
5	Cable	RegalWay	RWLP50-4.0A-NM RASM-2.5M	N/A	Aug. 08, 2024
6	Cable	RegalWay	RWLP50-4.0A-NM RASMRA-0.8M	N/A	Aug. 08, 2024
7	966 Chamber room	CM	9*6*6	N/A	May 17, 2024
8	Positioning Controller	MF	MF-7802	N/A	N/A
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A



<b>20 dB Spectrum Bandwidth &amp; Timing Testing</b>					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Jun. 16, 2024
2	Attenuator	Talent Microwave	TA10A0-S-26.5	N/A	N/A


Remark "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

**8. EUT TEST PHOTO****Radiated Emissions Test Photos****9 kHz to 30 MHz**

**Radiated Emissions Test Photos****30 MHz to 1 GHz**

**Radiated Emissions Test Photos****Above 1 GHz**

**Conducted Test Photos**


## APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

**Test Mode: N/A**

Note: "N/A" denotes test is not applicable to this device.

## APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ

Test Mode	TX Mode_315MHz	Polarization	Ant 0°
-----------	----------------	--------------	--------




No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		Level	Factor	ment		dB	Detector	Comment
1	0.0182	54.61	20.45	75.06	122.40	-47.34	AVG	
2	0.0590	46.52	19.83	66.35	112.19	-45.84	AVG	
3 *	0.1031	41.97	19.83	61.80	107.34	-45.54	QP	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_315MHz	Polarization	Ant 0°
-----------	----------------	--------------	--------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2.1201	24.61	19.80	44.41	69.54	-25.13	QP	
2		5.8812	17.85	19.96	37.81	69.54	-31.73	QP	
3		23.5524	15.36	20.83	36.19	69.54	-33.35	QP	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_315MHz	Polarization	Ant 90°
-----------	----------------	--------------	---------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.0090	59.84	20.60	80.44	128.52	-48.08	AVG	
2		0.0542	45.13	19.81	64.94	112.92	-47.98	AVG	
3	*	0.1198	39.84	19.83	59.67	106.04	-46.37	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_315MHz	Polarization	Ant 90°
-----------	----------------	--------------	---------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.5731	33.51	19.85	53.36	72.44	-19.08	QP	
2		7.4782	17.51	20.04	37.55	69.54	-31.99	QP	
3		20.2390	15.82	20.62	36.44	69.54	-33.10	QP	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ**

Test Mode	TX Mode_315MHz	Polarization	Vertical
-----------	----------------	--------------	----------




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1		315.000	63.95	-0.20	63.75	95.62	-31.87	peak
2 *		315.000	47.92	-0.20	47.72	75.62	-27.90	AVG

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.
- (3) About the duty cycle correction factor calculated, please refer to the Section 2.3.

Test Mode	TX Mode_315MHz	Polarization	Horizontal
-----------	----------------	--------------	------------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
1		315.000	74.98	-0.20	74.78	95.62	-20.84	peak	
2	*	315.000	58.95	-0.20	58.75	75.62	-16.87	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.
- (3) About the duty cycle correction factor calculated, please refer to the Section 2.3.

Test Mode	TX Mode_315MHz	Polarization	Vertical
-----------	----------------	--------------	----------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
1		155.6150	36.58	-11.02	25.56	43.50	-17.94	peak	
2		466.9850	36.75	-6.54	30.21	46.00	-15.79	peak	
3		541.6750	36.92	-5.21	31.71	46.00	-14.29	peak	
4		718.2150	37.08	-1.96	35.12	46.00	-10.88	peak	
5		840.9200	38.28	-0.68	37.60	46.00	-8.40	peak	
6	*	896.2100	38.24	0.11	38.35	46.00	-7.65	peak	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_315MHz	Polarization	Horizontal
-----------	----------------	--------------	------------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
1		421.3950	36.80	-7.53	29.27	46.00	-16.73	peak	
2		544.5850	36.72	-5.15	31.57	46.00	-14.43	peak	
3		645.4650	36.84	-2.98	33.86	46.00	-12.14	peak	
4		738.1000	37.97	-1.47	36.50	46.00	-9.50	peak	
5	*	912.7000	38.65	0.22	38.87	46.00	-7.13	peak	
6		986.4200	37.69	0.69	38.38	54.00	-15.62	peak	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ**

Test Mode	TX Mode_315MHz	Polarization	Vertical
-----------	----------------	--------------	----------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
1		2518.000	37.79	-3.71	34.08	74.00	-39.92	peak	
2		2518.000	21.76	-3.71	18.05	54.00	-35.95	AVG	
3		2834.000	36.65	-2.75	33.90	74.00	-40.10	peak	
4		2834.000	20.62	-2.75	17.87	54.00	-36.13	AVG	
5		3148.000	35.88	-1.80	34.08	74.00	-39.92	peak	
6	*	3148.000	19.85	-1.80	18.05	54.00	-35.95	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_315MHz	Polarization	Horizontal
-----------	----------------	--------------	------------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
1		2518.000	41.50	-3.71	37.79	74.00	-36.21	peak	
2		2518.000	25.47	-3.71	21.76	54.00	-32.24	AVG	
3		2834.000	41.07	-2.75	38.32	74.00	-35.68	peak	
4 *		2834.000	25.04	-2.75	22.29	54.00	-31.71	AVG	
5		3148.000	38.63	-1.80	36.83	74.00	-37.17	peak	
6		3148.000	22.60	-1.80	20.80	54.00	-33.20	AVG	


**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX E - 20 DB SPECTRUM BANDWIDTH**

Test Mode TX Mode\_315MHz

Frequency (MHz)	20 dB Bandwidth (MHz)	Limit (MHz)	Result
315	0.0370	0.7875	PASS




Date: 11.DEC.2023 17:32:16

## **APPENDIX F - TIMING TESTING**

Test Mode TX Mode\_315MHz

Frequency (MHz)	On Time (Sec)	Limit (Sec)
315	0.25	<5



Date: 11.DEC.2023 18:16:35

End of Test Report