



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

Dates of Tests: September 21 ,2023

Test Report S/N: LR500112311J

Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

2BEF2MINEE4BT

APPLICANT

melike inc.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	mineetimer
Manufacturer	:	melike inc.
Model name	:	minee 4(BT)
Variant Model name	:	-
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013
Frequency Range	:	2402 ~ 2480 MHz BLE
Max. Output Power	:	Max -17.30 dBm - Conducted
Data of issue	:	September 22 ,2023

This test report is issued under the authority of:

Ja-Beom.Koo

Ja-Beom Koo, Manager

The test was supervised by:

Eun-Hwan Jung

Eun-Hwan Jung, Test Engineer

TABLE OF CONTENTS

1. GENERAL INFORMATION -----	3
2. INFORMATION ABOUT TEST ITEM -----	4
3. TEST REPORT -----	5
3.1 SUMMARY OF TESTS -----	5
3.2 RF EXPOSURE EVALUATION-----	6

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2025-03-29	FCC CAB
VCCI	JAPAN	C-4948,	2026-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2026-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2026-10-15	VCCI registration
VCCI	JAPAN	G-847	2024-12-13	VCCI registration
IC	CANADA	5799A-1	2024-08-15	IC filing

2. Information about test item

2-1 Client & Manufacturer

Client Company name : melike inc.
 Address : 2nd floor, 7-14, Gangnamdae-ro 146-gil, Gangnam-gu, Seoul, Republic of Korea
 Tel / Fax : +82-10-3300-2488 / -

2-2 Equipment Under Test (EUT)

Model name : melike inc.
 Serial number : Identical prototype
 Date of receipt : September 12, 2023
 EUT condition : Pre-production, not damaged
 Antenna type : Chip Antenna (Max Gain : 0.5 dBi)
 Frequency Range : 2402 ~ 2480 MHz BLE
 RF output power : Max -17.30 dBm – Conducted
 Type of Modulation : GFSK
 Power Source : DC 3.7 V

2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
Frequency (MHz)	2402	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
§ 1.1310 and §2.1091	RF EXPOSURE EVULATION	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

3.2 RF EXPOSURE EVALUATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density (mW/cm ²)	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2\pi)$ $S = (0.02 * 1.12) / (4 * 20^2 * \pi)$ $S = 0.007 \text{ mW/cm}^2$	Where, $S = \text{Maximum power density (mW/cm}^2\text{)}$ $P = \text{Power input to the antenna (mW)}$ $G = \text{Numeric power gain of the antenna}$ $R = \text{Distance to the center of the radiation of the antenna}$ $(20 \text{ cm} = \text{limit for MPE})$
---	--

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 0.55 dBm \pm 0.5dB)

2.4GHz Mode

Max Peak output Power at antenna input terminal	-17.30	dBm
Max Peak output Power at antenna input terminal	0.019	mW
Prediction distance	20	cm
Prediction frequency	2480	MHz
Antenna Gain(typical)	0.5	dBi
Antenna Gain(numeric)	1.12	-

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance \leq 50 mm = **Used**

$[(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}]$

$= [0.19 / 5] * [\sqrt{2.480}] = 0.001 \leq 3.0$, for 1g SAR

Thus, SAR for this device is not required.