

TEST REPORT

Applicant Name: Shenzhen Neutop Optoelectronics Co., Ltd
Address: 502, BLDG 4, Pingshan minQi Technology Park, No. 65 Lishan Road, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen China
Report Number: 2501U29284E-RF-00C
FCC ID: 2BEGB-A01M21

Test Standard (s)
FCC PART 15.247

Sample Description

Product Type: Projector
Model No.: A01M21
Multiple Model(s) No.: A**M21 ("**" = 01-99 , indicates for different market or business purposes), D004
Trade Mark: Aurzen
Date Received: 2025-06-06
Issue Date: 2025-07-25

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Ekko Wu

Ekko Wu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked * is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.
This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
REQUIREMENTS AND TEST PROCEDURES	11
AC LINE CONDUCTED EMISSIONS.....	11
SPURIOUS EMISSIONS	13
6 DB EMISSION BANDWIDTH.....	16
MAXIMUM CONDUCTED OUTPUT POWER	18
100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	19
POWER SPECTRAL DENSITY	20
DUTY CYCLE.....	21
ANTENNA REQUIREMENT	22
TEST DATA AND RESULTS	23
AC LINE CONDUCTED EMISSIONS.....	23
SPURIOUS EMISSIONS	26
6dB EMISSION BANDWIDTH.....	119
99% OCCUPIED BANDWIDTH	125
MAXIMUM CONDUCTED OUTPUT POWER	131
POWER SPECTRAL DENSITY	134
100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	141
DUTY CYCLE.....	145
RF EXPOSURE EVALUATION	147
EUT PHOTOGRAPHS	149
TEST SETUP PHOTOGRAPHS	150

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501U29284E-RF-00C	Original Report	2025-07-25

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Projector
Tested Model	A01M21
Multiple Model(s)	A**M21 ("**"= 01-99 , indicates for different market or business purposes), D004
Frequency Range	2412~2462MHz
Maximum Conducted Output Peak Power	25.11dBm
Modulation Technique	DSSS, OFDM
Antenna Specification[#]	ANT0: 2.77dBi ANT1: 2.87dBi (provided by the applicant)
Voltage Range	DC 24V from adapter or DC 20V from USB Type-C Port
Sample serial number	348G-2 for Conducted and Radiated Emissions Test 348G-1 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Model: TEKA-EA2400375 Input: AC 100-240V~50/60Hz 2.0A MAX Output: DC 24.0V, 3.75A, 90.0W

Note:

1. The Multiple models are electrically identical with the test model except for model number and sales channel. Please refer to the declaration letter[#] for more detail, which was provided by manufacturer.
2. The EUT powered by adapter or USB Type-C Port, the worst case power supply adapter was selected to test for AC line conducted and radiated emission below 1GHz according to BT report test result.

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
Power Spectral Density		0.90dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.63dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4GHz Wi-Fi mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

802.11n-HT40 mode was tested with Channel 3, 6 and 9.

EUT Exercise Software

Exercise Software#		CMD		
Mode	Data rate	Power Level#		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	10	10	10
802.11g	6Mbps	10	10	10
802.11n20	MCS0	15	15	15
802.11n40	MCS0	12	12	12

Note:

1. The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the power and PSD across all data rates bandwidths, and modulations.
2. The device supports SISO in all modes, and MIMO 2T2R in 802.11n modes, per pretest, 2T2R mode was the worst mode and reported for 802.11n modes.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
GREATWALL	PC	NF50AL	Unknown
Redmi	Earphone	Unknown	Unknown
snom	Earphone	A100D	100D4342013597
SUOSHI	USB disk	S1256J	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Un-Detachable AC cable	1.2	Receptacle	AC Mains/LISN
Unshielded Detachable AC cable	0.5	Receptacle	Adapter
Unshielded Detachable AC cable	0.8	Receptacle	Adapter
Unshielded Un-detachable DC cable	1.0	Adapter	EUT
Unshielded Un-detachable Audio cable	1.5	EUT	Earphone
Shielded Detachable HDMI cable	2.0	EUT	PC

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions below 1GHz:




Diagram illustrating the experimental setup for the proposed method. The setup includes a Non-Conductive Table (80 cm above Ground Plane) and a Receptacle (1.0 Meter high). The EUT (Equipment Under Test) is connected to the Adapter, which is plugged into the Receptacle. The Adapter is connected to the AC Mains. The Receptacle is 150 cm above Ground Plane.

SUMMARY OF TEST RESULTS

Test Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
C63.10 §11.6	Duty Cycle	/

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2025/04/29	2026/04/28
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2025/04/29	2026/04/28
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2025/04/29	2026/04/28
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber Cable 1	F-03-EM236	2025/04/29	2026/04/28
Unknown	Cable	XH500C	J-10M-A	2025/04/29	2026/04/28
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2025/03/26	2026/03/25
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Filter Switch Unit	DT7220FSU	DS79906	2024/09/09	2025/09/08
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/04/29	2026/04/28
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV40-N	102259	2024/12/04	2025/12/03
ANRITSU	Microwave peak	MA24418A	12622	2025/04/29	2026/04/28
Unknown	10dB Attenuator	Unknown	F-03-EM065	2025/06/26	2026/06/25

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


REQUIREMENTS AND TEST PROCEDURES

AC Line Conducted Emissions

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{level} - \text{Limit} \\ \text{Level} &= \text{reading level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).


Spurious Emissions

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak

1-25GHz:**Pre-scan**

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	1 kHz	Peak
	<98%	1MHz	$\geq 1/T_{on}$	Peak

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	10 Hz	Peak
	<98%	1MHz	≥1/Ton	Peak

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The **Factor** is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

6 dB Emission Bandwidth

Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.8.1 & Clause 6.9.3

The steps for the first option are as follows:


- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “–6 dB down amplitude”. If a marker is below this “–6 dB down amplitude” value, then it shall be as close as possible to this value.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.

g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Maximum Conducted Output Power


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test method: ANSI C63.10-2020 clause 11.9.1.2 for peak power method or clause 11.9.2.3.2 for average power method.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

100 kHz Bandwidth of Frequency Band Edge

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.11.3


Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.

NOTE—the number of points can also be increased for large spans to retain frequency resolution

- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.



Power Spectral Density

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span > 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = No faster than coupled (auto) time.
- g) Trace mode = max-hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was added with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss


Duty Cycle

Test Procedure

According to ANSI C63.10-2020 Section 11.6

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has two internal antenna arrangement which were permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.

ANT	Antenna Type	Antenna Gain [#]	Impedance	Frequency Range
ANT0	FPC	2.77dBi	50Ω	2.4~2.5GHz
ANT1	FPC	2.87dBi	50Ω	2.4~2.5GHz

Result: Compliant


TEST DATA AND RESULTS

AC Line Conducted Emissions

Environmental Conditions

Temperature (°C)	25.4	Relative Humidity (%)	67
ATM Pressure (kPa)	100.0	Test engineer	Macy.shi
Test date	2025.7.4		
EUT operation mode	Transmitting (Maximum output power mode, 802.11n20 2462MHz)		

AC 120V 60 Hz, Line



Condition: Line


Project : 2501U29284E-RF

tester : Macy.shi Note: 2.4G WIFI Transmitting

Setting : RBW:9kHz

	Freq	Read Level	Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.195	12.29	33.16	10.68	10.19	53.80	-20.64	Average
2	0.195	23.03	43.90	10.68	10.19	63.80	-19.90	QP
3	0.315	10.90	31.69	10.60	10.19	49.84	-18.15	Average
4	0.315	21.40	42.19	10.60	10.19	59.84	-17.65	QP
5	0.491	20.05	40.73	10.50	10.18	46.14	-5.41	Average
6	0.491	21.47	42.15	10.50	10.18	56.14	-13.99	QP
7	1.147	19.53	40.41	10.70	10.18	46.00	-5.59	Average
8	1.147	20.87	41.75	10.70	10.18	56.00	-14.25	QP
9	3.454	11.15	32.35	10.94	10.26	46.00	-13.65	Average
10	3.454	13.20	34.40	10.94	10.26	56.00	-21.60	QP
11	20.270	20.05	41.28	10.98	10.25	50.00	-8.72	Average
12	20.270	25.11	46.34	10.98	10.25	60.00	-13.66	QP

AC 120V 60 Hz, Neutral



Condition: Neutral

Project : 2501U29284E-RF

tester : Macy.shi Note: 2.4G WIFI Transmitting

Setting : RBW: 9kHz


	Freq	Read Level	LISN Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.169	12.52	33.27	10.56	10.19	55.03	-21.76	Average
2	0.169	22.90	43.65	10.56	10.19	65.03	-21.38	QP
3	0.206	11.31	32.29	10.79	10.19	53.36	-21.07	Average
4	0.206	23.59	44.57	10.79	10.19	63.36	-18.79	QP
5	0.486	16.69	37.39	10.51	10.19	46.23	-8.84	Average
6	0.486	18.11	38.81	10.51	10.19	56.23	-17.42	QP
7	1.147	19.35	40.31	10.78	10.18	46.00	-5.69	Average
8	1.147	21.26	42.22	10.78	10.18	56.00	-13.78	QP
9	2.167	8.97	29.94	10.73	10.24	46.00	-16.06	Average
10	2.167	13.87	34.84	10.73	10.24	56.00	-21.16	QP
11	20.486	11.13	32.46	11.08	10.25	50.00	-17.54	Average
12	20.486	21.18	42.51	11.08	10.25	60.00	-17.49	QP

Spurious Emissions**Environmental Conditions**

Temperature (°C)	25.2&25.5	Relative Humidity (%)	50.1&52
ATM Pressure (kPa):	100.1&101.2	Test engineer:	Anson Su&Zenos Qiao
Test date:	2025.6.26&2025.7.5		
EUT operation mode:	Below 1GHz: Transmitting (Maximum output power mode, 802.11n20 2462MHz) Above 1GHz: Transmitting		
Note:	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. For the radiated spurious emission below 1GHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded. 3. After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.		

Below 1GHz:


9kHz-150kHz



Site : Chamber A
Condition : 3m
Project Number : 2501U29284E-RF
Test Mode : 2.4G WIFI Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.009	32.41	24.96	57.37	128.10	-70.73	Peak
2	0.018	30.76	23.16	53.92	122.44	-68.52	Peak
3	0.035	28.03	21.10	49.13	116.85	-67.72	Peak
4	0.056	25.83	38.66	64.49	112.69	-48.20	Peak
5	0.081	23.32	20.72	44.04	109.42	-65.38	Peak
6	0.111	21.35	33.30	54.65	106.69	-52.04	Peak


150kHz-30MHz



Site : Chamber A
Condition : 3m
Project Number : 2501U29284E-RF
Test Mode : 2.4G WIFI Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.216	15.14	40.86	56.00	100.90	-44.90	Peak
2	0.382	8.65	41.91	50.56	95.97	-45.41	Peak
3	0.606	5.10	43.14	48.24	71.92	-23.68	Peak
4	0.813	2.61	41.53	44.14	69.31	-25.17	Peak
5	1.153	0.77	43.20	43.97	66.21	-22.24	Peak
6	1.525	-0.27	38.20	37.93	63.73	-25.80	Peak


30MHz-1GHz_Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2501U29284E-RF
Test Mode : 2.4G WIFI Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	80.19	-17.92	51.05	33.13	40.00	-6.87	Peak
2	114.72	-12.18	47.95	35.77	43.50	-7.73	Peak
3	158.95	-12.72	52.01	39.29	43.50	-4.21	QP
4	275.76	-11.32	53.94	42.62	46.00	-3.38	QP
5	344.69	-10.30	49.32	39.02	46.00	-6.98	Peak
6	758.37	-2.71	41.90	39.19	46.00	-6.81	QP

30MHz-1GHz_Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2501U29284E-RF
Test Mode : 2.4G WIFI Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	56.72	-18.31	50.99	32.68	40.00	-7.32 QP
2	78.72	-17.88	53.24	35.36	40.00	-4.64 QP
3	84.52	-18.09	50.50	32.41	40.00	-7.59 QP
4	99.48	-16.05	52.67	36.62	43.50	-6.88 Peak
5	620.44	-4.84	44.40	39.56	46.00	-6.44 QP
6	758.37	-2.71	41.50	38.79	46.00	-7.21 QP

Above 1GHz:

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
ANT0 802.11b							
Low Channel							
4824	53.77	PK	H	-7.75	46.02	74	-27.98
4824	54.24	PK	V	-7.75	46.49	74	-27.51
Middle Channel							
4874	53.43	PK	H	-7.61	45.82	74	-28.18
4874	53.86	PK	V	-7.61	46.25	74	-27.75
High Channel							
4924	54.15	PK	H	-7.57	46.58	74	-27.42
4924	54.61	PK	V	-7.57	47.04	74	-26.96
ANT1 802.11b							
Low Channel							
4824	54.95	PK	H	-7.75	47.2	74	-26.8
4824	55.39	PK	V	-7.75	47.64	74	-26.36
Middle Channel							
4874	54.63	PK	H	-7.61	47.02	74	-26.98
4874	55.06	PK	V	-7.61	47.45	74	-26.55
High Channel							
4924	55.32	PK	H	-7.57	47.75	74	-26.25
4924	55.78	PK	V	-7.57	48.21	74	-25.79
ANT0 802.11g							
Low Channel							
4824	52.45	PK	H	-7.75	44.7	74	-29.3
4824	52.99	PK	V	-7.75	45.24	74	-28.76
Middle Channel							
4874	52.24	PK	H	-7.61	44.63	74	-29.37
4874	52.67	PK	V	-7.61	45.06	74	-28.94
High Channel							
4924	52.89	PK	H	-7.57	45.32	74	-28.68
4924	53.35	PK	V	-7.57	45.78	74	-28.22
ANT1 802.11g							
Low Channel							
4824	53.02	PK	H	-7.75	45.27	74	-28.73
4824	53.45	PK	V	-7.75	45.7	74	-28.3
Middle Channel							
4874	52.65	PK	H	-7.61	45.04	74	-28.96
4874	53.09	PK	V	-7.61	45.48	74	-28.52
High Channel							

4924	53.34	PK	H	-7.57	45.77	74	-28.23
4924	53.78	PK	V	-7.57	46.21	74	-27.79
802.11n20							
Low Channel							
4824	56.22	PK	H	-7.75	48.47	74	-25.53
4824	56.75	PK	V	-7.75	49	74	-25
Middle Channel							
4874	55.79	PK	H	-7.61	48.18	74	-25.82
4874	56.31	PK	V	-7.61	48.7	74	-25.3
High Channel							
4924	56.63	PK	H	-7.57	49.06	74	-24.94
4924	57.18	PK	V	-7.57	49.61	74	-24.39
802.11n40							
Low Channel							
4844	53.34	PK	H	-7.72	45.62	74	-28.38
4844	53.81	PK	V	-7.72	46.09	74	-27.91
Middle Channel							
4874	52.95	PK	H	-7.61	45.34	74	-28.66
4874	53.39	PK	V	-7.61	45.78	74	-28.22
High Channel							
4904	53.78	PK	H	-7.53	46.25	74	-27.75
4904	54.24	PK	V	-7.53	46.71	74	-27.29

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.

Test plots**Band Edge**


Left Band edge Horizontal Peak 2.4GWi-Fi b ANT0 2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant0-2412

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2386.108	-10.97	69.80	58.83	74.00	-15.17	Peak
2	2390.000	-10.98	62.66	51.68	74.00	-22.32	Peak


Left Band edge_Horizontal_Average_2.4GWi-Fi_b_ANT0_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant0-2412

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	2385.507	-10.97	61.62	50.65	54.00	-3.35	Average
2	2390.000	-10.98	51.61	40.63	54.00	-13.37	Average


Left Band edge_Vertical_Peak_2.4GWi-Fi_b_ANT0_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant0-2412

	Freq Factor		Read		Limit	Over	Remark
			Level	Level			
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2386.125	-10.97	68.12	57.15	74.00	-16.85	Peak
2	2390.000	-10.98	60.27	49.29	74.00	-24.71	Peak


Left Band edge_Vertical_Average_2.4GWi-Fi_b_ANT0_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant0-2412

	Freq Factor		Read Level		Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2386.645	-10.97	60.62	49.65	54.00	-4.35	Average
2	2390.000	-10.98	51.49	40.51	54.00	-13.49	Average


Right Band edge_Horizontal_Peak_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-b_ant0-2462

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	62.19	51.22	74.00	-22.78	Peak
2	2487.766	-10.98	67.70	56.72	74.00	-17.28	Peak


Right Band edge_Horizontal_Average_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant0-2462

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	53.48	42.51	54.00	-11.49	Average
2 2488.066	-10.98	60.02	49.04	54.00	-4.96	Average


Right Band edge_Vertical_Peak_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-b_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	62.21	51.24	74.00	-22.76 Peak
2	2488.321	-10.98	67.21	56.23	74.00	-17.77 Peak


Right Band edge_Vertical_Average_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant0-2462

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	2483.500	-10.97	50.35	39.38	54.00	-14.62	Average
2	2487.668	-10.98	54.12	43.14	54.00	-10.86	Average


Left Band edge_Horizontal_Peak_2.4GWi-Fi_b_ANT1_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2412

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2385.263	-10.97	66.40	55.43	74.00	-18.57 Peak
2	2390.000	-10.98	60.64	49.66	74.00	-24.34 Peak


Left Band edge_Horizontal_Average_2.4GWi-Fi_b_ANT1_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant1-2412

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2385.588	-10.97	58.95	47.98	54.00	-6.02	Average
2 2390.000	-10.98	51.12	40.14	54.00	-13.86	Average


Left Band edge_Vertical_Peak_2.4GWi-Fi_b_ANT1_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2412

	Freq Factor		Read		Limit	Over	Remark
			Level	Level			
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2386.076	-10.97	67.13	56.16	74.00	-17.84	Peak
2	2390.000	-10.98	60.18	49.20	74.00	-24.80	Peak


Left Band edge_Vertical_Average_2.4GWi-Fi_b_ANT1_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant1-2412

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2385.540	-10.97	59.43	48.46	54.00	-5.54 Average
2	2390.000	-10.98	50.94	39.96	54.00	-14.04 Average


Right Band edge_Horizontal_Peak_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.68	50.71	74.00	-23.29	Peak
2	2488.194	-10.98	66.58	55.60	74.00	-18.40	Peak


Right Band edge_Horizontal_Average_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	52.67	41.70	54.00	-12.30 Average
2	2487.301	-10.97	57.87	46.90	54.00	-7.10 Average


Right Band edge_Vertical_Peak_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-b_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.33	50.36	74.00	-23.64 Peak
2	2486.063	-10.97	65.17	54.20	74.00	-19.80 Peak


Right Band edge_Vertical_Average_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:10Hz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	51.63	40.66	54.00	-13.34	Average
2 2488.073	-10.98	56.07	45.09	54.00	-8.91	Average


Left Band edge_Horizontal_Peak_2.4GWi-Fi_g_ANT0_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2412

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.547	-10.98	75.70	64.72	74.00	-9.28	Peak
2	2390.000	-10.98	75.25	64.27	74.00	-9.73	Peak


Left Band edge_Horizontal_Average_2.4GWi-Fi_g_ANT0_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2412

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	-10.98	61.73	50.75	54.00	-3.25 Average
2	2390.000	-10.98	61.56	50.58	54.00	-3.42 Average


Left Band edge_Vertical_Peak_2.4GWi-Fi_g_ANT0_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2412

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.127	-10.98	73.50	62.52	74.00	-11.48	Peak
2	2390.000	-10.98	72.03	61.05	74.00	-12.95	Peak


Left Band edge_Vertical_Average_2.4GWi-Fi_g_ANT0_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2412

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.688	-10.98	61.39	50.41	54.00	-3.59	Average
2	2390.000	-10.98	60.78	49.80	54.00	-4.20	Average


Right Band edge_Horizontal_Peak_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	73.60	62.63	74.00	-11.37 Peak
2	2483.723	-10.97	75.09	64.12	74.00	-9.88 Peak


Right Band edge_Horizontal_Average_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.35	50.38	54.00	-3.62	Average
2	2483.557	-10.97	61.67	50.70	54.00	-3.30	Average


Right Band edge_Vertical_Peak_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	68.16	57.19	74.00	-16.81	Peak
2 2483.679	-10.97	68.56	57.59	74.00	-16.41	Peak


Right Band edge_Vertical_Average_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	55.68	44.71	54.00	-9.29	Average
2 2483.548	-10.97	55.82	44.85	54.00	-9.15	Average


Left Band edge_Horizontal_Peak_2.4GWi-Fi_g_ANT1_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2412

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.390	-10.98	71.18	60.20	74.00	-13.80 Peak
2	2390.000	-10.98	69.31	58.33	74.00	-15.67 Peak


Left Band edge_Horizontal_Average_2.4GWi-Fi_g_ANT1_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2412

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.863	-10.98	59.52	48.54	54.00	-5.46 Average
2	2390.000	-10.98	59.41	48.43	54.00	-5.57 Average


Left Band edge_Vertical_Peak_2.4GWi-Fi_g_ANT1_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2412

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.880	-10.98	73.25	62.27	74.00	-11.73	Peak
2	2390.000	-10.98	71.81	60.83	74.00	-13.17	Peak


Left Band edge_Vertical_Average_2.4GWi-Fi_g_ANT1_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2412

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.985	-10.98	60.63	49.65	54.00	-4.35 Average
2	2390.000	-10.98	60.52	49.54	54.00	-4.46 Average


Right Band edge_Horizontal_Peak_2.4GWi-Fi_g_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2462

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 2483.500	-10.97	72.31	61.34	74.00	-12.66 Peak
2 2485.508	-10.97	72.57	61.60	74.00	-12.40 Peak


Right Band edge_Horizontal_Average_2.4GWi-Fi_g_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2462

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	59.22	48.25	54.00	-5.75 Average
2	2483.627	-10.97	59.48	48.51	54.00	-5.49 Average


Right Band edge_Vertical_Peak_2.4GWi-Fi_g_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2462

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	69.21	58.24	74.00	-15.76	Peak
2	2483.968	-10.97	69.70	58.73	74.00	-15.27	Peak


Right Band edge_Vertical_Average_2.4GWi-Fi_g_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	57.16	46.19	54.00	-7.81 Average
2	2483.837	-10.97	57.36	46.39	54.00	-7.61 Average


Left Band edge_Horizontal_Peak_2.4GWi-Fi_n20_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-n20-2412

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.040	-10.98	77.43	66.45	74.00	-7.55 Peak
2	2390.000	-10.98	74.05	63.07	74.00	-10.93 Peak


Left Band edge_Horizontal_Average_2.4GWi-Fi_n20_2412MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWi-Fi-n20-2412

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.110	-10.98	60.55	49.57	54.00	-4.43 Average
2	2390.000	-10.98	60.04	49.06	54.00	-4.94 Average


Left Band edge_Vertical_Peak_2.4GWi-Fi_n20_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-n20-2412

	Freq Factor		Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.758	-10.98	77.49	66.51	74.00	-7.49	Peak
2	2390.000	-10.98	74.40	63.42	74.00	-10.58	Peak


Left Band edge_Vertical_Average_2.4GWi-Fi_n20_2412MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-n20-2412

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.635	-10.98	60.60	49.62	54.00	-4.38 Average
2	2390.000	-10.98	60.12	49.14	54.00	-4.86 Average


Right Band edge_Horizontal_Peak_2.4GWi-Fi_n20_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-n20-2462

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	74.64	63.67	74.00	-10.33	Peak
2 2483.600	-10.97	78.26	67.29	74.00	-6.71	Peak


Right Band edge_Horizontal_Average_2.4GWi-Fi_n20_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-n20-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.21	50.24	54.00	-3.76 Average
2	2483.515	-10.97	61.45	50.48	54.00	-3.52 Average


Right Band edge_Vertical_Peak_2.4GWi-Fi_n20_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-n20-2462

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	70.59	59.62	74.00	-14.38	Peak
2 2485.429	-10.97	71.63	60.66	74.00	-13.34	Peak


Right Band edge_Vertical_Average_2.4GWi-Fi_n20_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-n20-2462

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	57.78	46.81	54.00	-7.19	Average
2	2483.504	-10.97	57.91	46.94	54.00	-7.06	Average


Left Band edge_Horizontal_Peak_2.4GWi-Fi_n40_2422MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-n40-2422

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2388.910	-10.98	73.08	62.10	74.00	-11.90	Peak
2 2390.000	-10.98	71.06	60.08	74.00	-13.92	Peak


Left Band edge_Horizontal_Average_2.4GWi-Fi_n40_2422MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak
Note : 2.4GWiFi-n40-2422

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.950	-10.98	60.57	49.59	54.00	-4.41 Average
2	2390.000	-10.98	60.46	49.48	54.00	-4.52 Average


Left Band edge_Vertical_Peak_2.4GWi-Fi_n40_2422MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-n40-2422

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.070	-10.98	73.26	62.28	74.00	-11.72 Peak
2	2390.000	-10.98	71.62	60.64	74.00	-13.36 Peak


Left Band edge_Vertical_Average_2.4GWi-Fi_n40_2422MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak
Note : 2.4GWiFi-n40-2422

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.990	-10.98	59.24	48.26	54.00	-5.74 Average
2	2390.000	-10.98	59.17	48.19	54.00	-5.81 Average


Right Band edge_Horizontal_Peak_2.4GWi-Fi_n40_2452MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-n40-2452

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	72.05	61.08	74.00	-12.92	Peak
2 2484.113	-10.97	76.25	65.28	74.00	-8.72	Peak


Right Band edge_Horizontal_Average_2.4GWi-Fi_n40_2452MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak
Note : 2.4GWiFi-n40-2452

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	60.88	49.91	54.00	-4.09	Average
2 2483.978	-10.97	61.87	50.90	54.00	-3.10	Average


Right Band edge_Vertical_Peak_2.4GWi-Fi_n40_2452MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-n40-2452

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	66.87	55.90	74.00	-18.10	Peak
2 2484.124	-10.97	71.89	60.92	74.00	-13.08	Peak

Right Band edge_Vertical_Average_2.4GWi-Fi_n40_2452MHz




Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak
Note : 2.4GWiFi-n40-2452

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	57.48	46.51	54.00	-7.49 Average
2	2484.135	-10.97	58.46	47.49	54.00	-6.51 Average

1-18GHz (Listed with the worst harmonic margin test plot)


1-4GHz Horizontal 2.4GWi-Fi b ANT0 2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant0-2462

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 3670.334	-9.66	57.27	47.61	74.00	-26.39	Peak


1-4GHz_Vertical_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant0-2462

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3971.121	-9.29	56.26	46.97	74.00	-27.03 Peak


4-18GHz_Horizontal_Peak_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant0-2462

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-7.57	54.15	46.58	74.00	-27.42	Peak
2	17812.730	11.08	49.06	60.14	74.00	-13.86	Peak


4-18GHz_Horizontal_Average_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-b_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17989.500	13.16	33.95	47.11	54.00	-6.89	Average


4-18GHz_Vertical_Peak_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant0-2462

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4924.000	-7.57	54.61	47.04	74.00	-26.96	Peak
2 17993.000	13.17	47.41	60.58	74.00	-13.42	Peak


4-18GHz_Vertical_Average_2.4GWi-Fi_b_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWi-Fi-b_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17996.500	13.19	33.83	47.02	54.00	-6.98	Average


1-4GHz_Horizontal_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3648.206	-9.79	56.89	47.10	74.00	-26.90 Peak


1-4GHz_Vertical_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3643.706	-9.83	56.23	46.40	74.00	-27.60 Peak


4-18GHz_Horizontal_Peak_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 4924.000	-7.57	55.32	47.75	74.00	-26.25 Peak
2 17928.240	12.85	47.55	60.40	74.00	-13.60 Peak


4-18GHz_Horizontal_Average_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.20	33.79	46.99	54.00	-7.01	Average


4-18GHz_Vertical_Peak_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-b_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4924.000	-7.57	55.78	48.21	74.00	-25.79	Peak
2 17980.750	13.11	48.46	61.57	74.00	-12.43	Peak


4-18GHz_Vertical_Average_2.4GWi-Fi_b_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWi-Fi-b_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17993.000	13.17	33.74	46.91	54.00	-7.09	Average


1-4GHz_Horizontal_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3934.367	-9.48	56.18	46.70	74.00	-27.30 Peak


1-4GHz_Vertical_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Vertical
 Project No. : 2501U29284E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 3973.747	-9.28	55.40	46.12	74.00	-27.88	Peak


4-18GHz_Horizontal_Peak_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4924.000	-7.57	52.89	45.32	74.00	-28.68	Peak
2 17979.000	13.09	47.45	60.54	74.00	-13.46	Peak


4-18GHz_Horizontal_Average_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWi-Fi-g_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.250	13.19	33.79	46.98	54.00	-7.02	Average


4-18GHz_Vertical_Peak_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4924.000	-7.57	53.35	45.78	74.00	-28.22	Peak
2 17996.500	13.19	47.43	60.62	74.00	-13.38	Peak


4-18GHz_Vertical_Average_2.4GWi-Fi_g_ANT0_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 2.4GWiFi-g_ant0-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.20	33.75	46.95	54.00	-7.05	Average


1-4GHz_Horizontal_2.4GWi-Fi_g_ANT1_2462MHz



Condition : Horizontal
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWi-Fi-g_ant1-2462

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3663.583	-9.70	55.79	46.09	74.00	-27.91 Peak

1-4GHz_Vertical_2.4GWi-Fi_g_ANT1_2462MHz



Condition : Vertical
Project No. : 2501U29284E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4GWiFi-g_ant1-2462

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3928.741	-9.55	55.51	45.96	74.00	-28.04 Peak