

FCC PART 15E TEST REPORT FOR CERTIFICATION On Behalf of

TCL OVERSEAS MARKETING LTD

5.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer

Model Number: Q75H

Additional Model: Q70H, Q78H, Q79H, Q75HE, Q75HK, Q7****, Q75H-S, Q70H-S, Q78H-S, Q79H-S, Q75H-J, Q70H-J, Q78H-J, Q79H-J, Q75H-CA, Q70H-CA, Q78H-CA, Q79H-CA, R50C, R55C, R58C, R50D, R55D, R58D, R5*** (*can be any numerica number"0~9" or alphebtical number "A~Z")

FCC ID: 2BEHEQ75H



Applicant :	TCL OVERSEAS MARKETING LTD
Address:	5/F, Building 22E, 22 Science Park East Avenue HongKong
	Science Park Shatin Hong Kong
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2405224
Date of Test:	Apr. 15, 2024~ May. 15, 2024
Date of Report:	May. 21, 2024

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT).....	5
1.2. The antenna information for EUT.....	7
1.3. Information of RF Cable.....	7
2. SUMMARY OF TEST.....	8
2.1. Summary of test result.....	8
2.2. Test Facilities.....	9
2.3. Measurement uncertainty for EST Technology Co., Ltd.....	10
2.4. Assistant equipment used for test.....	10
2.5. Block Diagram.....	10
2.6. Test Mode.....	11
2.7. Channel List.....	13
2.8. Power Setting of Test Software.....	14
2.9. Duty Cycle of Test Signal.....	15
2.10. Test Equipment List.....	16
3. 6dB BANDWIDTH & 26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH.....	18
3.1. Limit.....	18
3.2. Test Setup.....	18
3.3. Spectrum Analyzer Setting.....	18
3.4. Test Procedure.....	19
3.5. Test Result.....	19
4. MAXIMUM CONDUCTED OUTPUT POWER.....	20
4.1. Limit.....	20
4.2. Test Setup.....	20
4.3. Spectrum Analyzer Setting.....	20
4.4. Test Procedure.....	20
4.5. Test Result.....	21
5. PEAK POWER SPECTRAL DENSITY.....	22
5.1. Limit.....	22
5.2. Test Setup.....	22
5.3. Spectrum Analyzer Setting.....	22
5.4. Test Procedure.....	22
5.5. Test Result.....	22
6. UNWANTED EMISSIONS AND BAND EDGE.....	23
6.1. Limit.....	23
6.2. Test Setup.....	24
6.3. Spectrum Analyzer Setting.....	25
6.4. Test Procedure.....	26
6.5. Test Result.....	27
7. FREQUENCY STABILITY.....	62
7.1. Limit.....	62

7.2. Test Setup.....	62
7.3. Spectrum Analyzer Setting.....	62
7.4. Test Procedure.....	63
7.5. Test Result.....	63
8. AC POWER LINE CONDUCTED EMISSIONS	64
8.1. Limit.....	64
8.2. Test Setup.....	64
8.3. Spectrum Analyzer Setting.....	64
8.4. Test Procedure.....	64
8.5. Test Result.....	65
9. ANTENNA REQUIREMENTS.....	67
9.1. Limit.....	67
9.2. Test Result.....	67
10. APPENDIX	68
11. TEST SETUP PHOTO.....	306
12. EUT PHOTO.....	308

Applicant:	TCL OVERSEAS MARKETING LTD		
Address:	5/F, Building 22E, 22 Science Park East Avenue HongKong Science Park Shatin Hong Kong		
Manufacturer:	TCL OVERSEAS MARKETING LTD		
Address:	5/F, Building 22E, 22 Science Park East Avenue HongKong Science Park Shatin Hong Kong		
Factory:	Tonly Technology Co., Ltd. Tongqiao Factory		
Address:	A&B Building, NO. 88, North Of Luen Fat Road, Tongqiao Industrial Base, Zhongkai High-tech Development Zone, Huizhou City, Guangdong Province, P.R.China		
E.U.T:	5.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer		
Model Number:	Q75H		
Additional Model:	Q70H, Q78H, Q79H, Q75HE, Q75HK, Q7****, Q75H-S, Q70H-S, Q78H-S, Q79H-S, Q75H-J, Q70H-J, Q78H-J, Q79H-J, Q75H-CA, Q70H-CA, Q78H-CA, Q79H-CA, R50C, R55C, R58C, R50D, R55D, R58D, R5*** (*can be any numerica number"0~9" or alphebtical number "A~Z") Note: They are identical except model name.		
Power Supply:	AC 100-240V, 50/60Hz		
Trade Name:	TCL, FFALCON	Serial No.:	-----
Date of Receipt:	Apr. 15, 2024	Date of Test:	Apr. 15, 2024~ May. 15, 2024
Test Specification:	FCC Part 15 Subpart E 15.407 ANSI C63.10:2013 FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 FCC KDB 662911 D01 Multiple Transmitter Output v02r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart E requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd. Date: May 21, 2024		
Prepared by:	 Ring Yang / Assistant	Reviewed by:	 Seven Wang / Engineer
		Approved by:	 Iceman Hu / Manager
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1.GENERAL INFORMATION

1.1.Description of Device (EUT)

FCC ID	:	2BEHEQ75H
Product Name	:	5.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer
Model Number	:	Q75H
Software Version	:	V06
Hardware Version	:	V02
Operation frequency	:	U-NII-1: 5150 MHz~5250 MHz U-NII-2A: 5250 MHz~5350 MHz U-NII-2C: 5470 MHz~5725 MHz U-NII-3: 5725 MHz~5850 MHz
Number of channel	:	U-NII-1: IEEE 802.11a / n HT20 / ac VHT20: 4 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel. U-NII-2A: IEEE 802.11a / n HT20 / ac VHT20: 4 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel. U-NII-2C: IEEE 802.11a / n HT20 / ac VHT20: 11 Channels; IEEE 802.11n HT40 / ac VHT40: 5 Channels; IEEE 802.11ac VHT80: 2 Channel. U-NII-3: IEEE 802.11a / n HT20 / ac VHT20: 5 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel.
Modulation	:	OFDM
Transmit Data Rate	:	IEEE 802.11a: 54, 48, 36, 24, 18, 12, 9, 6Mbps; IEEE 802.11n: up 300Mbps IEEE 802.11ac: up to 867Mbps
Channels Spacing	:	IEEE 802.11a: 20MHz; IEEE 802.11n HT20: 20MHz; IEEE 802.11n HT40: 40MHz; IEEE 802.11ac VHT20: 20MHz; IEEE 802.11ac VHT40: 40MHz; IEEE 802.11ac VHT80: 80MHz;

Transmit Power	:	U-NII-1	IEEE 802.11a: 12.13dBm IEEE 802.11n HT20: 13.31dBm IEEE 802.11n HT40: 15.12dBm IEEE 802.11ac VHT20: 12.87dBm IEEE 802.11ac VHT40: 15.19dBm IEEE 802.11ac VHT80: 14.67dBm
		U-NII-2A	IEEE 802.11a: 10.38dBm IEEE 802.11n HT20: 10.83dBm IEEE 802.11n HT40: 12.82dBm IEEE 802.11ac VHT20: 10.59dBm IEEE 802.11ac VHT40: 12.53dBm IEEE 802.11ac VHT80: 14.32dBm
		U-NII-2C	IEEE 802.11a: 10.61dBm IEEE 802.11n HT20: 11.26dBm IEEE 802.11n HT40: 12.82dBm IEEE 802.11ac VHT20: 11.25dBm IEEE 802.11ac VHT40: 13.05dBm IEEE 802.11ac VHT80: 14.58dBm
		U-NII-3	IEEE 802.11a: 10.67dBm IEEE 802.11n HT20: 11.30dBm IEEE 802.11n HT40: 12.94dBm IEEE 802.11ac VHT20: 11.47dBm IEEE 802.11ac VHT40: 13.27dBm IEEE 802.11ac VHT80: 14.68dBm
Sample Type	:	Prototype production	

Note: For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.2.The antenna information for EUT

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Internal	-	4.4
2	-	-	Internal	-	4.1

Remark:

- (1) After pre-test all antenna configurations,the worst case configuration as list below.
- (2) The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
- (3) The test results of this report only apply to the sample as received.

ANT No. TX Mode	SISO Configuration	MIMO Configuration
IEEE 802.11a	ANT 1 and ANT 2	/
IEEE 802.11n HT20	/	ANT1+ANT2
IEEE 802.11n HT40	/	ANT1+ANT2
IEEE 802.11ac VHT20	/	ANT1+ANT2
IEEE 802.11ac VHT40	/	ANT1+ANT2
IEEE 802.11ac VHT80	/	ANT1+ANT2

1.3.Information of RF Cable

Cable Loss(dB)	Provided by
1.0	TCL OVERSEAS MARKETING LTD

Note:

- 1.The customer declared the loss value of the RF Cable. and the test results of thisreport only apply to the sample as received.
- 2.The laboratory is not responsible for the accuracy of the cable loss.

2.SUMMARY OF TEST

2.1.Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	6dB Bandwidth & 26dB Bandwidth & 99% Occupied Bandwidth	15.407(a) 15.407(e)	PASS
2	Maximum Conducted Output Power	15.407(a)	PASS
3	Peak Power Spectral Density	15.407(a)	PASS
4	Unwanted Emissions and Band Edge	15.205 15.209 15.407(b)	PASS
5	Frequency Stability	15.407(g)	PASS
6	AC Power Line Conducted Emissions	15.207 15.407(b)(9)	PASS
7	Antenna Requirement	15.203	PASS

Note:"N/A" denotes test is not applicable in this test report.

2.2.Test Facilities

EMC Lab : Accredited by CNAS, CHINA
Registration No.: L5288
This Accreditation is valid until: November 12, 2029

Recognized by FCC, USA
Designation Number: CN1215
This Recognition is valid until: January 31, 2026

Accredited by A2LA, USA
Registration No.: 4366.01
This Accreditation is valid until: January 31, 2026

Recognized by Industry Canada
CAB identifier No.: CN0035
This Recognition is valid until: January 31, 2026

Recognized by VCCI, Japan
Registration No.:C-14103; T-20073; R-13663;
R-20103; G-20097
Date of registration: Apr. 20, 2020
This Recognition is valid until: Apr. 19, 2026

Recognized by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Recognized by Intertek
Registration No.: 2011-RTL-L2-64
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
Guangdong, China

2.3.Measurement uncertainty for EST Technology Co., Ltd.

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.54dB
Uncertainty for spurious emissions test (Below 30MHz)	±1.62 dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.62
Uncertainty for Radiation Emission test (1GHz to 18GHz)	4.86
Uncertainty for spurious emissions test (18GHz to 40GHz)	4.67
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	1.08dB
Uncertainty for Power density test	0.26dB
Temperature	±0.6°C
Humidity	±4.0 %
Volatage DC	±1.0%
Volatage (AC, <10KHz)	±1.5%

Note: This uncertainty represents an expanded uncertainty expressed at approximately The 95% confidence level using a coverage factor of k=2.


2.4.Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.5m	AC Cable

2.5.Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground.



(EUT: 5.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer)

2.6.Test Mode

Pre-scan has been combined all possible modulations and data rates to determine the worst case test mode,the worst case test mode was selected for the final test as listed below.

Test Item	Test Mode	Channel	Modulation	Data rate
6dB Bandwidth	IEEE 802.11a	149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	151/159	OFDM	MCS0
	IEEE 802.11ac VHT80	155	OFDM	MCS0
26dB Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/118/134	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122	OFDM	MCS0
99% Occupied Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140/ 149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/ 149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/ 149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/118/134/151/ 159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0
Maximum Conducted Output Power	IEEE 802.11a	36/40/48/52/60/64/100/116/140/ 149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/ 149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/ 149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/118/134/151/ 159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0

Peak Power Spectral Density	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/118/134/151/ 159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0
Unwanted Emissions and Band Edge(Above 1GHz)	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/118/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/118/134/151/ 159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0
Unwanted Emissions Below 1GHz	IEEE 802.11a	100	OFDM	6Mbps
Frequency Stability	Unmodulation	36/64/100/149	N/A	N/A
AC Power Line Conducted Emissions	IEEE 802.11a	100	OFDM	6Mbps

Note: In radiated measurement,the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7.Channel List

Band	Mode	Channel	Frequency (MHz)
U-NII-1	IEEE 802.11a & n HT20 & ac VHT20	36	5180
		40	5200
		44	5220
		48	5240
	IEEE 802.11n HT40 & ac VHT40	38	5190
		46	5230
	IEEE 802.11ac VHT80	42	5210
U-NII-2A	IEEE 802.11a & n HT20 & ac VHT20	52	5260
		56	5280
		60	5300
		64	5320
	IEEE 802.11n HT40 & ac VHT40	54	5270
		62	5310
	IEEE 802.11ac VHT80	58	5290
U-NII-2C	IEEE 802.11a & n HT20 & ac VHT20	100	5500
		104	5520
		108	5540
		112	5560
		116	5580
		120	5600
		124	5620
		128	5640
		132	5660
		136	5680
		140	5700
	IEEE 802.11n HT40 & ac VHT40	102	5510
		110	5550
		118	5590
		126	5630
		134	5670
	IEEE 802.11ac VHT80	106	5530
		122	5610
U-NII-3	IEEE 802.11a & n HT20 & ac VHT20	149	5745
		153	5765
		157	5785
		161	5805
		165	5825
	IEEE 802.11n HT40 & ac VHT40	151	5755
		159	5795
	IEEE 802.11ac VHT80	155	5775

2.8.Power Setting of Test Software

Software Name	CMD		
U-NII-1			
Frequency(MHz)	5180	5200	5240
IEEE 802.11a Setting	12,12	12,12	12,12
IEEE 802.11n HT20 Setting	10,10	10,10	10,10
IEEE 802.11ac VHT20 Setting	10,10	10,10	10,10
Frequency(MHz)	5190	5230	
IEEE 802.11n HT40 Setting	12,12	12,12	
IEEE 802.11ac VHT40 Setting	12,12	12,12	
Frequency(MHz)	5210		
IEEE 802.11ac VHT80 Setting	14,14		
U-NII-2A			
Frequency(MHz)	5260	5300	5320
IEEE 802.11a Setting	10.5,10.5	10.5,10.5	10.5,10.5
IEEE 802.11n HT20 Setting	8,8	8,8	8,8
IEEE 802.11ac VHT20 Setting	8,8	8,8	8,8
Frequency(MHz)	5270	5310	
IEEE 802.11n HT40 Setting	10,10	10,10	
IEEE 802.11ac VHT40 Setting	9.5,9.5	9.5,9.5	
Frequency(MHz)	5290		
IEEE 802.11ac VHT80 Setting	13.5,13.5		
U-NII-2C			
Frequency(MHz)	5500	5580	5700
IEEE 802.11a Setting	10,10	10,10	10,10
IEEE 802.11n HT20 Setting	8,8	8,8	7.5,7.5
IEEE 802.11ac VHT20 Setting	7.5,7.5	7.5,7.5	7.5,7.5
Frequency(MHz)	5510	5590	5670
IEEE 802.11n HT40 Setting	9.5,9.5	9.5,9.5	9.5,9.5
IEEE 802.11ac VHT40 Setting	9.5,9.5	9.5,9.5	9.5,9.5
Frequency(MHz)	5530	5610	
IEEE 802.11ac VHT80 Setting	13.5,13.5	13.5,13.5	
U-NII-3			
Frequency(MHz)	5745	5785	5825
IEEE 802.11a Setting	10,10	10,10	10,10
IEEE 802.11n HT20 Setting	7.5,7.5	7.5,7.5	7.5,7.5
IEEE 802.11ac VHT20 Setting	7.5,7.5	7.5,7.5	7.5,7.5
Frequency(MHz)	5755	5795	
IEEE 802.11n HT40 Setting	9.5,9.5	9.5,9.5	
IEEE 802.11ac VHT40 Setting	9.5,9.5	9.5,9.5	
Frequency(MHz)	5775		
IEEE 802.11ac VHT80 Setting	13.5,13.5		

Note: This information is provided by the applicant.

2.9.Duty Cycle of Test Signal

Refer to section 10: Appendix B

Note:

1. Duty Cycle=On Time/Total Time×100%.
2. Duty Factor=10×LOG(1/Duty Cycle).
3. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
4. If duty cycle≥98 %,the EUT is consider to be transmitting continuously,the conducted average output power and average power spectral density no need to add duty factor.
5. The on-time time is transmission duration(T).
6. The VBW Setting is use for RMS measurement in Unwanted Emissions and Band Edge(Above 1GHz) Test.

2.10. Test Equipment List

For AC power conducted emissions test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	EST-E001	LISAI	June 12,23	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E002	LISAI	June 12,23	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 12,23	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emissions test(9KHz-30MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 12,23	1 Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	EST-E054	LISAI	June 12,23	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	N/A	EST-001	N/A	N/A	N/A	N/A

For radiated emissions test(30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 12,23	1 Year
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 12,23	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZBECK	BBHA9120D	EST-E144	LISAI	June 12,23	1 Year
Horn Antenna	Com-Power	AHA-840	EST-E133	LISAI	June 12,23	1 Year
Low Noise Amplifier	RF	TRLA-010180 G45N	EST-E142	LISAI	June 12,23	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	EST-E069	LISAI	June 12,23	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

For connect EUT antenna terminal test


Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
TS 1120	Tonscend	/	/	/	/	/
Test Software	Tonscend	TS1120-3	3.3.38	/	/	/
RF Control Unit	Tonscend	JS0806-2	EST-E134	LISAI	June 12,23	1 Year
Signal and Spectrum Analyzer	Keysight	N9010B	EST-E141	LISAI	June 12,23	1 Year

3.6dB BANDWIDTH & 26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH

3.1.Limit

Band	Frequency (MHz)	Test Item	Limit
U-NII-1	5150-5250	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2A	5250-5350	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2C	5470-5725	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-3	5725-5850	6dB Bandwidth&99% Occupied Bandwidth	6dB Bandwidth≥500KHz

3.2.Test Setup



3.3.Spectrum Analyzer Setting

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

26dB Bandwidth	
Spectrum Parameters	Setting
RBW	approximately 1% of the emission bandwidth
VBW	>RBW
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth	
Spectrum Parameters	Setting
RBW	1% to 5% of the OBW
VBW	approximately three times the RBW
Span	between 1.5 times and 5.0 times the OBW
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4.Test Procedure

For 26dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is 26 dB down from the peak of the emission.Compare this with the RBW setting of the instrument.
Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 6dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 99% Occupied Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the 99% power bandwidth function to measure bandwidth.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

3.5.Test Result

Refer to section 10: Appendix A1/A2/A3


4. MAXIMUM CONDUCTED OUTPUT POWER

4.1. Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	1W(30dBm) (Max. e.i.r.p $\leq$ 125mW at any elevation angle above 30 degrees as measured from the horizon)
	Indoor Access Point	1W(30dBm)
	Fixed point-to-point Access Point	1W(30dBm)
	Mobile and Portable Client Device	250mW(23.98dBm)
U-NII-2A	All Device	250mW(23.98dBm) or 11dBm+10 log B, Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-2C	All Device	250mW(23.98dBm) or 11dBm+10 log B, Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-3	All Device	1W(30dBm)

Note: For the Band U-NII-2A and U-NII-2C, the maximum conducted output power limit calculate result refer to section 3.5.

4.2. Test Setup



4.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz
VBW	3MHz
Span	40MHz(20MHz Bandwidth mode) 80MHz(40MHz Bandwidth mode) 160MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	RMS
Trace Mode	Max Hold

4.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 4.3.
- Set the EUT transmit continuously with maximum output power.
- Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.

- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report.

4.5.Test Result


Refer to section 10: Appendix C

5. PEAK POWER SPECTRAL DENSITY

5.1. Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	17dBm/MHz
	Indoor Access Point	17dBm/MHz
	Fixed point-to-point Access Point	17dBm/MHz
	Mobile and Portable Client Device	11dBm/MHz
U-NII-2A	All Device	11dBm/MHz
U-NII-2C	All Device	11dBm/MHz
U-NII-3	All Device	30dBm/500KHz

5.2. Test Setup



5.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz(For U-NII-1&U-NII-2A&U-NII-2C) 500KHz(For U-NII-3)
VBW	3MHz(For U-NII-1&U-NII-2A&U-NII-2C) 2MHz(For U-NII-3)
Span	encompass the entire 26 dB EBW or 99% OBW of the signal
Sweep Time	Auto
Number of Sweep Point	$\geq 2 \times \text{SPAN} / \text{RBW}$
Detector	RMS(power averaging)
Trace Average	≥ 100 traces

5.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 5.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker-to-peak function to set the marker to the average of the emission.
- If the duty cycle of test signal $< 98\%$, the result = max measured value + $10 \times \log(1/\text{duty cycle})$;
If the duty cycle of test signal $\geq 98\%$, the result = max measured value.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

5.5. Test Result

Refer to section 10: Appendix D

6.UNWANTED EMISSIONS AND BAND EDGE

6.1.Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The unwanted emissions which fall in Restricted bands shall not exceed the field strength levels specified in the following table:

15.209 Radiated emission limits

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


Note:

1. $\text{dB}\mu\text{V/m} = 20\text{Log}(\mu\text{V/m})$
2. Above 1GHz the formula is used to convert the EIRP to field strength


$$E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{m}]) + 104.77$$
 where E is field strength and d is distance at which the field strength limit is specified in the applicable requirements.
 for example, 3m field strength($\text{dB}\mu\text{V/m}$)= $\text{EIRP}-20\log(3)+104.77=\text{EIRP}+95.2$

6.2.Test Setup


9kHz~30MHz



30~1000MHz



Above 1GHz



6.3.Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

Note : For 9KHz-90KHz&110KHz-150KHz,the detector is average,other frequency is CISPR QP detector.

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

Note : For 150KHz-490KHz,the detector is average,other frequency is CISPR QP detector.

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	AVG Measurement
	3MHz	Duty cycle≥98%,VBW=10Hz Duty cycle<98%,VBW≥1/T Video bandwidth mode=RMS (power averaging)
Start frequency	1GHz	
Stop frequency	40GHz	
Sweep Time	Auto	

Detector	PEAK
Trace Mode	Max Hold

Note : T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.7 for the on-time time.

6.4.Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 6.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.
- i. IEEE 802.11a, IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80 all have been tested, only worst case IEEE 802.11n HT20 is recorded.

6.5.Test Result

Radiated Emissions Below 1GHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 235

File: \\EMC-966-1\test data\2024\RF\T\TCL Dou Mei Ti\Q75H-FCC.EM6 (236)

Date: 2024-04-23



Site no. : 1# 966 Chamber Data no. : 235
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : FCC PART 15 C(3M)
Env. / Ins. : Temp:22.3°C.Humi:60%;Press:101.1kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	137.67	12.00	1.67	15.55	29.22	43.50	14.28	QP
2	154.16	11.80	1.78	9.11	22.69	43.50	20.81	QP
3	167.74	10.50	1.86	10.10	22.46	43.50	21.04	QP
4	185.20	8.70	1.96	14.24	24.90	43.50	18.60	QP
5	224.00	10.26	2.18	17.62	30.06	46.00	15.94	QP
6	288.02	13.68	2.56	6.45	22.69	46.00	23.31	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 236

File: \\EMC-966-1\test data\2024\RF\TTCCL Dou Mei Ti\Q75H-FCC.EM6 (236)

Date: 2024-04-23



Site no. : 1# 966 Chamber Data no. : 236
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 C(3M)
Env. / Ins. : Temp:22.3°C.Humi:60%;Press:101.1KPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	136.70	12.70	1.67	10.54	24.91	43.50	18.59	QP
2	184.23	9.10	1.96	17.64	28.70	43.50	14.80	QP
3	228.85	10.74	2.21	21.79	34.74	46.00	11.26	QP
4	285.11	13.50	2.54	13.83	29.87	46.00	16.13	QP
5	380.17	16.20	2.97	9.98	29.15	46.00	16.85	QP
6	441.28	17.74	3.21	7.42	28.37	46.00	17.63	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.

Radiated Emissions Above 1G


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 203

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti\\Q75H-FCC.EM6 (236)

Date: 2024-04-26



Site no. : 1# 966 Chamber Data no. : 203
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5180MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	49.21	47.96	68.20	20.24	Peak
2	8973.00	37.97	7.75	43.42	43.14	45.44	68.20	22.76	Peak
3	11540.00	38.85	8.57	42.57	41.53	46.38	74.00	27.62	Peak
4	13053.00	39.72	9.29	40.80	37.61	45.82	68.20	22.38	Peak
5	13954.00	39.99	9.74	40.80	38.65	47.58	68.20	20.62	Peak
6	15671.00	38.36	10.51	43.84	40.55	45.58	74.00	28.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 204

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-26



Site no. : 1# 966 Chamber Data no. : 204
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5180MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	45.89	44.64	68.20	23.56	Peak
2	8871.00	37.85	7.66	43.48	42.40	44.43	68.20	23.77	Peak
3	10299.00	38.41	7.92	43.56	42.22	44.99	68.20	23.21	Peak
4	12271.00	39.04	8.95	41.82	38.99	45.16	74.00	28.84	Peak
5	14124.00	39.94	9.83	41.10	38.39	47.06	68.20	21.14	Peak
6	15348.00	38.91	10.38	43.58	40.36	46.07	68.20	22.13	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 205

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 205
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5200MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8650.00	37.58	7.47	43.61	43.40	44.84	68.20	23.36	Peak
2	9721.00	38.14	7.77	43.69	42.89	45.11	68.20	23.09	Peak
3	12067.00	38.86	8.86	42.11	40.13	45.74	74.00	28.26	Peak
4	13852.00	39.96	9.69	40.80	38.11	46.96	68.20	21.24	Peak
5	15297.00	39.00	10.36	43.53	40.47	46.30	68.20	21.90	Peak
6	16181.00	37.89	10.81	44.12	38.75	43.33	74.00	30.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 206

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 206
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5200MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8463.00	37.36	7.31	43.73	44.01	44.95	74.00	29.05	Peak
2	9551.00	38.11	7.77	43.62	43.81	46.07	68.20	22.13	Peak
3	10826.00	38.78	8.18	43.14	41.97	45.79	74.00	28.21	Peak
4	13444.00	39.83	9.48	40.80	38.06	46.57	68.20	21.63	Peak
5	14889.00	39.56	10.19	43.00	39.57	46.32	68.20	21.88	Peak
6	15858.00	38.04	10.59	43.99	40.38	45.02	74.00	28.98	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 207

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 207
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5240MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7902.00	36.72	6.89	44.01	44.21	43.81	68.20	24.39	Peak
2	8990.00	37.99	7.77	43.41	43.21	45.56	68.20	22.64	Peak
3	10979.00	38.89	8.25	43.01	41.43	45.56	74.00	28.44	Peak
4	13104.00	39.73	9.31	40.80	38.51	46.75	68.20	21.45	Peak
5	14940.00	39.53	10.22	43.13	39.93	46.55	68.20	21.65	Peak
6	16283.00	37.94	10.91	44.13	38.66	43.38	68.20	24.82	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 208

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 208
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5240MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8820.00	37.78	7.62	43.51	43.11	45.00	68.20	23.20	Peak
2	10503.00	38.55	8.02	43.39	41.95	45.13	68.20	23.07	Peak
3	12560.00	39.30	9.07	41.42	39.10	46.05	74.00	27.95	Peak
4	14005.00	40.00	9.77	40.80	38.24	47.21	68.20	20.99	Peak
5	15518.00	38.62	10.45	43.71	40.21	45.57	74.00	28.43	Peak
6	16504.00	38.05	11.11	44.15	38.38	43.39	68.20	24.81	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 209

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 209
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5260MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8429.00	37.31	7.28	43.75	43.91	44.75	74.00	29.25	Peak
2	10265.00	38.39	7.90	43.58	42.08	44.79	68.20	23.41	Peak
3	10809.00	38.77	8.17	43.15	42.00	45.79	74.00	28.21	Peak
4	12985.00	39.69	9.25	40.82	38.23	46.35	68.20	21.85	Peak
5	13937.00	39.98	9.74	40.80	39.87	48.79	68.20	19.41	Peak
6	15858.00	38.04	10.59	43.99	40.99	45.63	74.00	28.37	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 210

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 210
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5260MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7239.00	36.19	6.68	44.08	44.94	43.73	68.20	24.47	Peak
2	9024.00	38.00	7.78	43.41	43.04	45.41	74.00	28.59	Peak
3	11506.00	38.85	8.55	42.59	41.15	45.96	74.00	28.04	Peak
4	12560.00	39.30	9.07	41.42	39.25	46.20	74.00	27.80	Peak
5	14532.00	39.73	10.02	42.11	39.27	46.91	68.20	21.29	Peak
6	15892.00	37.98	10.60	44.02	40.33	44.89	74.00	29.11	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 211

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 211
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5300MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	46.18	44.93	68.20	23.27	Peak
2	9024.00	38.00	7.78	43.41	43.38	45.75	74.00	28.25	Peak
3	10877.00	38.81	8.20	43.09	41.45	45.37	74.00	28.63	Peak
4	12577.00	39.32	9.08	41.39	39.95	46.96	74.00	27.04	Peak
5	13988.00	40.00	9.76	40.80	38.15	47.11	68.20	21.09	Peak
6	14974.00	39.51	10.23	43.22	40.01	46.53	68.20	21.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 212

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 212
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5300MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	44.94	43.69	68.20	24.51	Peak
2	8531.00	37.44	7.37	43.68	44.18	45.31	68.20	22.89	Peak
3	10367.00	38.46	7.95	43.50	42.12	45.03	68.20	23.17	Peak
4	11931.00	38.81	8.79	42.25	41.38	46.73	74.00	27.27	Peak
5	13512.00	39.85	9.52	40.80	38.24	46.81	68.20	21.39	Peak
6	14889.00	39.56	10.19	43.00	39.62	46.37	68.20	21.83	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 213

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 213
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5320MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7987.00	36.79	6.91	44.00	43.79	43.49	68.20	24.71	Peak
2	9602.00	38.12	7.77	43.64	42.36	44.61	68.20	23.59	Peak
3	11387.00	38.86	8.48	42.69	40.99	45.64	74.00	28.36	Peak
4	13495.00	39.85	9.51	40.80	38.25	46.81	68.20	21.39	Peak
5	15246.00	39.08	10.34	43.49	40.36	46.29	68.20	21.91	Peak
6	15841.00	38.07	10.58	43.98	40.43	45.10	74.00	28.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 214

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 214
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5320MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	45.60	44.35	68.20	23.85	Peak
2	8990.00	37.99	7.77	43.41	43.49	45.84	68.20	22.36	Peak
3	10809.00	38.77	8.17	43.15	42.04	45.83	74.00	28.17	Peak
4	12594.00	39.33	9.09	41.37	39.02	46.07	74.00	27.93	Peak
5	14073.00	39.96	9.80	40.97	38.24	47.03	68.20	21.17	Peak
6	15280.00	39.02	10.36	43.52	40.27	46.13	68.20	22.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 215

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 215
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5500MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8531.00	37.44	7.37	43.68	43.86	44.99	68.20	23.21	Peak
2	10418.00	38.49	7.98	43.46	41.54	44.55	68.20	23.65	Peak
3	11982.00	38.80	8.82	42.21	40.60	46.01	74.00	27.99	Peak
4	14141.00	39.93	9.84	41.14	39.34	47.97	68.20	20.23	Peak
5	15314.00	38.97	10.37	43.55	40.60	46.39	68.20	21.81	Peak
6	16521.00	38.06	11.13	44.15	38.32	43.36	68.20	24.84	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 216

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti\\Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 216
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5500MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8990.00	37.99	7.77	43.41	43.28	45.63	68.20	22.57	Peak
2	10775.00	38.74	8.15	43.18	41.40	45.11	74.00	28.89	Peak
3	12968.00	39.67	9.25	40.85	38.23	46.30	68.20	21.90	Peak
4	14022.00	39.99	9.78	40.84	37.81	46.74	68.20	21.46	Peak
5	15841.00	38.07	10.58	43.98	40.51	45.18	74.00	28.82	Peak
6	17660.00	40.48	12.15	43.21	38.34	47.76	68.20	20.44	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 217

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 217
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5580MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7936.00	36.75	6.90	44.01	44.17	43.81	68.20	24.39	Peak
2	9687.00	38.14	7.77	43.68	42.61	44.84	68.20	23.36	Peak
3	12543.00	39.29	9.06	41.44	38.96	45.87	74.00	28.13	Peak
4	13461.00	39.84	9.49	40.80	38.00	46.53	68.20	21.67	Peak
5	14889.00	39.56	10.19	43.00	39.92	46.67	68.20	21.53	Peak
6	15841.00	38.07	10.58	43.98	40.90	45.57	74.00	28.43	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 218

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 218
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5580MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	45.32	44.07	68.20	24.13	Peak
2	9551.00	38.11	7.77	43.62	42.85	45.11	68.20	23.09	Peak
3	11982.00	38.80	8.82	42.21	40.54	45.95	74.00	28.05	Peak
4	13597.00	39.88	9.56	40.80	38.56	47.20	68.20	21.00	Peak
5	14923.00	39.54	10.21	43.09	39.55	46.21	68.20	21.99	Peak
6	15841.00	38.07	10.58	43.98	40.99	45.66	74.00	28.34	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 219

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 219
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5700MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	47.38	46.13	68.20	22.07	Peak
2	9092.00	38.02	7.78	43.43	43.04	45.41	74.00	28.59	Peak
3	11353.00	38.86	8.46	42.72	41.05	45.65	74.00	28.35	Peak
4	12628.00	39.37	9.10	41.32	38.96	46.11	74.00	27.89	Peak
5	13869.00	39.96	9.70	40.80	37.97	46.83	68.20	21.37	Peak
6	14957.00	39.52	10.23	43.17	39.39	45.97	68.20	22.23	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 220

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 220
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5700MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	45.97	44.72	68.20	23.48	Peak
2	8990.00	37.99	7.77	43.41	42.55	44.90	68.20	23.30	Peak
3	10809.00	38.77	8.17	43.15	42.44	46.23	74.00	27.77	Peak
4	13597.00	39.88	9.56	40.80	38.62	47.26	68.20	20.94	Peak
5	14736.00	39.63	10.12	42.62	38.80	45.93	68.20	22.27	Peak
6	16232.00	37.92	10.86	44.12	38.38	43.04	68.20	25.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 221

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 221
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5745MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8565.00	37.48	7.40	43.66	44.00	45.22	68.20	22.98	Peak
2	10809.00	38.77	8.17	43.15	42.07	45.86	74.00	28.14	Peak
3	12560.00	39.30	9.07	41.42	39.24	46.19	74.00	27.81	Peak
4	13614.00	39.88	9.57	40.80	39.11	47.76	68.20	20.44	Peak
5	14736.00	39.63	10.12	42.62	39.49	46.62	68.20	21.58	Peak
6	15892.00	37.98	10.60	44.02	39.41	43.97	74.00	30.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 222

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei TiQ75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 222
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5745MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	46.64	45.39	68.20	22.81	Peak
2	8956.00	37.95	7.74	43.43	43.04	45.30	68.20	22.90	Peak
3	10928.00	38.85	8.23	43.05	41.33	45.36	74.00	28.64	Peak
4	12577.00	39.32	9.08	41.39	39.32	46.33	74.00	27.67	Peak
5	14056.00	39.97	9.79	40.93	38.53	47.36	68.20	20.84	Peak
6	15858.00	38.04	10.59	43.99	40.64	45.28	74.00	28.72	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 223

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 223
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5785MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	45.55	44.30	68.20	23.90	Peak
2	9092.00	38.02	7.78	43.43	42.88	45.25	74.00	28.75	Peak
3	10792.00	38.75	8.16	43.16	43.49	47.24	74.00	26.76	Peak
4	11880.00	38.81	8.76	42.29	40.61	45.89	74.00	28.11	Peak
5	13495.00	39.85	9.51	40.80	38.27	46.83	68.20	21.37	Peak
6	14889.00	39.56	10.19	43.00	39.93	46.68	68.20	21.52	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 224

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 224
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5785MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	36.16	6.67	44.08	46.23	44.98	68.20	23.22	Peak
2	9415.00	38.08	7.78	43.57	43.36	45.65	74.00	28.35	Peak
3	11523.00	38.85	8.56	42.58	40.87	45.70	74.00	28.30	Peak
4	12577.00	39.32	9.08	41.39	39.20	46.21	74.00	27.79	Peak
5	14141.00	39.93	9.84	41.14	38.44	47.07	68.20	21.13	Peak
6	16300.00	37.95	10.92	44.13	39.47	44.21	68.20	23.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 225

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 225
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5825MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	9347.00	38.07	7.78	43.54	42.79	45.10	74.00	28.90	Peak
2	10554.00	38.59	8.04	43.35	41.83	45.11	68.20	23.09	Peak
3	11251.00	38.87	8.40	42.80	41.18	45.65	74.00	28.35	Peak
4	13121.00	39.74	9.32	40.80	38.53	46.79	68.20	21.41	Peak
5	14005.00	40.00	9.77	40.80	38.48	47.45	68.20	20.75	Peak
6	15331.00	38.94	10.38	43.56	40.34	46.10	68.20	22.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 226

File: \\EMC-966-1\test data\2024\RF\T\TCL Dou Mei Ti\Q75H-FCC.EM6 (236)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 226
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5825MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	8973.00	37.97	7.75	43.42	42.91	45.21	68.20	22.99	Peak
2	10741.00	38.72	8.14	43.20	42.00	45.66	74.00	28.34	Peak
3	12560.00	39.30	9.07	41.42	38.66	45.61	74.00	28.39	Peak
4	13835.00	39.95	9.68	40.80	38.48	47.31	68.20	20.89	Peak
5	15399.00	38.82	10.40	43.62	39.36	44.96	74.00	29.04	Peak
6	16351.00	37.98	10.97	44.14	38.39	43.20	68.20	25.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 18GHz to 40GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All test mode had been pre-test, only Low/Middle/High Channel of the worst case modulation mode was reported

Band Edge


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 91

File: \\EMC-966-1\test data\2024\RF\TTC\TCL Dou Mei Ti\Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : site Data no. : 91
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5180MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.97	5.52	44.27	52.13	46.35	54.00	7.65	Average
2	5150.00	32.97	5.52	44.27	59.72	53.94	68.20	14.26	Peak
3	5179.00	33.00	5.55	44.26	104.01	98.30	68.20	-30.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 92

File: \\EMC-966-1\test data\2024\RF\TTC\TCL Dou Mei Ti\Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 92
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5180MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.97	5.52	44.27	51.12	45.34	54.00	8.66	Average
2	5150.00	32.97	5.52	44.27	64.97	59.19	68.20	9.01	Peak
3	5179.70	33.00	5.55	44.26	108.97	103.26	68.20	-35.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 93

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 93
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5320MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5321.50	33.15	5.65	44.24	109.15	103.71	68.20	-35.51	Peak
2	5350.10	33.19	5.68	44.23	49.13	43.77	54.00	10.23	Average
3	5350.10	33.19	5.68	44.23	62.49	57.13	74.00	16.87	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.

2. Margin= Limit - Emission Level.

3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 94

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 94
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5320MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5317.60	33.15	5.65	44.24	103.96	98.52	68.20	-30.32	Peak
2	5350.10	33.19	5.68	44.23	56.58	51.22	74.00	22.78	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.

2. Margin= Limit - Emission Level.

3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 95

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 95
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5500MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5470.00	33.32	5.77	44.21	61.13	56.01	68.20	12.19	Peak
2	5499.12	33.35	5.79	44.20	104.00	98.94	68.20	-30.74	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 96

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 96
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5500MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5470.00	33.32	5.77	44.21	64.29	59.17	68.20	9.03	Peak
2	5499.84	33.35	5.79	44.20	109.20	104.14	68.20	-35.94	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 97

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 97
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5700MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5701.39	33.57	5.94	44.16	108.96	104.31	68.20	-36.11	Peak
2	5725.00	33.60	5.96	44.15	67.05	62.46	68.20	5.74	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 98

File: \\EMC-966-1\\test data\\2024\\RF\\TCL Dou Mei Ti Q75H-FCC.EM6 (242)

Date: 2024-04-29



Site no. : 1# 966 Chamber Data no. : 98
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:21.5°C;Humi:51%;Press:101.52kPa
Engineer : ZQL
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : IEEE 802.11n HT20 TX 5700MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5700.66	33.57	5.94	44.16	101.70	97.05	68.20	-28.85	Peak
2	5725.00	33.60	5.96	44.15	55.51	50.92	68.20	17.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.

18000MHz-40000MHz

Pass

Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible


limit has no need to be reported.

7.FREQUENCY STABILITY

7.1.Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the operational description.

7.2.Test Setup



7.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	10KHz
VBW	10KHz
Span	200KHz
Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

7.4.Test Procedure

For measurement frequency stability under temperature variation :

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Set the temperature control on the chamber to the Specified temperature and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.
- h. Repeat step d through step f to measured the temperature form -20°C to +50°C in 10°C steps.

For frequency stability under voltage variation:

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Unless otherwise specified, set the temperature control on the chamber to the ambient room temperature (+15°C to +25°C) and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency.
- h. Repeat step d through step f to measured the varied from 85% to 115% of the rated voltage.

7.5.Test Result

Refer to section 10: Appendix G

8.AC POWER LINE CONDUCTED EMISSIONS


8.1.Limit

Frequency			Maximum RF Line Voltage	
			Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz	~	500kHz	66 ~ 56*	56 ~ 46*
500kHz	~	5MHz	56	46
5MHz	~	30MHz	60	50

Notes:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

8.2.Test Setup



8.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold

8.4.Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 8.3.
- f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.
- g. Record the results in the test report.

8.5. Test Result


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 42

File: \\EMC-Ce-2\\Test Data\\2024\\RF\\T\\TCL Duo Mei Ti\\Q85H.EM6 (132)

Date: 2024-04-24



Site no : 2#CE Shield Room Data no. : 42
Env. / Ins. : Temp:25.4℃ Humi:58% Press:101.30kPa LINE Phase : LINE
Limit : FCC PART 15C QP
Engineer : GGZ
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17	10.12	9.89	9.83	29.84	55.21	25.37	Average
2	0.17	10.12	9.89	19.33	39.34	65.21	25.87	QP
3	0.20	10.16	9.93	7.44	27.53	53.80	26.27	Average
4	0.20	10.16	9.93	18.36	38.45	63.80	25.35	QP
5	0.61	10.05	9.97	7.73	27.75	46.00	18.25	Average
6	0.61	10.05	9.97	16.25	36.27	56.00	19.73	QP
7	1.09	9.97	10.05	1.06	21.08	46.00	24.92	Average
8	1.09	9.97	10.05	10.23	30.25	56.00	25.75	QP
9	1.53	9.98	10.02	0.74	20.74	46.00	25.26	Average
10	1.53	9.98	10.02	9.42	29.42	56.00	26.58	QP
11	1.91	9.98	10.00	0.09	20.07	46.00	25.93	Average
12	1.91	9.98	10.00	10.86	30.84	56.00	25.16	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 44

File: \\EMC-Ce-2\Test Data\2024\RF\TTCL Duo Mei TiQ85H.EM6 (132)

Date: 2024-04-24



Site no : 2#CE Shield Room Data no. : 44
Env. / Ins. : Temp:25.4℃ Humi:58% Press:101.30kPa LINE Phase : NEUTRAL
Limit : FCC PART 15C QP
Engineer : GGZ
EUT : 5.1.2 Channel Dolby Atmos Sound Bar with
Wireless Subwoofer
Power : AC 120V/60Hz
M/N : Q75H
Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.19	10.14	9.93	11.38	31.45	54.02	22.57	Average
2	0.19	10.14	9.93	19.33	39.40	64.02	24.62	QP
3	0.23	10.15	9.94	7.24	27.33	52.44	25.11	Average
4	0.23	10.15	9.94	17.25	37.34	62.44	25.10	QP
5	0.60	10.00	9.97	10.86	30.83	46.00	15.17	Average
6	0.60	10.00	9.97	19.26	39.23	56.00	16.77	QP
7	1.12	9.99	10.04	1.24	21.27	46.00	24.73	Average
8	1.12	9.99	10.04	9.33	29.36	56.00	26.64	QP
9	1.51	10.00	10.02	1.58	21.60	46.00	24.40	Average
10	1.51	10.00	10.02	8.25	28.27	56.00	27.73	QP
11	1.89	10.00	10.00	5.09	25.09	46.00	20.91	Average
12	1.89	10.00	10.00	12.33	32.33	56.00	23.67	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

9.ANTENNA REQUIREMENTS

9.1.Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

9.2.Test Result

The antennas used for this product is internal antenna, so compliance with antenna requirements. (Please refer to the EUT photo for details)

10.APPENDIX

Appendix A1: Emission Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	20.000	5170.000	5190.000	---	---
11A	Ant2	5180	20.120	5169.960	5190.080	---	---
11A	Ant1	5200	19.920	5190.000	5209.920	---	---
11A	Ant2	5200	19.960	5189.960	5209.920	---	---
11A	Ant1	5240	20.160	5229.840	5250.000	---	---
11A	Ant2	5240	20.080	5229.920	5250.000	---	---
11A	Ant1	5260	19.880	5250.120	5270.000	---	---
11A	Ant2	5260	19.800	5250.040	5269.840	---	---
11A	Ant1	5300	20.080	5290.000	5310.080	---	---
11A	Ant2	5300	20.000	5289.960	5309.960	---	---
11A	Ant1	5320	20.080	5309.920	5330.000	---	---
11A	Ant2	5320	19.760	5310.040	5329.800	---	---
11A	Ant1	5500	19.760	5490.080	5509.840	---	---
11A	Ant2	5500	20.000	5490.040	5510.040	---	---
11A	Ant1	5580	20.080	5569.960	5590.040	---	---
11A	Ant2	5580	19.720	5570.120	5589.840	---	---
11A	Ant1	5700	19.720	5690.120	5709.840	---	---
11A	Ant2	5700	19.840	5690.080	5709.920	---	---
11A	Ant1	5745	19.920	5734.880	5754.800	---	---
11A	Ant2	5745	19.920	5735.080	5755.000	---	---
11A	Ant1	5785	20.080	5774.880	5794.960	---	---
11A	Ant2	5785	20.200	5775.040	5795.240	---	---
11A	Ant1	5825	19.720	5815.160	5834.880	---	---
11A	Ant2	5825	20.120	5814.880	5835.000	---	---
11N20MIMO	Ant1	5180	20.400	5169.800	5190.200	---	---
11N20MIMO	Ant2	5180	19.960	5169.960	5189.920	---	---
11N20MIMO	Ant1	5200	20.400	5189.800	5210.200	---	---
11N20MIMO	Ant2	5200	19.880	5189.960	5209.840	---	---
11N20MIMO	Ant1	5240	20.400	5229.880	5250.280	---	---
11N20MIMO	Ant2	5240	19.760	5230.120	5249.880	---	---
11N20MIMO	Ant1	5260	20.400	5249.840	5270.240	---	---
11N20MIMO	Ant2	5260	19.840	5250.080	5269.920	---	---
11N20MIMO	Ant1	5300	20.320	5289.840	5310.160	---	---
11N20MIMO	Ant2	5300	19.840	5290.080	5309.920	---	---
11N20MIMO	Ant1	5320	20.360	5309.800	5330.160	---	---
11N20MIMO	Ant2	5320	19.880	5310.120	5330.000	---	---
11N20MIMO	Ant1	5500	20.360	5489.880	5510.240	---	---
11N20MIMO	Ant2	5500	20.000	5489.960	5509.960	---	---
11N20MIMO	Ant1	5580	20.160	5570.000	5590.160	---	---
11N20MIMO	Ant2	5580	19.960	5569.920	5589.880	---	---
11N20MIMO	Ant1	5700	20.400	5689.760	5710.160	---	---
11N20MIMO	Ant2	5700	19.840	5690.000	5709.840	---	---
11N20MIMO	Ant1	5745	20.160	5734.920	5755.080	---	---
11N20MIMO	Ant2	5745	19.960	5735.000	5754.960	---	---
11N20MIMO	Ant1	5785	20.560	5774.640	5795.200	---	---
11N20MIMO	Ant2	5785	20.120	5775.040	5795.160	---	---
11N20MIMO	Ant1	5825	20.480	5814.760	5835.240	---	---
11N20MIMO	Ant2	5825	20.040	5814.960	5835.000	---	---
11N40MIMO	Ant1	5190	40.720	5169.520	5210.240	---	---

11N40MIMO	Ant2	5190	39.680	5170.160	5209.840	---	---
11N40MIMO	Ant1	5230	40.480	5209.840	5250.320	---	---
11N40MIMO	Ant2	5230	39.840	5210.080	5249.920	---	---
11N40MIMO	Ant1	5270	40.720	5249.600	5290.320	---	---
11N40MIMO	Ant2	5270	39.520	5250.320	5289.840	---	---
11N40MIMO	Ant1	5310	40.800	5289.520	5330.320	---	---
11N40MIMO	Ant2	5310	40.080	5290.000	5330.080	---	---
11N40MIMO	Ant1	5510	40.640	5489.680	5530.320	---	---
11N40MIMO	Ant2	5510	39.360	5490.560	5529.920	---	---
11N40MIMO	Ant1	5550	40.960	5529.520	5570.480	---	---
11N40MIMO	Ant2	5550	39.600	5530.240	5569.840	---	---
11N40MIMO	Ant1	5670	40.800	5649.600	5690.400	---	---
11N40MIMO	Ant2	5670	40.160	5650.080	5690.240	---	---
11N40MIMO	Ant1	5755	40.560	5734.680	5775.240	---	---
11N40MIMO	Ant2	5755	40.000	5735.080	5775.080	---	---
11N40MIMO	Ant1	5795	40.640	5774.760	5815.400	---	---
11N40MIMO	Ant2	5795	40.000	5775.000	5815.000	---	---
11AC20MIMO	Ant1	5180	20.200	5169.840	5190.040	---	---
11AC20MIMO	Ant2	5180	19.920	5170.040	5189.960	---	---
11AC20MIMO	Ant1	5200	20.240	5189.920	5210.160	---	---
11AC20MIMO	Ant2	5200	19.960	5190.040	5210.000	---	---
11AC20MIMO	Ant1	5240	20.520	5229.760	5250.280	---	---
11AC20MIMO	Ant2	5240	20.000	5229.920	5249.920	---	---
11AC20MIMO	Ant1	5260	20.400	5249.800	5270.200	---	---
11AC20MIMO	Ant2	5260	20.160	5249.920	5270.080	---	---
11AC20MIMO	Ant1	5300	20.400	5289.760	5310.160	---	---
11AC20MIMO	Ant2	5300	20.000	5289.880	5309.880	---	---
11AC20MIMO	Ant1	5320	20.400	5309.880	5330.280	---	---
11AC20MIMO	Ant2	5320	19.920	5310.080	5330.000	---	---
11AC20MIMO	Ant1	5500	20.320	5489.800	5510.120	---	---
11AC20MIMO	Ant2	5500	19.920	5490.080	5510.000	---	---
11AC20MIMO	Ant1	5580	20.440	5569.760	5590.200	---	---
11AC20MIMO	Ant2	5580	19.920	5570.080	5590.000	---	---
11AC20MIMO	Ant1	5700	20.720	5689.680	5710.400	---	---
11AC20MIMO	Ant2	5700	19.920	5690.080	5710.000	---	---
11AC20MIMO	Ant1	5745	20.560	5734.600	5755.160	---	---
11AC20MIMO	Ant2	5745	19.960	5735.040	5755.000	---	---
11AC20MIMO	Ant1	5785	20.280	5774.880	5795.160	---	---
11AC20MIMO	Ant2	5785	20.120	5775.000	5795.120	---	---
11AC20MIMO	Ant1	5825	20.520	5814.800	5835.320	---	---
11AC20MIMO	Ant2	5825	19.920	5815.040	5834.960	---	---
11AC40MIMO	Ant1	5190	40.480	5169.680	5210.160	---	---
11AC40MIMO	Ant2	5190	40.080	5170.000	5210.080	---	---
11AC40MIMO	Ant1	5230	40.480	5209.680	5250.160	---	---
11AC40MIMO	Ant2	5230	40.240	5209.840	5250.080	---	---
11AC40MIMO	Ant1	5270	40.640	5249.680	5290.320	---	---
11AC40MIMO	Ant2	5270	39.520	5250.480	5290.000	---	---
11AC40MIMO	Ant1	5310	40.320	5289.920	5330.240	---	---
11AC40MIMO	Ant2	5310	39.680	5290.320	5330.000	---	---
11AC40MIMO	Ant1	5510	40.640	5490.000	5530.640	---	---
11AC40MIMO	Ant2	5510	39.680	5490.080	5529.760	---	---
11AC40MIMO	Ant1	5550	40.560	5529.760	5570.320	---	---
11AC40MIMO	Ant2	5550	40.160	5530.000	5570.160	---	---
11AC40MIMO	Ant1	5670	40.800	5649.760	5690.560	---	---
11AC40MIMO	Ant2	5670	39.760	5650.160	5689.920	---	---
11AC40MIMO	Ant1	5755	41.120	5734.280	5775.400	---	---
11AC40MIMO	Ant2	5755	39.680	5735.160	5774.840	---	---

11AC40MIMO	Ant1	5795	40.640	5774.520	5815.160	---	---
11AC40MIMO	Ant2	5795	39.760	5775.240	5815.000	---	---
11AC80MIMO	Ant1	5210	81.440	5169.200	5250.640	---	---
11AC80MIMO	Ant2	5210	80.800	5169.520	5250.320	---	---
11AC80MIMO	Ant1	5290	81.280	5249.520	5330.800	---	---
11AC80MIMO	Ant2	5290	80.640	5249.520	5330.160	---	---
11AC80MIMO	Ant1	5530	81.600	5489.200	5570.800	---	---
11AC80MIMO	Ant2	5530	80.000	5490.160	5570.160	---	---
11AC80MIMO	Ant1	5610	81.920	5569.040	5650.960	---	---
11AC80MIMO	Ant2	5610	80.320	5570.160	5650.480	---	---
11AC80MIMO	Ant1	5775	80.480	5735.000	5815.480	---	---
11AC80MIMO	Ant2	5775	80.160	5734.840	5815.000	---	---

Test Graphs

11A-Ant1-5180



11A-Ant2-5180




11A-Ant1-5200



11A-Ant2-5200



11A-Ant1-5240



11A-Ant2-5240



11A-Ant1-5260



11A-Ant2-5260



11A-Ant1-5300



11A-Ant2-5300



11A-Ant1-5320



11A-Ant2-5320



11A-Ant1-5500



11A-Ant2-5500



11A-Ant1-5580



11A-Ant2-5580



11A-Ant1-5700



11A-Ant2-5700



11A-Ant1-5745



11A-Ant2-5745



11A-Ant1-5785



11A-Ant2-5785



11A-Ant1-5825



11A-Ant2-5825



11N20MIMO-Ant1-5180



11N20MIMO-Ant2-5180



11N20MIMO-Ant1-5200



11N20MIMO-Ant2-5200



11N20MIMO-Ant1-5240



11N20MIMO-Ant2-5240



11N20MIMO-Ant1-5260



11N20MIMO-Ant2-5260



11N20MIMO-Ant1-5300



11N20MIMO-Ant2-5300



11N20MIMO-Ant1-5320



11N20MIMO-Ant2-5320



11N20MIMO-Ant1-5500



11N20MIMO-Ant2-5500



11N20MIMO-Ant1-5580



11N20MIMO-Ant2-5580



11N20MIMO-Ant1-5700



11N20MIMO-Ant2-5700



11N20MIMO-Ant1-5745



11N20MIMO-Ant2-5745



11N20MIMO-Ant1-5785




11N20MIMO-Ant2-5785



11N20MIMO-Ant1-5825



11N20MIMO-Ant2-5825



11N40MIMO-Ant1-5190



11N40MIMO-Ant2-5190



11N40MIMO-Ant1-5230



11N40MIMO-Ant2-5230



11N40MIMO-Ant1-5270



11N40MIMO-Ant2-5270



11N40MIMO-Ant1-5310



11N40MIMO-Ant2-5310



11N40MIMO-Ant1-5510



11N40MIMO-Ant2-5510



11N40MIMO-Ant1-5550



11N40MIMO-Ant2-5550

