

## FCC 47 CFR MPE REPORT

TCL OVERSEAS MARKETING LTD

7.1.4 Channel Dolby Atmos Sound Bar with Wireless Subwoofer and Satellite Speakers

Model Number: Q85H

Additional Model: Q80H, Q88H, Q89H, Q85HE, Q85HK, Q8\*\*\*\*, Q85H-S, Q80H-S, Q88H-S, Q89H-S, Q85H-J, Q80H-J, Q88H-J, Q89H-J, Q85H-CA, Q80H-CA, Q88H-CA, Q89H-CA, R70C, R75C, R78C, R70D, R75D, R78D, R7\*\*\*, Q80H Pro, Q88H Pro, Q89H Pro, Q85HE Pro, Q85HK Pro, Q8\*\*\*\*, Q85H Pro-S, Q80H Pro-S, Q88H Pro-S, Q89H Pro-S, Q85H Pro-J, Q80H Pro-J, Q88H Pro-J, Q89H Pro-J, Q85H Pro-CA, Q80H Pro-CA, Q88H Pro-CA, Q89H Pro-CA, R70C Pro, R75C Pro, R78C Pro, R70D Pro, R75D Pro, R78D Pro (\*can be any numerica number "0~9" or alphebtical number "A~Z")

FCC ID: 2BEHEQ85H

Applicant:	TCL OVERSEAS MARKETING LTD
Address:	5/F, Building 22E, 22 Science Park East Avenue HongKong
	Science Park Shatin Hong Kong
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2405038
Date of Test:	Apr. 15, 2024~ May. 07, 2024
Date of Report:	May. 11, 2024

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: Pd (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Antenna	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	ant 1	7.43	5.534
	2441	ant 1	7.23	5.284
	2480	ant 1	7.2	5.248
$\pi/4$ -DQPSK	2402	ant 1	9.84	9.638
	2441	ant 1	9.7	9.333
	2480	ant 1	9.49	8.892
8-DPSK	2402	ant 1	10.19	10.447
	2441	ant 1	10.09	10.209
	2480	ant 1	9.82	9.594
BLE 1M	2402	ant 1	2.77	1.892
	2440	ant 1	2.62	1.828
	2480	ant 1	2.39	1.734
BLE 2M	2402	ant 1	2.88	1.941
	2440	ant 1	2.53	1.791
	2480	ant 1	2.59	1.816
2.4G SRD-GFSK	2406	ant 1	7.19	5.236
	2442	ant 1	6.39	4.355
	2474	ant 1	6.44	4.406
IEEE 802.11b	2412	ant 1	18.9	77.625
		ant 2	19.18	82.794
	2437	ant 1	19.12	81.658
		ant 2	19.1	81.283
	2462	ant 1	18.75	74.989
		ant 2	18.87	77.090
IEEE 802.11g	2412	ant 1	22.5	177.828
		ant 2	23.84	242.103
	2437	ant 1	22.9	194.984
		ant 2	23.48	222.844
	2462	ant 1	22.71	186.638
		ant 2	22.87	193.642
IEEE 802.11n HT20	2412	ant 1	22.47	176.604
		ant 2	22.94	196.789
	2437	ant 1	22.4	173.780
		ant 2	22.56	180.302

	2462	ant 1	22.05	160.325	
		ant 2	22.49	177.419	
IEEE 802.11n HT40	2422	ant 1	22.61	182.390	
		ant 2	22.9	194.984	
	2437	ant 1	22.76	188.799	
		ant 2	23.06	202.302	
	2452	ant 1	22.62	182.810	
		ant 2	22.91	195.434	
IEEE 802.11a	5180	ant 1	14.7	29.512	
		ant 2	14.04	25.351	
	5200	ant 1	14.41	27.606	
		ant 2	13.91	24.604	
	5240	ant 1	14.56	28.576	
		ant 2	13.92	24.660	
	5260	ant 1	14.42	27.669	
		ant 2	13.88	24.434	
	5300	ant 1	14.19	26.242	
		ant 2	13.85	24.266	
	5320	ant 1	14.05	25.410	
		ant 2	13.69	23.388	
	5500	ant 1	14.26	26.669	
		ant 2	13.7	23.442	
	5580	ant 1	14.14	25.942	
		ant 2	13.67	23.281	
	5700	ant 1	14.54	28.445	
		ant 2	14.32	27.040	
	5745	ant 1	14.6	28.840	
		ant 2	14.19	26.242	
	5785	ant 1	14.13	25.882	
		ant 2	13.93	24.717	
	5825	ant 1	13.96	24.889	
		ant 2	14.03	25.293	
	IEEE 802.11n20	5180	ant 1	14.46	27.925
			ant 2	14	25.119
		5200	ant 1	14.16	26.062
			ant 2	13.72	23.550
5240		ant 1	14.52	28.314	
		ant 2	13.9	24.547	

	5260	ant 1	14.06	25.468
		ant 2	13.63	23.067
	5300	ant 1	13.94	24.774
		ant 2	13.7	23.442
	5320	ant 1	13.83	24.155
		ant 2	13.61	22.961
	5500	ant 1	13.88	24.434
		ant 2	13.63	23.067
	5580	ant 1	14.13	25.882
		ant 2	13.59	22.856
	5700	ant 1	16.63	46.026
		ant 2	14.26	26.669
	5745	ant 1	14.4	27.542
		ant 2	14.39	27.479
	5785	ant 1	14.04	25.351
		ant 2	13.89	24.491
	5825	ant 1	13.95	24.831
		ant 2	14.25	26.607
IEEE 802.11ac VHT20	5180	ant 1	14.64	29.107
		ant 2	13.9	24.547
	5200	ant 1	14.31	26.977
		ant 2	13.97	24.946
	5240	ant 1	14.38	27.416
		ant 2	13.92	24.660
	5260	ant 1	14.21	26.363
		ant 2	13.86	24.322
	5300	ant 1	14.02	25.235
		ant 2	13.77	23.823
	5320	ant 1	13.84	24.210
		ant 2	13.71	23.496
	5500	ant 1	13.92	24.660
		ant 2	13.62	23.014
	5580	ant 1	13.91	24.604
		ant 2	13.59	22.856
	5700	ant 1	14.49	28.119
		ant 2	14.31	26.977
5745	ant 1	14.27	26.730	
	ant 2	14.22	26.424	

	5785	ant 1	13.87	24.378
		ant 2	13.75	23.714
	5825	ant 1	13.84	24.210
		ant 2	14	25.119
IEEE 802.11n HT40	5190	ant 1	14.84	30.479
		ant 2	14.46	27.925
	5230	ant 1	14.69	29.444
		ant 2	14.23	26.485
	5270	ant 1	14.59	28.774
		ant 2	13.98	25.003
	5310	ant 1	14.08	25.586
		ant 2	13.93	24.717
	5510	ant 1	14.02	25.235
		ant 2	13.77	23.823
	5550	ant 1	14.56	28.576
		ant 2	13.9	24.547
	5670	ant 1	14.63	29.040
		ant 2	14.39	27.479
	5755	ant 1	14.63	29.040
		ant 2	14.52	28.314
5795	ant 1	14.3	26.915	
	ant 2	14.34	27.164	
IEEE 802.11ac VHT40	5190	ant 1	14.63	29.040
		ant 2	14.17	26.122
	5230	ant 1	14.61	28.907
		ant 2	14.06	25.468
	5270	ant 1	14.45	27.861
		ant 2	13.86	24.322
	5310	ant 1	13.94	24.774
		ant 2	14.68	29.376
	5510	ant 1	14	25.119
		ant 2	13.68	23.335
	5590	ant 1	14.17	26.122
		ant 2	13.71	23.496
	5670	ant 1	15.7	37.154
		ant 2	14.34	27.164
5755	ant 1	14.67	29.309	
	ant 2	15.32	34.041	

IEEE 802.11ac VHT80	5795	ant 1	14.37	27.353
		ant 2	14.4	27.542
	5210	ant 1	12.58	18.113
		ant 2	12.04	15.996
	5290	ant 1	12.44	17.539
		ant 2	12.03	15.959
	5530	ant 1	12.44	17.539
		ant 2	11.95	15.668
	5610	ant 1	12.12	16.293
		ant 2	11.67	14.689
	5775	ant 1	12.49	17.742
		ant 2	12.34	17.140



### 3. Calculated Result and Limit

#### SISO

The Worst Mode	Antenna	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm <sup>2</sup> )	Limited of Power Density (S) (mW /cm <sup>2</sup> )	Test Result
					(dBi)	(Linear)			
<b>2.4G Band</b>									
GFSK	ant 1	7.43	7±1	8	2.4	1.738	0.0022	1	Complies
π/4-DQPSK	ant 1	9.84	9±1	10	2.4	1.738	0.0035	1	Complies
8-DPSK	ant 1	10.19	10±1	11	2.4	1.738	0.0044	1	Complies
BLE	ant 1	2.88	2 ±1	3	2.4	1.738	0.0007	1	Complies
2.4G SRD	ant 1	7.19	7±1	8	2.4	1.738	0.0022	1	Complies
IEEE 802.11b	ant 1	19.12	19±1	20	2.4	1.738	0.0346	1	Complies
	ant 2	19.18	19±1	20	2.3	1.698	0.0338	1	Complies
IEEE 802.11g	ant 1	22.90	22±1	23	2.4	1.738	0.0690	1	Complies
	ant 2	23.84	23±1	24	2.3	1.698	0.0849	1	Complies
IEEE 802.11n HT20	ant 1	22.47	22±1	23	2.4	1.738	0.0690	1	Complies
	ant 2	22.94	22±1	23	2.3	1.698	0.0674	1	Complies
IEEE 802.11n HT40	ant 1	22.76	22±1	23	2.4	1.738	0.0690	1	Complies
	ant 2	23.06	23±1	24	2.3	1.698	0.0849	1	Complies
<b>5G Band</b>									
IEEE 802.11a	ant 1	14.7	14±1	15	4.4	2.754	0.0173	1	Complies
	ant 2	14.32	14±1	15	4.1	2.570	0.0162	1	Complies
IEEE 802.11n HT20	ant 1	16.63	16±1	17	4.4	2.754	0.0275	1	Complies
	ant 2	14.39	14±1	15	4.1	2.570	0.0162	1	Complies
IEEE802.11ac VHT20	ant 1	14.64	14±1	15	4.4	2.754	0.0173	1	Complies
	ant 2	14.31	14±1	15	4.1	2.570	0.0162	1	Complies
IEEE 802.11n HT40	ant 1	14.84	14±1	15	4.4	2.754	0.0173	1	Complies
	ant 2	14.52	14±1	15	4.1	2.570	0.0162	1	Complies
IEEE 802.11ac VHT40	ant 1	15.7	15±1	16	4.4	2.754	0.0218	1	Complies
	ant 2	15.32	15±1	16	4.1	2.570	0.0204	1	Complies
IEEE 802.11ac VHT80	ant 1	12.58	12±1	13	4.4	2.754	0.0109	1	Complies
	ant 2	12.34	12±1	13	4.1	2.570	0.0102	1	Complies

**MIMO**

Mode	Power Density (S) (mW/cm <sup>2</sup> ) Antenna 0	Power Density (S) (mW/cm <sup>2</sup> ) Antenna 1	Power Density (S) (mW/cm <sup>2</sup> ) Total	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
<b>2.4G Band</b>					
IEEE 802.11n HT20	0.0690	0.0674	0.1364	1	Complies
IEEE 802.11n HT40	0.0690	0.0849	0.1538	1	Complies
<b>5G Band</b>					
IEEE 802.11n HT20	0.0275	0.0162	0.0436	1	Complies
IEEE 802.11ac VHT20	0.0173	0.0162	0.0335	1	Complies
IEEE 802.11n HT40	0.0173	0.0162	0.0335	1	Complies
IEEE 802.11ac VHT40	0.0218	0.0204	0.0422	1	Complies
IEEE 802.11ac VHT80	0.0109	0.0102	0.0211	1	Complies

**2.4G SRD+BT+WIFI**

MAX Power Density (S) (mW/cm <sup>2</sup> ) 2.4G SRD	MAX Power Density (S) (mW/cm <sup>2</sup> ) Bluetooth	MAX Power Density (S) (mW/cm <sup>2</sup> ) WiFi	Total Ratio	Limit Ratio	Test Result
0.0022	0.0044	0.1538	0.1604	1	Complies

Note: 2.4 and 5GHz bands are share an antenna, can't both the 2.4 and 5 GHz bands operate simultaneously.

**End of Test Report**