

SPECIFICATION



深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

通力 Z100-SW WIFI 天线组件

Tonly Z100-SW WIFI Antenna assembly

产 品 规 格 书

Product Specification

客 户 connection	通力 Tonly	频 段 frequency range	2400 ~ 2500MHz、5150 ~ 5850MHz
项目名称 entry name	Z100-SW	版 本 edition	V3.0
物料编号 Material No	1Z-100SW-012	颜 色 Color	黑色+白色 Black+White
客户料号 Customer Item Number	290000-019632		
环保要求 environmental requirement	☒ RoHS ☒ REACH ☒ HF		
R F 设计 R F Design	刘柱东 ZhuDong.Liu	结构设计 Structural Design	周锐斌 Rui Bin.Zhou
品质经理 Quality Manager	潘帅帅 ShuaiShuai.Pan	技术总监 Technical Director	张 磊 Lei.Zhang
日 期 Date	2025-04-23		

客户确认:

Customer confirmation:

装配是否符合贵司要求: ☐OK ☐NG

Whether the assembly meets your company's requirements: ☐OK ☐NG

深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

深圳市龙岗区布吉镇吉华路 513 号上水径村(国防培训基地
对面) 达成工业园综合楼 7 楼

TEL:0755-28576002

FAX:0755-84276383

上海分部: 上海市张江高科技园区集成电路产业区龙东大道
3000 号 8 号楼 201 室

TEL:021-61630552

FAX:755-84276383

Buji Town, Longgang District, Shenzhen, China Jihua Road 513,
Shangshuijing Village (opposite the national defense
training base) Dacheng Industrial Park, Building 7.

TEL:0755-28576002

FAX:0755-84276383

Room201, Building8, LongDongRoad3000#, Semiconductor Industry
Park, ZhangJiang Hitech Zone, ShangHai

TEL:021-61630552

FAX:755-84276383

[illegible]

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

索引 Indexes

一、项目说明 Project Description.....	4
二、 WIFI 天线 antenna.....	4
1、 规格 specifications.....	4
1.1 电气规格标准 Electrical specifications and standards.....	5
1.1.1 电性能指标 Electrical performance index.....	5
1.1.2 天线位置图片 Antenna position picture.....	5
1.2 结构规格标准 Structural specifications and standards.....	5
1.2.1 天线组成 Antenna composition..	5
2、测试环境 testing environment.....	6
3、测试 test.	7
3.1 驻波(VSWR)的测试 Test of standing wave (VSWR).....	7
3.1.1 测试连接 Test connection.....	7
3.2 效率、功率 (TRP)、灵敏度 (TIS) 的测试 Testing of efficiency, power (TRP), sensitivity (TIS).....	7
3.2.1 测试的场地 Test site.....	7
3.2.2 测试的仪表 Tested Instruments.....	7
3.2.3 测试数据 test data.....	7-8
4、VSWR 参数图 Parameter diagram.....	9
5、天线测试结果：整机数据—隔离度 Antenna Test Results: Whole Unit Data - Isolation	9
6、无源场型图 Passive field pattern diagram.....	10-11
7、环境处理 Environmental treatment	12
8、结论 conclusion.....	12
三、工程图 schedule drawing.....	13

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

一 项目说明 Project Description


客户名: Customer Name:	通力 Tonly
整机类型: Type of complete machine:	低音箱 subwoofer box
天线频段: Antenna band:	2400 ~ 2500MHz
天线形式: Antenna form:	FPC+同轴线+线材海绵 FPC + coaxial cable + cable sponge
馈电形式: Feed form:	焊接 weld
硬件版本: Hardware version:	/

二 WIFI 天线组件 Antenna assembly

1 规格 specifications

本报告主要提供 Z100-SW 项目天线的各项电气和结构性能参数的测试状况。下图为大显设计的天线图片。

This report mainly provides the testing status of various electrical and structural performance parameters of the antenna for the Z100-SW project. The following image shows an antenna with a large display design.



天线外观图

antenna appearing diagram

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1.1 电气规格标准 Electrical specifications and standards

1.1.1 电性能指标 Electrical performance index

天线工作频段在 2400 ~ 2500 MHz、5150~5850MHz。 下表是大显设计和量产天线的电性能指标。

The operating frequency band of the antenna is between 2400 and 2500 MHz、5150and 5850 MHz. The following table shows the electrical performance indicators of large display design and mass production antennas.

Frequency Range	Frequency (MHz)	VSWR
WIFI	2400 ~ 2500	≤ 2
WIFI	5150~5850	≤ 2

1.1.2 天线位置图片 Antenna position picture



2 结构规格标准 Structural specifications and standards

1.2.1 天线组成 Antenna composition

天线主要是由 FPC+同轴线+线材海绵 组成。

The antenna is mainly composed of FPC + coaxial cable + cable sponge.

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

2、测试设备 The Equipment of Active Test

Satimo 3D Chamber $6 \times 4 \times 4$ (m)

Agilent 8960 E5515c

Network analyzer-R&S ZVL



图 2

Figure 2

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

3 测试 test

3.1 驻波(VSWR)的测试 Test of standing wave (VSWR)

3.1.1 测试连接: VSWR 测试装置依次连接为: R&S ZVL 网络分析仪 → 测试线 → 测试治

Test connection: The VSWR test device is sequentially connected as follows: R&S ZVL network analyzer → test line → test fixture

实测(附图)Actual measurement (attached drawing)

3.2 增益及效率、功率 (TRP)、灵敏度 (TIS) 的测试

Gain and efficiency, power (TRP), sensitivity (TIS) testing

3.2.1 测试的场地 Test site:

大显微波暗室。测试频率范围为 400MHz—6GHz, 静区范围为 50cm 圆周, 反射率小于 -50 dB。

Large display microwave anechoic chamber. The test frequency range is 400MHz - 6GHz, the static zone range is 50cm circumferential, and the reflectivity is less than - 50dB.

3.2.2 测试的仪表 Tested Instruments:

R&S ZVL 网络分析仪、Agilent8960 E5515C、标准喇叭天线、法国 SATIMO-SG24SYSTEM 系统、打印机等。

R&S ZVL network analyzer, Agilent 8960 E5515C, standard horn antenna, French SATIMO-SG24SYSTEM system, printer, etc.

3.2.3 测试数据: 在微波暗室中, 测试的功率和灵敏度相关的数值如下表

Test data: In a microwave anechoic chamber, the values related to the power and sensitivity tested are shown in the table below

OTA 有源传导数据: OTA active conduction data:

		TPR	TIS
802. 11b 11M	1	10. 45	-88
	6	10. 64	-88
	11	10. 22	-88
802. 11g 54M	1	11. 32	-74
	6	11. 42	-74
	11	11. 37	-74
802. 11n MCS7	1	11. 08	-73
	6	11. 17	-73
	11	11. 21	-73
802. 11a 54M	36	11. 12	-75
	149	7. 25	-75
	161	6. 97	-75

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

OTA 有源数据: OTA active data:

		TPR	TIS
802.11b 11M	1	7.12	-84.31
	6	7.16	-84.62
	11	7.02	-84.55
802.11g 54M	1	8.42	-71.28
	6	8.57	-71.41
	11	8.37	-71.31
802.11n MCS7	1	8.19	-70.31
	6	8.37	-70.37
	11	8.27	-70.29
802.11a 54M	36	8.34	-71.58
	149	4.31	-71.62
	161	3.42	-71.31

无源效率&增益 Passive efficiency&gain:


Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
2400	45.16	-3.45	2.44
2450	46.43	-3.33	2.45
2500	45.36	-3.43	2.42
5150	43.98	-3.57	2.32
5250	44.78	-3.49	2.36
5350	44.82	-3.49	2.39
5450	45.34	-3.44	2.42
5550	46.53	-3.32	2.52
5650	44.61	-3.51	2.37
5750	44.22	-3.54	2.33
5850	43.72	-3.59	2.29

www.Topant.com.cn

Confidentiality requirements


Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

4、VSWR 参数图 VSWR parameter diagram



5、天线测试结果: 整机数据--隔离度 Antenna Test Results: Whole Unit Data - Isolation

WIFI-BT




www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

6、无源场型图 Passive Field Pattern Diagram


2.4G



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd


5.8G



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

7、环境处理 Environmental treatment:



去掉散热片 屏蔽罩贴铜箔屏蔽
Remove the heat sink. Shield shield with copper foil.

8、结论 conclusion

此天线是在客户提供样机基础上设计，电参数和结构性能已达到技术要求，请确认！

This antenna is designed based on the prototype provided by the customer. The electrical parameters and structural performance have met the technical requirements, please confirm!

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd


1		2		3		4		5		6	
第三视角	第三角	第三角									
	比例 1:1										
单位	mm										

A

B

C

D



注:

- "*"为重点尺寸；
- 未标注尺寸请依图纸；
- 不可有虚焊、漏焊、短线、断线等操作不良；
- 符合 RoHS 要求；



深圳大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

机型	Z100-SW	产品颜色	黑色	日期	2025/03/13
项目编码	CZ-100SW-012	模面处理		结构设计	周锐斌
零件名称	WiFi天线			射频设计	刘柱东
零件编码	1Z-100SW-012			审核	吴锡欢
材质	FPC+线材海绵+同轴线			批准	张磊
保存路径				当前版本	A

C	线材海绵	PU海绵	黑色	
B	端子线	Cable线	白色	
A	FPC	电解铜 PI	黑色	
序号	零件名称	材质	颜色	备注

1

2

3

4

5

6