

FCC/ISED - TEST REPORT

Report Number	: 68.710.24.0269.01	Date of Issue: <u>2024-09-05</u>
Model/HVIN	: Q10	
Product Type	: Robot Vacuum Cleaner	
Applicant	: Shenzhen Tunnu Innovation Co., Ltd.	
Address	: 4 Floor, Tsinghua University Research Institute, Yuehai Street, NanShan district, 518000 Shenzhen, Guangdong Province, PEOPLE'S REPUBLIC OF CHINA	
Manufacturer	: Shenzhen Tunnu Innovation Co., Ltd.	
Address	: 4 Floor, Tsinghua University Research Institute, Yuehai Street, NanShan district, 518000 Shenzhen, Guangdong Province, PEOPLE'S REPUBLIC OF CHINA	
Test Result	: ■ Positive <input type="checkbox"/> Negative	
Total pages including Appendices	: 37	

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation chapter A-3.4.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test.....	4
4	Summary of Test Standards.....	5
5	Summary of Test Results.....	6
6	General Remarks	7
7	Test Setups	8
7.1	Radiated test setups	8
7.2	Conducted RF test setups	9
7.3	AC Power Line Conducted Emission test setups.....	9
8	Systems Test Configuration	10
9	Technical Requirement	11
9.1	Conducted Emission.....	11
9.2	Conducted Peak Output Power & EIRP.....	14
9.3	Power Spectral Density	16
9.4	6 dB Bandwidth and 99% Occupied Bandwidth.....	18
9.5	Spurious RF Conducted Emissions	21
9.6	Band Edge.....	24
9.7	Spurious Radiated Emissions for Transmitter.....	26
10	Test Equipment List	35
11	System Measurement Uncertainty	37

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Guankou Erlu, Nantou, Nanshan District, Shenzhen, Guangdong, China

Telephone: 86 755 8828 6998

Fax: 86 755 8828 5299

FCC Registration No.: 514049

FCC Designation Number: CN5009

ISED CAB identifier: CN0077

IC Registration No.: 10320A

3 Description of the Equipment Under Test

Product:	Robot Vacuum Cleaner
Model no.:	Q10
Product Marketing Name (PMN):	Robot Vacuum Cleaner
Hardware Version Identification No. (HVIN):	Q10
FCC ID:	2BELS-Q10
IC:	32336-Q10
Options and accessories:	<p>Base station Manufacturer: Shenzhen Topband Co., Ltd. Model: Q10-S Input: 120VAC, 60Hz, 24W for Charging, 80W for Drying, 800W for Heating water, 1000W for Collecting dust Output: DC23.65V, 2.5A</p>
Ratings:	<p>Input: DC23.65V, 2.5A (for charging only) Battery: 14.4V, 5000mAh</p>
RF Transmission Frequency:	2402MHz - 2480MHz for BLE (1Mbps)
No. of Operated Channel:	40 for BLE (1Mbps)
Modulation:	GFSK
Antenna Type:	Integrated FPC antenna
Antenna Gain:	4.2 dBi for Bluetooth
Description of the EUT:	<p>The EUT is a Robot Vacuum Cleaner supports Wi-Fi and Bluetooth functions: 2412MHz - 2462MHz for 2.4GHz Wi-Fi; 2402MHz - 2480MHz for BLE (1Mbps); 2402MHz - 2480MHz for BR/EDR.</p>
Remark:	This report is only for BLE (1Mbps).

NOTE 1: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 April 2018 + Amendment 1 March 2019 + Amendment 2 February 2021	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 3 August 2023	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10-2020.

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C/ RSS-247 Issue 3/RSS-Gen Issue 5		Test Site	Test Result			Test Environment
Test Condition			Pass	Fail	N/A	
§15.207 & RSS-GEN 8.8	Conducted emission AC power port	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 22.4°C H: 53.2%
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted peak output power	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 23.2°C H: 51.5%
RSS-247 5.4(d)	Equivalent Isotropic Radiated Power	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 23.2°C H: 51.5%
§15.247(a)(2) & RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 23.2°C H: 51.5%
§15.247(e) & RSS-247 5.2(b)	Power spectral density	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 23.2°C H: 51.5%
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 23.2°C H: 51.5%
§15.247(d) & RSS-247 5.5	Band edge	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 23.2°C H: 51.5%
§15.247(d) & §15.209 & §15.205 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	T: 24.7°C H: 49.3%
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--

Note 1: N/A=Not Applicable.

Note 2: The EUT uses an Integrated FPC antenna, which gain is 4.2dBi for Bluetooth. In accordance to §15.203 & RSS-Gen 6.8, it is considered sufficiently to comply with the provisions of this section.

Note 3: T: Temperature, H: Humidity.

6 General Remarks

The conducted emissions of Q10 were tested with a Base station, and the input voltage is 120VAC/60Hz; The RF tests of Q10 were tested with battery operation, the battery voltage is 14.4VDC.

This submittal(s) (test report) is intended for FCC ID: 2BELS-Q10, complies with Section 15.207, 15.209, 15.205, 15.247 of the FCC Part 15, Subpart C rules.

This submittal(s) (test report) is intended for IC: 32336-Q10, complies with RSS-247 and RSS-Gen.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: 2024-07-09

Testing Start Date: 2024-07-17


Testing End Date: 2024-08-09

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:

Prepared by:

Tested by:



Jessie He
Project Manager

Myron Yu
Project Engineer


Carry Cai

Carry Cai
Test Engineer


7 Test Setups

7.1 Radiated test setups


9kHz - 30MHz



Below 1GHz




Above 1GHz



7.2 Conducted RF test setups



7.3 AC Power Line Conducted Emission test setups



8 Systems Test Configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MODEL NO.	MANUFACTURER	S/N
Laptop	X220	ThinkPad	EMC-158

Test software information:

Test Software Version	Adb tool	
Modulation	Setting TX Power	Packet Type
GFSK	Default parameters	PRBS9

The system was configured to non-hopping mode, testing channel 0, 19, 39.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Limit


According to §15.207 & RSS-GEN 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Remark: ** Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : Robot Vacuum Cleaner
 M/N : Q10
 Operating Condition : Charging + BLE Transmitting
 Test Specification : Line
 Comment : AC 120V/60Hz



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.173500	57.49	---	64.77	7.27	L1	9.67
0.318000	42.75	---	59.76	17.01	L1	9.67
0.434000	40.59	---	57.18	16.58	L1	9.68
2.394000	31.47	---	56.00	24.53	L1	9.75
16.238000	34.97	---	60.00	25.03	L1	9.99
24.494000	33.40	---	60.00	26.60	L1	10.13

Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.173500	---	41.40	54.79	13.39	L1	9.67
0.173500	55.06	---	64.79	9.73	L1	9.67

Conducted Emission

Product Type : Robot Vacuum Cleaner
 M/N : Q10
 Operating Condition : Charging + BLE Transmitting
 Test Specification : Neutral
 Comment : AC 120V/60Hz



Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Corr. (dB)
0.173500	57.24	---	64.58	7.34	N	9.67
0.222000	49.69	---	62.74	13.05	N	9.67
0.438000	43.17	---	57.10	13.93	N	9.67
1.458000	30.92	---	56.00	25.08	N	9.70
9.606000	32.91	---	60.00	27.09	N	9.91
16.242000	32.23	---	60.00	27.77	N	10.02

Final_Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Corr. (dB)
0.173500	---	40.43	54.79	14.36	N	9.67
0.173500	54.81	---	64.79	9.98	N	9.67

9.2 Conducted Peak Output Power & EIRP

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following test receiver settings:
Span = approximately 5 times the 6dB bandwidth, centered on a channel need to test,
RBW > the 6dB bandwidth of the emission being measured, $VBW \geq 3RBW$,
Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power and record the results in the test report.
5. Repeat above procedures until all frequencies measured were complete.

Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

According to & RSS-247 5.4(d), EIRP limit as below:


Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤4	≤36

Test Results

Mode	Frequency (MHz)	Gain (dBi)	Conducted Output Power (dBm)	EIRP (dBm)	Conducted Output Power Limit (dBm)	EIRP Limit (dBm)	Verdict
BLE 1Mbps	2402	4.2	0.79	4.99	<=30	<=36	Pass
	2440	4.2	0.39	4.59	<=30	<=36	Pass
	2480	4.2	0.60	4.80	<=30	<=36	Pass

Note1: E.I.R.P = Measured Power + Antenna Gain

Test Graphs



9.3 Power Spectral Density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
4. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW \geq 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
5. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
6. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3KHz]


≤ 8

Test Results

Mode	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
		Result	Limit	
BLE 1Mbps	2402	-14.29	≤ 8	Pass
	2440	-14.65	≤ 8	Pass
	2480	-14.46	≤ 8	Pass

Note1: Antenna Gain: Ant1: 3.20dBi;

Test Graphs



9.4 6 dB Bandwidth and 99% Occupied Bandwidth

Test Method for 6 dB Bandwidth

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
RBW=100KHz, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Use the automatic bandwidth measurement capability of an instrument, use the X dB bandwidth mode with X set to 6 dB.
5. Allow the trace to stabilize, record the 6 dB Bandwidth value.

Limit

Limit [kHz]

\geq 500

Test Method for 99 % Bandwidth

1. Connect EUT test port to spectrum analyzer.
Use the following spectrum analyzer settings:
RBW=1% to 5% of the actual occupied, VBW \geq 3RBW, Sweep = auto,
Detector function = peak, Trace = max hold
2. Use the occupied bandwidth measurement capability of test receiver.
3. Allow the trace to stabilize, record the occupied bandwidth value.

Limit

Limit [kHz]

Test Results


6dB bandwidth

Mode	Frequency (MHz)	6dB Bandwidth (MHz)		Verdict
		Result	Limit	
BLE 1Mbps	2402	0.723	\geq 0.5	Pass
	2440	0.723	\geq 0.5	Pass
	2480	0.727	\geq 0.5	Pass


99% bandwidth

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Verdict
		Result	Limit	
BLE 1Mbps	2402	1.029	/	Pass
	2440	1.029	/	Pass
	2480	1.029	/	Pass

Test Graphs of 6dB Bandwidth



Test Graphs of 99% Bandwidth



9.5 Spurious RF Conducted Emissions

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.


Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20


Test Results

Mode	Frequency (MHz)	Level of Reference (dBm)	Limit (dBm)	Verdict
BLE 1Mbps	2402	0.09	-19.91	Pass
	2440	-0.32	-20.32	Pass
	2480	-0.13	-20.13	Pass
	Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.			

Test Graphs of Reference Level



Test Graphs of Conducted Spurious Emissions



9.6 Band Edge

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.

Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS-247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB.

Frequency Range MHz	Limit (dBc)
30-25000	-20

Test Results

Mode	Frequency (MHz)	Level of Reference (dBm)	Limit (dBm)	Verdict
BLE 1Mbps	2402	0.09	-19.91	Pass
	2480	-0.13	-20.13	Pass

Test Graphs



9.7 Spurious Radiated Emissions for Transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:
 - 1) Procedure for Unwanted Emissions Measurements Below 1000 MHz

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 100 KHz to 120KHz, VBW \geq RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 2) For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 1MHz, VBW \geq RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 3) Procedures for average unwanted emissions measurements above 1000 MHz
 - a) RBW = 1MHz.
 - b) VBW \ [3 x RBW].
 - c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2. Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
 - d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
 - e) Sweep time = auto.
 - f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
 - g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is [10 log (1 / D)], where D is the duty cycle. For example, if the transmit duty

cycle was 50%, then 3 dB shall be added to the measured emission levels.

- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission(AV) at frequency above 1GHz.

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS 247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in § 15.209(a) and RSS-Gen is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a) and RSS-Gen section 8.9, must also comply with the radiated emission limits specified in § 15.209(a) and RSS-Gen section 8.10.

Frequency MHz	Field Strength μV/m	Field Strength dBμV/m	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit 3m(dBμV/m)=Limit 300m(dBμV/m)+40Log(300m/3m) (Below 30MHz)


Note 2: Limit 3m(dBμV/m)=Limit 30m(dBμV/m)+40Log(30m/3m) (Below 30MHz)

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.


Transmitting spurious emission test result as below:

Emission below 1GHz



Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
50.693333	24.62	40.00	15.38	200.0	H	0.0	17.98
105.983333	23.88	43.50	19.62	100.0	H	21.0	16.25
195.870000	23.45	43.50	20.05	100.0	H	245.0	16.57
344.226111	28.19	46.00	17.81	200.0	H	296.0	20.23
606.772778	34.78	46.00	11.22	200.0	H	261.0	25.34
908.981667	38.56	46.00	7.44	100.0	H	29.0	29.04




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
44.927222	24.26	40.00	15.74	100.0	V	63.0	17.65
102.157222	22.84	43.50	20.66	100.0	V	232.0	16.42
196.462778	25.13	43.50	18.37	100.0	V	232.0	16.61
331.885556*	28.20	46.00	17.81	200.0	V	325.0	19.52
611.353333*	34.58	46.00	11.42	100.0	V	274.0	25.35
956.080556	39.07	46.00	6.93	200.0	V	272.0	28.98


Emission above 1GHz

BLE_1Mbps_Low Channel:




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2306.000000	43.94	74.00	30.06	150.0	H	279.0	-3.20
3188.500000	48.24	74.00	25.76	150.0	H	251.0	-0.36
4319.000000*	48.22	74.00	25.78	150.0	H	151.0	2.48
7077.500000	39.35	74.00	34.65	150.0	H	204.0	5.26
10258.500000	40.43	74.00	33.57	150.0	H	120.0	8.75
14135.500000	42.26	74.00	31.74	150.0	H	176.0	11.43




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2265.500000*	46.42	74.00	27.58	150.0	V	115.0	-3.04
2691.000000*	46.93	74.00	27.07	150.0	V	251.0	-2.04
4367.000000*	48.34	74.00	25.66	150.0	V	333.0	2.80
6262.000000	40.33	74.00	33.67	150.0	V	148.0	5.22
10237.000000	40.86	74.00	33.14	150.0	V	176.0	8.71
14487.500000*	42.58	74.00	31.42	150.0	V	232.0	12.18



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2353.984000*	46.09	74.00	27.91	150.0	H	0.0	-3.38
2390.288000	46.30	74.00	27.70	150.0	H	255.0	-3.05
2400.128000	47.53	74.00	26.47	150.0	H	31.0	-3.03
2401.920000	92.63	74.00	-18.63	150.0	H	31.0	-3.03



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2350.432000*	47.44	74.00	26.56	150.0	V	44.0	-3.42
2389.600000*	47.85	74.00	26.15	150.0	V	0.0	-3.05
2400.160000	48.78	74.00	25.22	150.0	V	329.0	-3.03
2401.744000	86.01	74.00	-12.01	150.0	V	153.0	-3.03

BLE_1Mbps _Middle Channel:



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2297.000000*	45.01	74.00	28.99	150.0	H	259.0	-3.25
3188.000000	46.12	74.00	27.88	150.0	H	1.0	-0.36
4665.000000*	48.89	74.00	25.11	150.0	H	0.0	4.32
6593.000000	39.21	74.00	34.79	150.0	H	94.0	5.23
10801.500000*	41.61	74.00	32.39	150.0	H	35.0	9.23
15224.000000	43.95	74.00	30.05	150.0	H	152.0	13.29




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2294.000000*	48.28	74.00	25.72	150.0	V	166.0	-3.25
3192.000000	48.19	74.00	25.81	150.0	V	166.0	-0.36
4426.500000	47.78	74.00	26.22	150.0	V	235.0	3.19
7193.000000	39.15	74.00	34.85	150.0	V	176.0	5.34
9831.000000	40.42	74.00	33.58	150.0	V	120.0	8.21
13802.000000	41.90	74.00	32.10	150.0	V	291.0	10.85


BLE_1Mbps_High Channel:

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2290.000000*	44.48	74.00	29.52	150.0	H	265.0	-3.25
3186.000000	47.67	74.00	26.33	150.0	H	224.0	-0.36
4411.000000	47.87	74.00	26.13	150.0	H	197.0	3.09
7037.500000	39.21	74.00	34.79	150.0	H	316.0	5.27
9746.000000	39.51	74.00	34.49	150.0	H	148.0	8.17
14760.500000	43.05	74.00	30.95	150.0	H	148.0	12.61


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2268.000000*	47.49	74.00	26.51	150.0	V	162.0	-3.07
3188.000000	50.44	74.00	23.56	150.0	V	307.0	-0.36
4814.000000*	49.44	74.00	24.56	150.0	V	356.0	4.24
6390.000000	40.53	74.00	33.47	150.0	V	258.0	5.08
9122.000000*	40.33	74.00	33.67	150.0	V	342.0	7.86
14316.000000	42.90	74.00	31.10	150.0	V	231.0	11.75



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2479.750000	93.95	74.00	-19.95	150.0	H	39.0	-3.04
2483.600000*	43.76	74.00	30.24	150.0	H	184.0	-3.06
2500.275000	42.96	74.00	31.04	150.0	H	248.0	-3.16
2518.875000	44.50	74.00	29.50	150.0	H	166.0	-3.10



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2480.237500	89.31	74.00	-15.31	150.0	V	66.0	-3.04
2483.500000*	46.06	74.00	27.94	150.0	V	355.0	-3.06
2500.037500	47.75	74.00	26.25	150.0	V	355.0	-3.16
2522.225000	47.32	74.00	26.68	150.0	V	359.0	-3.09

Remark:

- (1) “*” means the emission(s) appear within the restrict bands shall follow the requirement of § 15.205 and RSS-Gen section 8.10.
- (2) Data of measurement within frequency ranges 9kHz-30MHz and 18-26GHz are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report,
- (3) Level= Reading Level + Correction Factor
- (4) Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss

(The Reading Level is recorded by software which is not shown in the sheet)

10 Test Equipment List

Conducted Emission Test (AMN)(CSR #2)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-19-002	102590	1	2025-5-13
LISN	Rohde & Schwarz	ENV216	68-4-87-19-001	102472	1	2025-5-12
LISN	Rohde & Schwarz	ENV4200	68-4-87-14-001	100249	1	2025-5-13
Attenuator	Shanghai Huaxiang	TS2-26-3	68-4-81-16-003	080928189	1	2025-5-11
Cable	OUQIAO	RG142	68-4-90-19-005-A20	----	----	----
Test software	Rohde & Schwarz	EMC32	68-4-90-19-005-A01	Version10.35.02	N/A	N/A
Shielding Room	TDK	CSR #2	68-4-90-19-005	----	3	2025-10-15

Radiated Emission Test (9kHz-30MHz) (SAC-3 #1)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 7	68-4-74-19-001	102176	1	2025-5-13
Loop Antenna	Rohde & Schwarz	HFH2-Z2	68-4-80-14-006	100398	1	2025-7-24
Cable	HUBER-SUHNER	RG214	68-4-90-14-001-A21	----	----	----
3m Semi-anechoic chamber	TDK	SAC-3 #1	68-4-90-14-001	----	3	2026-10-25
Test software	Rohde & Schwarz	EMC32	68-4-90-14-001-A10	Version10.35.02	N/A	N/A

Radiated Emission Test (1GHz-18GHz) (SAC-3 #2)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2025-5-13
Wave Guide Antenna	ETS	3117	68-4-80-19-001	00218954	1	2025-4-10
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2025-5-11
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-002	100746	1	2025-5-11
Cable	OUQIAO	18DLB5-NMNM-7000	68-4-90-19-006-A22	----	----	----
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	3	2026-10-25
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A	N/A

Radiated Emission Test (18GHz-40GHz) (SAC-3 #2)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2025-5-13
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2025-7-2
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2025-7-17
Cable	JUNFLON	MWX241	68-4-90-19-006-A21	----	----	----



3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	3	2026-10-25
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A	N/A

RF Test System

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2025-5-11
RF Meas. and Switch Matrix Unit	TST PASS	TSCB3023R2	68-4-93-23-001	2811685c	1	2025-5-11
Cable	JUNFLON	J12J103539	68-4-90-19-003-A20	----	----	----
Cable	JUNFLON	J12J103539	68-4-90-19-003-A21	----	----	----
Cable	JUNFLON	J12J103539	68-4-90-19-003-A22	----	----	----
Test software	TST PASS	TST PASS	68-4-93-23-001-A03	Version 2.0	N/A	N/A
Test software	Tonscend	JS1120-3	68-4-74-14-006-A13	Version 2.6.77.0518	N/A	N/A
Shielding Room	TDK	TS8997	68-4-90-19-003	----	3	2025-10-15

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission in new shielding room (68-4-90-19-005) 150kHz-30MHz (for test using AMN ENV216)	3.15dB
Uncertainty for Radiated Emission in 3m chamber (68-4-90-14-001) 9kHz-30MHz	4.70dB
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 30MHz-1000MHz	Horizontal: 4.63dB; Vertical: 4.78dB
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 1000MHz-18000MHz	Horizontal: 5.38dB; Vertical: 5.38dB
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 18GHz-40GHz	5.29dB
Uncertainty for Conducted RF test with TS 8997	RF Power Conducted: 1.31dB Frequency test involved: 0.6×10^{-8} or 1%

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3 and 4.3.4.

---END OF REPORT---