

TEST REPORT

Applicant Name: Shenzhen Eve-Innovations Technology Co., Ltd
Address: Rm 802, Jinqi Zhigu Building, No.1 Tangling Road, Taoyuan Street, Nanshan, Shenzhen, Guangdong, China
Report Number: SZ4240116-03716E-RF-00A
FCC ID: 2BEN9-PYB

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: EVEBOT PrintInd Handheld Printer
Model No.: PYB-P
Multiple Model(s) No.: N/A
Trade Mark: N/A
Date Received: 2024/01/17
Issue Date: 2024/06/13

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

April Zhang
RF Engineer

Approved By:

Nancy Wang
RF Supervisor

Note: The information marked[#] is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
FCC§15.247 (I), §1.1307 (B) (3) &§2.1093 – RF EXPOSURE	13
APPLICABLE STANDARD	13
MEASUREMENT RESULT	13
FCC §15.203 – ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
FACTOR & OVER LIMIT CALCULATION.....	16
TEST DATA	16
FCC §15.209, §15.205 & §15.247(D) – UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	21
FACTOR & OVER LIMIT/MARGIN CALCULATION	21
TEST DATA	21
FCC §15.247(A) (2) –6 DB EMISSION BANDWIDTH.....	36
STANDARD APPLICABLE	36
TEST PROCEDURE	36
TEST DATA	36

FCC §15.247(B) (3)- PEAK OUTPUT POWER MEASUREMENT	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	38
FCC §15.247(E) – POWER SPECTRAL DENSITY.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST DATA	45
EUT PHOTOGRAPHS.....	46
TEST SETUP PHOTOGRAPHS	47

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	SZ4240116-03716E-RF-00A	Original Report	2024/06/13

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	EVEBOT PrintInd Handheld Printer
Tested Model	PYB-P
Multiple Model(s)	N/A
Frequency Range	BLE: 2402-2480MHz
Maximum Conducted Peak Output Power	BLE: 5.51dBm
Modulation Technique	BLE: GFSK
Antenna Specification [#]	1.33dBi (provided by the applicant)
Voltage Range	DC 7.4V from battery or DC 5V from type-C port
Sample serial number	2GPX-2 for Conducted and Radiated Emissions Test 2GPX-1 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

Objective

This report is in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.247 rules.

Test Methodology

All tests and measurements indicated in this document were performed in accordance ANSI C63.10-2013.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	$\pm 5\%$	
RF output power, conducted	0.72 dB(k=2, 95% level of confidence)	
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.94dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
	Temperature	$\pm 1^\circ\text{C}$
Humidity		$\pm 1\%$
	Supply voltages	$\pm 0.4\%$

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software

“ESPRFTest Tool_v2.8_manual.exe”[#] exercise software was used and the power level is 6[#]. The software and power level was provided by the applicant.

Duty cycle

Test Modes	Ton (ms)	Ton+off (ms)	Duty Cycle (%)	1/Ton (Hz)	VBW Setting (Hz)
Middle	2.064	2.513	82.13	484	500.00

BLE 1M



ProjectNo.:SZ4240116-03716E-RF Tester:Cheeb Huang
Date: 6.FEB.2024 13:12:35

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
UMIDIGI	Adapter	HF-0502000U	Unknown
Bull	Receptacle	Unknown	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter
Un-shielding Un-detachable Cable	1.5	Receptacle	LISN/AC Mains

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions below 1 GHz:



For Radiated Emissions above 1 GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1307 (b) (3) & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/01/16	2025/01/15
Rohde & Schwarz	LISN	ENV216	101613	2024/01/16	2025/01/15
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2023/08/03	2024/08/02
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2023/06/08	2024/06/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2024/07/19
ETS	Passive Loop Antenna	6512	29604	2023/07/07	2024/07/06
Unknown	Cable	Chamber Cable 1	F-03-EM236	2023/08/03	2024/08/02
Unknown	Cable	Chamber Cable 4	EC-007	2023/08/03	2024/08/02
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2023/04/18	2024/04/17
COM-POWER	Pre-amplifier	PA-122	181919	2023/06/29	2024/06/28
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2024/07/25
Unknown	RF Cable	KMSE	0735	2023/10/08	2024/10/07
Unknown	RF Cable	UFA147	219661	2023/10/08	2024/10/07
MICRO-TRONICS	2.8G Passband filter	HPM50111	F-03-EM217	2023/08/03	2024/08/02
A.H.System	Pre-amplifier	PAM-1840VH	190	2023/08/03	2024/08/02
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
RF Conducted Test					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200982	2023/12/18	2024/12/17
MARCONI	10dB Attenuator	6534/3	2942	2023/07/04	2024/07/03
Micro-Tronics	RF Cable	8082135	W1113	2023/07/04	2024/07/03

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (3) &§2.1093 – RF EXPOSURE**Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^{1/2} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result**For worst case:**

Mode	Frequency (MHz)	Max tune-up conducted power [#] (dBm)	Max tune-up conducted power [#] (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
Bluetooth	2402-2480	7.00	5.01	5	1.6	3	Yes
BLE	2402-2480	6.00	3.98	5	1.3	3	Yes

Result: Compliant

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has an internal antenna arrangement which was permanently attached and the maximum antenna gain[#] is 1.33dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data


Environmental Conditions

Temperature:	24 °C
Relative Humidity:	65 %
ATM Pressure:	101 kPa

The testing was performed by Macy Shi on 2024-02-02.


EUT operation mode: Transmitting (Maximum output mode BLE 1Mbps High channel)

AC 120V/60 Hz, Line



Freq	Read		LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV					
1	0.17	-1.03	19.52	10.40	10.15	55.03	-35.51 Average
2	0.17	4.50	25.05	10.40	10.15	65.03	-39.98 QP
3	0.30	0.41	20.84	10.31	10.12	50.28	-29.44 Average
4	0.30	7.91	28.34	10.31	10.12	60.28	-31.94 QP
5	0.50	0.24	20.59	10.20	10.15	46.00	-25.41 Average
6	0.50	9.50	29.85	10.20	10.15	56.00	-26.15 QP
7	0.56	2.86	23.32	10.27	10.19	46.00	-22.68 Average
8	0.56	14.90	35.36	10.27	10.19	56.00	-20.64 QP
9	3.60	-2.83	17.81	10.38	10.26	46.00	-28.19 Average
10	3.60	2.98	23.62	10.38	10.26	56.00	-32.38 QP
11	5.17	-3.34	17.37	10.49	10.22	50.00	-32.63 Average
12	5.17	2.18	22.89	10.49	10.22	60.00	-37.11 QP

AC 120V/60 Hz, Neutral



Condition: Neutral

Project : SZ4240116-03716E-RF

Tester : Macy shi

Note : BLE

Freq	Read		LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV					
1	0.17	-1.78	18.72	10.35	10.15	55.12	-36.40 Average
2	0.17	2.97	23.47	10.35	10.15	65.12	-41.65 QP
3	0.28	-2.45	18.38	10.67	10.16	50.90	-32.52 Average
4	0.28	0.44	21.27	10.67	10.16	60.90	-39.63 QP
5	0.40	-1.92	19.05	10.75	10.22	47.81	-28.76 Average
6	0.40	2.43	23.40	10.75	10.22	57.81	-34.41 QP
7	0.57	-0.43	20.45	10.68	10.20	46.00	-25.55 Average
8	0.57	6.77	27.65	10.68	10.20	56.00	-28.35 QP
9	3.80	-3.60	17.04	10.38	10.26	46.00	-28.96 Average
10	3.80	-0.20	20.44	10.38	10.26	56.00	-35.56 QP
11	6.81	-4.00	16.62	10.40	10.22	50.00	-33.38 Average
12	6.81	-0.42	20.20	10.40	10.22	60.00	-39.80 QP


FCC §15.209, §15.205 & §15.247(D) – UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.205, FCC 15.209, FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1-25 GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/\text{Ton}$

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23~25.6 °C
Relative Humidity:	50~55 %
ATM Pressure:	101 kPa

The testing was performed by Warren Huang on 2024-02-19 for below 1GHz and Dylan Yang from 2024-03-11 to 2023-03-25 for above 1GHz.

EUT operation mode: Transmitting


Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.

9 kHz-30 MHz: *(Maximum output mode BLE 1Mbps High channel)*

For the radiated spurious emission below 30MHz, the emissions are 20dB below the limit or the noise floor which are not recorded.

30-1000 MHz: (Maximum output mode BLE 1Mbps High channel)


Horizontal



Site : chamber
Condition : 3m Horizontal
Project Number: SZ4240116-03716E-RF
Note : BLE
Tester : Warren Huang

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	Level	dB _{BuV}	dB _{BuV/m}	
1	40.56	-10.74	23.76	13.02	40.00	-26.98	QP
2	144.97	-11.04	31.22	20.18	43.50	-23.32	QP
3	173.66	-12.12	28.50	16.38	43.50	-27.12	QP
4	388.16	-7.95	26.80	18.85	46.00	-27.15	QP
5	688.05	-1.74	26.60	24.86	46.00	-21.14	QP
6	920.50	1.26	27.40	28.66	46.00	-17.34	QP

Vertical



Site : chamber
Condition : 3m Vertical
Project Number: SZ4240116-03716E-RF
Note : BLE
Tester : Warren Huang

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
			MHz	dB/m	dBuV	dBuV/m	dB
1	33.58	-7.86	28.60	20.74	40.00	-19.26	QP
2	98.27	-15.60	24.50	8.90	43.50	-34.60	QP
3	145.03	-11.49	31.65	20.16	43.50	-23.34	QP
4	398.68	-7.63	25.31	17.68	46.00	-28.32	QP
5	698.08	-1.95	25.56	23.61	46.00	-22.39	QP
6	881.79	0.34	24.95	25.29	46.00	-20.71	QP

1-25 GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/Ave										
BLE 1M												
Low Channel 2402MHz												
4804.00	52.16	PK	H	2.42	54.58	74	-19.42					
4804.00	47.38	AV	H	2.42	49.80	54	-4.20					
4804.00	51.24	PK	V	2.42	53.66	74	-20.34					
4804.00	46.23	AV	V	2.42	48.65	54	-5.35					
Middle Channel 2440MHz												
4880.00	51.56	PK	H	2.58	54.14	74	-19.86					
4880.00	46.23	AV	H	2.58	48.81	54	-5.19					
4880.00	51.07	PK	V	2.58	53.65	74	-20.35					
4880.00	46.12	AV	V	2.58	48.70	54	-5.30					
High Channel 2480MHz												
4960.00	52.22	PK	H	2.68	54.90	74	-19.10					
4960.00	46.79	AV	H	2.68	49.47	54	-4.53					
4960.00	51.67	PK	V	2.68	54.35	74	-19.65					
4960.00	45.96	AV	V	2.68	48.64	54	-5.36					


Note:


Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude/Level = Factor + Reading


Margin = Corrected Amplitude/Level - Limit

The other spurious emission which is in the noise floor level was not recorded.

Test plots for Band Edge Measurements (Radiated):





BLE 1M			
Test Channel:	2480MHz	Ant. Polar. :	Horizontal





Condition : Horizontal
Project No.: SZ4240116-03716E
Tester : Dylan
Note : BLE_2480


Freq	Factor	Read		Limit		Over Limit
		Level	dB/m	Level	dBuV/m	
1	2487.644	-3.18	41.08	37.90	54.00	Average -16.10
2	2487.644	-3.18	55.24	52.06	74.00	peak -21.94





Listed with the worst harmonic margin test plot (Low channel):











FCC §15.247(a) (2) –6 dB EMISSION BANDWIDTH

Standard Applicable


According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions


Temperature:	25.1 °C
Relative Humidity:	49 %
ATM Pressure:	101 kPa

The testing was performed by Cheeb Huang on 2024-02-06.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Modes	Test Channel	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
BLE 1M	Lowest	2402	0.654	≥0.5
	Middle	2440	0.654	≥0.5
	Highest	2480	0.654	≥0.5

6 dB Bandwidth

FCC §15.247(b) (3)- PEAK OUTPUT POWER MEASUREMENT

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.9.1.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions


Temperature:	25.1 °C
Relative Humidity:	49 %
ATM Pressure:	101 kPa

The testing was performed by Cheeb Huang on 2024-02-06.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Modes	Test Frequency (MHz)	Peak Conducted Output Power (dBm)	Limits (dBm)
BLE 1M	2402	5.32	≤30
	2440	5.04	≤30
	2480	5.51	≤30



FCC §15.247(e) – POWER SPECTRAL DENSITY

Applicable Standard


According to FCC §15.247(e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions


Temperature:	25.1 °C
Relative Humidity:	49 %
ATM Pressure:	101 kPa

The testing was performed by Cheeb Huang on 2024-02-06.

Test Mode: Transmitting

Test Result: Compliant.

Test Modes	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1M	2402	-11.77	≤8.00
	2440	-11.55	≤8.00
	2480	-11.13	≤8.00




FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

Test Procedure



Test Method: ANSI C63.10-2013 Clause 11.11

1. Set the RBW =100 kHz.
2. Set the VBW $\geq 3 \times$ RBW.
3. Detector = peak
4. Sweep time = auto couple.
5. Trace mode=max hold
6. All trace to fully stabilize
7. Use the peak marker function to determine the maximum amplitude level.
Ensure that amplitude of all unwanted emissions outside of the authorized frequency band(excluding restricted frequency bands) is attenuated by at least the minimum requirement specified in 11.11.
Report the three highest emissions relative to the limit.

Test Data


Environmental Conditions

Temperature:	25.1 °C
Relative Humidity:	49 %
ATM Pressure:	101 kPa

The testing was performed by Cheeb Huang on 2024-02-06.

EUT operation mode: Transmitting

Test Result: Compliant.



EUT PHOTOGRAPHS

Please refer to the attachment SZ4240116-03716E-RF External photo and SZ4240116-03716E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment SZ4240116-03716E-RF Test Setup photo.

******* END OF REPORT *******