

Test Report

Report No.: MTi240118006-01E1

Date of issue: 2024-03-14

Applicant: Shenzhen Ruimeihong Electronics Come., LTD

Product: Wireless Remote Control

Model(s): RC200

FCC ID: 2BEPC-RC200

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

The test report is only used for customer scientific research, teaching, internal quality control and other purposes, and is for internal reference only.



Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1 General Description	5
1.1 Description of the EUT	5
1.2 Description of test modes	5
1.3 Environmental Conditions	6
1.4 Description of support units	6
1.5 Measurement uncertainty	6
2 Summary of Test Result	7
3 Test Facilities and accreditations	8
3.1 Test laboratory	8
4 List of test equipment	9
5 Evaluation Results (Evaluation)	10
5.1 Antenna requirement	10
6 Radio Spectrum Matter Test Results (RF)	10
6.1 20dB Bandwidth	10
6.2 Dwell Time	13
6.3 Duty Cycle	15
6.4 Radiated Emission (below 1GHz)	19
6.5 Radiated Emission (above 1GHz)	23
Photographs of the test setup	26
Photographs of the EUT	27

Test Result Certification	
Applicant:	Shenzhen Ruimeihong Electronics Come., LTD
Address:	A503, QingHuamei Rd 11, Guanhu str., Longhua Distr., Shenzhen, China
Manufacturer:	Shenzhen Ruimeihong Electronics Come., LTD
Address:	A503, QingHuamei Rd 11, Guanhu str., Longhua Distr., Shenzhen, China
Factory:	Shenzhen Ruimeihong Electronics Come., LTD
Address:	A503, QingHuamei Rd 11, Guanhu str., Longhua Distr., Shenzhen, China
Product description	
Product name:	Wireless Remote Control
Trade mark:	N/A
Model name:	RC200
Series Model(s):	N/A
Standards:	47 CFR Part 15.231
Test Method:	ANSI C63.10-2020
Date of Test	
Date of test:	2024-01-30 to 2024-03-14
Test result:	Pass

Test Engineer	:	Letter. Lan.
		(Letter Lan)
Reviewed By	:	Leon Chen
		(Leon Chen)
Approved By	:	Tom Xue
		(Tom Xue)

1 General Description

1.1 Description of the EUT

Product name:	Wireless Remote Control
Model name:	RC200
Series Model(s):	N/A
Model difference:	N/A
Electrical rating:	Input: 12V
Accessories:	N/A
Hardware version:	V1.0
Software version:	V1.0
Test sample(s) number:	MTi240118006-01S1001
RF specification	
Operating frequency range:	418 MHz
Channel number:	1
Modulation type:	OOK
Antenna(s) type:	PCB Antenna
Antenna(s) gain:	3dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX

1.2.1 Operation channel list

Channel	Frequency (MHz)
1	418

Test Channel List

Operation Band: 1

Bandwidth (MHz)	Channel (MHz)
0.015	418

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software:

For power setting, refer to below table.

Mode	418MHz
/	DTF

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
/	/	/	/
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Occupied channel bandwidth	±3 %
Time	±1 %
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (above 1GHz)	±5.3dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15.231	47 CFR 15.203	Pass
2	20dB Bandwidth	47 CFR Part 15.231	47 CFR 15.231(c)	Pass
3	Dwell Time	47 CFR Part 15.231	47 CFR 15.231(a)(1)	Pass
4	Field Strength of The Fundamental Signal	47 CFR Part 15.231	47 CFR 15.231(b)	Pass
5	Radiated Emission (below 1GHz)	47 CFR Part 15.231	47 CFR 15.231	Pass
6	Radiated Emission (above 1GHz)	47 CFR Part 15.231	47 CFR 15.231	Pass

Note: The device is a DC power supply and does not apply to conducted emissions.

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093



4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
20dB Bandwidth Dwell Time Duty Cycle						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2023-04-26	2024-04-25
2	ESG Series Analog Signal Generator	Agilent	E4421B	GB40051240	2023-04-25	2024-04-24
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2023-04-25	2024-04-24
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2023-04-25	2024-04-24
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2023-04-26	2024-04-25
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2023-04-26	2024-04-25
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2023-05-05	2024-05-04
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2023-04-25	2024-04-24
9	DC Power Supply	Agilent	E3632A	MY40027695	2023-05-05	2024-05-04
Field Strength of The Fundamental Signal Radiated Emission (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2023-06-11	2025-06-10
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2023-04-25	2024-04-24
5	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03
Radiated Emission (above 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2023-06-17	2025-06-16
3	Amplifier	Agilent	8449B	3008A01120	2023-06-26	2024-06-25
4	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03
5	MXA signal analyzer	Agilent	N9020A	MY54440859	2023-06-01	2024-05-31



5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Conclusion:	The antenna of the EUT is permanently attached. The EUT complies with the requirement of FCC PART 15.203.

6 Radio Spectrum Matter Test Results (RF)

6.1 20dB Bandwidth

Test Requirement:	47 CFR 15.231(c)
Test Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Method:	ANSI C63.10-2020, section 6.9.2
Procedure:	<p>a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.</p> <p>b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.</p> <p>c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.</p> <p>d) Steps a) through c) might require iteration to adjust within the specified tolerances.</p> <p>e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.</p> <p>f) Set detection mode to peak and trace mode to max hold.</p> <p>g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).</p> <p>h) Determine the “-xx dB down amplitude” using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the</p>



instrument.

i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “ f_{xx} dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “ f_{xx} dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

6.1.1 E.U.T. Operation:


Operating Environment:

Temperature: 26.8 °C Humidity: 21.4 % Atmospheric Pressure: 100 kPa

Pre test mode: Mode1

Final test mode: Mode1


6.1.2 Test Setup Diagram:



6.1.3 Test Data:

Frequency (MHz)	20dB emission bandwidth (MHz)	Limit (MHz)
418	0.015	≤ 1.045

Test plots as below




6.2 Dwell Time

Test Requirement:	47 CFR 15.231(a)(1)
Test Limit:	(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
Test Method:	ANSI C63.10-2020, Section 7.4
Procedure:	<p>For evaluation of periodic operation characteristics, the following procedure may be used:</p> <ul style="list-style-type: none"> a) Trigger the spectrum analyzer sweep on the RF waveform of the unlicensed wireless device. b) Set the spectrum analyzer sweep time greater than the specified time for periodic operation. c) Manually activate and deactivate the unlicensed wireless device and confirm that it ceases transmission within the specified time of deactivation. d) Document the test results. e) Verify and document that periodic transmissions at regular predetermined intervals do not exist, except where regulatory requirements allow polling or supervision transmissions, including data, to determine system integrity. <p>Compliance is addressed by an attestation supported by the equipment theory of operation.</p>

6.2.1 E.U.T. Operation:


Operating Environment:				
Temperature:	26.8 °C	Humidity:	21.4 %	Atmospheric Pressure: 100 kPa
Pre test mode:	Mode1			
Final test mode:	Mode1			

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

The EUT cease transmission within 5s






6.3 Duty Cycle


Test Limit:	No limit, only for Report Use.
Test Method:	ANSI C63.10-2020, Section 7.5
Procedure:	<p>a) Adjust and configure any EUT switches, controls, or input data streams to ensure that the EUT is transmitting or encoded to obtain the “worst-case” pulse ON time.</p> <p>b) Couple the final radio frequency output signal to the input of a spectrum analyzer. This may be performed by a radiated, direct connection (i.e., conducted) or by a “near-field” coupling method. The signal received shall be of sufficient level to trigger adequately the spectrum analyzer sweep display. NOTE—If the bandwidth of the pulse is greater than the RBW of the spectrum analyzer, then a similar measurement may be performed using a wideband digital storage oscilloscope (DSO).</p> <p>c) Adjust the center frequency of the spectrum analyzer to the center of the RF signal.</p> <p>d) Set the spectrum analyzer for ZERO SPAN.</p> <p>e) Adjust the SWEEP TIME to obtain at least a 100 ms period of time on the horizontal display axis of the spectrum analyzer.</p> <p>f) If the pulse train is periodic (i.e., consists of a series of pulses that repeat in a characteristic pattern over a constant time period), and the period (T) is less than or equal to 100 ms, then:</p> <ol style="list-style-type: none"> 1) Set the TRIGGER on the spectrum analyzer to capture at least one period of the pulse train, including any blanking intervals. 2) Determine the total maximum pulse “ON time” (t_{ON}) over one period of the pulse train. An example of a periodic pulse train and the associated period is shown in Figure 14. If the pulse train contains pulses of different widths, then t_{ON} is determined by summing the duration of all of the pulses within the pulse train [i.e., $t_{ON} = \sum(t_1 + t_2 + \dots + t_n)$]. 3) The duty cycle is then determined by dividing the total maximum “ON time” by the period of the pulse train (t_{ON}/T). g) If the pulse train is nonperiodic or is periodic with a period that exceeds 100 ms, or as an alternative to step f), then: <ol style="list-style-type: none"> 1) Set the TRIGGER on the spectrum analyzer to capture the greatest amount of pulse “ON time” over 100 ms. 2) Find the 100 ms period that contains the maximum “on time”; this may require summing the duration of multiple pulses as described in step f2). 3) Determine the duty cycle by dividing the total maximum “ON time” by 100 ms ($t_{ON}/100 \text{ ms}$).

6.3.1 E.U.T. Operation:

Operating Environment:				
Temperature:	26.8 °C	Humidity:	21.4 %	Atmospheric Pressure: 100 kPa
Pre test mode:	Mode1			
Final test mode:	Mode1			

6.3.2 Test Setup Diagram:





6.3.3 Test Data:


Note:



1. Measurement (dB μ V/m) = Reading Level (dB μ V) + Correct Factor(dB/m)
2. AV Level (dB μ V/m) = PK Level (dB μ V/m) + AV Factor(dB)


	On time (ms)	Times	T _{on} (ms)	Total T _{on} time (ms)
T _{on1}	0.82	27	22.14	27.74
T _{on2}	0.4	14	5.6	

Total T _{on} time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle correction factor (dB)
27.74	65	0.427	-7.39

Note: Duty cycle correction factor = $20 * \log (\text{Duty cycle})$









6.4 Radiated Emission (below 1GHz)

Test Requirement:	47 CFR 15.231		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p> <p>In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:</p>			
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	40.66-40.70	2.250	225
	70-130	1.250	125
	130-174	11250 to 3750	1125 to 375
	174-260	3.750	375
	260-470	13750 to 12500	1375 to 1250
	Above 470	12500	1250
Test Method:	ANSI C63.10-2020, Section 6.5		
Procedure:	<p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin</p>		



would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the middle channel, the Highest channel.

h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.

i. Repeat above procedures until all frequencies measured was complete.
Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

6.4.1 E.U.T. Operation:


Operating Environment:

Temperature: 26.8 °C	Humidity: 21.4 %	Atmospheric Pressure: 100 kPa
----------------------	------------------	-------------------------------

Pre test mode:	Mode1
----------------	-------

Final test mode:	Mode1
------------------	-------


6.4.2 Test Setup Diagram:





6.4.3 Test Data:

Mode1 / Polarization: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1		44.2752	34.46	-7.50	26.96	40.00	-13.04	QP	
2		119.8556	30.87	-9.22	21.65	43.50	-21.85	QP	
3		166.0680	40.61	-11.02	29.59	43.50	-13.91	QP	
4		216.7828	30.70	-8.89	21.81	46.00	-24.19	QP	
5		297.2241	31.50	-4.84	26.66	46.00	-19.34	QP	
6	*	418.0000	78.87	-4.76	74.11	80.30	-6.19	QP	
7		709.1823	28.32	0.32	28.64	46.00	-17.36	QP	

Note: 418M is the main frequency



Mode1 / Polarization: Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over	Detector	Comment
1	44.2752	37.86	-7.50	30.36	40.00	-9.64	QP	
2	77.3212	38.59	-12.89	25.70	40.00	-14.30	QP	
3	100.2286	27.72	-8.60	19.12	43.50	-24.38	QP	
4	171.3926	32.56	-11.13	21.43	43.50	-22.07	QP	
5	231.7179	32.42	-7.26	25.16	46.00	-20.84	QP	
6 *	418.0000	68.72	-4.76	63.96	80.30	-16.34	QP	
7	629.4772	26.27	0.39	26.66	46.00	-19.34	QP	

Note: 418M is the main frequency



6.5 Radiated Emission (above 1GHz)

Test Requirement:	47 CFR 15.231		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p> <p>In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:</p>			
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	40.66-40.70	2.250	225
	70-130	1.250	125
	130-174	¹ 1250 to 3750	¹ 125 to 375
	174-260	3.750	375
	260-470	¹ 3750 to 12500	¹ 375 to 1250
	Above 470	12500	1250
Test Method:	ANSI C63.10-2020, Section 6.6		
Procedure:	<p>a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified</p>		



and then reported in a data sheet.
g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
i. Repeat above procedures until all frequencies measured was complete.
Remark:
1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

6.5.1 E.U.T. Operation:


Operating Environment:

Temperature:	26.8 °C	Humidity:	21.4 %	Atmospheric Pressure:	100 kPa
--------------	---------	-----------	--------	-----------------------	---------

Pre test mode:	Mode1
----------------	-------

Final test mode:	Mode1
------------------	-------

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dB μ V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)	Peak/AVG	H/V
TX mode							
1299.000	50.16	-15.61	34.55	74.00	-39.45	Peak	V
/	/	/	27.16	54.00	-26.84	AVG	V
1732.000	50.52	-13.71	36.81	74.00	-37.19	Peak	V
/	/	/	29.42	54.00	-24.58	AVG	V
2411.000	52.66	-12.41	40.25	74.00	-33.75	Peak	V
/	/	/	32.86	54.00	-21.14	AVG	V
4485.000	51.58	-8.57	43.01	74.00	-30.99	peak	V
/	/	/	35.62	54.00	-30.99	AVG	V
1299.000	51.13	-15.61	35.52	74.00	-38.48	Peak	H
/	/	/	28.13	54.00	-25.87	AVG	H
1732.000	51.78	-13.71	38.07	74.00	-35.93	Peak	H
/	/	/	30.68	54.00	-23.32	AVG	H
2411.000	52.17	-12.41	39.76	74.00	-34.24	Peak	H
/	/	/	32.37	54.00	-21.63	AVG	H
4553.000	52.18	-8.66	43.52	74.00	-30.48	peak	H
/	/	/	36.13	54.00	-30.48	AVG	H

Note: correction factor =-7.39 dB

Photographs of the test setup

Refer to Appendix - Test Setup Photos

Photographs of the EUT

Refer to Appendix - EUT Photos

----End of Report----