

TEST REPORT

FCC MPE Test for flexAU10-3.55G-4TW
Certification

APPLICANT

HFR, Inc.

REPORT NO.

HCT-RF-2312-FC022

DATE OF ISSUE

February 27, 2024

Tested by
Kyung Soo Kang



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

**HCT Co., Ltd.**

74, Seocheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.
HCT-RF-2312-FC022

DATE OF ISSUE
February 27, 2024

Additional Model
flexAU10-3.55G-4TC

Applicant	HFR, Inc. Hana EZ Tower, 5F, 10 Seongnam-daero 43beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, 13636, Korea
Eut Type	flexAU
Model Name	flexAU10-3.55G-4TW
FCC ID	2BEQ9-AU10-3550-4T
Location of Test	<input checked="" type="checkbox"/> Permanent Testing Lab <input type="checkbox"/> On Site Testing (Address: 74, Seocheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	February 27, 2024	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The above Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme) / A2LA(American Association for Laboratory Accreditation)(4114.01), which signed the ILAC-MRA.

RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	^(a) (100)	30
1.34 - 30.....	824/f	2.19/f	^(a) (180/f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

^(a) = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

3.1 MPE calculation for standalone operations: Ceiling

- (4 Port) 5G NR n48 10 MHz [1 Carrier]

Maximum output Power at antenna input terminal	21.00	dBm
Maximum output Power at antenna input terminal	125.89	mW
Prediction distance	20.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	5.07	dBi
Antenna Gain(numeric)	3.214	-
Power density at prediction frequency(S)	0.0805	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 20 MHz [1 Carrier]

Maximum output Power at antenna input terminal	24.01	dBm
Maximum output Power at antenna input terminal	251.77	mW
Prediction distance	20.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	5.07	dBi
Antenna Gain(numeric)	3.214	-
Power density at prediction frequency(S)	0.1610	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 40 MHz [1 Carrier]

Maximum output Power at antenna input terminal	27.02	dBm
Maximum output Power at antenna input terminal	503.50	mW
Prediction distance	20.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	5.07	dBi
Antenna Gain(numeric)	3.214	-
Power density at prediction frequency(S)	0.3219	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 60 MHz [1 Carrier]

Maximum output Power at antenna input terminal	28.81	dBm
Maximum output Power at antenna input terminal	760.33	mW
Prediction distance	20.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	5.07	dBi
Antenna Gain(numeric)	3.214	-
Power density at prediction frequency(S)	0.4861	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 100 MHz [1 Carrier]

Maximum output Power at antenna input terminal	31.02	dBm
Maximum output Power at antenna input terminal	1264.74	mW
Prediction distance	20.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	5.07	dBi
Antenna Gain(numeric)	3.214	-
Power density at prediction frequency(S)	0.8086	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

3.2 MPE calculation for standalone operations: Wall**- (4 Port) 5G NR n48 10 MHz [1 Carrier]**

Maximum output Power at antenna input terminal	21.00	dBm
Maximum output Power at antenna input terminal	125.89	mW
Prediction distance	28.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	8.87	dBi
Antenna Gain(numeric)	7.709	-
Power density at prediction frequency(S)	0.0985	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 20 MHz [1 Carrier]

Maximum output Power at antenna input terminal	24.01	dBm
Maximum output Power at antenna input terminal	251.77	mW
Prediction distance	28.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	8.87	dBi
Antenna Gain(numeric)	7.709	-
Power density at prediction frequency(S)	0.1970	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 40 MHz [1 Carrier]

Maximum output Power at antenna input terminal	27.02	dBm
Maximum output Power at antenna input terminal	503.50	mW
Prediction distance	28.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	8.87	dBi
Antenna Gain(numeric)	7.709	-
Power density at prediction frequency(S)	0.3940	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 60 MHz [1 Carrier]

Maximum output Power at antenna input terminal	28.81	dBm
Maximum output Power at antenna input terminal	760.33	mW
Prediction distance	28.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	8.87	dBi
Antenna Gain(numeric)	7.709	-
Power density at prediction frequency(S)	0.5949	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- (4 Port) 5G NR n48 100 MHz [1 Carrier]

Maximum output Power at antenna input terminal	31.02	dBm
Maximum output Power at antenna input terminal	1264.74	mW
Prediction distance	28.00	cm
Prediction frequency	3 550.00	MHz
Antenna Gain(typical)	8.87	dBi
Antenna Gain(numeric)	7.709	-
Power density at prediction frequency(S)	0.9896	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²