

FCC RF Exposure Report

For

SHENZHEN HAOCHENG TECHNOLOGY CO.,LTD501, Main Building, Qiaocheng No.1 Plaza, No.2 shenyun Road, Gaofa Community, 

Shahe Street, Nanshan District, Shenzhen city

Model :T91

Report Number: WSCT-ANAB-R&E250600041A

Report Date: 04 July 2025

FCC ID: 2BEQO-T91

Prepared By: World Standardization Certification & Testing Group
(Shenzhen) Co., Ltd.
Building A-B, Baoli'an Industrial Park, No.58 and
60, Tangtou Avenue, Shiyan Street, Bao'an District,
Shenzhen City, Guangdong Province, China
Tel: +86-755-26996192
Fax: +86-755-86376605



Table of contents

1	General information	3
1.1	Notes	3
1.2	EUT Information	4
2	Testing laboratory	5
3	ACCREDITATIONS	5
4	Applicant and Manufacturer	5
5	Test standard/s:	5
6	Test result	6
7	Conclusion	7



WSCT**WSCT Modified History****WSCT**

REV.	Modification Description	Issued Date	Remark
REV.1.0	Initial Test Report Relesse	04 July 2025	Li Huaibi

1 General information**1.1 Notes**

The test results of this test report relate exclusively to the test item specified in this test report. Shenzhen Timeway Testing Laboratories does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report is not to be reproduced or published in full without the prior written permission.

1.2 EUT Information

Device Information:	
Product Type:	Smart Watch
Model:	T91
Trade Name:	NA
Software Version:	V1.03
Hardware Version:	K1670 V1.0
Device Type:	Portable device
Exposure Category:	uncontrolled environment / general population
Production Unit or Identical Prototype:	Production Unit
Antenna Type :	Wire Antenna
Device Operating Configurations:	
Modulation:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Channel Separation:	BT:1MHz BLE:2MHz
Operation Frequency:	2402MHz~2480MHz
Antenna Gain:	-16.41dBi
Power Source:	Li-ion Battery: LD 442222 3.8V 220mAh 0.836Wh

Note: The test results of this test report relate exclusively to the test item specified in this test report. World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report is not to be reproduced or published in full without the prior written permission.



2 Testing laboratory

Test Site	World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.
Laboratory A:	Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtou Avenue, Shiyuan Street, Bao'an District, Shenzhen City, Guangdong Province, China
TEL:	+86-755-26996192
FAX:	+86-755-86376605

3 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:2017.

USA

ANAB - Certificate Number: AT-3951

China

CNAS (Registration Number: L3732)

Canada

ISED(CAB identifier:CN0178)

Copies of granted accreditation certificates are available for downloading from our web site,

<http://www.wsct-cert.com>

4 Applicant and Manufacturer

Applicant/Client Name:	SHENZHEN HAOCHEUNG TECHNOLOGY CO.,LTD
Applicant Address:	501, Main Building, Qiaocheng No.1 Plaza, No.2 shenyun Road, Gaofa Community, Shahe Street, Nanshan District, Shenzhen city
Manufacturer Name:	SHENZHEN HAOCHEUNG TECHNOLOGY CO.,LTD
Manufacturer Address:	501, Main Building, Qiaocheng No.1 Plaza, No.2 shenyun Road, Gaofa Community, Shahe Street, Nanshan District, Shenzhen city

5 Test standards:

No.	Identity	Document Title
1	47 CFR Part 15C	Radio frequency devices intentional radiators
2	47 CFR Part 2.1093	Radio frequency radiation exposure evaluation: portable devices
3	KDB447498 D01	General RF Exposure Guidance v06



6 Test result

I .According KDB 447498 D01 4.3.1 General SAR test exclusion guidance

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops and tablets, etc.

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f (\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- 1). $f (\text{GHz})$ is the RF channel transmit frequency in GHz
- 2) Power and distance are rounded to the nearest mW and mm before calculation
- 3) The result is rounded to one decimal place for comparison
- 4) The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz.



BT:

Test Mode	Channel Frequency (GHz)	Conducted power (dBm)	Conducted power (mW)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	5.98	3.96	6.50	4.47	5.00	1.385	3.00	Yes
	2.441	6.29	4.26	6.50	4.47	5.00	1.396	3.00	Yes
	2.480	5.86	3.85	6.50	4.47	5.00	1.407	3.00	Yes
π/4-DQPSK	2.402	7.65	5.82	8.50	7.08	5.00	2.194	3.00	Yes
	2.441	8.06	6.40	8.50	7.08	5.00	2.212	3.00	Yes
	2.480	7.54	5.68	8.50	7.08	5.00	2.230	3.00	Yes
8-DPSK	2.402	8.19	6.59	9.00	7.94	5.00	2.462	3.00	Yes
	2.441	8.52	7.11	9.00	7.94	5.00	2.482	3.00	Yes
	2.480	8.02	6.34	9.00	7.94	5.00	2.502	3.00	Yes

Test Mode	Channel Frequency (GHz)	Conducted power (dBm)	Conducted power (mW)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.402	2.93	1.96	3.50	2.24	5.00	0.694	3.00	Yes
	2.440	3.35	2.16	3.50	2.24	5.00	0.700	3.00	Yes
	2.480	2.93	1.96	3.50	2.24	5.00	0.705	3.00	Yes

7 Conclusion

For the max result : $2.502 \leqslant$ FCC Limit 3.0 for 1g SAR.

--END OF REPORT--

