


# TEST REPORT

|                                       |                                                                                                                                                      |                                                                                       |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| FCC ID.....:                          | 2BEQO-X11                                                                                                                                            |                                                                                       |
| Test Report No.....:                  | TCT250422E035                                                                                                                                        |                                                                                       |
| Date of issue.....:                   | May 27, 2025                                                                                                                                         |                                                                                       |
| Testing laboratory .....              | SHENZHEN TONGCE TESTING LAB                                                                                                                          |                                                                                       |
| Testing location/ address:            | 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China |                                                                                       |
| Applicant's name.....:                | SHENZHEN HAOCHENG TECHNOLOGY CO., LTD                                                                                                                |                                                                                       |
| Address.....:                         | 501, Main Building, Qiaocheng No.1 Plaza, No.2 shenyun Road, Gaofa Community, Shahe Street, Nanshan District, Shenzhen city, 518000 China            |                                                                                       |
| Manufacturer's name ...:              | SHENZHEN HAOCHENG TECHNOLOGY CO., LTD                                                                                                                |                                                                                       |
| Address.....:                         | 501, Main Building, Qiaocheng No.1 Plaza, No.2 shenyun Road, Gaofa Community, Shahe Street, Nanshan District, Shenzhen city, 518000 China            |                                                                                       |
| Standard(s) .....                     | FCC CFR Title 47 Part 1.1310<br>KDB 680106 D01 RF Exposure Wireless Charging App v04                                                                 |                                                                                       |
| Product Name.....:                    | MAGNETIC POWER BANK                                                                                                                                  |                                                                                       |
| Trade Mark .....                      | N/A                                                                                                                                                  |                                                                                       |
| Model/Type reference.....:            | X11                                                                                                                                                  |                                                                                       |
| Rating(s).....:                       | Rechargeable Li-ion Battery DC 3.85V                                                                                                                 |                                                                                       |
| Date of receipt of test item .....    | Apr. 22, 2025                                                                                                                                        |                                                                                       |
| Date (s) of performance of test.....: | Apr. 22, 2025 ~ May 27, 2025                                                                                                                         |                                                                                       |
| Tested by (+signature) ...:           | Rleo LIU                                                                                                                                             |  |
| Check by (+signature)....:            | Beryl ZHAO                                                                                                                                           |  |
| Approved by (+signature):             | Tomsin                                                                                                                                               |  |

**General disclaimer:**

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## Table of Contents

|                                                      |          |
|------------------------------------------------------|----------|
| <b>1. General Product Information .....</b>          | <b>3</b> |
| 1.1. EUT description .....                           | 3        |
| 1.2. Model(s) list.....                              | 3        |
| <b>2. General Information.....</b>                   | <b>4</b> |
| 2.1. Test environment and mode.....                  | 4        |
| 2.2. Description of Support Units.....               | 4        |
| <b>3. Facilities and Accreditations .....</b>        | <b>5</b> |
| 3.1. Facilities .....                                | 5        |
| 3.2. Location .....                                  | 5        |
| <b>4. Technical Requirements Specification .....</b> | <b>6</b> |
| 4.1. Requirements.....                               | 6        |
| 4.2. Test Setup .....                                | 7        |
| 4.3. Test Procedure .....                            | 8        |
| 4.4. Test Instruments List .....                     | 8        |
| 4.5. Test Result .....                               | 9        |
| 4.6. Test Set-up Photo .....                         | 11       |

## 1. General Product Information

### 1.1. EUT description

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Product Name.....:          | MAGNETIC POWER BANK                         |
| Model/Type reference.....:  | X11                                         |
| Sample Number.....:         | TCT250422E034-0101                          |
| Operation Frequency .....   | Watch: 327.08kHz<br>Mobile Phone: 150.69kHz |
| Output power.....:          | 1W/5W/7.5W/10W/15W                          |
| Modulation Technology ..... | Load modulation                             |
| Antenna Type.....:          | Inductive loop coil Antenna                 |
| Rating(s).....:             | Rechargeable Li-ion Battery DC 3.85V        |

### 1.2. Model(s) list

None.

## 2. General Information

### 2.1. Test environment and mode

| Operating Environment: |     |                                                                   |
|------------------------|-----|-------------------------------------------------------------------|
| Temperature:           |     | 25 °C                                                             |
| Humidity:              |     | 55 % RH                                                           |
| Atmospheric Pressure:  |     | 1010 mbar                                                         |
| Test Mode:             |     |                                                                   |
| AC Mode                | TM1 | Charging                                                          |
| DC Mode                | TM2 | wireless charging(5W)                                             |
|                        | TM3 | wireless charging(10W)+full load(5W)                              |
|                        | TM4 | wireless charging(1W)+full load(14W)                              |
| Remark:                |     | Wireless function is not supported when the EUT is being charged. |

### 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment    | Model No. | Serial No.     | FCC ID | Trade Name |
|--------------|-----------|----------------|--------|------------|
| Adapter      | EP-TA200  | R37M4PR7QD4SE3 | /      | SAMSUNG    |
| Mobile Phone | SM-G9350  | R28HA2ER3GT    | /      | SAMSUNG    |
| Apple Watch  | A1757     | /              | /      | Apple      |

### 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

#### 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

## 4. Technical Requirements Specification

### 4.1. Requirements

According to the item 5 of KDB 680106 D01 RF Exposure Wireless Charging App v04:


- 1) Power transfer frequency is below 1 MHz.  
**Wireless power transfer operation frequency is Watch: 327.08kHz**  
**Mobile Phone: 150.69kHz**
- 2) Output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.  
**The max output power is 15W**
- 3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)  
**The EUT is in physical contact with the the client device.**
- 4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions)  
**Mobile exposure**
- 5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1.  
**Yes, E-field and H-field strengths meet the requirements**
- 6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.  
**Yes, all the modes were tested**

Limits For Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposures</b>        |                               |                               |                                     |                          |
| 0.3-3.0                                                        | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0-30                                                         | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30-300                                                         | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1500                                                       | /                             | /                             | f/300                               | 6                        |
| 1500-100,000                                                   | /                             | /                             | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34                                                       | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30                                                        | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                                                         | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500                                                       | /                             | /                             | f/1500                              | 30                       |
| 1500-100,000                                                   | /                             | /                             | 1.0                                 | 30                       |


F=frequency in MHz  
 \*=Plane-wave equivalent power density  
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

## 4.2. Test Setup




### 4.3. Test Procedure

- 1) The RF exposure test was performed in an echoic chamber;
- 2) In addition to what is described in KDB 680106 D01, please measure and provide magnetic and electrical field strength at a distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 0cm, 2cm, 4cm, ..... 20cm. Which is between the edge of the charger and the edge of of probe, for test setup B;
- 3) The highest emission leve laws recorded and compared with limit as soon as measurement of each points (A,B, C,D, E)were completed;
- 4) According to the requirements if KDB 680106 D01 v04, If the center of the probe sensing element is located more than 5 mm (The sensitive elements are located approximately 8 mm below the external surface specified in user manual of EHP-200A) from the probe outer surface, the field strengths need to be estimated through modeling for those positions that are not reachable;
- 5) Use **Biot-Savart Law**, the value of 0 cm can be estimated through the results of 2 cm, according to the formula:



$$B = \frac{\mu_0 * I * N * R^2}{2 * (R^2 + x^2)^{3/2}}$$



$$B = \frac{\mu_0 * I * N}{2 * x}$$

**Remark:**

B: H-field(Unit:T)

$\mu_0$ : Space permeability= $4\pi \times 10^{-7}$

I (Unit: A): The current element passing through a radiated coil.

R: Radius of radiated coil, according to the coil specification: R=0.017m

X: The distance from the sensing elements of the probe to the edge of the radiated coil (the dimensions of EUT and load are take into account) (Unit: m)

N: Turns of the radiated coil, according to the coil specification: N=12.

### 4.4. Test Instruments List

| Equipment                            | Manufacturer | Model No. | Serial No. | Date of Cal.  | Due Date      |
|--------------------------------------|--------------|-----------|------------|---------------|---------------|
| Electric and Magnetic Field Analyzer | Narda        | EHP-200A  | 180ZX20511 | Jun. 27, 2024 | Jun. 26, 2025 |



## 4.5. Test Result

Test Result for Test setup B:

Watch (1W):

H-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, ..... 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (A/m)

| Test distance (cm) | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|--------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 2                  | 0.374                | 0.375                | 0.374                | 0.276                | 0.320                | 0.307                | 1.63         |
| 4                  | 0.223                | 0.230                | 0.258                | 0.231                | 0.127                | 0.122                | 1.63         |
| 6                  | 0.218                | 0.225                | 0.255                | 0.227                | 0.125                | 0.120                | 1.63         |
| 8                  | 0.210                | 0.217                | 0.247                | 0.224                | 0.122                | 0.118                | 1.63         |
| 10                 | 0.204                | 0.215                | 0.242                | 0.220                | 0.120                | 0.115                | 1.63         |
| 12                 | 0.202                | 0.210                | 0.238                | 0.216                | 0.117                | 0.112                | 1.63         |
| 14                 | 0.196                | 0.206                | 0.231                | 0.212                | 0.116                | 0.096                | 1.63         |
| 16                 | 0.192                | 0.202                | 0.224                | 0.210                | 0.113                | 0.089                | 1.63         |
| 18                 | 0.185                | 0.194                | 0.220                | 0.204                | 0.105                | 0.073                | 1.63         |
| 20                 | 0.182                | 0.190                | 0.215                | 0.201                | 0.101                | 0.065                | 1.63         |

Use the Biot-Savart Law to estimated the results of 2cm through 4 cm.

| Test position | Measure Value(A/m) | Estimated Value (A/m) | Agreement Ratio | Limits |
|---------------|--------------------|-----------------------|-----------------|--------|
| A             | 0.374              | 0.347                 | 7.22%           | 30%    |
| B             | 0.375              | 0.288                 | 23.20%          | 30%    |
| C             | 0.374              | 0.394                 | 5.35%           | 30%    |
| D             | 0.276              | 0.353                 | 27.90%          | 30%    |
| E             | 0.320              | 0.411                 | 28.44%          | 30%    |
| F             | 0.307              | 0.395                 | 28.66%          | 30%    |

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

| Test position | Estimated Value (A/m) | Limits(A/m) |
|---------------|-----------------------|-------------|
| A             | 0.842                 | 1.63        |
| B             | 0.567                 |             |
| C             | 0.790                 |             |
| D             | 0.583                 |             |
| E             | 1.618                 |             |
| F             | 1.552                 |             |

**Mobile Phone:**

5W, 10W, 15W load all have been tested, only worse case Max load (15W) is reported.

H-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, ..... 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (A/m)

| Test distance (cm) | Test Position A(A/m) | Test Position B(A/m) | Test Position C(A/m) | Test Position D(A/m) | Test Position E(A/m) | Test Position F(A/m) | Limits (A/m) |
|--------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--------------|
| 2                  | 0.408                | 0.415                | 0.412                | 0.294                | 0.322                | 0.315                | 1.63         |
| 4                  | 0.259                | 0.263                | 0.263                | 0.241                | 0.129                | 0.126                | 1.63         |
| 6                  | 0.251                | 0.255                | 0.256                | 0.235                | 0.128                | 0.124                | 1.63         |
| 8                  | 0.249                | 0.251                | 0.249                | 0.231                | 0.127                | 0.122                | 1.63         |
| 10                 | 0.244                | 0.246                | 0.244                | 0.227                | 0.124                | 0.118                | 1.63         |
| 12                 | 0.232                | 0.238                | 0.237                | 0.222                | 0.122                | 0.115                | 1.63         |
| 14                 | 0.216                | 0.226                | 0.223                | 0.216                | 0.117                | 0.107                | 1.63         |
| 16                 | 0.212                | 0.220                | 0.218                | 0.212                | 0.115                | 0.102                | 1.63         |
| 18                 | 0.205                | 0.217                | 0.215                | 0.206                | 0.110                | 0.094                | 1.63         |
| 20                 | 0.202                | 0.216                | 0.212                | 0.203                | 0.106                | 0.090                | 1.63         |

Use the Biot-Savart Law to estimated the results of 2cm through 4 cm.

| Test position | Measure Value(A/m) | Estimated Value (A/m) | Agreement Ratio | Limits |
|---------------|--------------------|-----------------------|-----------------|--------|
| A             | 0.408              | 0.403                 | 1.23%           | 30%    |
| B             | 0.415              | 0.329                 | 20.72%          | 30%    |
| C             | 0.412              | 0.401                 | 2.67%           | 30%    |
| D             | 0.294              | 0.368                 | 25.17%          | 30%    |
| E             | 0.322              | 0.418                 | 29.81%          | 30%    |
| F             | 0.315              | 0.408                 | 29.11%          | 30%    |

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

| Test position | Estimated Value (A/m) | Limits(A/m) |
|---------------|-----------------------|-------------|
| A             | 1.062                 | 1.63        |
| B             | 0.708                 |             |
| C             | 1.007                 |             |
| D             | 0.758                 |             |
| E             | 1.628                 |             |
| F             | 1.592                 |             |

#### 4.6. Test Set-up Photo

Please refer to document Appendix No.: TCT250422E034-A

**\*\*\*\*\*END OF REPORT\*\*\*\*\***