

Maximum Permissible Exposure Evaluation

FCC ID: 2BEQW-BW-4TA-BS

1. Client Information

Applicant	:	XING FENG TECHNOLOGY HONG KONG LIMITED
Address	:	RM 1002, 10/F EASEY COMM BLDG 253-261 HENNESSY RD WAN CHAI HK, 999077, China
Manufacturer	:	JUFENG TECH COMPANY LIMITED
Address	:	Lot S9, Street No. 11, Hai Son Industrial Park (Stage 3 + 4), Duc Hoa Ha Commune, Duc Hoa District, Long An Province, Viet Nam

2. General Description of EUT

EUT Name	:	Wire Free Camera with Battery
Models No.	:	BW-4TA-BS, CAM-BW4, CAM-2P-BW4
Model Difference	:	All PCB boards and circuit diagrams are the same, the only difference is that model names.
Sample ID	:	HC-C-202408-0071-01-01# & HC-C-202408-0071-01-02#
Product Description	:	Operation Frequency: 802.11b/g/n(HT20)/ax(HE20): 2412MHz~2462MHz 802.11n(HT40)/ax(HE40): 2422MHz~2452MHz
Power Rating	:	Input: DC 5V/1A
Li-ion Polymer Battery	:	DC 3.6V by 2600mAh Rechargeable Li-ion battery*2
Software Version	:	----
Hardware Version	:	----
Connecting I/O Port(S)	:	Please refer to the User's Manual

MPE Calculations

1. Antenna Gain:

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)
2.4G Wi-Fi	N/A	N/A	PIFA	3.5

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios} \leq 1.0$$



5. Test Result:

2.4G Wi-Fi Worst Maximum MPE Result								
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]
802.11b	1	2412	16	16±1	17	3.5	20	0.0223
		2437	16.6	17±1	18	3.5	20	0.0281
		2462	16.57	17±1	18	3.5	20	0.0281
802.11g	1	2412	15.53	16±1	17	3.5	20	0.0223
		2437	15.5	16±1	17	3.5	20	0.0223
		2462	15.27	15±1	16	3.5	20	0.0177
802.11n (HT20)	1	2412	15.75	16±1	17	3.5	20	0.0223
		2437	15.73	16±1	17	3.5	20	0.0223
		2462	15.44	15±1	16	3.5	20	0.0177
802.11n (HT40)	1	2422	16.22	16±1	17	3.5	20	0.0223
		2437	16.21	16±1	17	3.5	20	0.0223
		2452	16.1	16±1	17	3.5	20	0.0223
802.11ax (HE20)	1	2412	15.78	16±1	17	3.5	20	0.0223
		2437	15.69	16±1	17	3.5	20	0.0223
		2462	15.49	15±1	16	3.5	20	0.0177
802.11ax (HE40)	1	2422	16.29	16±1	17	3.5	20	0.0223
		2437	16.21	16±1	17	3.5	20	0.0223
		2452	16.11	16±1	17	3.5	20	0.0223

Note:

N_{TX}= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

Remark:

1. Output power including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.
4. Only the worst power was evaluated for each wireless function

6. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 2.4G WIFI: 2412~2462MHz

MPE limit S: 1mW/ cm²

The worst MPE is calculated as **0.0281mW/cm² < limit 1mW/cm²**. So, RF exposure limit warning or SAR test are not required. The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

For a more detailed features description, please refer to the RF Test Report.

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF THE REPORT-----