

TEST REPORT

Applicant Name : Shenzhen Xinyi Technology Co., Ltd
Address : C505, Bay Area Digital Warehouse, Taoyuan Community, Dalang Street, Longhua District, Shenzhen, China
Report Number : 2504T31635E-RFA
FCC ID: 2BERO-HY300X

Test Standard (s)

47 CFR §1.1307& §2.1091

Sample Description

Product Type: Smart Projector
Model No.: HY300X, HY300X-1, HY300X-3, HY300X-4, HY300X-5
Trade Mark: MAGCUBIC
Date Received: 2025-05-16
Report Date: 2025-07-03


Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:



Matt Liang
EMC Engineer

Approved By:



Bob Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked "#" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST FACILITY	4
MAXIMUM PERMISSIBLE EXPOSURE (MPE)	5
APPLICABLE STANDARD.....	5
RESULT	5
EXHIBIT A-EUT PHOTOGRAPHS	7

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2504T31635E-RFA	Original Report	2025-07-03

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Smart Projector
Tested Model	HY300X
Multiple Model	HY300X-1, HY300X-3, HY300X-4, HY300X-5
Model Difference [#]	The difference between the above models is only difference appearance color and model name. Please refer to DOS letter for details. The applicant provided model "HY300X" for testing.
Voltage Range [#]	DC 12V or 36V from adapter
Adapter Information [#]	Model: HYP317-360095US Input: 100-240V~, 50/60Hz 1.0A Max Output1: 36.0V ---0.95A Output2: 12.0V ---0.7A Total Output Power: 42.6W

Frequency Range	Bluetooth, BLE 1M/2M: 2402-2480MHz 2.4G Wi-Fi: 2412-2462MHz, 2422-2452MHz 5G Wi-Fi: 5150-5250MHz, 5725-5850MHz
Antenna Specification [#]	Bluetooth, BLE 1M/2M, 2.4G Wi-Fi: 3.32 dBi 5G Wi-Fi: 5150-5250MHz: 3.41dBi 5725-5850MHz: 4.90dBi (It is provided by the applicant.)
Sample Serial Number	331Q-6 (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts C and Part 2-Subpart J, Radiofrequency Radiation Exposure of the Federal Communication Commission rules.

The results were performed in order to determine compliance with FCC §2.1091 rules.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01.

MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Mode	Frequency (MHz)	Antenna Gain [#]		Tune up conducted power [#]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BT	2480	3.32	2.15	9.2	8.32	20	0.004	1.0
BLE	2480	3.32	2.15	8.0	6.31	20	0.003	1.0
2.4G WIFI	2462	3.32	2.15	23.5	223.87	20	0.096	1.0
5G WIFI	5200	3.41	2.19	12.2	16.60	20	0.007	1.0
	5745	4.90	3.09	12.0	15.85	20	0.010	1.0

Note 1: The tune-up conducted power and antenna gain are declared by the applicant.

Note 2: The Bluetooth and WIFI can't transmission simultaneously.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Annex: 2504T31635E-RF EUT EXTERNAL PHOTOGRAPHS and 2504T31635E-RF EUT INTERNAL PHOTOGRAPHS.

***** END OF REPORT *****