

Radio Test Report

Report No: STS2401144H01

Issued for

shenzhenshizhaozhaochuangxinyouxiangongsi

Room 8811, No. 82 Wangcheng Road, Yucui Community,
Longhua Street, Longhua District Shenzhen Guangdong
518110 China

Product Name: Speaker

Brand Name: HOTMAY

Model Name: HOTMAY BS1

Series Model(s): BS1, BS2, BS3, BS4, BS5, BSHD, HOT2,
HOT3, HOT4, HOT5, HOT1 HD, HOT1
plus, HOT amp, HOT spk, HOTSOUND,
HOTSUN, P1, P2, P3, P500, P1000, P1500

FCC ID: 2BESQ-9HOTMAY

Test Standards: FCC 47CFR §2.1091

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.



TEST REPORT

Applicant's Name : shenzhenshizhaozhaochuangxinyouxiangongsi
Address : Room 8811, No. 82 Wangcheng Road, Yucui Community, Longhua Street, Longhua District Shenzhen Guangdong 518110 China
Manufacturer's Name : Shenzhen Abramtek Technology Co., Ltd
Address : Room 405, Building E, Chao Loft Cultural Creative Park, 150 Huayue Road, Dalang Street, Longhua Town, Shenzhen, China 518109

Product Description


Product Name : Speaker
Brand : HOTMAY
Model Number : HOTMAY BS1
Series Model(s) : BS1, BS2, BS3, BS4, BS5, BSHD, HOT2, HOT3, HOT4, HOT5, HOT1 HD, HOT1 plus, HOT amp, HOT spk, HOTSOUND, HOTSUN, P1, P2, P3, P500, P1000, P1500

Standards : FCC 47CFR §2.1091
447498 D04 Interim General RF Exposure Guidance v01

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test


Date of receipt of test item : 23 Jan. 2024
Date (s) of performance of tests : 23 Jan. 2024 ~ 02 Feb. 2024
Date of Issue : 02 Feb. 2024
Test Result : **Pass**

Testing Engineer : 

(Aaron Bu)

Technical Manager : 

(Chris Chen)

Authorized Signatory : 

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR §2.1091 REQUIREMENT	7
2.1 TEST STANDARDS	7
2.2 LIMIT	7
2.3 TEST RESULT	10

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	02 Feb. 2024	STS2401144H01	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Speaker								
Brand	HOTMAY								
Model Number	HOTMAY BS1								
Series Model(s)	BS1, BS2, BS3, BS4, BS5, BSHD, HOT2, HOT3, HOT4, HOT5, HOT1 HD, HOT1 plus, HOT amp, HOT spk, HOTSOUND, HOTSUN, P1, P2, P3, P500, P1000, P1500								
Model Difference	The name of the model is different, the color is different, and the material of the main cylinder is different, and the rest is exactly the same. The difference does not affect its EMC performance.								
Product Description	<p>The EUT is Speaker</p> <table border="1"><tr><td>Operation Frequency:</td><td>2402 – 2480 MHz</td></tr><tr><td>Modulation Type:</td><td>GFSK(1Mbps), π/4-DQPSK(2Mbps), 8DPSK(3Mbps)</td></tr><tr><td>Antenna gain:</td><td>0dBi</td></tr><tr><td>Antenna Designation:</td><td>PCB Antenna</td></tr></table>	Operation Frequency:	2402 – 2480 MHz	Modulation Type:	GFSK(1Mbps), π/4-DQPSK(2Mbps), 8DPSK(3Mbps)	Antenna gain:	0dBi	Antenna Designation:	PCB Antenna
Operation Frequency:	2402 – 2480 MHz								
Modulation Type:	GFSK(1Mbps), π/4-DQPSK(2Mbps), 8DPSK(3Mbps)								
Antenna gain:	0dBi								
Antenna Designation:	PCB Antenna								
Rating	Input: DC 24 V 2.5A DC 20V 3.25A								
Adapter	Power supply one Input: 100-240V~50/60Hz 1.5A Output: DC-20V 3.25A Power supply two Input: 100-240V~50/60Hz Output: DC-24V 2.5A								
Hardware version number	BS1 VER:A1 2023-09-25								
Software version number	F3031_32M_V106E_FA0008_20240115_6424.xuv								



1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

Follow the maximum permissible exposure (MPE) limits specified in 447498 D04 Interim General Radio Frequency Exposure Guidelines v01. The gain of the antenna used in the product was extracted from the supplied antenna data sheet and the maximum total power input to the antenna was also measured. Calculate the distance from the product to the MPE limit by the formula.

2.2 LIMIT

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



(C) Or using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.



For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of Part 1.1307 for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of Part 1.1307 for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of Part 1.1307.

Evaluatedk = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limitk = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310.



2.3 TEST RESULT

Turn up

Mode	Detector	Turn up Power
BT	PK	3±1dBm

Protocol	Fre. (GHz)	Separation distance (cm)	Max Turn up power (dBm)	ANT Gain (dBi)	Max EIRP (dBm)	Max EIRP (W)	Limit (W)	Ratio	Result
BT	2.480	20	4	0	4	0.003	0.7680	0.003	Pass

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.
2. ERP=EIRP-2.15

*****END OF THE REPORT*****