



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR240100007004

Page: 1 of 196

TEST REPORT

Application No.: SHCR2401000070HS
FCC ID: 2BESUJYC08A-01
Applicant: Xianglu Robotics(Jiangsu) Co., Ltd.
Address of Applicant: Room 1701, No.5(South), Zhihui Road, Huishan economic development District, Wuxi City, Jiangsu Province.
Manufacturer: Xianglu Robotics(Jiangsu) Co., Ltd.
Address of Manufacturer: Room 1701, No.5(South), Zhihui Road, Huishan economic development District, Wuxi City, Jiangsu Province.
Factory: Xianglu Robotics(Dongguan) Co., Ltd.
Address of Factory: No.11, Songbailangxinyuan No.2 Road, Dalang Town, Dongguan City, Guangdong Province.

Equipment Under Test (EUT):

EUT Name: Intelligent Cooking Machine
Model No.: JYC08A-01
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2024-01-10
Date of Test: 2024-03-19 to 2024-03-26
Date of Issue: 2024-05-07

Test Result:	Pass*
---------------------	-------


* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2024-05-07	/

Authorized for issue by:			
Tested By		 Wade Zhang	
		Wade Zhang/Project Engineer	
Approved By		 Parlam Zhan	
		Parlam Zhan / Reviewer	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass
Transmission in the Absence of Data		N/A	47 CFR Part 15, Subpart E 15.407 (c)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Duty Cycle		KDB 789033 II B 1	KDB 789033 D02 II B 1	Pass
26dB Emission bandwidth		KDB 789033 D02 II C 1	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band)		KDB 789033 D02 II C 2	47 CFR Part 15, Subpart E 15.407 (e)	Pass
Maximum Conducted output power		KDB 789033 D02 II E	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Peak Power spectrum density		KDB 789033 D02 II F	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Radiated Emissions (Below 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Frequency Stability		ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart E 15.407 (g)	Pass

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	7
4.3 POWER LEVEL SETTING USING IN TEST	7
4.4 MEASUREMENT UNCERTAINTY	8
4.5 TEST LOCATION	8
4.6 TEST FACILITY	9
4.7 DEVIATION FROM STANDARDS	9
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	9
5 EQUIPMENT LIST	10
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	12
6.1 ANTENNA REQUIREMENT	12
6.1.1 <i>Test Requirement:</i>	12
6.1.2 <i>Conclusion</i>	12
6.2 TRANSMISSION IN THE ABSENCE OF DATA	13
6.2.1 <i>Test Requirement:</i>	13
6.2.2 <i>Conclusion</i>	13
7 RADIO SPECTRUM MATTER TEST RESULTS	14
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz)	14
7.1.1 <i>E.U.T. Operation</i>	14
7.1.2 <i>Test Mode Description</i>	14
7.1.3 <i>Test Setup Diagram</i>	15
7.1.4 <i>Measurement Procedure and Data</i>	15
7.2 DUTY CYCLE	20
7.2.1 <i>E.U.T. Operation</i>	20
7.2.2 <i>Test Mode Description</i>	20
7.2.3 <i>Test Setup Diagram</i>	20
7.2.4 <i>Measurement Procedure and Data</i>	20
7.3 26dB EMISSION BANDWIDTH	21
7.3.1 <i>E.U.T. Operation</i>	21
7.3.2 <i>Test Mode Description</i>	21
7.3.3 <i>Test Setup Diagram</i>	21
7.3.4 <i>Measurement Procedure and Data</i>	21
7.4 MINIMUM 6 dB BANDWIDTH (5.725-5.85 GHz BAND)	22
7.4.1 <i>E.U.T. Operation</i>	22
7.4.2 <i>Test Mode Description</i>	22
7.4.3 <i>Test Setup Diagram</i>	22
7.4.4 <i>Measurement Procedure and Data</i>	22
7.5 MAXIMUM CONDUCTED OUTPUT POWER	23
7.5.1 <i>E.U.T. Operation</i>	23
7.5.2 <i>Test Mode Description</i>	23
7.5.3 <i>Test Setup Diagram</i>	24
7.5.4 <i>Measurement Procedure and Data</i>	24

7.6	PEAK POWER SPECTRUM DENSITY.....	25
7.6.1	<i>E.U.T. Operation.....</i>	25
7.6.2	<i>Test Mode Description.....</i>	25
7.6.3	<i>Test Setup Diagram.....</i>	26
7.6.4	<i>Measurement Procedure and Data.....</i>	26
7.7	RADIATED EMISSIONS (BELOW 1GHz).....	27
7.7.1	<i>E.U.T. Operation.....</i>	27
7.7.2	<i>Test Mode Description.....</i>	27
7.7.3	<i>Test Setup Diagram.....</i>	28
7.7.4	<i>Measurement Procedure and Data.....</i>	28
7.8	RADIATED EMISSIONS (ABOVE 1GHz)	31
7.8.1	<i>E.U.T. Operation.....</i>	31
7.8.2	<i>Test Mode Description.....</i>	31
7.8.3	<i>Test Setup Diagram.....</i>	32
7.8.4	<i>Measurement Procedure and Data.....</i>	33
7.9	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	142
7.9.1	<i>E.U.T. Operation.....</i>	142
7.9.2	<i>Test Mode Description.....</i>	142
7.9.3	<i>Test Setup Diagram.....</i>	143
7.9.4	<i>Measurement Procedure and Data.....</i>	144
7.10	FREQUENCY STABILITY	195
7.10.1	<i>E.U.T. Operation.....</i>	195
7.10.2	<i>Test Mode Description.....</i>	195
7.10.3	<i>Test Setup Diagram.....</i>	195
7.10.4	<i>Measurement Procedure and Data</i>	195
8	TEST SETUP PHOTO	196
9	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	196

4 General Information

4.1 Details of E.U.T.

Power Supply:	AC 380V 50Hz
Test Voltage:	AC 380V 50Hz&DC12V

Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	UNII Band I	802.11a/n(HT20)/ac(VHT20) / ax(HEW20)	5180-5240	4
		802.11n(HT40)/ac(VHT40)/ax(HEW40)	5190-5230	2
	UNII Band II-A	802.11a/n(HT20)/ac(VHT20) / ax(HEW20)	5260-5320	4
		802.11n(HT40)/ac(VHT40)/ax(HEW40)	5270-5310	2
	UNII Band II-C	802.11a/n(HT20)/ac(VHT20) / ax(HEW20)	5500-5700	11
		802.11n(HT40)/ac(VHT40)/ax(HEW40)	5510-5670	5
	UNII Band III	802.11a/n(HT20)/ac(VHT20) / ax(HEW20)	5745-5825	5
		802.11n(HT40)/ac(VHT40)/ax(HEW40)	5755-5795	2
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM)			
Date Rate:	802.11a:6/9/12/18/24/36/48/54Mbps 802.11n:MCS0-MCS7 802.11ac:VHT MCS0-MCS7 802.11ax: HEW MCS0-MCS7			
Channel Spacing:	802.11a/n(HT20)/ac(VHT20)/ax(HEW20): 20MHz 802.11n(HT40)/ac(VHT40)/ax(HEW40): 40MHz			
Antenna Type:	Mushroom antenna			
Antenna Gain:	U-NII-1: 5.84dBi; U-NII-2A:5.36dBi; U-NII-2C:5.43dBi; UNII Band III: 5.23dBi (Provided by manufacturer)			
DFS Function:	Slave without Radar detection			
TPC Function:	Without TPC function			

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	LENOVO	L460	-
Router	NETGEAR	RAX50	-
SecureCRT	VanDyke	V 6.2.0	-
Serial port adapter plate	-	Test Plate 3	-

4.3 Power level setting using in test

Test Mode	802.11a	802.11n(HT20)	802.11ac(VHT20)	802.11ax(HEW20)
Channel	Ant 1	Ant 1	Ant 1	Ant 1
36	10	10	10	10
40	10	10	10	10
48	10	10	10	10
52	10	10	10	10
60	10	10	10	10
64	10	10	10	10
100	10	10	10	10
116	10	10	10	10
140	10	10	10	10
149	10	10	10	10
157	10	10	10	10
165	10	10	10	10
Test Mode	802.11n(HT40)	802.11ac(VHT40)	802.11ax(HEW40)	
Channel	Ant 1	Ant 1	Ant 1	
38	10	10	10	
46	10	10	10	
54	10	10	10	
62	10	10	10	
102	10	10	10	
110	10	10	10	
134	10	10	10	
151	10	10	10	
159	10	10	10	

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty cycle	0.4%
4	Occupied Bandwidth	3%
5	RF conducted power	0.6dB
6	RF power density	2.9dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	5.2dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious emission test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		5.1dB (1GHz-6GHz)
		5.4dB (6GHz-18GHz)
10	Temperature test	1°C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

- SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).
- SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
- Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

- **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 8617A

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Conducted Test					
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2023-12-19	2024-12-18
Spectrum Analyzer	Keysight	N9020B	SHEM241-1	2023-12-19	2024-12-18
Spectrum Analyzer	Agilent	N9020A	SHEM181-1	2023-08-01	2024-07-31
Signal Generator	R&S	SMR20	SHEM006-1	2023-08-01	2024-07-31
Signal Generator	Agilent	N5182A	SHEM182-1	2023-08-01	2024-07-31
Communication Tester	R&S	CMW270	SHEM183-1	2023-06-01	2024-05-31
Communication Tester	R&S	CMW500	SHEM268-1	2023-06-01	2024-05-31
Power Sensor	Keysight	U2021XA * 4	SHEM184-1	2023-08-01	2024-07-31
Splitter	Anritsu	MA1612A	SHEM185-1	/	/
Coupler	e-meca	803-S-1	SHEM186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEM087-1	2022-11-08	2024-11-07
AC Power Stabilizer	APC	KDF-31020T-V0-F0	SHEM216-1	2023-12-19	2024-12-18
DC Power Supply	HP	6010A	SHEM222-1	2023-12-19	2024-12-18
Conducted test Cable	/	RF01-RF04	/	2023-12-19	2024-12-18
Switcher	Tonscend	JS0806	SHEM184-1	2023-08-01	2024-07-31
Test software	Tonscend	JS Tonscend BT/WIFI System	Version: 2.6	/	/
Switcher+Power Sensor	TST	TSPS2023R	SHEM263-1	2023-08-01	2024-07-31
Test software	TST	TST PASS	Version: 2.0	/	/
RF Radiated Test					
EMI test Receiver	R&S	ESU40	SHEM051-1	2023-12-19	2024-12-18
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2023-12-19	2024-12-18
Communication Tester	R&S	CMW500	SHEM268-1	2023-06-01	2024-05-31
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEM135-1	2023-12-19	2024-12-18
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM048-1	2023-09-03	2025-09-02
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM202-1	2023-04-17	2025-04-16
Horn Antenna (1-18GHz)	Schwarzbeck	HF906	SHEM009-1	2022-08-11	2024-08-10
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEM050-1	2023-09-03	2025-09-02
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEM049-1	2023-09-03	2025-09-02
Pre-Amplifier	HP	8447D	SHEM236-1	2023-12-19	2024-12-18
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEM049-2	2023-12-19	2024-12-18
Band Filter	LORCH	9BRX-875/X150	SHEM156-1	/	/
Band Filter	LORCH	13BRX-1950/X500	SHEM083-2	/	/
Band Filter	LORCH	5BRX-2400/X200	SHEM155-1	/	/
Band Filter	LORCH	5BRX-5500/X1000	SHEM157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G	SHEM157-1	/	/
High pass Filter	Wainwright	WHKS1700	SHEM157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2023-05-06	2026-05-05
RE test Cable	/	PT18-NMNM-10M	SHEM217-2	2023-12-19	2024-12-18
Test software	ESE	E3	Version: 6.111221a	/	/



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR240100007005

Page: 11 of 196

Conducted Emissions at AC Mains Power Port (150kHz-30MHz)						
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date	
EMI test receiver	Rohde & Schwarz	ESR7	SHEM162-1	2023/12/19	2024/12/18	
Line impedance stabilization network	SCHWARZBECK	NSLK8127	SHEM061-1	2023/12/19	2024/12/18	
Line impedance stabilization network	EMCO	3816_2	SHEM019-1	2023/12/19	2024/12/18	
Pulse limiter	Rohde & Schwarz	ESH3-Z2	SHEM029-1	2023/12/19	2024/12/18	
Shielding Room	ZHONGYU	8*4*3M	SHEM079-2	2023/12/19	2024/12/18	
CE test Cable	/	/	SHEM172-1	2023/12/19	2024/12/18	
Test Software	ESE	e3	Version: 6.191211	N/A	N/A	

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is mushroom antenna and no consideration of replacement. The best-case gain of the U-NII-1: 5.84dBi; U-NII-2A:5.36dBi; U-NII-2C:5.43dBi, U-NII-3:5.23dBi

Antenna location: Refer to internal photo.

6.2 Transmission in the Absence of Data

6.2.1 Test Requirement:

47 CFR Part 15, Subpart E 15.407 (c)

6.2.2 Conclusion

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

WIFI chip support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Pre-scan	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Pre-scan	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Pre-scan	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\text{ohm}/50\mu\text{H} + 5\text{ohm}$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 05; Line: Live line L1




LISN : LINE
EUT/Project No : 0070HS
Test Mode : 05

	Freq (MHz)	Read level (dBuV)	LISN Factor	Cable Loss (dB)	Emission Level (dBuV)	Emission Limit (dBuV)	Over Limit (dB)	Remark
1	0.15	30.32	0.37	9.90	40.59	55.87	-15.28	Average
2	0.15	42.34	0.37	9.90	52.61	65.87	-13.26	QP
3	0.18	31.64	0.27	9.90	41.81	54.33	-12.52	Average
4	0.18	45.62	0.27	9.90	55.79	64.33	-8.54	QP
5	0.67	17.33	0.05	9.90	27.28	46.00	-18.72	Average
6	0.67	27.33	0.05	9.90	37.28	56.00	-18.72	QP
7	1.03	13.89	0.06	10.00	23.95	46.00	-22.05	Average
8	1.03	25.95	0.06	10.00	36.01	56.00	-19.99	QP
9	2.93	20.22	0.12	10.14	30.48	46.00	-15.52	Average
10	2.93	32.38	0.12	10.14	42.64	56.00	-13.36	QP
11	3.17	17.51	0.13	10.15	27.79	46.00	-18.21	Average
12	3.17	31.68	0.13	10.15	41.96	56.00	-14.04	QP

Notes: Emission Level = Read Level + LISN Factor + Cable loss

Test Mode: 05; Line: Live line L2




LISN : LINE
EUT/Project No : 0070HS
Test Mode : 05

	Freq (MHz)	Read level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Emission Level (dBuV)	Over Limit (dBuV)	Over Limit (dB)	Remark
1	0.18	20.42	0.28	9.90	30.60	54.50	-23.90	Average
2	0.18	40.96	0.28	9.90	51.14	64.50	-13.36	QP
3	0.24	21.53	0.19	9.90	31.62	52.08	-20.46	Average
4	0.24	36.54	0.19	9.90	46.63	62.08	-15.45	QP
5	0.66	29.68	0.06	9.90	39.64	46.00	-6.36	Average
6	0.66	34.93	0.06	9.90	44.89	56.00	-11.11	QP
7	1.02	25.49	0.05	10.00	35.54	46.00	-10.46	Average
8	1.02	31.71	0.05	10.00	41.76	56.00	-14.24	QP
9	2.93	23.59	0.12	10.14	33.85	46.00	-12.15	Average
10	2.93	33.00	0.12	10.14	43.26	56.00	-12.74	QP
11	7.65	20.57	0.28	10.32	31.17	50.00	-18.83	Average
12	7.65	28.56	0.28	10.32	39.16	60.00	-20.84	QP

Notes: Emission Level = Read Level + LISN Factor + Cable loss

Test Mode: 05; Line: Live line L3




LISN : LINE
EUT/Project No : 0070HS
Test Mode : 05

Freq (MHz)	Read level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Emission Level (dBuV)	Emission Limit (dBuV)	Over Limit (dB)	Remark
1 0.16	34.50	0.36	9.90	44.76	55.52	-10.76	Average
2 0.16	43.55	0.36	9.90	53.81	65.52	-11.71	QP
3 0.18	33.65	0.28	9.90	43.83	54.33	-10.50	Average
4 0.18	41.86	0.28	9.90	52.04	64.33	-12.29	QP
5 0.22	28.26	0.22	9.90	38.38	53.01	-14.63	Average
6 0.22	39.30	0.22	9.90	49.42	63.01	-13.59	QP
7 0.69	13.08	0.07	9.90	23.05	46.00	-22.95	Average
8 0.69	25.08	0.07	9.90	35.05	56.00	-20.95	QP
9 1.46	12.43	0.07	10.06	22.56	46.00	-23.44	Average
10 1.46	24.53	0.07	10.06	34.66	56.00	-21.34	QP
11 3.16	19.49	0.12	10.15	29.76	46.00	-16.24	Average
12 3.16	34.36	0.12	10.15	44.63	56.00	-11.37	QP

Notes: Emission Level = Read Level + LISN Factor + Cable loss

Test Mode: 05; Line: Neutral Line



LISN : NEUTRAL
EUT/Project No : 0070HS
Test Mode : 05

	Freq (MHz)	Read level (dBuV)	LISN Factor	Cable Loss (dB)	Emission Level (dBuV)	Over Limit (dBuV)	Over Limit (dB)	Remark
1	0.17	27.05	0.34	9.90	37.29	55.16	-17.87	Average
2	0.17	43.20	0.34	9.90	53.44	65.16	-11.72	QP
3	0.67	15.03	0.06	9.90	24.99	46.00	-21.01	Average
4	0.67	26.43	0.06	9.90	36.39	56.00	-19.61	QP
5	3.19	20.43	0.12	10.15	30.70	46.00	-15.30	Average
6	3.19	30.28	0.12	10.15	40.55	56.00	-15.45	QP
7	3.96	14.85	0.14	10.17	25.16	46.00	-20.84	Average
8	3.96	24.42	0.14	10.17	34.73	56.00	-21.27	QP
9	5.65	17.81	0.18	10.24	28.23	50.00	-21.77	Average
10	5.65	26.57	0.18	10.24	36.99	60.00	-23.01	QP
11	7.73	15.62	0.25	10.33	26.20	50.00	-23.80	Average
12	7.73	26.60	0.25	10.33	37.18	60.00	-22.82	QP

Notes: Emission Level = Read Level + LISN Factor + Cable loss

7.2 Duty Cycle

Test Requirement KDB 789033 D02 II B 1

Test Method: KDB 789033 II B 1

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 19.7 °C Humidity: 41.8 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.3 26dB Emission bandwidth

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II C 1

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 19.8 °C


Humidity: 42.0 % RH

Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.4 Minimum 6 dB bandwidth (5.725-5.85 GHz band)

Test Requirement 47 CFR Part 15, Subpart E 15.407 (e)

Test Method: KDB 789033 D02 II C 2

Limit:

Frequency band(MHz)	Limit
5725-5850	≥500 kHz


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 19.8 °C Humidity: 42.2 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram**7.4.4 Measurement Procedure and Data**

Please Refer to Appendix for Details

7.5 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II E

Limit:

Frequency band(MHz)	Limit
5150-5250	≤1W(30dBm) for master device
	≤250mW(24dBm) for client device
5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*
5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*
5725-5850	≤1W(30dBm)
Remark:	* Where B is the 26dB emission bandwidth in MHz. The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 19.8 °C Humidity: 42.2 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

7.6 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II F

Limit:

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 19.8 °C


Humidity: 42.2 % RH

Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Pre-scan	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Pre-scan	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Pre-scan	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram




7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
3. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

Test Mode: 05; Polarity: Horizontal



Antenna Polarity :HORIZONTAL

EUT/Project :0070HS


Test mode :05

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	128.113	46.51	11.90	2.56	33.08	27.89	43.50	-15.61	QP
2	166.651	47.60	13.15	2.85	33.00	30.60	43.50	-12.90	QP
3	198.588	50.64	10.08	3.00	33.00	30.72	43.50	-12.78	QP
4	263.819	49.29	12.11	3.45	32.80	32.05	46.00	-13.95	QP
5	528.246	46.81	18.46	5.04	32.70	37.61	46.00	-8.39	QP
6	935.546	33.45	23.70	7.08	31.57	32.66	46.00	-13.34	QP

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical



Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Test mode : 05

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	44.587	46.16	13.79	1.30	33.20	28.05	40.00	-11.95 QP
2	71.581	44.81	11.10	1.72	33.20	24.43	40.00	-15.57 QP
3	128.113	40.50	11.90	2.56	33.08	21.88	43.50	-21.62 QP
4	385.281	40.95	15.53	4.25	32.77	27.96	46.00	-18.04 QP
5	528.246	40.32	18.46	5.04	32.70	31.12	46.00	-14.88 QP
6	938.833	35.48	23.70	7.09	31.55	34.72	46.00	-11.28 QP

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

7.8 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1GHz	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 19.8 °C Humidity: 42.3 % RH Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

		recorded in the report.
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.8.3 Test Setup Diagram




7.8.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.

Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10360.35	33.86	37.85	9.02	33.56	47.17	68.20	-21.03	Peak
15540.00	31.60	43.36	12.59	36.82	50.73	54.00	-3.27	Peak
20720.83	30.61	43.94	14.46	38.82	50.19	54.00	-3.81	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10360.35	34.97	37.85	9.02	33.56	48.28	68.20	-19.92	Peak
15540.24	31.47	43.36	12.59	36.82	50.60	54.00	-3.40	Peak
20720.83	30.28	43.94	14.46	38.82	49.86	54.00	-4.14	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10440.49	33.94	37.88	9.03	33.60	47.25	68.20	-20.95	Peak
15660.00	31.92	43.04	12.63	36.81	50.78	54.00	-3.22	Peak
20880.05	29.72	43.98	14.50	39.02	49.18	54.00	-4.82	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10440.49	35.50	37.88	9.03	33.60	48.81	68.20	-19.39	Peak
15660.00	31.81	43.04	12.63	36.81	50.67	54.00	-3.33	Peak
20880.05	30.45	43.98	14.50	39.02	49.91	54.00	-4.09	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10480.71	35.67	37.90	9.04	33.62	48.99	68.20	-19.21	Peak
15720.90	31.98	42.93	12.54	36.81	50.64	54.00	-3.36	Peak
20960.48	30.86	44.00	14.53	39.12	50.27	54.00	-3.73	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10480.71	34.74	37.90	9.04	33.62	48.06	68.20	-20.14	Peak
15720.90	31.44	42.93	12.54	36.81	50.10	54.00	-3.90	Peak
20960.48	30.86	44.00	14.53	39.12	50.27	54.00	-3.73	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10360.35	34.14	37.85	9.02	33.56	47.45	68.20	-20.75	Peak
15540.24	29.92	43.36	12.59	36.82	49.05	54.00	-4.95	Peak
20720.83	30.03	43.94	14.46	38.82	49.61	54.00	-4.39	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10360.35	34.57	37.85	9.02	33.56	47.88	68.20	-20.32	Peak
15540.24	31.63	43.36	12.59	36.82	50.76	54.00	-3.24	Peak
20720.83	30.26	43.94	14.46	38.82	49.84	54.00	-4.16	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10440.49	35.04	37.88	9.03	33.60	48.35	68.20	-19.85	Peak
15660.00	31.33	43.04	12.63	36.81	50.19	54.00	-3.81	Peak
20880.05	31.20	43.98	14.50	39.02	50.66	54.00	-3.34	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10440.49	33.36	37.88	9.03	33.60	46.67	68.20	-21.53	Peak
15660.00	32.10	43.04	12.63	36.81	50.96	54.00	-3.04	Peak
20880.05	30.72	43.98	14.50	39.02	50.18	54.00	-3.82	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10480.71	33.89	37.90	9.04	33.62	47.21	68.20	-20.99	Peak
15720.90	32.11	42.93	12.54	36.81	50.77	54.00	-3.23	Peak
20960.48	29.64	44.00	14.53	39.12	49.05	54.00	-4.95	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10480.71	33.72	37.90	9.04	33.62	47.04	68.20	-21.16	Peak
15720.90	31.39	42.93	12.54	36.81	50.05	54.00	-3.95	Peak
20960.48	30.99	44.00	14.53	39.12	50.40	54.00	-3.60	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10380.35	34.21	37.85	9.02	33.56	47.52	68.20	-20.68	Peak
15570.67	30.97	43.25	12.64	36.81	50.05	54.00	-3.95	Peak
20760.83	29.97	43.94	14.46	38.82	49.55	54.00	-4.45	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10380.35	34.16	37.85	9.02	33.56	47.47	68.20	-20.73	Peak
15570.67	31.85	43.25	12.64	36.81	50.93	54.00	-3.07	Peak
20760.83	30.76	43.94	14.46	38.82	50.34	54.00	-3.66	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10460.71	34.07	37.90	9.04	33.62	47.39	68.20	-20.81	Peak
15690.00	32.11	43.04	12.63	36.81	50.97	54.00	-3.03	Peak
20920.48	31.34	44.00	14.53	39.12	50.75	54.00	-3.25	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10460.71	33.46	37.90	9.04	33.62	46.78	68.20	-21.42	Peak
15690.00	31.60	43.04	12.63	36.81	50.46	54.00	-3.54	Peak
20920.48	30.40	44.00	14.53	39.12	49.81	54.00	-4.19	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10360.35	34.23	37.85	9.02	33.56	47.54	68.20	-20.66	Peak
15540.24	31.82	43.36	12.59	36.82	50.95	54.00	-3.05	Peak
20720.83	31.23	43.94	14.46	38.82	50.81	54.00	-3.19	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10360.35	34.43	37.85	9.02	33.56	47.74	68.20	-20.46	Peak
15540.24	31.35	43.36	12.59	36.82	50.48	54.00	-3.52	Peak
20720.83	30.26	43.94	14.46	38.82	49.84	54.00	-4.16	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10440.49	32.99	37.88	9.03	33.60	46.30	68.20	-21.90	Peak
15660.00	31.42	43.04	12.63	36.81	50.28	54.00	-3.72	Peak
20880.05	29.92	43.98	14.50	39.02	49.38	54.00	-4.62	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10440.49	34.34	37.88	9.03	33.60	47.65	68.20	-20.55	Peak
15660.00	32.01	43.04	12.63	36.81	50.87	54.00	-3.13	Peak
20880.05	30.47	43.98	14.50	39.02	49.93	54.00	-4.07	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10480.71	33.77	37.90	9.04	33.62	47.09	68.20	-21.11	Peak
15720.90	31.96	42.93	12.54	36.81	50.62	54.00	-3.38	Peak
20960.48	30.44	44.00	14.53	39.12	49.85	54.00	-4.15	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10480.71	33.41	37.90	9.04	33.62	46.73	68.20	-21.47	Peak
15720.90	31.59	42.93	12.54	36.81	50.25	54.00	-3.75	Peak
20960.48	31.07	44.00	14.53	39.12	50.48	54.00	-3.52	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10380.35	34.54	37.85	9.02	33.56	47.85	68.20	-20.35	Peak
15570.67	30.30	43.25	12.64	36.81	49.38	54.00	-4.62	Peak
20760.83	29.96	43.94	14.46	38.82	49.54	54.00	-4.46	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10380.35	32.73	37.85	9.02	33.56	46.04	68.20	-22.16	Peak
15570.67	31.24	43.25	12.64	36.81	50.32	54.00	-3.68	Peak
20760.83	30.20	43.94	14.46	38.82	49.78	54.00	-4.22	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10460.71	33.61	37.90	9.04	33.62	46.93	68.20	-21.27	Peak
15690.00	31.51	43.04	12.63	36.81	50.37	54.00	-3.63	Peak
20920.48	29.99	44.00	14.53	39.12	49.40	54.00	-4.60	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10460.71	35.50	37.90	9.04	33.62	48.82	68.20	-19.38	Peak
15690.00	31.40	43.04	12.63	36.81	50.26	54.00	-3.74	Peak
20920.48	30.20	44.00	14.53	39.12	49.61	54.00	-4.39	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10520.04	34.38	37.91	9.05	33.63	47.71	68.20	-20.49	Peak
15780.96	31.85	42.79	12.50	36.80	50.34	54.00	-3.66	Peak
21040.96	30.05	44.05	14.57	39.31	49.36	54.00	-4.64	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10520.04	34.20	37.91	9.05	33.63	47.53	68.20	-20.67	Peak
15780.96	31.03	42.79	12.50	36.80	49.52	54.00	-4.48	Peak
21040.96	30.32	44.05	14.57	39.31	49.63	54.00	-4.37	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10560.02	33.59	37.96	9.07	33.67	46.95	68.20	-21.25	Peak
15840.18	32.08	42.65	12.48	36.76	50.45	54.00	-3.55	Peak
21120.03	30.28	44.07	14.59	39.41	49.53	54.00	-4.47	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10560.02	34.30	37.96	9.07	33.67	47.66	68.20	-20.54	Peak
15840.18	31.91	42.65	12.48	36.76	50.28	54.00	-3.72	Peak
21120.03	29.97	44.07	14.59	39.41	49.22	54.00	-4.78	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10640.42	33.90	38.02	9.09	33.71	47.30	54.00	-6.70	Peak
15960.80	32.53	42.32	12.44	36.63	50.66	54.00	-3.34	Peak
21280.79	30.03	44.11	14.64	39.61	49.17	54.00	-4.83	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10640.42	33.28	38.02	9.09	33.71	46.68	54.00	-7.32	Peak
15960.80	32.16	42.32	12.44	36.63	50.29	54.00	-3.71	Peak
21280.79	29.89	44.11	14.64	39.61	49.03	54.00	-4.97	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10520.04	34.76	37.91	9.05	33.63	48.09	68.20	-20.11	Peak
15780.96	32.11	42.79	12.50	36.80	50.60	54.00	-3.40	Peak
21040.96	29.25	44.05	14.57	39.31	48.56	54.00	-5.44	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10520.04	34.17	37.91	9.05	33.63	47.50	68.20	-20.70	Peak
15780.96	31.69	42.79	12.50	36.80	50.18	54.00	-3.82	Peak
21040.96	29.52	44.05	14.57	39.31	48.83	54.00	-5.17	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10560.02	33.88	37.96	9.07	33.67	47.24	68.20	-20.96	Peak
15840.18	31.90	42.65	12.48	36.76	50.27	54.00	-3.73	Peak
21120.03	30.03	44.07	14.59	39.41	49.28	54.00	-4.72	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10560.02	33.87	37.96	9.07	33.67	47.23	68.20	-20.97	Peak
15840.18	32.54	42.65	12.48	36.76	50.91	54.00	-3.09	Peak
21120.03	29.94	44.07	14.59	39.41	49.19	54.00	-4.81	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10640.42	33.25	38.02	9.09	33.71	46.65	54.00	-7.35	Peak
15960.80	32.28	42.32	12.44	36.63	50.41	54.00	-3.59	Peak
21280.79	30.95	44.11	14.64	39.61	50.09	54.00	-3.91	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10640.42	33.79	38.02	9.09	33.71	47.19	54.00	-6.81	Peak
15960.80	31.95	42.32	12.44	36.63	50.08	54.00	-3.92	Peak
21280.79	30.43	44.11	14.64	39.61	49.57	54.00	-4.43	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10520.04	33.85	37.91	9.05	33.63	47.18	68.20	-21.02	Peak
15780.96	32.76	42.79	12.50	36.80	51.25	54.00	-2.75	Peak
21040.96	29.25	44.05	14.57	39.31	48.56	54.00	-5.44	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10520.04	33.95	37.91	9.05	33.63	47.28	68.20	-20.92	Peak
15780.96	32.91	42.79	12.50	36.80	51.40	54.00	-2.60	Peak
21040.96	29.92	44.05	14.57	39.31	49.23	54.00	-4.77	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10560.02	34.79	37.96	9.07	33.67	48.15	68.20	-20.05	Peak
15840.18	32.25	42.65	12.48	36.76	50.62	54.00	-3.38	Peak
21120.03	29.14	44.07	14.59	39.41	48.39	54.00	-5.61	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10560.02	33.93	37.96	9.07	33.67	47.29	68.20	-20.91	Peak
15840.18	32.69	42.65	12.48	36.76	51.06	54.00	-2.94	Peak
21120.03	30.44	44.07	14.59	39.41	49.69	54.00	-4.31	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10640.42	32.58	38.02	9.09	33.71	45.98	54.00	-8.02	Peak
15960.80	31.90	42.32	12.44	36.63	50.03	54.00	-3.97	Peak
21280.79	29.87	44.11	14.64	39.61	49.01	54.00	-4.99	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10640.42	33.81	38.02	9.09	33.71	47.21	54.00	-6.79	Peak
15960.80	30.81	42.32	12.44	36.63	48.94	54.00	-5.06	Peak
21280.79	28.90	44.11	14.64	39.61	48.04	54.00	-5.96	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10540.47	34.62	37.94	9.05	33.65	47.96	68.20	-20.24	Peak
15810.18	31.73	42.65	12.48	36.76	50.10	54.00	-3.90	Peak
21080.96	30.53	44.05	14.57	39.31	49.84	54.00	-4.16	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10540.47	33.56	37.94	9.05	33.65	46.90	68.20	-21.30	Peak
15810.18	32.63	42.65	12.48	36.76	51.00	54.00	-3.00	Peak
21080.96	28.52	44.05	14.57	39.31	47.83	54.00	-6.17	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10620.67	34.59	37.99	9.08	33.69	47.97	54.00	-6.03	Peak
15930.10	32.18	42.37	12.46	36.67	50.34	54.00	-3.66	Peak
21240.79	30.47	44.11	14.64	39.61	49.61	54.00	-4.39	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10620.67	34.98	37.99	9.08	33.69	48.36	54.00	-5.64	Peak
15930.10	32.12	42.37	12.46	36.67	50.28	54.00	-3.72	Peak
21240.79	30.10	44.11	14.64	39.61	49.24	54.00	-4.76	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10540.47	34.41	37.94	9.05	33.65	47.75	68.20	-20.45	Peak
15810.18	31.84	42.65	12.48	36.76	50.21	54.00	-3.79	Peak
21080.96	29.59	44.05	14.57	39.31	48.90	54.00	-5.10	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10540.47	35.15	37.94	9.05	33.65	48.49	68.20	-19.71	Peak
15810.18	32.04	42.65	12.48	36.76	50.41	54.00	-3.59	Peak
21080.96	29.20	44.05	14.57	39.31	48.51	54.00	-5.49	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10620.67	34.65	37.99	9.08	33.69	48.03	54.00	-5.97	Peak
15930.10	32.64	42.37	12.46	36.67	50.80	54.00	-3.20	Peak
21240.79	29.15	44.11	14.64	39.61	48.29	54.00	-5.71	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
10620.67	34.96	37.99	9.08	33.69	48.34	54.00	-5.66	Peak
15930.10	32.70	42.37	12.46	36.67	50.86	54.00	-3.14	Peak
21240.79	30.17	44.11	14.64	39.61	49.31	54.00	-4.69	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11000.90	35.14	38.28	9.37	34.15	48.64	54.00	-5.36	Peak
16500.77	31.42	41.74	12.79	36.20	49.75	68.20	-18.45	Peak
22000.50	31.18	44.36	14.88	40.70	49.72	68.20	-18.48	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11000.90	36.17	38.28	9.37	34.15	49.67	54.00	-4.33	Peak
16500.77	31.73	41.74	12.79	36.20	50.06	68.20	-18.14	Peak
22000.50	30.87	44.36	14.88	40.70	49.41	68.20	-18.79	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11200.36	33.18	38.28	9.63	34.67	46.42	54.00	-7.58	Peak
16800.32	30.86	41.70	12.85	35.90	49.51	68.20	-18.69	Peak
22400.30	31.06	44.47	14.99	41.19	49.33	54.00	-4.67	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11200.36	33.79	38.28	9.63	34.67	47.03	54.00	-6.97	Peak
16800.32	30.67	41.70	12.85	35.90	49.32	68.20	-18.88	Peak
22400.30	31.15	44.47	14.99	41.19	49.42	54.00	-4.58	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11400.85	35.07	38.28	9.85	35.43	47.77	54.00	-6.23	Peak
17000.60	31.72	41.72	13.08	35.64	50.88	68.20	-17.32	Peak
22800.13	30.56	44.60	15.12	41.79	48.49	54.00	-5.51	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11400.85	35.17	38.28	9.85	35.43	47.87	54.00	-6.13	Peak
17100.60	32.04	41.79	13.09	35.58	51.34	68.20	-16.86	Peak
22800.13	31.97	44.60	15.12	41.79	49.90	54.00	-4.10	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11000.90	35.78	38.28	9.37	34.15	49.28	54.00	-4.72	Peak
16500.77	31.59	41.74	12.79	36.20	49.92	68.20	-18.28	Peak
22000.50	30.96	44.36	14.88	40.70	49.50	68.20	-18.70	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11000.90	34.14	38.28	9.37	34.15	47.64	54.00	-6.36	Peak
16500.77	32.24	41.74	12.79	36.20	50.57	68.20	-17.63	Peak
22000.50	30.30	44.36	14.88	40.70	48.84	68.20	-19.36	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11200.36	33.03	38.28	9.63	34.67	46.27	54.00	-7.73	Peak
16800.32	31.25	41.70	12.85	35.90	49.90	68.20	-18.30	Peak
22400.30	30.83	44.47	14.99	41.19	49.10	54.00	-4.90	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11200.36	32.47	38.28	9.63	34.67	45.71	54.00	-8.29	Peak
16800.32	29.54	41.70	12.85	35.90	48.19	68.20	-20.01	Peak
22400.30	31.88	44.47	14.99	41.19	50.15	54.00	-3.85	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11400.85	34.83	38.28	9.85	35.43	47.53	54.00	-6.47	Peak
17100.60	30.94	41.79	13.09	35.58	50.24	68.20	-17.96	Peak
22800.13	30.18	44.60	15.12	41.79	48.11	54.00	-5.89	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11400.85	33.87	38.28	9.85	35.43	46.57	54.00	-7.43	Peak
17100.60	30.35	41.79	13.09	35.58	49.65	68.20	-18.55	Peak
22800.13	31.37	44.60	15.12	41.79	49.30	54.00	-4.70	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11000.90	33.88	38.28	9.37	34.15	47.38	54.00	-6.62	Peak
16500.77	32.45	41.74	12.79	36.20	50.78	68.20	-17.42	Peak
22000.50	30.43	44.36	14.88	40.70	48.97	68.20	-19.23	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11000.90	33.75	38.28	9.37	34.15	47.25	54.00	-6.75	Peak
16500.77	31.75	41.74	12.79	36.20	50.08	68.20	-18.12	Peak
22000.50	30.20	44.36	14.88	40.70	48.74	68.20	-19.46	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11200.36	32.47	38.28	9.63	34.67	45.71	54.00	-8.29	Peak
16800.32	30.11	41.70	12.85	35.90	48.76	68.20	-19.44	Peak
22400.30	30.54	44.47	14.99	41.19	48.81	54.00	-5.19	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11200.36	34.28	38.28	9.63	34.67	47.52	54.00	-6.48	Peak
16800.32	31.00	41.70	12.85	35.90	49.65	68.20	-18.55	Peak
22400.30	30.73	44.47	14.99	41.19	49.00	54.00	-5.00	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11400.85	35.11	38.28	9.85	35.43	47.81	54.00	-6.19	Peak
17100.60	31.48	41.79	13.09	35.58	50.78	68.20	-17.42	Peak
22800.13	30.92	44.60	15.12	41.79	48.85	54.00	-5.15	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11400.85	34.47	38.28	9.85	35.43	47.17	54.00	-6.83	Peak
17100.60	31.86	41.79	13.09	35.58	51.16	68.20	-17.04	Peak
22800.13	30.87	44.60	15.12	41.79	48.80	54.00	-5.20	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB		
11020.90	33.61	38.28	9.37	34.15	47.11	54.00	-6.89	Peak	
16530.28	30.75	41.67	12.79	36.16	49.05	68.20	-19.15	Peak	
22040.50	29.74	44.36	14.88	40.70	48.28	54.00	-5.72	Peak	

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11020.90	33.84	38.28	9.37	34.15	47.34	54.00	-6.66	Peak
16530.28	31.01	41.67	12.79	36.16	49.31	68.20	-18.89	Peak
22040.50	30.90	44.36	14.88	40.70	49.44	54.00	-4.56	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11180.36	34.14	38.28	9.63	34.67	47.38	54.00	-6.62	Peak
16770.97	33.25	41.69	12.78	35.97	51.75	68.20	-16.45	Peak
22360.30	31.32	44.47	14.99	41.19	49.59	54.00	-4.41	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11180.36	33.73	38.28	9.63	34.67	46.97	54.00	-7.03	Peak
16770.97	31.58	41.69	12.78	35.97	50.08	68.20	-18.12	Peak
22360.30	31.30	44.47	14.99	41.19	49.57	54.00	-4.43	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11340.56	35.17	38.28	9.81	35.17	48.09	54.00	-5.91	Peak
17010.40	30.29	41.72	13.08	35.64	49.45	68.20	-18.75	Peak
22680.61	30.13	44.55	15.08	41.59	48.17	54.00	-5.83	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11340.56	35.31	38.28	9.81	35.17	48.23	54.00	-5.77	Peak
17010.40	31.50	41.72	13.08	35.64	50.66	68.20	-17.54	Peak
22680.61	30.11	44.55	15.08	41.59	48.15	54.00	-5.85	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11020.90	33.89	38.28	9.37	34.15	47.39	54.00	-6.61	Peak
16530.28	31.36	41.67	12.79	36.16	49.66	68.20	-18.54	Peak
22040.50	30.24	44.36	14.88	40.70	48.78	54.00	-5.22	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11020.90	34.14	38.28	9.37	34.15	47.64	54.00	-6.36	Peak
16530.28	31.84	41.67	12.79	36.16	50.14	68.20	-18.06	Peak
22040.50	29.74	44.36	14.88	40.70	48.28	54.00	-5.72	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11180.36	33.73	38.28	9.63	34.67	46.97	54.00	-7.03	Peak
16770.97	31.63	41.69	12.78	35.97	50.13	68.20	-18.07	Peak
22360.30	32.58	44.47	14.99	41.19	50.85	54.00	-3.15	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11000.15	34.85	38.28	9.37	34.15	48.35	54.00	-5.65	Peak
16770.97	31.29	41.69	12.78	35.97	49.79	68.20	-18.41	Peak
22360.30	30.49	44.47	14.99	41.19	48.76	54.00	-5.24	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11340.56	34.83	38.28	9.81	35.17	47.75	54.00	-6.25	Peak
17010.40	32.36	41.72	13.08	35.64	51.52	68.20	-16.68	Peak
22680.61	30.29	44.55	15.08	41.59	48.33	54.00	-5.67	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11340.56	34.43	38.28	9.81	35.17	47.35	54.00	-6.65	Peak
17010.40	30.63	41.72	13.08	35.64	49.79	68.20	-18.41	Peak
22680.61	30.54	44.55	15.08	41.59	48.58	54.00	-5.42	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11490.60	34.68	38.28	9.88	35.68	47.16	54.00	-6.84	Peak
17235.24	32.31	42.00	13.15	35.39	52.07	68.20	-16.13	Peak
22980.58	29.92	44.64	15.17	41.99	47.74	54.00	-6.26	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11490.60	34.19	38.28	9.88	35.68	46.67	54.00	-7.33	Peak
17235.24	34.38	42.00	13.15	35.39	54.14	68.20	-14.06	Peak
22980.58	31.16	44.64	15.17	41.99	48.98	54.00	-5.02	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11570.81	35.23	38.29	9.90	35.96	47.46	54.00	-6.54	Peak
17355.20	32.63	42.22	13.19	35.24	52.80	68.20	-15.40	Peak
23140.49	31.98	44.71	15.24	42.28	49.65	68.20	-18.55	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11570.81	35.64	38.29	9.90	35.96	47.87	54.00	-6.13	Peak
17355.20	32.34	42.22	13.19	35.24	52.51	68.20	-15.69	Peak
23140.49	31.18	44.71	15.24	42.28	48.85	68.20	-19.35	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11650.50	34.15	38.30	9.91	36.41	45.95	54.00	-8.05	Peak
17475.87	32.60	42.26	13.23	35.08	53.01	68.20	-15.19	Peak
23300.27	30.90	44.75	15.28	42.48	48.45	68.20	-19.75	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11650.50	33.56	38.30	9.91	36.41	45.36	54.00	-8.64	Peak
17475.87	33.09	42.26	13.23	35.08	53.50	68.20	-14.70	Peak
23300.27	30.81	44.75	15.28	42.48	48.36	68.20	-19.84	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11490.60	34.38	38.28	9.88	35.68	46.86	54.00	-7.14	Peak
17235.24	33.00	42.00	13.15	35.39	52.76	68.20	-15.44	Peak
22980.58	31.75	44.64	15.17	41.99	49.57	54.00	-4.43	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11490.60	33.77	38.28	9.88	35.68	46.25	54.00	-7.75	Peak
17235.24	32.64	42.00	13.15	35.39	52.40	68.20	-15.80	Peak
22980.58	31.24	44.64	15.17	41.99	49.06	54.00	-4.94	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11570.81	35.03	38.29	9.90	35.96	47.26	54.00	-6.74	Peak
17355.20	33.84	42.22	13.19	35.24	54.01	68.20	-14.19	Peak
23140.49	31.87	44.71	15.24	42.28	49.54	68.20	-18.66	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11570.81	34.29	38.29	9.90	35.96	46.52	54.00	-7.48	Peak
17355.20	31.91	42.22	13.19	35.24	52.08	68.20	-16.12	Peak
23140.49	30.19	44.71	15.24	42.28	47.86	68.20	-20.34	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11650.50	34.31	38.30	9.91	36.41	46.11	54.00	-7.89	Peak
17475.87	32.11	42.26	13.23	35.08	52.52	68.20	-15.68	Peak
23300.27	32.27	44.75	15.28	42.48	49.82	68.20	-18.38	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11650.50	34.18	38.30	9.91	36.41	45.98	54.00	-8.02	Peak
17475.87	32.71	42.26	13.23	35.08	53.12	68.20	-15.08	Peak
23300.27	31.01	44.75	15.28	42.48	48.56	68.20	-19.64	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11490.60	34.05	38.28	9.88	35.68	46.53	54.00	-7.47	Peak
17235.24	31.47	42.00	13.15	35.39	51.23	68.20	-16.97	Peak
22980.58	30.37	44.64	15.17	41.99	48.19	54.00	-5.81	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11490.60	34.39	38.28	9.88	35.68	46.87	54.00	-7.13	Peak
17235.24	32.29	42.00	13.15	35.39	52.05	68.20	-16.15	Peak
22980.58	30.83	44.64	15.17	41.99	48.65	54.00	-5.35	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11570.81	35.59	38.29	9.90	35.96	47.82	54.00	-6.18	Peak
17355.20	33.42	42.22	13.19	35.24	53.59	68.20	-14.61	Peak
23140.49	31.19	44.71	15.24	42.28	48.86	68.20	-19.34	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11570.81	34.71	38.29	9.90	35.96	46.94	54.00	-7.06	Peak
17355.20	32.71	42.22	13.19	35.24	52.88	68.20	-15.32	Peak
23140.49	31.90	44.71	15.24	42.28	49.57	68.20	-18.63	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11650.50	33.46	38.30	9.91	36.41	45.26	54.00	-8.74	Peak
17475.87	31.87	42.26	13.23	35.08	52.28	68.20	-15.92	Peak
23300.27	29.37	44.75	15.28	42.48	46.92	68.20	-21.28	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11650.50	34.01	38.30	9.91	36.41	45.81	54.00	-8.19	Peak
17475.87	32.26	42.26	13.23	35.08	52.67	68.20	-15.53	Peak
23300.27	29.74	44.75	15.28	42.48	47.29	68.20	-20.91	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11510.14	34.94	38.29	9.89	35.80	47.32	54.00	-6.68	Peak
17265.24	32.56	42.00	13.15	35.39	52.32	68.20	-15.88	Peak
23020.65	30.53	44.66	15.19	42.08	48.30	54.00	-5.70	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11510.14	34.82	38.29	9.89	35.80	47.20	54.00	-6.80	Peak
17265.24	32.06	42.00	13.15	35.39	51.82	68.20	-16.38	Peak
23020.65	29.82	44.66	15.19	42.08	47.59	54.00	-6.41	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11590.59	34.74	38.29	9.92	36.11	46.84	54.00	-7.16	Peak
17385.45	34.32	42.24	13.21	35.16	54.61	68.20	-13.59	Peak
23180.49	30.91	44.71	15.24	42.28	48.58	68.20	-19.62	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11590.59	34.50	38.29	9.92	36.11	46.60	54.00	-7.40	Peak
17385.45	33.05	42.24	13.21	35.16	53.34	68.20	-14.86	Peak
23180.49	30.85	44.71	15.24	42.28	48.52	68.20	-19.68	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11510.14	33.85	38.29	9.89	35.80	46.23	54.00	-7.77	Peak
17265.24	31.77	42.00	13.15	35.39	51.53	68.20	-16.67	Peak
23020.65	30.08	44.66	15.19	42.08	47.85	54.00	-6.15	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11510.14	34.08	38.29	9.89	35.80	46.46	54.00	-7.54	Peak
17265.24	32.17	42.00	13.15	35.39	51.93	68.20	-16.27	Peak
23020.65	30.90	44.66	15.19	42.08	48.67	54.00	-5.33	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11590.59	35.52	38.29	9.92	36.11	47.62	54.00	-6.38	Peak
17385.45	32.66	42.24	13.21	35.16	52.95	68.20	-15.25	Peak
23180.49	30.69	44.71	15.24	42.28	48.36	68.20	-19.84	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High



Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
11590.59	35.44	38.29	9.92	36.11	47.54	54.00	-6.46	Peak
17385.45	32.39	42.24	13.21	35.16	52.68	68.20	-15.52	Peak
23180.49	29.94	44.71	15.24	42.28	47.61	68.20	-20.59	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

7.9 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:


Temperature: 19.8 °C Humidity: 42.3 % RH Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is

		recorded in the report.
Final test	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40, Only the data of worst case is recorded in the report.

7.9.3 Test Setup Diagram




7.9.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4827.13	44.65	33.63	5.60	36.79	47.09	74.00	-26.91	Peak
5150.00	43.09	33.78	5.54	36.88	45.53	74.00	-28.47	Peak
5185.63	95.81	33.87	5.65	36.89	98.44	74.00	24.44	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5107.97	48.47	33.67	5.53	36.87	50.80	74.00	-23.20	Peak
5150.00	44.59	33.78	5.54	36.88	47.03	74.00	-26.97	Peak
5181.84	105.27	33.87	5.65	36.89	107.90	74.00	33.90	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4859.77	44.14	33.66	5.27	36.80	46.27	74.00	-27.73	Peak
5150.00	41.20	33.78	5.54	36.88	43.64	74.00	-30.36	Peak
5175.01	92.45	33.87	5.65	36.89	95.08	74.00	21.08	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4926.44	48.04	33.64	5.37	36.82	50.23	74.00	-23.77	Peak
5150.00	44.37	33.78	5.54	36.88	46.81	74.00	-27.19	Peak
5184.87	102.45	33.87	5.65	36.89	105.08	74.00	31.08	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5088.55	45.28	33.67	5.51	36.87	47.59	74.00	-26.41	Peak
5150.00	44.25	33.78	5.54	36.88	46.69	74.00	-27.31	Peak
5185.63	91.01	33.87	5.65	36.89	93.64	74.00	19.64	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4924.27	47.39	33.64	5.37	36.82	49.58	74.00	-24.42	Peak
5150.00	46.95	33.78	5.54	36.88	49.39	74.00	-24.61	Peak
5184.11	101.03	33.87	5.65	36.89	103.66	74.00	29.66	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5135.47	44.97	33.74	5.59	36.88	47.42	74.00	-26.58	Peak
5150.00	44.13	33.78	5.54	36.88	46.57	74.00	-27.43	Peak
5192.18	89.40	33.91	5.65	36.89	92.07	74.00	18.07	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4914.01	47.30	33.65	5.37	36.82	49.50	74.00	-24.50	Peak
5150.00	42.60	33.78	5.54	36.88	45.04	74.00	-28.96	Peak
5188.33	98.39	33.91	5.65	36.89	101.06	74.00	27.06	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4832.28	45.19	33.63	5.60	36.79	47.63	74.00	-26.37	Peak
5150.00	44.73	33.78	5.54	36.88	47.17	74.00	-26.83	Peak
5190.64	89.60	33.91	5.65	36.89	92.27	74.00	18.27	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 05; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4997.12	48.18	33.69	5.64	36.84	50.67	74.00	-23.33	Peak
5150.00	47.77	33.78	5.54	36.88	50.21	74.00	-23.79	Peak
5181.41	102.07	33.87	5.65	36.89	104.70	74.00	30.70	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5325.60	95.15	34.17	5.47	36.93	97.86	74.00	23.86	Peak
5350.00	44.80	34.19	5.60	36.94	47.65	74.00	-26.35	Peak
5385.17	42.36	34.34	5.70	36.95	45.45	74.00	-28.55	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5315.79	104.70	34.16	5.44	36.93	107.37	74.00	33.37	Peak
5350.00	48.08	34.19	5.60	36.94	50.93	74.00	-23.07	Peak
5406.03	48.32	34.36	5.75	36.95	51.48	74.00	-22.52	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Line Limit	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB		
5325.92	93.80	34.17	5.47	36.93	96.51	74.00	22.51	Peak	
5350.00	41.29	34.19	5.60	36.94	44.14	74.00	-29.86	Peak	
5376.69	43.80	34.29	5.63	36.95	46.77	74.00	-27.23	Peak	

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Over Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB		
5323.86	103.94	34.17	5.47	36.93	106.65	74.00	32.65	Peak	
5350.00	45.22	34.19	5.60	36.94	48.07	74.00	-25.93	Peak	
5361.20	48.15	34.24	5.56	36.94	51.01	74.00	-22.99	Peak	

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB		
5314.84	93.21	34.16	5.44	36.93	95.88	74.00	21.88	Peak	
5350.00	41.84	34.19	5.60	36.94	44.69	74.00	-29.31	Peak	
5370.93	43.91	34.29	5.63	36.95	46.88	74.00	-27.12	Peak	

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5315.00	104.49	34.16	5.44	36.93	107.16	74.00	33.16	Peak
5350.00	45.27	34.19	5.60	36.94	48.12	74.00	-25.88	Peak
5364.55	47.27	34.24	5.56	36.94	50.13	74.00	-23.87	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5311.78	89.23	34.16	5.44	36.93	91.90	74.00	17.90	Peak
5350.00	43.46	34.19	5.60	36.94	46.31	74.00	-27.69	Peak
5360.43	45.68	34.24	5.56	36.94	48.54	74.00	-25.46	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5319.80	100.71	34.16	5.44	36.93	103.38	74.00	29.38	Peak
5350.00	45.91	34.19	5.60	36.94	48.76	74.00	-25.24	Peak
5382.04	48.47	34.29	5.63	36.95	51.44	74.00	-22.56	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 06; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5304.13	89.16	34.14	5.63	36.92	92.01	74.00	18.01	Peak
5350.00	43.40	34.19	5.60	36.94	46.25	74.00	-27.75	Peak
5359.36	45.25	34.24	5.56	36.94	48.11	74.00	-25.89	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 06; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5322.65	100.14	34.16	5.44	36.93	102.81	74.00	28.81	Peak
5350.00	46.37	34.19	5.60	36.94	49.22	74.00	-24.78	Peak
5372.85	47.61	34.29	5.63	36.95	50.58	74.00	-23.42	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5453.58	45.73	34.44	5.75	36.97	48.95	74.00	-25.05	Peak
5460.00	46.02	34.44	5.75	36.97	49.24	74.00	-24.76	Peak
5494.85	98.99	34.49	5.67	36.98	102.17	74.00	28.17	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5378.69	48.17	34.29	5.63	36.95	51.14	74.00	-22.86	Peak
5460.00	47.13	34.44	5.75	36.97	50.35	74.00	-23.65	Peak
5496.05	105.53	34.52	5.73	36.98	108.80	74.00	34.80	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5458.87	46.59	34.44	5.75	36.97	49.81	74.00	-24.19	Peak
5460.00	43.79	34.44	5.75	36.97	47.01	74.00	-26.99	Peak
5498.80	98.07	34.52	5.73	36.98	101.34	74.00	27.34	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5441.14	47.61	34.42	5.72	36.96	50.79	74.00	-23.21	Peak
5460.00	46.80	34.44	5.75	36.97	50.02	74.00	-23.98	Peak
5497.94	105.60	34.52	5.73	36.98	108.87	74.00	34.87	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5429.92	42.91	34.39	5.64	36.96	45.98	74.00	-28.02	Peak
5460.00	40.46	34.44	5.75	36.97	43.68	74.00	-30.32	Peak
5495.19	82.16	34.49	5.67	36.98	85.34	74.00	11.34	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5410.93	44.67	34.36	5.75	36.95	47.83	74.00	-26.17	Peak
5460.00	42.95	34.44	5.75	36.97	46.17	74.00	-27.83	Peak
5494.68	89.06	34.49	5.67	36.98	92.24	74.00	18.24	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5455.20	47.59	34.44	5.75	36.97	50.81	74.00	-23.19	Peak
5460.00	47.39	34.44	5.75	36.97	50.61	74.00	-23.39	Peak
5495.33	94.57	34.52	5.73	36.98	97.84	74.00	23.84	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Over Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB		
5422.18	47.35	34.39	5.64	36.96	50.42	74.00	-23.58	Peak	
5460.00	44.53	34.44	5.75	36.97	47.75	74.00	-26.25	Peak	
5499.55	101.69	34.52	5.73	36.98	104.96	74.00	30.96	Peak	

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 07; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5445.50	46.62	34.42	5.72	36.96	49.80	74.00	-24.20	Peak
5460.00	41.71	34.44	5.75	36.97	44.93	74.00	-29.07	Peak
5505.69	92.95	34.52	5.73	36.98	96.22	74.00	22.22	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 07; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB		
5426.53	46.71	34.39	5.64	36.96	49.78	74.00	-24.22	Peak	
5460.00	47.28	34.44	5.75	36.97	50.50	74.00	-23.50	Peak	
5497.25	101.64	34.52	5.73	36.98	104.91	74.00	30.91	Peak	

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Line Over Limit	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	dB	
5620.13	42.32	34.52	5.79	37.00	45.63	68.20	-22.57	Peak	
5649.67	42.97	34.53	5.87	37.00	46.37	68.20	-21.83	Peak	

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5634.49	46.19	34.53	5.83	37.00	49.55	68.20	-18.65	Peak
5641.49	47.25	34.53	5.87	37.00	50.65	68.20	-17.55	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5951.35	41.48	34.85	5.71	37.05	44.99	68.20	-23.21	Peak
5974.80	43.43	34.90	5.97	37.05	47.25	68.20	-20.95	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5929.22	43.88	34.81	5.91	37.05	47.55	68.20	-20.65	Peak
5986.36	43.56	34.94	5.88	37.06	47.32	68.20	-20.88	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Line Limit	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dBuv/m	dB	
5622.84	42.75	34.52	5.79	37.00	46.06	68.20	-22.14	Peak	
5649.28	42.27	34.53	5.87	37.00	45.67	68.20	-22.53	Peak	

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5612.38	46.73	34.52	5.79	37.00	50.04	68.20	-18.16	Peak
5633.71	46.82	34.53	5.83	37.00	50.18	68.20	-18.02	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5943.56	41.78	34.85	5.71	37.05	45.29	68.20	-22.91	Peak
5976.04	41.75	34.94	5.88	37.06	45.51	68.20	-22.69	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5954.64	44.40	34.85	5.71	37.05	47.91	68.20	-20.29	Peak
5979.34	43.74	34.94	5.88	37.06	47.50	68.20	-20.70	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5635.27	43.24	34.53	5.83	37.00	46.60	68.20	-21.60	Peak
5641.10	43.30	34.53	5.87	37.00	46.70	68.20	-21.50	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5636.44	46.00	34.53	5.83	37.00	49.36	68.20	-18.84	Peak
5644.61	46.25	34.53	5.87	37.00	49.65	68.20	-18.55	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5957.93	43.31	34.85	5.71	37.05	46.82	68.20	-21.38	Peak
5983.05	42.39	34.94	5.88	37.06	46.15	68.20	-22.05	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5929.63	43.93	34.81	5.91	37.05	47.60	68.20	-20.60	Peak
5977.28	43.59	34.94	5.88	37.06	47.35	68.20	-20.85	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Emission Limit	Line Limit	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB		
5626.72	43.97	34.53	5.83	37.00	47.33	68.20	-20.87	Peak	
5632.94	42.44	34.53	5.83	37.00	45.80	68.20	-22.40	Peak	

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5611.60	45.78	34.52	5.79	37.00	49.09	68.20	-19.11	Peak
5627.50	46.86	34.53	5.83	37.00	50.22	68.20	-17.98	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5964.92	41.44	34.90	5.97	37.05	45.26	68.20	-22.94	Peak
5991.73	41.75	34.94	5.88	37.06	45.51	68.20	-22.69	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5954.64	43.32	34.85	5.71	37.05	46.83	68.20	-21.37	Peak
5979.75	42.61	34.94	5.88	37.06	46.37	68.20	-21.83	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5622.07	43.17	34.52	5.79	37.00	46.48	68.20	-21.72	Peak
5646.95	42.71	34.53	5.87	37.00	46.11	68.20	-22.09	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5621.68	47.00	34.52	5.79	37.00	50.31	68.20	-17.89	Peak
5629.44	48.92	34.53	5.83	37.00	52.28	68.20	-15.92	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 08; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5964.92	41.91	34.90	5.97	37.05	45.73	68.20	-22.47	Peak
5983.88	42.63	34.94	5.88	37.06	46.39	68.20	-21.81	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 08; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High



Antenna Polarity : VERTICAL

EUT/Project : 0070HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5955.05	44.40	34.85	5.71	37.05	47.91	68.20	-20.29	Peak
5980.99	43.04	34.94	5.88	37.06	46.80	68.20	-21.40	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

7.10 Frequency Stability

Test Requirement 47 CFR Part 15, Subpart E 15.407 (g)

Test Method: ANSI C63.10 (2013) Section 6.8

7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 19.8 °C Humidity: 42.3 % RH Atmospheric Pressure: 1010 mbar

7.10.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40/80, Only the data of worst case is recorded in the report.
Final test	06	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40/80, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40/80, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac/ax 20/40/80, Only the data of worst case is recorded in the report.

7.10.3 Test Setup Diagram

7.10.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SHCR2401000070HS

9 EUT Constructional Details (EUT Photos)

Refer to Appendix - Photographs of EUT Constructional Details for SHCR2401000070HS

- End of the Report -