

WARNING

Risk of explosion. This equipment has arcing or sparking parts that should not be exposed to flammable vapors. This equipment should be located at least 460 mm (18 inches) above the floor.

This device is intended only for charging vehicles not requiring ventilation during charging.

Automatic RCD reset feature provided.

Do not touch the hang plate and heat sink while charging to avoid scald injury.

FCC ID: 2BEVA-CHG50A

IC: 32112-CHG50A

HVIN: CHG50ABV13

FVIN: V1.0.7_48A

CAUTION

Risk of electric shock. Do not remove cover or attempt to open the enclosure after installation. No user serviceable parts inside. Refer servicing to qualified service personnel.

Data Sheet

Model: GS-AC48-B02

Input/Output: 48A/240V AC

Frequency: 50/60Hz

IP Degree: NEMA 4

Operating Temp: -30° to 50°

Environment: Indoor/Outdoor

Manufacturer: Sichuan Green Science & Technology Co., Ltd.

Production Date:

Serial Number:



Made in China

WARNING

Risk of explosion. This equipment has arcing or sparking parts that should not be exposed to flammable vapors. This equipment should be located at least 460 mm (18 inches) above the floor.

This device is intended only for charging vehicles not requiring ventilation during charging.

Automatic RCD reset feature provided.

Do not touch the hang plate and heat sink while charging to avoid scald injury.

FCC ID: 2BEVA-CHG50A

IC: 32112-CHG50A

HVIN: CHG50ABV13

FVIN: V1.0.7_40A

CAUTION

Risk of electric shock. Do not remove cover or attempt to open the enclosure after installation. No user serviceable parts inside. Refer servicing to qualified service personnel.

Data Sheet

Model: GS-AC40-B02

Input/Output: 40A/240V AC

Frequency: 50/60Hz

IP Degree: NEMA 4

Operating Temp: -30° to 50°

Environment: Indoor/Outdoor

Manufacturer: Sichuan Green Science & Technology Co., Ltd.

Production Date:

Serial Number:

FC



Made in China

WARNING

Risk of explosion. This equipment has arcing or sparking parts that should not be exposed to flammable vapors. This equipment should be located at least 460 mm (18 inches) above the floor.

This device is intended only for charging vehicles not requiring ventilation during charging.

Automatic RCD reset feature provided.

Do not touch the hang plate and heat sink while charging to avoid scald injury.

FCC ID: 2BEVA-CHG50A

IC: 32112-CHG50A

HVIN: CHG50ABV13

FVIN: V1.0.7_32A

CAUTION

Risk of electric shock. Do not remove cover or attempt to open the enclosure after installation. No user serviceable parts inside. Refer servicing to qualified service personnel.

Data Sheet

Model: GS-AC32-B02

Input/Output: 32A/240V AC

Frequency: 50/60Hz

IP Degree: NEMA 4

Operating Temp: -30° to 50°

Environment: Indoor/Outdoor

Manufacturer: Sichuan Green Science & Technology Co., Ltd.

Production Date:

Serial Number:



Made in China

Location

