



FCC 47 CFR MPE REPORT

Changsha Benlei Technology Co., Ltd.

Smart Cutting Maching

Model Number: SA501

Additional Model: S501,SA01,SA502,S502,SA02,SA501-PK,SA501-OG,

SA501-PL,SA501-GN,SA501-YL,SA501-BU,SA501-RD,SA501-WH

FCC ID: 2BEVY-SA501

Applicant:	Changsha Benlei Technology Co., Ltd.
Address:	Room 3002-621, Comprehensive Building, Sifang Community,
	No.168 Shuangyong Road, Sifangping Street, Kaifu District,
	Changsha City,Hunan Province,China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R2401206
Date of Test:	Nov. 20, 2023~Jan. 17, 2024
Date of Report:	Jan. 19, 2024

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	-1.19	0.760
	2441	-1.1	0.776
	2480	-0.19	0.957
$\pi/4$ -DQPSK	2402	-0.52	0.887
	2441	-0.47	0.897
	2480	0.45	1.109
BLE 1M	2402	-1.43	0.719
	2440	-1.37	0.729
	2480	-0.5	0.891
BLE 2M	2402	-1.1	0.776
	2440	-1.07	0.782
	2480	-0.12	0.973

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	-0.19	0±1	1	-0.58	0.875	0.00022	1	Complies
$\pi/4$ -DQPSK	0.45	0±1	1	-0.58	0.875	0.00022	1	Complies
BLE 1M	-0.5	0±1	1	-0.58	0.875	0.00022	1	Complies
BLE 2M	-0.12	0±1	1	-0.58	0.875	0.00022	1	Complies

End of Test Report