

RF Exposure Requirements

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Fengyunling Technology Co., Ltd.
Address of applicant: Room 605, Building 43, Universiade Software Town,
No.8288 Longgang Avenue, Henggang Street,
Longgang District, Shenzhen,China

Manufacturer: Shenzhen Fengyunling Technology Co., Ltd.
Address of manufacturer: Room 605, Building 43, Universiade Software Town,
No.8288 Longgang Avenue, Henggang Street,
Longgang District, Shenzhen,China

General Description of EUT

Product Name: Bluetooth handle remote control
Trade Name: /
Model No.: Y01
Adding Model(s): Y03
Rated Voltage: DC 3V from Battery
Power Adapter Model: /
Serial number: S-001
FCC ID: 2BEWK-Y01

Technical Characteristics of EUT	
Bluetooth Version:	BLE
Frequency Range:	2402-2480MHz
RF Output Power:	3.09dBm
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB
Antenna Gain:	-0.08dBi

1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

1.3 Calculation Method

Bluetooth

Tx frequency range: 2402~2480MHz

Min. test separation distance: 5mm

Maximum Tune-up Conducted Output Power: 3.1dBm

RF channel transmit frequency: 2402MHz

Result: 0.6329

Limit: 3.0

So the transmitter complies with the RF exposure requirements and the SAR is not required.