



FCC - TEST REPORT

Report Number : **709502407723-00A** Date of Issue: October 23, 2024

Model : **TTFM-53**

Product Type : Smart Tag

Applicant : Zhejiang Lingzhu Technology CO., Ltd

Address : Room 302, No 1 Building Huace Center, Xihu District, Hangzhou
City, Zhejiang Province, China

Manufacturer : Zhejiang Lingzhu Technology CO., Ltd

Address : Room 302, No 1 Building Huace Center, Xihu District, Hangzhou
City, Zhejiang Province, China

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including
Appendices : 41



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.



1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards	6
5	Summary of Test Results	7
6	General Remarks	8
7	Test Setups	9
8	Systems test configuration	11
9	Technical Requirement.....	12
9.1	Conducted peak output power	12
9.2	6dB bandwidth	14
9.3	Power spectral density.....	16
9.4	Spurious RF conducted emissions	18
9.5	Band edge	22
9.6	Spurious radiated emissions for transmitter.....	25
10	Test Equipment List.....	38
11	System Measurement Uncertainty	39
12	Photographs of Test Set-ups.....	40
13	Photographs of EUT	41



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Telephone: +86 21 6141 0123

Fax: +86 21 6140 8600

FCC Registration No.: 820234

FCC Designation Number: CN1183

ISED CAB identifier CN0101

IC Registration No.: 31668

3 Description of the Equipment under Test

Description of the Equipment Under Test

Product: Smart Tag

Model no.: TTFM-53

FCC ID: 2BEWX-TTFM-53

Options and accessories: NA

Rating: DC 3V

RF Transmission Frequency: 2402~2480 MHz (LE 5.2)

No. of Operated Channel: 40

Modulation: GFSK

Data speed: 1Mbps

Channel list:

Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Antenna Type: PCB

Antenna Gain: -4.44 dBi

Description of the EUT: The Equipment Under Test (EUT) is a Smart Tag with BLE function which support BLE operated 1Mbps. We tested it and listed the worst data in this report.



Test sample no.: SHA-849602-2 (Radiated sample)
 SHA-849602-3 (Conducted sample)

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Measurement Guidance v05r02 and ANSI C63.10-2013.



5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	---	---	☒	☐	☐
§15.247 (b) (3)	Conducted peak output power	12-13	Site 1	☒	☐	☐
§15.247(a)(1)	20dB bandwidth and 99% Occupied Bandwidth	---	---	☐	☐	☒
§15.247(a)(1)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Dwell Time - Average Time of Occupancy	---	---	☐	☐	☒
§15.247(a)(2)	6dB bandwidth	14-15	Site 1	☒	☐	☐
§15.247(e)	Power spectral density	16-17	Site 1	☒	☐	☐
§15.247(d)	Spurious RF conducted emissions	18-21	Site 1	☒	☐	☐
§15.247(d)	Band edge	22-24	Site 1	☒	☐	☐
§15.247(d) & §15.209 & §15.205	Spurious radiated emissions for transmitter	25-37	Site 1	☒	☐	☐
§15.203	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.

Remark 2: The EUT uses a PCB Antenna, which gain is -4.44dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2BEWX-TTFM-53, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

We tested it and listed the worst data in this report.

SUMMARY:

All tests according to the regulations cited on page 7 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: September 13, 2024

Testing Start Date: September 23, 2024

Testing End Date: October 15, 2024

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:



Hui TONG
Review Engineer


Wenqiang LU
Project Engineer

Tianji XU
Test Engineer


7 Test Setups

7.1 Radiated test setups

9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:







1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.2 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	E470	PF-OU5TS7 17/09

Test software: BK32xx RF Test_V2.1.0.exe, which used to control the EUT in continues transmitting mode.

The system was configured to channel 0, 19, and 39 for the test.

Test Mode Applicability and Tested Channel Detail:

Mode	Tested Channel	Data Rate (Mbps)	Modulation	Power level setting
Bluetooth LE	0	1	GFSK	7
	19	1	GFSK	7
	39	1	GFSK	7

9 Technical Requirement

9.1 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
RBW > the 6 dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

Limits

According to §15.247 (b) (3), conducted peak output power limit as below:


	Frequency Range	Limit	Limit
	MHz	W	dBm
Conducted peak output power	2400-2483.5	≤ 1	≤ 30

Test result as below table

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	4.56	Pass
Middle channel 2440MHz	4.58	Pass
High channel 2480MHz	4.42	Pass



Peak output power (1Mbps)





9.2 6dB bandwidth

Test Method for 6 dB Bandwidth

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
RBW=100KHz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Use the automatic bandwidth measurement capability of an instrument, use the X dB bandwidth mode with X set to 6 dB.
5. Allow the trace to stabilize, record the 6 dB Bandwidth value.

Limit

According to §15.247(a)(2), 6dB bandwidth limit as below:


6dB bandwidth Limit [kHz]
≥ 500

Test result

Frequency MHz	6dB bandwidth kHz	Result
Top channel 2402MHz	705	Pass
Middle channel 2440MHz	695	Pass
Bottom channel 2480MHz	690	Pass



6dB Bandwidth



9.3 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:


1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
4. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
5. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
6. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3KHz]
 ≤ 8

Test result

Frequency MHz	Power spectral density dBm/3kHz	Result
Top channel 2402MHz	-10.72	Pass
Middle channel 2440MHz	-10.9	Pass
Bottom channel 2480MHz	-10.31	Pass



9.4 Spurious RF conducted emissions

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.

Limit


According to §15.247(d), spurious RF conducted emissions limit as below:

Frequency Range MHz	Limit (dBc)
30-25000	-20




Spurious RF conducted emissions

Out-of-Band Emissions (1Mbps)
Channel 0 (2402MHz)






Out-of-Band Emissions (1Mbps)
Channel 19 (2440MHz)





Out-of-Band Emissions (1Mbps)
Channel 39 (2480MHz)





9.5 Band edge

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize, use the peak and delta measurement to record the result.
5. The level displayed must comply with the limit specified in this Section.
6. Repeat above procedures until all frequencies measured were complete and submit all the plots.

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3), the attenuation required shall be 30 dB instead of 20 dB.


According to §15.247(d), band edge limit as below:


Frequency Range	Limit (dBc)
MHz	
30-25000	-20



Test result

1Mbps





9.6 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10
 - 1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz to 120kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 2) For Peak unwanted emissions Above 1GHz:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
Procedures for average unwanted emissions measurements above 1GHz
 - a) RBW = 1MHz.
 - b) VBW \ [3 × RBW].
 - c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2.
Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
 - d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
 - e) Sweep time = auto.
 - f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
 - g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
 - 2) If linear voltage averaging mode was used in the preceding step e), then the correction



factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission (AV) at frequency above 1GHz.

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

Frequency MHz	Field Strength μV/m	Field Strength dBμV/m	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit 3m(dBμV/m)=Limit 300m(dBμV/m)+40Log(300m/3m) (Below 30MHz)

Note 2: Limit 3m(dBμV/m)=Limit 30m(dBμV/m)+40Log(30m/3m) (Below 30MHz)

Spurious Radiated Emissions for Transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Data of measurement within frequency range 9kHz-30MHz is the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss-Amplifier Factor

(The Reading Level is recorded by software which is not shown in the sheet)



Test result

The worst case of Radiated Emission below 1GHz: Only the worst case listed as below.

30-1000MHz Radiated Emission

EUT Information


EUT Name:	Smart Tag
Model:	TTFM-53
Client:	Zhejiang Lingzhu Technology CO., Ltd
Op Cond:	Power on and TX at 2440MHz
Operator:	Tianji XU
Test Spec:	FCC Part 15.209(a)
Sample No:	SHA-849602-2

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup:	RE_VULB9168
Receiver:	[ESR 3]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)
42.360000	18.5	1000.0	120.000	112.0	H	31.0	20.1	21.5
60.720000	18.4	1000.0	120.000	100.0	H	228.0	20.0	21.6
115.320000	20.5	1000.0	120.000	211.0	H	34.0	17.7	23.0
144.540000	26.8	1000.0	120.000	200.0	H	186.0	20.6	16.7
156.200000	28.7	1000.0	120.000	236.0	H	224.0	21.0	14.8
446.840000	26.1	1000.0	120.000	301.0	H	196.0	25.8	19.9

(continuation of the "Limit and Margin" table from column 16 ...)

Frequency (MHz)	Limit - QPK (dBuV/m)	Comment
42.360000	40.0	
60.720000	40.0	
115.320000	43.5	
144.540000	43.5	
156.200000	43.5	
446.840000	46.0	

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
 Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)



30-1000MHz Radiated Emission

EUT Information


EUT Name: Smart Tag
Model: TTFM-53
Client: Zhejiang Lingzhu Technology CO., Ltd
Op Cond: Power on and TX at 2440MHz
Operator: Tianji XU
Test Spec: FCC Part 15.209(a)
Sample No: SHA-849602-2

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup: RE_VULB9168
Receiver: [ESR 3]
Level Unit: dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB

RE_VULB9168_pre_Cont_30-1000





Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)
31.360000	25.2	1000.0	120.000	100.0	H	332.0	19.4	14.8
136.360000	24.5	1000.0	120.000	212.0	H	12.0	20.0	19.0
142.520000	24.1	1000.0	120.000	150.0	H	134.0	20.6	19.4
171.480000	21.4	1000.0	120.000	100.0	H	286.0	20.2	22.1
437.920000	25.7	1000.0	120.000	186.0	H	331.0	25.6	20.3
731.160000	31.2	1000.0	120.000	224.0	H	186.0	31.5	14.8

(continuation of the "Limit and Margin" table from column 16 ...)

Frequency (MHz)	Limit - QPK (dBuV/m)	Comment
31.360000	40.0	
136.360000	43.5	
142.520000	43.5	
171.480000	43.5	
437.920000	46.0	
731.160000	46.0	

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)



Radiated Emission 1-18GHz


Frequency:2402MHz

RE_HF907_BRF_Pre



Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azi mut h	Corr. (dB)	Margin - PK+ (dB)	Limit - PK+ (dBuV/
1570.600000	43.2	100.0	V	65.0	-14.2	30.8	74.0
7206.700000	48.5	192.0	V	136.	0.8	25.5	74.0
16726.600000	51.8	183.0	V	227.	7.2	22.2	74.0


RE_HF907_BRF_Pre



Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2366.390000	47.1	104.0	H	124.0	-0.8	26.9	74.0
2390.800000	46.3	162.0	H	13.0	-0.8	27.7	74.0
2402.000000	97.5	177.0	H	227.0	-0.8	/	/




RE_HF907_BRF_Pre



Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azimuth	Corr. (dB)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
1991.800000	40.3	201.0	V	331.	-11.9	33.7	74.0
7206.700000	50.1	136.0	V	15.0	0.8	23.9	74.0
15696.400000	51.2	106.0	V	227.	5.8	22.8	74.0

RE_HF907_BRF_Pre




Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2374.600000	46.1	117.0	V	135.0	-0.8	27.9	74.0
2390.800000	46.4	140.0	V	31.0	-0.8	27.6	74.0
2402.000000	89.5	138.0	V	213.0	-0.8	/	/




Frequency:2440MHz

RE_HF907_BRF_Pre



Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azi mut h	Corr. (dB)	Margin - PK+ (dB)	Limit - PK+ (dBuV/)
7319.200000	50.1	137.0	V	321.	0.8	23.9	74.0
11241.400000	50.3	116.0	V	137.	4.5	23.7	74.0
15723.700000	51.9	220.0	V	287.	5.8	22.1	74.0

RE_HF907_BRF_Pre




Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azi mut h	Corr. (dB)	Margin - PK+ (dB)	Limit - PK+ (dBuV/)
7320.400000	47.6	122.0	V	311.	0.8	26.4	74.0
10053.100000	49.5	149.0	V	258.	3.6	24.5	74.0
15881.800000	51.6	206.0	V	96.0	5.9	22.4	74.0




Frequency:2480MHz

RE_HF907_BRF_Pre



Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azi mut h	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/
6908.800000	46.1	156.0	H	325.	0.5	27.9	74.0
7440.100000	49.8	214.0	H	23.0	0.8	24.2	74.0
17130.100000	51.9	152.0	H	117.	7.3	22.1	74.0


RE_HF907_BRF_Pre



Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2480.000000	95.8	117.0	H	21.0	-0.3	/	/
2483.500000	51.4	209.0	H	335.0	-0.3	22.6	74.0
2509.000000	50.7	136.0	H	48.0	-0.2	23.3	74.0




RE_HF907_BRF_Pre



Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azimuth	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/)
7438.600000	47.5	100.0	V	53.0	0.8	26.5	74.0
13813.600000	51.2	181.0	V	117.	4.7	22.8	74.0
16772.200000	52.3	171.0	V	287.	7.1	21.7	74.0

RE_HF907_BRF_Pre




Frequency (MHz)	MaxPeak (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2480.000000	86.7	195.0	V	359.0	-0.3	/	/
2483.500000	47.1	197.0	V	42.0	-0.3	26.9	74.0
2493.400000	46.4	167.0	V	135.0	-0.3	27.6	74.0

The worst case of Radiated Emission Above 18GHz

Frequency:2480MHz


Full Spectrum



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
18488.812500	---	42.49	54.00	11.51	192.0	H	215.0	8.1
18528.000000	47.68	---	74.00	26.32	142.0	H	283.0	8.1
24468.687500	50.32	---	74.00	23.68	144.0	H	276.0	9.0
24547.062500	---	44.99	54.00	9.01	105.0	H	283.0	9.0
28299.437500	51.17	---	74.00	22.83	213.0	H	113.0	9.5
28322.812500	---	46.36	54.00	7.64	164.0	H	98.0	9.6
30130.937500	52.49	---	74.00	21.51	212.0	H	46.0	10.0
30211.375000	---	46.38	54.00	7.62	211.0	H	120.0	10.0
34183.750000	---	47.37	54.00	6.63	217.0	H	347.0	11.4
34244.937500	52.50	---	74.00	21.50	124.0	H	0.0	11.5
36811.375000	55.17	---	74.00	18.83	137.0	H	229.0	13.2
36902.125000	---	48.94	54.00	5.06	129.0	H	193.0	13.2

Full Spectrum



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
18484.687500	49.15	---	74.00	24.85	193.0	V	35.0	8.1
18595.375000	---	43.60	54.00	10.40	137.0	V	298.0	8.1
23132.187500	49.88	---	74.00	24.12	115.0	V	0.0	8.9
23222.250000	---	45.44	54.00	8.56	174.0	V	173.0	8.9
28433.500000	52.11	---	74.00	21.89	125.0	V	56.0	9.6
28876.250000	---	45.62	54.00	8.38	109.0	V	135.0	9.5
30460.937500	53.45	---	74.00	20.55	185.0	V	0.0	10.1
31622.812500	---	46.71	54.00	7.29	107.0	V	246.0	10.1
34809.375000	---	48.30	54.00	5.70	189.0	V	290.0	12.1
34843.750000	53.07	---	74.00	20.93	160.0	V	152.0	12.2
36938.562500	54.64	---	74.00	19.36	171.0	V	70.0	13.2
36989.437500	---	49.01	54.00	4.99	182.0	V	0.0	13.2

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss - Amplifier gain
- (3) Margin = limit – Corrected Reading

10 Test Equipment List

List of Test Instruments
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal spectrum analyzer	Agilent	N9020B	MY59050168	2024-2-19	2025-2-18
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2024-8-1	2025-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2024-8-1	2025-7-31
	Trilog Super Broadband Test Antenna	SCHWARZBECK	VULB 9168	961	2024-8-30	2025-8-29
	Double-ridged waveguide horn antenna	Rohde & Schwarz	HF907	102868	2024-4-14	2027-4-13
	Pre-amplifier	Shenzhen HzEMC	HPA-081843	HYP A23026	2024-4-16	2025-4-15
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2024-6-26	2025-6-25
	Double Ridged Horn Antenna	ETS-Lindgren	3116C	00246076	2023-7-7	2026-7-6
CE	3m Semi-anechoic chamber	TDK	9X6X6	----	2025-4-15	2027-5-7
	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2024-8-1	2025-7-31
	LISN	Rohde & Schwarz	ENV216	101924	2024-8-1	2025-7-31

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	MTS 8310	MWRFTtest	3.0.0.0
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	9kHz to 30MHz, 3.52dB 30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
RF Conducted Measurement	Power related: 1.16dB Frequency related: 6.00×10^{-8}

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3.



12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

-----End of Test Report-----