

Test report No:
2570646R.702B

FCC TEST REPORT

Product Name	Smart Camera
Trademark	N/A
Model and /or type reference	SC155-WG3C, SC256-WG5
FCC ID	2BEWXSC256WG
Applicant's name / address	Zhejiang Lingzhu Technology Co., Ltd. Room 302, No 1 Building Huace Center, Xihu District, Hangzhou City, Zhejiang Province, China
Test method requested, standard	47 CFR FCC Part 15 (Section 15.247) ANSI C63.10: 2020
Verdict Summary	IN COMPLIANCE
Documented by (name / position & signature)	Tim Cao / Project Manager 
Approved by (name / position & signature)	Frank He / Technical Manager 
Date of issue	2025-09-10
Report Version	V1.0
Report template No	Template_FCC Part 15C-RF-V1.0

INDEX

	page
General conditions	4
Environmental conditions	4
Possible test case verdicts	5
Abbreviations	5
Document History	6
Remarks and Comments.....	6
Used Equipment	7
Uncertainty	9
1 General Information.....	10
2 Description of Test Setup	11
2.1 Auxiliary equipment /Accessories/Test software for the EUT	11
2.2 Test Configuration / Block diagram used for tests	12
3 Verdict summary section	14
3.1 Standards.....	14
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	14
3.3 Overview of results.....	15
3.4 Test Facility.....	16
4 Test Items Of Limit/Setup/Procedure	17
4.1 DTS Bandwidth	17
4.1.1 Limit	17
4.1.2 Test Setup.....	17
4.1.3 Test Procedure	17
4.2 Maximum Conducted Output Power	18
4.2.1 Limit	18
4.2.2 Test Setup.....	18
4.2.3 Test Procedure	19
4.3 Maximum Power Spectral Density	20
4.3.1 Limit	20
4.3.2 Test Setup.....	20
4.3.3 Test Procedure	20
4.4 Band Edge Measurements	21
4.4.1 Limit	21
4.4.2 Test Setup.....	21
4.4.3 Test Procedure	21

4.5	Conducted Spurious Emission	22
4.5.1	Limit	22
4.5.2	Test Setup	22
4.5.3	Test Procedure	22
4.6	Duty cycle	23
4.6.1	Limit	23
4.6.2	Test Setup	23
4.6.3	Test Procedure	23
4.7	Emissions in Restricted Bands	24
4.7.1	Limit	24
4.7.2	Test Setup	25
4.7.3	Test Procedure	26
4.8	AC Power Line Conducted Emission	27
4.8.1	Limit	27
4.8.2	Test Setup	27
4.9.3	Test Procedure	27
4.9	Antenna Requirement.....	28
4.9.1	Limit:	28
4.9.2	Antenna Connector Construction:	28
5	Test setup photo and EUT Photo.....	29
6	Test Result.....	30
	Appendix A: DTS Bandwidth	30
	Appendix B: Maximum conducted output power	44
	Appendix C: Maximum power spectral density.....	45
	Appendix D: Band edge measurements.....	52
	Appendix E: Emissions in non restricted frequency bands	84
	Appendix F: Duty Cycle	106
	Appendix G: Emissions in Restricted Bands	113
	Appendix H: AC Power Line Conducted Emission	165

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Jul. 22, 2025
Date (start test)	Jul. 25, 2025
Date (finish test)	Sep.10, 2025

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2570646R.702B	V1.0	Initial issue of report.	2025-09-10

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with 47 CFR FCC Part 15 (Section 15.247).
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1 General Information.

USED EQUIPMENT

Conducted Test / TR8

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
Wireless Connectivity Tester	R&S	CMW 270	102593	2025.05.10	2026.05.09	V 4.0.60	N/A
Coaxial Cable	N/A	N/A	2477	2025.06.11	2026.06.10	N/A	N/A
Coaxial Cable	N/A	N/A	2478	2025.06.11	2026.06.10	N/A	N/A
High and low temperature and fast temperature change test box	ASTUOD	ASTD-FBT-225K	N/A	2025.03.15	2026.03.14	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-1909	THM-032	2025.07.11	2026.07.10	N/A	N/A
Test system							
Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
MAX Signal Analyzer	Keysight	N9010A	MY48030494	2024.10.26	2025.10.25	A.14.03	N/A
RF Control Unit	Tonscend	JS0806-2	22G8060594	2025.01.26	2026.01.25	N/A	N/A
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	2025.03.23	2026.03.22	B.01.96	N/A
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	2025.03.23	2026.03.22	N/A	N/A
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	2025.07.06	2026.07.05	B.01.95	N/A
Test Software	Tonscend	TS1120	JS1120-3	N/A	N/A	N/A	V3.0.22

Radiated Emissions (30MHz-40GHz) / AC6

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
Signal analyzer	R&S	FSV30	104212	2025.07.06	2026.07.05	A 08.54	N/A
Half Wave Tuned Dipole Antenna	COM-POWER	AD-100	40137	2023.04.07	2026.04.06	N/A	N/A
Horn Antenna	RFSPIN	DRH18-E	CE2C07A18EN	2024.12.07	2025.12.06	N/A	N/A
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9168	01231	2025.05.28	2026.05.27	N/A	N/A
Pre-Amplifier	XH	LNA1845	LNA23040284	2025.07.04	2026.07.03	N/A	N/A
Pre-Amplifier	SCHWARZBECK	BBV 9721	00114	2025.07.04	2026.07.03	N/A	N/A
Coaxial Cable	N/A	N/A	2225	2025.06.11	2026.06.10	N/A	N/A
Notch Filter	Micro-mve	MFN-2400.2485.S1	AN0003N	2025.06.11	2026.06.10	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	RF04	2025.07.11	2026.07.10	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	RF08	2025.07.11	2026.07.10	N/A	N/A
Test Software	Tonscend	JS36	JS36-RSE	N/A	N/A	N/A	V5.0.0

Radiated Emission(9KHz-1GHz) / AC2

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100176	2025.05.12	2026.05.11	4.42 SP3	N/A
Loop Antenna	R&S	HFH2-Z2E	101149	2025.03.27	2026.03.26	N/A	N/A
Bilog Antenna	Teseq GmbH	CBL6112D	27613	2024.09.08	2025.09.07	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	AC2-TH	2025.07.04	2026.07.03	N/A	N/A
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2025.04.27	2026.04.26	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	3

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95% .

Test item	Uncertainty
AC Power Line Conducted Emission	9kHz~150kHz: 2.8 dB 150kHz~30MHz: 2.4 dB
Peak Power Output	± 1.3 dB
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~300MHz: 3.5 dB, 300MHz~1GHz: 3.6 dB Vertical: 30MHz~300MHz: 3.6 dB, 300MHz~1GHz: 3.5 dB
Radiated Emission(1GHz~40GHz)	Horizontal: 1GHz~40GHz: 5.0 dB Vertical: 1GHz~40GHz: 4.8 dB
RF antenna conducted test	± 1.3 dB
Radiated Emission Band Edge	± 5.0 dB
DTS Bandwidth	± 1.0 kHz
Occupied Bandwidth	± 1.0 kHz
Power Density	± 1.3 dB

1 GENERAL INFORMATION

Product Name	Smart Camera
Model No.	SC155-WG3C, SC256-WG5
Model difference.....	The differences between SC155-WG3C & SC256-WG5 are identical except the main control, sensor, main board ,lens and software version, others are all same.
Trademark.....	N/A
Operating temperature	-20~50 °C
Manufacturer	Zhejiang Lingzhu Technology Co., Ltd.
Manufacturer address.....	Room 302, No 1 Building Huace Center, Xihu District, Hangzhou City, Zhejiang Province,China
Power Supply	5Vdc 1.5A Max.(type C) 3.7Vdc (lithium-ion battery)
Test SN.....	JRPGF06FN00001
Wireless specification	802.11b/g/n
Operating frequency range(s)	2400-2483.5MHz
Type of Modulation.....	802.11b:DSSS-DBPSK,DQPSK,CCK 802.11g/n: OFDM-BPSK, QPSK, 16QAM, 64QAM
Antenna Type.....	Dipole
Antenna Gain	0.49 dBi

Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

2 DESCRIPTION OF TEST SETUP


2.1 Auxiliary equipment /Accessories/Test software for the EUT

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) Notebook	Think pad x220	Lenovo	Adapter
(2) USB Control Cable	N/A	N/A	N/A
(3) USB Control Cable	N/A	N/A	N/A
software	Type / Version	Manufacturer	Supplied by
AmebaD_mptool	2.1	N/A	N/A


Accessories Information	Cable		
	Length used during test [m]	Attached during test	Shielded
(2)USB Control Cable	1	☒	☐
(3)USB Control Cable	8	☒	☐

2.2 Test Configuration / Block diagram used for tests


Test setup Diagram- Conducted test



Test setup Diagram- Radiated test



Test setup Diagram- AC Line Conducted Emission Test



3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
CFR 47, FCC Part 15 C	2024	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.
(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

Requirement – Test Item	Standard(s)	Verdict	Remark
DTS Bandwidth	FCC 15.247(a)(2)	PASS	Test data please refer to Appendix A
Maximum conducted output power	15.247 (b)(3)	PASS	Test data please refer to Appendix B
Maximum power spectral density	FCC 15.247(e)	PASS	Test data please refer to Appendix C
Band edge measurements	FCC 15.247(d) FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix D
Conducted Spurious Emission	FCC 15.247(d), FCC 15.209	PASS	Test data please refer to Appendix E
Duty cycle	ANSI C63.10:2020	PASS	Test data please refer to Appendix F
Emissions in Restricted Bands	FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix G
AC Power Line Conducted Emission	FCC 15.207	PASS	Test data please refer to Appendix H
Antenna Requirement	FCC 15.203	PASS	---
Note: The radiation measurement is pre tested under X, Y, and Z axis positioning to find the worst placement for final testing.			

Mode	Channel	Frequency(MHz)	Power Setting
802.11b 1Mbps	1	2412	106
	6	2437	106
	11	2462	106
802.11g 6Mbps	1	2412	102
	6	2437	103
	11	2462	103
802.11n-HT20 MCS0	1	2412	98
	6	2437	98
	11	2462	100
802.11n-HT40 MCS0	3	2422	98
	6	2437	98
	9	2452	96

3.4 Test Facility

Test Location : FCC Designation Number: CN1199

4 TEST ITEMS OF LIMIT/SETUP/PROCEDURE

4.1 DTS Bandwidth

VERDICT: PASS


4.1.1 Limit

Standard

FCC Part 15 Subpart C Paragraph 15.247 (a)(2);

Systems using digital modulation techniques operate in the 2400-2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz

4.1.2 Test Setup



4.1.3 Test Procedure

	Reference Rule	Chapter	Description
☒	ANSI C63.10	11.8	DTS bandwidth
☐	ANSI C63.10	11.8.1	Option 1
☒	ANSI C63.10	11.8.2	Option 2
☒	ANSI C63.10	6.9	Occupied bandwidth
☐	ANSI C63.10	6.9.2	relative measurement procedure
☒	ANSI C63.10	6.9.3	power bandwidth (99%) measurement procedure

4.2 Maximum Conducted Output Power


VERDICT: PASS

4.2.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247 (b)(3);
☒	GTX <6dBi	Pout≤30dBm
☐	GTX >6dBi	
☐	Non-Fix point-point	Pout≤30-(GTX -6)
☐	Fix point-point	Pout≤30-[(GTX-6)]/3
☐	Point-to-multipoint	Pout≤30-(GTX-6)
☐	Overlap Beams	Pout≤30-[(GTX-6)]/3
☐	Aggregate power transmitted simultaneously on all beams	Pout≤30-[(GTX-6)]/3
☐	single directional beam	Pout≤30-[(GTX-6)]/3+8dB

Note 1 : GTX directional gain of transmitting antennas.
Note 2 : Pout is maximum peak conducted output power .

4.2.2 Test Setup



4.2.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.9	Fundamental emission output power
	☐	ANSI C63.10		11.9.1 Maximum peak conducted output power
		☐	ANSI C63.10	11.9.1.1 RBW $\geq$ DTS bandwidth
		☐	ANSI C63.10	11.9.1.2 Integrated band power method
		☐	ANSI C63.10	11.9.1.3 PKPM1 Peak power meter method
	☒	ANSI C63.10		11.9.2 Maximum conducted (average) output power
		☐	ANSI C63.10	11.9.2.2 Measurement using a spectrum analyzer (SA)
		☐	ANSI C63.10	11.9.2.2.2 Method AVGSA-1(Duty cycle $\geq 98\%$)
		☐	ANSI C63.10	11.9.2.2.3 Method AVGSA-1A(Duty cycle $\geq 98\%$)
		☐	ANSI C63.10	11.9.2.2.4 Method AVGSA-2(Duty cycle $\leq 98\%$)
		☐	ANSI C63.10	11.9.2.2.5 Method AVGSA-2A(Duty cycle $\leq 98\%$)
		☐	ANSI C63.10	11.9.2.2.4 Method AVGSA-3
		☐	ANSI C63.10	11.9.2.2.5 Method AVGSA-3A
		☒	ANSI C63.10	11.9.2.3 Measurement using a power meter (PM)
		☒	ANSI C63.10	11.9.2.3.1 Method AVGPM
		☐	ANSI C63.10	11.9.2.3.2 Method AVGPM-G

4.3 Maximum Power Spectral Density


VERDICT: PASS

4.3.1 Limit

Standard FCC Part 15 Subpart C Paragraph 15.247 (b)(3);

 Power Spectral Density $\leq 8\text{dBm}/3\text{kHz}$

4.3.2 Test Setup



4.3.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.10	Maximum power spectral density level in the fundamental emission
	☐	ANSI C63.10	11.10.2	Method PKPSD (peak PSD)
	☒	ANSI C63.10	11.10.3	Method AVGPSD-1(Duty cycle $\geq 98\%$)
	☐	ANSI C63.10	11.10.4	Method AVGPSD-1A(Duty cycle $\geq 98\%$)
	☐	ANSI C63.10	11.10.5	Method AVGPSD-2(Duty cycle $< 98\%$)
	☐	ANSI C63.10	11.10.6	Method AVGPSD-2A(Duty cycle $< 98\%$)
	☐	ANSI C63.10	11.10.7	Method AVGPSD-3
	☐	ANSI C63.10	11.10.8	Method AVGPSD-3A

4.4 Band Edge Measurements

VERDICT: PASS


4.4.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(d) , 15.209;		
Frequency bands (MHz)	Detector	Limit (dB μ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

4.4.2 Test Setup

Above 1GHz Test Setup:



4.4.3 Test Procedure


	References Rule	Chapter	Description
☒	ANSI C63.10	6.10	Band-edge testing
☒	☒ ANSI C63.10	6.10.5	Restricted-band band-edge measurements
☐	☐ ANSI C63.10	6.10.6	Marker-delta method
☒	ANSI C63.10	11.12	Emissions in restricted frequency bands
☒	☒ ANSI C63.10	11.12.1	Radiated emission measurements
☒	☒ ANSI C63.10	11.12.2.7	Radiated spurious emission test
☐	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.5 Conducted Spurious Emission**VERDICT: PASS****4.5.1 Limit**

Standard	FCC Part 15 Subpart C Paragraph 15.247(d);
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

4.5.2 Test Setup**4.5.3 Test Procedure**

References Rule	Chapter	Description
☒ ANSI C63.10	11.11	Emissions in non-restricted frequency bands
☒ ANSI C63.10	11.11.1	General
☒ ANSI C63.10	11.11.2	Reference level measurement
☒ ANSI C63.10	11.11.3	Emission level measurement

4.6 Duty cycle	VERDICT: PASS
----------------	---------------

4.6.1 Limit
N/A

4.6.2 Test Setup

The diagram illustrates the test setup. On the left, a 'Test system' is shown, which includes a computer monitor displaying a waveform and several control units below it. On the right, a 'Temperature and chamber' is depicted, featuring a control panel and a chamber door with 'EUT' (Equipment Under Test) visible inside. A blue line connects the test system to the chamber. Below these components, a horizontal bar represents the 'Ground Reference Plane', with arrows pointing outwards from its center.

4.6.3 Test Procedure			
References Rule		Chapter	Description
☒	ANSI C63.10	11.6	Duty cycle (D), transmission duration (T), and maximum power control level

4.7 Emissions in Restricted Bands**VERDICT: PASS****4.7.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.205

Restricted Bands of operation

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

Restricted Band Emissions Limit

FCC Part 15 Subpart C Paragraph 15.209

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)


Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment.


Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.7.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



4.7.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10	11.12.1	Radiated emission measurements
	☒	ANSI C63.10	11.12.2.7	Radiated spurious emission test
	☒	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	☒	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.8 AC Power Line Conducted Emission

VERDICT: PASS

4.8.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.207 ;	
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾]	Limit: AV [dB(μV) ¹⁾]
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50


¹⁾ At the transition frequency, the lower limit applies.

²⁾ The limit decreases linearly with the logarithm of the frequency.

NOTE 1: The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.

NOTE 2: Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.

4.8.2 Test Setup



4.9.3 Test Procedure

	References Rule	Chapter	Item
☒	ANSI C63.10	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.9 Antenna Requirement**VERDICT: PASS****4.9.1 Limit:****Standard**

FCC Part 15 Subpart C Paragraph 15.203;

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.9.2 Antenna Connector Construction:

The use of a permanently attached antenna



The antenna use of a unique coupling to the intentional radiator



The use of a nonstandard antenna jack or electrical connector

Please refer to the attached document "Internal Photograph" to show the antenna connector.

5 TEST SETUP PHOTO AND EUT PHOTO


Remark: The test setup photo and EUT Photo please see appendix.

6 TEST RESULT

Appendix A: DTS Bandwidth

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.000	2407.000	2417.000	0.5	PASS
11B	Ant1	2437	10.000	2432.040	2442.040	0.5	PASS
11B	Ant1	2462	10.000	2457.000	2467.000	0.5	PASS
11G	Ant1	2412	16.520	2403.760	2420.280	0.5	PASS
11G	Ant1	2437	16.480	2428.760	2445.240	0.5	PASS
11G	Ant1	2462	16.440	2453.800	2470.240	0.5	PASS
11N20SISO	Ant1	2412	17.560	2403.240	2420.800	0.5	PASS
11N20SISO	Ant1	2437	17.560	2428.240	2445.800	0.5	PASS
11N20SISO	Ant1	2462	17.640	2453.200	2470.840	0.5	PASS
11N40SISO	Ant1	2422	36.320	2403.840	2440.160	0.5	PASS
11N40SISO	Ant1	2437	36.320	2418.840	2455.160	0.5	PASS
11N40SISO	Ant1	2452	36.320	2433.840	2470.160	0.5	PASS

Test Graphs







11B-Ant1-2437-PASS



11B-Ant1-2462-PASS




11G-Ant1-2412-PASS




11G-Ant1-2437-PASS




11G-Ant1-2462-PASS




11N20SISO-Ant1-2412-PASS




11N20SISO-Ant1-2437-PASS




11N20SISO-Ant1-2462-PASS



11N40SISO-Ant1-2422-PASS



11N40SISO-Ant1-2437-PASS




11N40SISO-Ant1-2452-PASS

Occupied Channel Bandwidth Test Result


TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	14.512	2404.7831	2419.2951	---	---
11B	Ant1	2437	14.536	2429.7508	2444.2868	---	---
11B	Ant1	2462	14.506	2454.7705	2469.2765	---	---
11G	Ant1	2412	16.956	2403.4688	2420.4248	---	---
11G	Ant1	2437	16.933	2428.4816	2445.4146	---	---
11G	Ant1	2462	16.962	2453.4695	2470.4315	---	---
11N20SISO	Ant1	2412	17.910	2403.0780	2420.9880	---	---
11N20SISO	Ant1	2437	17.854	2428.0709	2445.9249	---	---
11N20SISO	Ant1	2462	17.960	2453.0110	2470.9710	---	---
11N40SISO	Ant1	2422	35.739	2404.1905	2439.9295	---	---
11N40SISO	Ant1	2437	35.766	2419.1640	2454.9300	---	---
11N40SISO	Ant1	2452	35.758	2434.1629	2469.9209	---	---

Test Graphs







11B-Ant1-2462




11G-Ant1-2412




11G-Ant1-2437




11G-Ant1-2462




11N20SISO-Ant1-2412




11N20SISO-Ant1-2437




11N20SISO-Ant1-2462



11N40SISO-Ant1-2422



11N40SISO-Ant1-2437



11N40SISO-Ant1-2452


Appendix B: Maximum conducted output power


Test Mode	Frequency [MHz]	Conducted Power [dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
802.11b 1Mbps	2412	17.64	≤ 30	18.13	≤ 36	PASS
	2437	17.83	≤ 30	18.32	≤ 36	PASS
	2462	17.68	≤ 30	18.17	≤ 36	PASS
802.11g 6Mbps	2412	16.58	≤ 30	17.07	≤ 36	PASS
	2437	16.85	≤ 30	17.34	≤ 36	PASS
	2462	16.47	≤ 30	16.96	≤ 36	PASS
802.11n- HT20 MCS0	2412	15.41	≤ 30	15.9	≤ 36	PASS
	2437	15.88	≤ 30	16.37	≤ 36	PASS
	2462	15.84	≤ 30	16.33	≤ 36	PASS
802.11n- HT40 MCS0	2412	14.89	≤ 30	15.38	≤ 36	PASS
	2437	14.92	≤ 30	15.41	≤ 36	PASS
	2462	14.81	≤ 30	15.3	≤ 36	PASS
Note: EIRP [dBm] = Conducted Power [dBm] + Antenna Gain [dBi], Please refer to Chapter 1 for antenna gain.						

Appendix C: Maximum power spectral density


TestMode	Antenna	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-13.61	≤8.00	PASS
11B	Ant1	2437	-13.52	≤8.00	PASS
11B	Ant1	2462	-13.63	≤8.00	PASS
11G	Ant1	2412	-14.49	≤8.00	PASS
11G	Ant1	2437	-14.79	≤8.00	PASS
11G	Ant1	2462	-14.29	≤8.00	PASS
11N20SISO	Ant1	2412	-15.65	≤8.00	PASS
11N20SISO	Ant1	2437	-16.41	≤8.00	PASS
11N20SISO	Ant1	2462	-15.90	≤8.00	PASS
11N40SISO	Ant1	2422	-18.59	≤8.00	PASS
11N40SISO	Ant1	2437	-18.15	≤8.00	PASS
11N40SISO	Ant1	2452	-18.90	≤8.00	PASS

Test Graphs







11B-Ant1-2437-PASS




11B-Ant1-2462-PASS




11G-Ant1-2412-PASS




11G-Ant1-2437-PASS




11G-Ant1-2462-PASS




11N20SISO-Ant1-2412-PASS




11N20SISO-Ant1-2437-PASS




11N20SISO-Ant1-2462-PASS



11N40SISO-Ant1-2422-PASS




11N40SISO-Ant1-2437-PASS




11N40SISO-Ant1-2452-PASS

Appendix D: Band edge measurements
Transmit at 2412MHz by 802.11b




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2387.28	54.4	54.36	-0.060	74.00	19.64	PK	Horizo	PASS
2	2390.00	53.3	53.22	-0.050	74.00	20.78	PK	Horizo	PASS

Transmit at 2412MHz by 802.11b




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2385.60	48.8	48.71	-0.060	74.00	25.29	PK	Vertic	PASS
2	2390.00	47.5	47.49	-0.050	74.00	26.51	PK	Vertic	PASS

Transmit at 2412MHz by 802.11b




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2332.96	38.2	38.05	-0.180	54.00	15.95	AV	Horizo	PASS
2	2390.00	42.4	42.31	-0.050	54.00	11.69	AV	Horizo	PASS

Transmit at 2412MHz by 802.11b




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2332.62	34.4	34.20	-0.180	54.00	19.80	AV	Vertic	PASS
2	2390.00	35.9	35.81	-0.050	54.00	18.19	AV	Vertic	PASS

Transmit at 2462MHz by 802.11b




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	52.7	52.99	0.270	74.00	21.01	PK	Horizo	PASS
2	2487.09	55.0	55.27	0.290	74.00	18.73	PK	Horizo	PASS

Transmit at 2462MHz by 802.11b



Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	44.4	44.68	0.270	74.00	29.32	PK	Vertic	PASS
2	2490.59	45.8	46.11	0.300	74.00	27.89	PK	Vertic	PASS


Transmit at 2462MHz by 802.11b



Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	42.6	42.91	0.270	54.00	11.09	AV	Horizo	PASS
2	2488.00	42.8	43.04	0.290	54.00	10.96	AV	Horizo	PASS

Transmit at 2462MHz by 802.11b




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	35.8	36.09	0.270	54.00	17.91	AV	Vertic	PASS
2	2487.76	36.1	36.40	0.290	54.00	17.60	AV	Vertic	PASS

Transmit at 2412MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.63	69.3	69.29	-0.050	74.00	4.71	PK	Horizo	PASS
2	2390.00	71.0	70.90	-0.050	74.00	3.10	PK	Horizo	PASS

Transmit at 2412MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.05	57.7	57.66	-0.060	74.00	16.34	PK	Vertic	PASS
2	2390.00	62.4	62.32	-0.050	74.00	11.68	PK	Vertic	PASS

Transmit at 2412MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2367.57	39.4	39.30	-0.110	54.00	14.70	AV	Horizo	PASS
2	2390.00	53.7	53.68	-0.050	54.00	0.32	AV	Horizo	PASS

Transmit at 2412MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2367.01	34.1	33.99	-0.110	54.00	20.01	AV	Vertic	PASS
2	2390.00	46.1	46.05	-0.050	54.00	7.95	AV	Vertic	PASS

Transmit at 2462MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	68.5	68.72	0.270	74.00	5.28	PK	Horizo	PASS
2	2484.02	67.8	68.07	0.270	74.00	5.93	PK	Horizo	PASS

Transmit at 2462MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	58.3	58.61	0.270	74.00	15.39	PK	Vertic	PASS
2	2484.59	56.6	56.87	0.270	74.00	17.13	PK	Vertic	PASS

Transmit at 2462MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	52.8	53.04	0.270	54.00	0.96	AV	Horizo	PASS
2	2484.83	50.9	51.13	0.280	54.00	2.87	AV	Horizo	PASS

Transmit at 2462MHz by 802.11g




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	43.5	43.80	0.270	54.00	10.20	AV	Vertic	PASS
2	2485.07	41.4	41.65	0.280	54.00	12.35	AV	Vertic	PASS

Transmit at 2412MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.18	66.2	66.10	-0.060	74.00	7.90	PK	Horizo	PASS
2	2390.00	72.6	72.53	-0.050	74.00	1.47	PK	Horizo	PASS

Transmit at 2412MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.41	63.6	63.51	-0.050	74.00	10.49	PK	Vertic	PASS
2	2390.00	66.6	66.57	-0.050	74.00	7.43	PK	Vertic	PASS

Transmit at 2412MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.40	48.7	48.61	-0.060	54.00	5.39	AV	Horizo	PASS
2	2390.00	50.5	50.41	-0.050	54.00	3.59	AV	Horizo	PASS

Transmit at 2412MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.74	41.9	41.79	-0.060	54.00	12.21	AV	Vertic	PASS
2	2390.00	43.3	43.21	-0.050	54.00	10.79	AV	Vertic	PASS

Transmit at 2462MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	71.8	72.09	0.270	74.00	1.91	PK	Horizo	PASS
2	2483.87	71.8	72.03	0.270	74.00	1.97	PK	Horizo	PASS

Transmit at 2462MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	62.8	63.08	0.270	74.00	10.92	PK	Vertic	PASS
2	2483.92	62.0	62.24	0.270	74.00	11.76	PK	Vertic	PASS

Transmit at 2462MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	51.9	52.14	0.270	54.00	1.86	AV	Horizo	PASS
2	2484.06	51.7	51.93	0.270	54.00	2.07	AV	Horizo	PASS

Transmit at 2462MHz by 802.11n(20MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	42.9	43.20	0.270	54.00	10.80	AV	Vertic	PASS
2	2485.94	40.0	40.25	0.290	54.00	13.75	AV	Vertic	PASS

Transmit at 2422MHz by 802.11n(40MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.94	72.4	72.35	-0.060	74.00	1.65	PK	Horizo	PASS
2	2390.00	70.9	70.85	-0.050	74.00	3.15	PK	Horizo	PASS

Transmit at 2422MHz by 802.11n(40MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2385.90	64.4	64.36	-0.060	74.00	9.64	PK	Vertic	PASS
2	2390.00	63.8	63.72	-0.050	74.00	10.28	PK	Vertic	PASS

Transmit at 2422MHz by 802.11n(40MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.94	53.6	53.50	-0.060	54.00	0.50	AV	Horizo	PASS
2	2390.00	53.7	53.61	-0.050	54.00	0.39	AV	Horizo	PASS

Transmit at 2422MHz by 802.11n(40MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.67	46.5	46.39	-0.060	54.00	7.61	AV	Vertic	PASS
2	2390.00	46.2	46.19	-0.050	54.00	7.81	AV	Vertic	PASS

Transmit at 2452MHz by 802.11n(40MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	68.8	69.11	0.270	74.00	4.89	PK	Horizo	PASS
2	2485.99	70.5	70.75	0.290	74.00	3.25	PK	Horizo	PASS

Transmit at 2452MHz by 802.11n(40MHz)




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	59.5	59.75	0.270	74.00	14.25	PK	Vertic	PASS
2	2485.92	61.2	61.47	0.290	74.00	12.53	PK	Vertic	PASS

Transmit at 2452MHz by 802.11n(40MHz)



Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	53.4	53.67	0.270	54.00	0.33	AV	Horizo	PASS
2	2484.50	52.8	53.05	0.270	54.00	0.95	AV	Horizo	PASS

Transmit at 2452MHz by 802.11n(40MHz)



Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	44.0	44.29	0.270	54.00	9.71	AV	Vertic	PASS
2	2486.67	41.2	41.53	0.290	54.00	12.47	AV	Vertic	PASS

Appendix E: Emissions in non restricted frequency bands

Reference level measurement

